

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: Derrick & Kristi Hall Residence
 Street:
 City, State, Zip: Lake City, FL, 32055
 Owner: Derrick & Kristi Hall
 Design Location: FL, Gainesville

Builder Name: S & S Construction
 Permit Office: Columbia County
 Permit Number:
 Jurisdiction:
 County: Columbia (Florida Climate Zone 2)

1. New construction or existing New (From Plans)
 2. Single family or multiple family Single-family
 3. Number of units, if multiple family 1
 4. Number of Bedrooms 3
 5. Is this a worst case? No
 6. Conditioned floor area above grade (ft²) 2478
 Conditioned floor area below grade (ft²) 0

7. Windows (286.3 sqft.) Description Area
 a. U-Factor: Dbl, U=0.36 286.33 ft²
 SHGC: SHGC=0.25
 b. U-Factor: N/A ft²
 SHGC:
 c. U-Factor: N/A ft²
 SHGC:
 d. U-Factor: N/A ft²
 SHGC:
 Area Weighted Average Overhang Depth: 7.001 ft.
 Area Weighted Average SHGC: 0.250

8. Floor Types (2478.0 sqft.) Insulation Area
 a. Slab-On-Grade Edge Insulation R=0.0 2148.00 ft²
 b. Floor over Garage R=0.0 330.00 ft²
 c. N/A R= ft²

9. Wall Types (2830.3 sqft.) Insulation Area
 a. Frame - Wood, Exterior R=13.0 2476.30 ft²
 b. Frame - Wood, Adjacent R=13.0 354.00 ft²
 c. N/A R= ft²
 d. N/A R= ft²
 10. Ceiling Types (2602.0 sqft.) Insulation Area
 a. Under Attic (Vented) R=38.0 2602.00 ft²
 b. N/A R= ft²
 c. N/A R= ft²
 11. Ducts R= ft²
 a. Sup: Attic, Ret: Attic, AH: Garage 6 619

12. Cooling systems kBtu/hr Efficiency
 a. Central Unit 34.0 SEER:14.00

13. Heating systems kBtu/hr Efficiency
 a. Electric Heat Pump 42.4 HSPF:8.20

14. Hot water systems Cap: 50 gallons
 a. Electric EF: 0.920
 b. Conservation features
 None

15. Credits CV, Pstat

Glass/Floor Area: 0.116

Total Proposed Modified Loads: 65.71

Total Baseline Loads: 67.32

PASS

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: 

DATE: 9/4/2020

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: _____

DATE: _____

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.

BUILDING OFFICIAL: _____

DATE: _____



- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires an envelope leakage test report with envelope leakage no greater than 5.00 ACH50 (R402.4.1.2).

INPUT SUMMARY CHECKLIST REPORT

PROJECT

Title:	Derrick & Kristi Hall Residence	Bedrooms:	3	Address Type:	Lot Information
Building Type:	User	Conditioned Area:	2478	Lot #	37
Owner Name:	Derrick & Kristi Hall	Total Stories:	2	Block/Subdivision:	Cobblestone
# of Units:	1	Worst Case:	No	PlatBook:	
Builder Name:	S & S Construction	Rotate Angle:	0	Street:	
Permit Office:	Columbia County	Cross Ventilation:	Yes	County:	Columbia
Jurisdiction:		Whole House Fan:	No	City, State, Zip:	Lake City , FL , 32055
Family Type:	Single-family				
New/Existing:	New (From Plans)				
Comment:					

CLIMATE

✓	Design Location	TMY Site	Design Temp		Int Design Temp		Heating Degree Days	Design Moisture	Daily Temp Range
			97.5 %	2.5 %	Winter	Summer			
_____	FL, Gainesville	FL_GAINESVILLE_REGI	32	92	70	75	1305.5	51	Medium

BLOCKS

Number	Name	Area	Volume
1	Block1	2478	21972

SPACES

Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated
1	1st Floor	2148	19332	Yes	6	3	1	Yes	Yes	Yes
2	2nd Floor	330	2640	No	2	0	1	Yes	Yes	Yes

FLOORS

✓	#	Floor Type	Space	Perimeter	Perimeter R-Value	Area	Joist R-Value	Tile	Wood	Carpet
_____	1	Slab-On-Grade Edge Insulation	1st Floor	261 ft	0	2148 ft²	----	0	0	1
_____	2	Floor over Garage	2nd Floor	----	----	330 ft²	0	0	0	1

ROOF

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pitch (deg)
_____	1	Hip	Composition shingles	2979 ft²	0 ft²	Medium	Y	0.96	No	0.9	No	0	33.7

ATTIC

✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
_____	1	Partial cathedral ceili	Vented	300	2478 ft²	Y	N

INPUT SUMMARY CHECKLIST REPORT

CEILING

✓	#	Ceiling Type	Space	R-Value	Ins Type	Area	Framing Frac	Truss Type
✓	1	Under Attic (Vented)	1st Floor	38	Double Batt	2255 ft²	0.11	Wood
✓	2	Under Attic (Vented)	2nd Floor	38	Double Batt	347 ft²	0.11	Wood

WALLS

✓	#	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	In	Height Ft	In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
✓	1	S	Exterior	Frame - Wood	1st Floor	13	8	10	9		79.5 ft²		0.23	0.75	0
✓	2	W	Exterior	Frame - Wood	1st Floor	13	4		9		36.0 ft²		0.23	0.75	0
✓	3	S	Exterior	Frame - Wood	1st Floor	13	20	8	9		186.0 ft²		0.23	0.75	0
✓	4	S	Exterior	Frame - Wood	1st Floor	13	13	4	9		120.0 ft²		0.23	0.75	0
✓	5	E	Exterior	Frame - Wood	1st Floor	13	42		9		378.0 ft²		0.23	0.75	0
✓	6	N	Exterior	Frame - Wood	1st Floor	13	13	4	9		120.0 ft²		0.23	0.75	0
✓	7	W	Exterior	Frame - Wood	1st Floor	13	14		9		126.0 ft²		0.23	0.75	0
✓	8	N	Exterior	Frame - Wood	1st Floor	13	18	2	9		163.5 ft²		0.23	0.75	0
✓	9	E	Exterior	Frame - Wood	1st Floor	13	10		9		90.0 ft²		0.23	0.75	0
✓	10	N	Exterior	Frame - Wood	1st Floor	13	11	4	9		102.0 ft²		0.23	0.75	0
✓	11	E	Exterior	Frame - Wood	1st Floor	13	8		9		72.0 ft²		0.23	0.75	0
✓	12	N	Exterior	Frame - Wood	1st Floor	13	25	8	9		231.0 ft²		0.23	0.75	0
✓	13	W	Exterior	Frame - Wood	1st Floor	13	28	4	9		255.0 ft²		0.23	0.75	0
✓	14	S	Garage	Frame - Wood	1st Floor	13	25	4	9		228.0 ft²		0.23	0.75	0
✓	15	W	Garage	Frame - Wood	1st Floor	13	14		9		126.0 ft²		0.23	0.75	0
✓	16	S	Exterior	Frame - Wood	2nd Floor	13	12	8	8		101.3 ft²		0.23	0.75	0
✓	17	E	Exterior	Frame - Wood	2nd Floor	13	26		8		208.0 ft²		0.23	0.75	0
✓	18	W	Exterior	Frame - Wood	2nd Floor	13	26		8		208.0 ft²		0.23	0.75	0

DOORS

✓	#	Ornt	Door Type	Space	Storms	U-Value	Width Ft	In	Height Ft	In	Area
✓	1	S	Insulated	1st Floor	None	.46	3		6	8	20 ft²
✓	2	S	Insulated	1st Floor	None	.46	3		6	8	20 ft²

WINDOWS

Orientation shown is the entered, Proposed orientation.

✓	#	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Area	Overhang Depth	Separation	Int Shade	Screening
✓	1	S	1	Vinyl	Low-E Double	Yes	0.36	0.25	N	10.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	2	S	3	Vinyl	Low-E Double	Yes	0.36	0.25	N	30.0 ft²	7 ft 6 in	1 ft 0 in	None	None
✓	3	S	3	TIM	Low-E Double	Yes	0.36	0.25	N	13.3 ft²	7 ft 6 in	1 ft 0 in	None	None
✓	4	S	4	Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	5	E	5	Vinyl	Low-E Double	Yes	0.36	0.25	N	6.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	6	E	5	Vinyl	Low-E Double	Yes	0.36	0.25	N	4.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	7	E	5	Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	8	N	6	Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	9	N	8	Vinyl	Low-E Double	Yes	0.36	0.25	N	45.0 ft²	18 ft 0 in	1 ft 0 in	None	None
✓	10	E	9	TIM	Low-E Double	Yes	0.36	0.25	N	40.0 ft²	16 ft 0 in	1 ft 0 in	None	None

INPUT SUMMARY CHECKLIST REPORT

WINDOWS

Orientation shown is the entered, Proposed orientation.

✓	#	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Area	Overhang Depth	Separation	Int Shade	Screening
✓	11	N	10	Vinyl	Low-E Double	Yes	0.36	0.25	N	30.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	12	N	12	Vinyl	Low-E Double	Yes	0.36	0.25	N	30.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	13	N	12	Vinyl	Low-E Double	Yes	0.36	0.25	N	10.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	14	W	13	Vinyl	Low-E Double	Yes	0.36	0.25	N	8.0 ft²	1 ft 6 in	1 ft 0 in	None	None
✓	15	S	16	Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 0 in	3 ft 0 in	None	None

GARAGE

✓	#	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg. Wall Height	Exposed Wall Insulation
✓	1	667.342 ft²	667.342 ft²	63.33 ft	9 ft	1

INFILTRATION

#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Proposed ACH(50)	.000282	1831	100.52	189.04	.1457	5

HEATING SYSTEM

✓	#	System Type	Subtype	Speed	Efficiency	Capacity	Block	Ducts
✓	1	Electric Heat Pump/	None	Single	HSPF:8.2	42.44 kBtu/hr	1	sys#1

COOLING SYSTEM

✓	#	System Type	Subtype	Subtype	Efficiency	Capacity	Air Flow	SHR	Block	Ducts
✓	1	Central Unit/	None	Single	SEER: 14	34.02 kBtu/hr	1020 cfm	0.7	1	sys#1

HOT WATER SYSTEM

✓	#	System Type	SubType	Location	EF	Cap	Use	SetPnt	Conservation
✓	1	Electric	None	Garage	0.92	50 gal	40 gal	120 deg	None

SOLAR HOT WATER SYSTEM

✓	FSEC Cert #	Company Name	System Model#	Collector Model#	Collector Area	Storage Volume	FEF
✓	None	None			ft²		

DUCTS

✓	#	Location	Supply R-Value	Area	Location	Return Area	Leakage Type	Air Handler	CFM 25 TOT	CFM25 OUT	QN	RLF	HVAC # Heat	Cool
✓	1	Attic	6	619 ft²	Attic	123.9 ft²	Default Leakage	Garage	(Default)	c(Default)	c		1	1

INPUT SUMMARY CHECKLIST REPORT

TEMPERATURES

Programable Thermostat: Y

Ceiling Fans:

Cooling	<input type="checkbox"/> Jan	<input type="checkbox"/> Feb	<input type="checkbox"/> Mar	<input type="checkbox"/> Apr	<input type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input type="checkbox"/> Oct	<input type="checkbox"/> Nov	<input type="checkbox"/> Dec
Heating	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input type="checkbox"/> Apr	<input type="checkbox"/> May	<input type="checkbox"/> Jun	<input type="checkbox"/> Jul	<input type="checkbox"/> Aug	<input type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec
Venting	<input type="checkbox"/> Jan	<input type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input type="checkbox"/> May	<input type="checkbox"/> Jun	<input type="checkbox"/> Jul	<input type="checkbox"/> Aug	<input type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec

Thermostat Schedule: HERS 2006 Reference

Hours

Schedule Type		1	2	3	4	5	6	7	8	9	10	11	12
Cooling (WD)	AM	78	78	78	78	78	78	78	78	80	80	80	80
	PM	80	80	78	78	78	78	78	78	78	78	78	78
Cooling (WEH)	AM	78	78	78	78	78	78	78	78	78	78	78	78
	PM	78	78	78	78	78	78	78	78	78	78	78	78
Heating (WD)	AM	66	66	66	66	66	68	68	68	68	68	68	68
	PM	68	68	68	68	68	68	68	68	68	68	66	66
Heating (WEH)	AM	66	66	66	66	66	68	68	68	68	68	68	68
	PM	68	68	68	68	68	68	68	68	68	68	66	66

MASS

Mass Type	Area	Thickness	Furniture Fraction	Space
Default(8 lbs/sq.ft.)	0 ft²	0 ft	0.3	1st Floor
Default(8 lbs/sq.ft.)	0 ft²	0 ft	0.3	2nd Floor

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 98

The lower the Energy Performance Index, the more efficient the home.

1. New home or, addition	1. <u>New (From Plans)</u>	12. Ducts, location & insulation level
2. Single-family or multiple-family	2. <u>Single-family</u>	a) Supply ducts R <u>6.0</u>
3. No. of units (if multiple-family)	3. <u>1</u>	b) Return ducts R <u>6.0</u>
4. Number of bedrooms	4. <u>3</u>	c) AHU location <u>Garage</u>
5. Is this a worst case? (yes/no)	5. <u>No</u>	13. Cooling system: Capacity <u>34.0</u>
6. Conditioned floor area (sq. ft.)	6. <u>2478</u>	a) Split system SEER <u> </u>
7. Windows, type and area		b) Single package SEER <u> </u>
a) U-factor:(weighted average)	7a. <u>0.360</u>	c) Ground/water source SEER/COP <u> </u>
b) Solar Heat Gain Coefficient (SHGC)	7b. <u>0.250</u>	d) Room unit/PTAC EER <u> </u>
c) Area	7c. <u>286.3</u>	e) Other <u>14.0</u>
8. Skylights		14. Heating system: Capacity <u>42.4</u>
a) U-factor:(weighted average)	8a. <u>NA</u>	a) Split system heat pump HSPF <u> </u>
b) Solar Heat Gain Coefficient (SHGC)	8b. <u>NA</u>	b) Single package heat pump HSPF <u> </u>
9. Floor type, insulation level:		c) Electric resistance COP <u> </u>
a) Slab-on-grade (R-value)	9a. <u>0.0</u>	d) Gas furnace, natural gas AFUE <u> </u>
b) Wood, raised (R-value)	9b. <u>0.0</u>	e) Gas furnace, LPG AFUE <u> </u>
c) Concrete, raised (R-value)	9c. <u> </u>	f) Other <u>8.20</u>
10. Wall type and insulation:		15. Water heating system
A. Exterior:		a) Electric resistance EF <u>0.92</u>
1. Wood frame (Insulation R-value)	10A1. <u>13.0</u>	b) Gas fired, natural gas EF <u> </u>
2. Masonry (Insulation R-value)	10A2. <u> </u>	c) Gas fired, LPG EF <u> </u>
B. Adjacent:		d) Solar system with tank EF <u> </u>
1. Wood frame (Insulation R-value)	10B1. <u>13.0</u>	e) Dedicated heat pump with tank EF <u> </u>
2. Masonry (Insulation R-value)	10B2. <u> </u>	f) Heat recovery unit HeatRec% <u> </u>
11. Ceiling type and insulation level		g) Other <u> </u>
a) Under attic	11a. <u>38.0</u>	16. HVAC credits claimed (Performance Method)
b) Single assembly	11b. <u> </u>	a) Ceiling fans <u> </u>
c) Knee walls/skylight walls	11c. <u> </u>	b) Cross ventilation <u>Yes</u>
d) Radiant barrier installed	11d. <u>Yes</u>	c) Whole house fan <u>No</u>
		d) Multizone cooling credit <u> </u>
		e) Multizone heating credit <u> </u>
		f) Programmable thermostat <u>Yes</u>

*Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

I certify that this home has complied with the Florida Building Code, Energy Conservation, through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL display card will be completed based on installed code compliant features.

Builder Signature: _____ Date: _____

Address of New Home: _____ City/FL Zip: Lake City, FL 32055