



REVISIONS	
7-23-07	

SOFTPLAN
ARCHITECTURAL DESIGN SOFTWARE




ALTERNATE WALL TIE CONNECTION WHERE
THREADED ROD CANNOT BE PLACED IN WALL.
SCALE: 1/2" = 1'-0"



GABLE END WALL BALLOON FRAMING DETAIL
SCALE: 1/2" = 1'-0"

STRUCTURAL PLAN
SCALE: 1/4" = 1'-0"



STRUCTURAL PLAN NOTES

- N-1 ALL LOAD BEARING FRAME WALL & PORCH HEADERS SHALL BE A MINIMUM OF (2) 2X12 SYP#2 (U.N.O.)
- N-2 ALL LOAD BEARING FRAME WALL HEADERS SHALL HAVE (1) JACK STUD & (1) KING STUD EACH SIDE (U.N.O.)
- N-3 DIMENSIONS ON STRUCTURAL SHEETS ARE NOT EXACT. REFER TO ARCHITECTURAL FLOOR PLAN FOR ACTUAL DIMENSIONS
- N-4 PERMANENT TRUSS BRACING IS TO BE INSTALLED AT LOCATIONS AS SHOWN ON THE SEALED TRUSS DRAWINGS. LATERAL BRACING IS TO BE RESTRAINED PER BCS11-03, BCS1-B1, BCS1-B2, & BCS1-B3. BCS1-B1, BCS1-B2, & BCS1-B3 ARE FURNISHED BY THE TRUSS SUPPLIER, WITH THE SEALED TRUSS PACKAGE

THREADED ROD LEGEND

- INDICATES LOCATION OF: 1ST FLOOR 1/2" A307 ALL THREADED ROD
- INDICATES LOCATION OF: 2ND FLOOR 1/2" A307 ALL THREADED ROD

HEADER LEGEND

- HEADER/BEAM CALL-OUT (U.N.O.)
- NUMBER OF KING STUDS (FULL LENGTH)
- NUMBER OF JACK STUDS (UNDER HEADER)
- SPAN OF HEADER
- SIZE OF HEADER MATERIAL
- NUMBER OF PLIES IN HEADER

TOTAL SHEAR WALL SEGMENTS

SWS = 0.0' INDICATES SHEAR WALL SEGMENTS

	REQUIRED	ACTUAL
TRANSVERSE	39.3'	49.0'
LONGITUDINAL	28.6'	44.0'

WALL LEGEND


SWS = 0.0'	1ST FLOOR EXTERIOR WALL
SWS = 0.0'	2ND FLOOR EXTERIOR
IBW	1ST FLOOR INTERIOR BEARING WALLS SEE DETAILS ON SHEET S-1
IBW	2ND FLOOR INTERIOR BEARING WALLS SEE DETAILS ON SHEET S-1

CONNECTIONS, WALL, & HEADER DESIGN IS BASED ON REACTIONS & UPLIFTS FROM TRUSS ENGINEERING FURNISHED BY BUILDER, ANDERSON TRUSS JOB #7-092

WINDLOAD ENGINEER: Mark Disoway, P.E. No. 53915, P.O. Box 861, Lake City, FL 32056, 386-754-5419
DIMENSIONS: Stated dimensions supersede scaled dimensions. Refer all questions to Mark Disoway, P.E. for resolution. Do not proceed without clarification.
COPYRIGHTS AND PROPERTY RIGHTS: Mark Disoway, P.E. hereby expressly reserves its common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disoway.
CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with section R301.2.1, Florida building code residential 2004, to the best of my knowledge.
LIMITATION: This design is valid for one building, at specified location.
MARK DISOWAY
P.E. 53915
SEAL

ERKINGER BUILDERS

Todd Manning
ADDRESS: Columbia County, Florida
Mark Disoway P.E.
P.O. Box 861
Lake City, Florida 32056
Phone: (386) 754-5419
Fax: (386) 269-4871
PRINTED DATE: July 23, 2007
DRAWN BY: David Disoway
CHECKED BY: VA QUALIFIER # 7182
MATTHEW ERKINGER
FINALS DATE: 09 / MAY / 07
JOB NUMBER: 703191
DRAWING NUMBER
S-3
OF 6 SHEETS




12"x12" FRAMED PORCH COLUMN DETAIL
w/ THD. ROD HOLD DOWN
SCALE: N.T.S.

FILE COPY

REVISIONS	

SOFTMAN
ARCHITECTURAL GROUP, INC.



FRONT ELEVATION
SCALE: 1/4" = 1'-0"


NOTE: BUILDER TO VERIFY WINDOW
HEIGHT BEFORE BEGINNING CONSTRUCTION



RIGHT ELEVATION
SCALE: 1/4" = 1'-0"



LEFT ELEVATION
SCALE: 1/4" = 1'-0"



REAR ELEVATION
SCALE: 1/4" = 1'-0"

WINDLOAD ENGINEER: Mark Disoway,
P.E. No. 53915, P.O. Box 868, Lake City, FL
32056, 386-754-5419

DIMENSIONS:
Stated dimensions supersede scaled
dimensions. Refer all questions to
Mark Disoway, P.E. for resolution.
Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:
Mark Disoway, P.E. hereby expressly reserves
all common law copyrights and property right in
these instruments of service. This document is
not to be reproduced, stored or copied in any
form or manner without first the express written
permission and consent of Mark Disoway.

CERTIFICATION: I hereby certify that I have
examined this plan, and that the applicable
portions of the plan, relating to wind engineering
comply with section PC1.2.1, Florida building
code residential 2004, to the best of my
knowledge.

LIMITATION: This design is valid for one
building, at specified location.

MARK DISOWAY
P.E. 53915
09 MAY 07
SAL

ERKINGER BUILDERS

Todd Manning

ADDRESS:
Columbia County, Florida

Mark Disoway P.E.
P.O. Box 868
Lake City, Florida 32056
Phone: (386) 754 - 5419
Fax: (386) 269 - 4871

PRINTED DATE:
May 09, 2007

DRAWN BY: David Disoway
CHECKED BY:

VA QUALIFIER # 7882

MATTHEWERKINGER

FINALS DATE:
09 / MAY / 07

JOB NUMBER:
70191

DRAWING NUMBER
A1

OF 6 SHEETS

REQUIRED ROOF VENTILATION:
AS PER FLORIDA BUILDING CODE 2309.7

RIDGE VENT
MIN. 50% TOTAL VENT AREA
LOCATED IN THE UPPER PORTION OF ATTIC (MIN. 3" ABOVE EAVE)
3139 S.F. / 300 x 50% = 5.3 S.F. RIDGE VENT AREA REQUIRED
49 FEET OF RIDGE VENT REQUIRED

SOFFIT VENT
3139 S.F. / 300 x 50% = 5.3 S.F. SOFFIT VENT AREA REQUIRED
177 FEET OF SOFFIT VENT REQUIRED

BUILDER MUST VERIFY THE FOLLOWING MINIMUM NET FREE VENT AREAS:


1. RIDGE VENTS = 16 IN2/FT (.11 FT2/FT)
2. OFF-RIDGE VENTS = .70 FT2 PER 4' UNIT
3. SOFFIT VENTS = 4.3 IN2/FT (.03 FT2/FT)



FILE COPY

REVISIONS

SOFTPLAN
ARCHITECTURAL DESIGN SOFTWARE



WINDLOAD ENGINEER: Mark Disosway,
PE No. 53115, P.O. Box 888, Lake City, FL
32056, 386-754-5419

DIMENSIONS:
Stated dimensions supercede scaled
dimensions. Refer all questions to
Mark Disosway, P.E. for resolution.
Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:
Mark Disosway, P.E. hereby expressly reserves
its common law copyright and property right in
these instruments of service. This document is
not to be reproduced, altered or copied in any
form or manner without first the express written
permission and consent of Mark Disosway.

CERTIFICATION: I hereby certify that I have
examined this plan, and that the applicable
portions of the plan, relating to wind engineering
comply with section 1609.2, Florida building
code residential 2004, to the best of my
knowledge.

LIMITATION: This design is valid for one
building, at specified location.

MARK DISOSWAY
P.E. 53115

09/14/07

SEAL

ERKINGER BUILDERS

Todd Manning

ADDRESS:
Columbia County, Florida

Mark Disosway P.E.
P.O. Box 888
Lake City, Florida 32056
Phone: (386) 754 - 5419
Fax: (386) 219 - 4871

PRINTED DATE:
May 08, 2007

DRAWN BY: David Disosway CHECKED BY:

VA QUALIFIER # 7882

MATTHEW ERKINGER


FINAL DATE:
09 / MAY / 07

JOB NUMBER:
703191

DRAWING NUMBER
A2

OF 6 SHEETS

REVISIONS

SOFTPLAN
ARCHITECTURAL DESIGN SOFTWARE


ELECTRICAL PLAN
SCALE: 1/4" = 1'-0"

ELECTRICAL PLAN NOTES

- E -1 WIRE ALL APPLIANCES, HVAC UNITS AND OTHER EQUIPMENT PER MANUF. SPECIFICATIONS.
- E -2 CONSULT THE OWNER FOR THE NUMBER OF SEPERATE TELEPHONE LINES TO BE INSTALLED.
- E -3 ALL INSTALLATIONS SHALL BE PER NATL. ELECTRIC CODE.
- E -4 ALL SMOKE DETECTORS SHALL BE 120V W/ BATTERY BACKUP OF THE PHOTOELECTRIC TYPE, AND SHALL BE INTERLOCKED TOGETHER. INSTALL INSIDE AND NEAR ALL BEDROOMS.
- E -5 TELEPHONE, TELEVISION AND OTHER LOW VOLTAGE DEVICES OR OUTLETS SHALL BE AS PER THE OWNER'S DIRECTIONS, & IN ACCORDANCE W/ APPLICABLE SECTIONS OF NEC-LATEST EDITION.
- E -6 ELECTRICAL CONTR SHALL BE RESPONSIBLE FOR THE DESIGN & SIZING OF ELECTRICAL SERVICE AND CIRCUITS.
- E -7 ENTRY OF SERVICE (UNDERGROUND OR OVERHEAD) TO BE DETERMINED BY POWER COMPANY.
- E -8 ALL BEDROOM RECEPTACLES SHALL BE AFCI (ARC FAULT CIRCUIT INTERRUPT)
- E -9 ALL OUTLETS TO BE LOCATED ABOVE BASE FLOOD ELEVATION
- E -10 A SERVICE DISCONNECT WITH OVER CURRENT PROTECTION SHALL BE INSTALLED OUTSIDE OF THE BUILDING, ON THE LOAD SIDE OF THE METER. AT THE PLACE ELECTRIC CONDUCTORS ENTER THE BUILDING. SERVICE ENTRANCE CONDUCTORS MAY NOT BE LOCATED INSIDE OF THE OF THE BUILDING WITHOUT SPECIAL APPROVAL OF THE BUILDING OFFICIAL.

ELECTRICAL LEGEND

	CEILING FAN (PRE-WIRE FOR LIGHT KIT)
	DOUBLE SECURITY LIGHT
	2X4 FLUORESCENT LIGHT FIXTURE
	RECESSED CAN LIGHT
	BATH EXHAUST FAN WITH LIGHT
	BATH EXHAUST FAN
	LIGHT FIXTURE
	DUPLEX OUTLET
	220v OUTLET
	GFI DUPLEX OUTLET
	SMOKE DETECTOR
	WALL SWITCH
	3 WAY WALL SWITCH
	4 WAY WALL SWITCH
	WATER PROOF GFI OUTLET
	PHONE JACK
	TELEVISION JACK
	GARAGE DOOR OPENER
	WALL HEATER

WIRELOAD ENGINEER: Mark Discosway,
P.E. No. 53915, PCB 868, Lake City, FL
32056, 386-754-5419

DIMENSIONS:
Stated dimensions supersede scaled
dimensions. Refer all queries to
Mark Discosway, P.E. for resolution.
Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:
Mark Discosway, P.E. hereby expressly reserves
its common law copyrights and property right in
these instruments of service. This document is
not to be reproduced, altered or copied in any
form or manner without the express written
permission and consent of Mark Discosway.

CERTIFICATION: I hereby certify that I have
examined this plan, and the applicable
portions of the plan, relative to wind engineering
comply with section R301.21, Florida building
code residential 2004, to the best of my
knowledge.

LIMITATION: This design is valid for one
building, at specified locale.

MARK DISCOSWAY
P.E. 53915

Mark Discosway
09 MAY 07
SEAL

ERKINGER BUILDERS

Todd Manning

ADDRESS:
Columbia County, Florida

Mark Discosway P.E.
P.O. Box 868
Lake City, Florida 32056
Phone: (386) 754 - 5419
Fax: (386) 269 - 4871

PRINTED DATE:

May 09, 2007

DRAWN BY: David Discosway CHECKED BY:

VA QUALIFIER # 7882

MATTHEW ERKINGER

FINALS DATE:
09 / MAY / 07



JOB NUMBER:
703111

DRAWING NUMBER

A3

OF 6 SHEETS






INTERIOR BEARING WALL
SCALE: 1/2" = 1'-0"

ONE STORY WALL SECTION
SCALE: 3/4" = 1'-0"


EXTERIOR WALL STUD TABLE FOR SPF #2 STUDS

STUD SIZE	STUD HEIGHT
(1) 2x4 @ 16" OC	TO 11'-8" STUD HEIGHT
(1) 2x4 @ 12" OC	TO 13'-0" STUD HEIGHT
(1) 2x6 @ 16" OC	TO 18'-10" STUD HEIGHT
(1) 2x6 @ 12" OC	TO 20'-0" STUD HEIGHT


THIS STUD HEIGHT TABLE IS PER VFCM 2001, TABLE 3.208. EXTERIOR LOAD BEARING & NON LOAD BEARING STUD LENGTHS RESISTING INTERIOR ZONE WIND LOADS 110 MPH EXPOSURE B STUD SPACINGS SHALL BE MULTIPLIED BY 0.85 FOR FRAMING LOCATED WITHIN 4 FEET OF CORNERS FOR END ZONE LOADING. EXAMPLE 16" O.C. x 0.85 = 13.6" O.C.



CONTINUOUS FRAME TO CEILING DIAPHRAGM DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.



BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




SUPPORTIVE CENTER POST TO BEAM DETAIL
SCALE: N.T.S.




TYPICAL GABLE END (X-BRACING)
ALL MEMBERS SHALL BE SYP



TYPICAL PORCH POST DETAIL
SCALE: 1/2" = 1'-0"




TYPICAL 1ST STORY HEADER STRAPPING DETAIL
SCALE: 1/2" = 1'-0"



GARAGE DOOR BUCK INSTALLATION DETAIL
SCALE: N.T.S.




BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




TYPICAL GABLE END (X-BRACING)
ALL MEMBERS SHALL BE SYP



TYPICAL PORCH POST DETAIL
SCALE: 1/2" = 1'-0"




TYPICAL 1ST STORY HEADER STRAPPING DETAIL
SCALE: 1/2" = 1'-0"




GARAGE DOOR BUCK INSTALLATION DETAIL
SCALE: N.T.S.



BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.



BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




TYPICAL GABLE END (X-BRACING)
ALL MEMBERS SHALL BE SYP



TYPICAL PORCH POST DETAIL
SCALE: 1/2" = 1'-0"




TYPICAL 1ST STORY HEADER STRAPPING DETAIL
SCALE: 1/2" = 1'-0"




GARAGE DOOR BUCK INSTALLATION DETAIL
SCALE: N.T.S.



BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




TYPICAL GABLE END (X-BRACING)
ALL MEMBERS SHALL BE SYP




TYPICAL PORCH POST DETAIL
SCALE: 1/2" = 1'-0"




TYPICAL 1ST STORY HEADER STRAPPING DETAIL
SCALE: 1/2" = 1'-0"




GARAGE DOOR BUCK INSTALLATION DETAIL
SCALE: N.T.S.



BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




TYPICAL GABLE END (X-BRACING)
ALL MEMBERS SHALL BE SYP




TYPICAL PORCH POST DETAIL
SCALE: 1/2" = 1'-0"




TYPICAL 1ST STORY HEADER STRAPPING DETAIL
SCALE: 1/2" = 1'-0"




GARAGE DOOR BUCK INSTALLATION DETAIL
SCALE: N.T.S.



BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




TYPICAL GABLE END (X-BRACING)
ALL MEMBERS SHALL BE SYP




TYPICAL PORCH POST DETAIL
SCALE: 1/2" = 1'-0"




TYPICAL 1ST STORY HEADER STRAPPING DETAIL
SCALE: 1/2" = 1'-0"




GARAGE DOOR BUCK INSTALLATION DETAIL
SCALE: N.T.S.




BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




TYPICAL GABLE END (X-BRACING)
ALL MEMBERS SHALL BE SYP




TYPICAL PORCH POST DETAIL
SCALE: 1/2" = 1'-0"




TYPICAL 1ST STORY HEADER STRAPPING DETAIL
SCALE: 1/2" = 1'-0"




GARAGE DOOR BUCK INSTALLATION DETAIL
SCALE: N.T.S.




BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.




TYPICAL GABLE END (X-BRACING)
ALL MEMBERS SHALL BE SYP




TYPICAL PORCH POST DETAIL
SCALE: 1/2" = 1'-0"




TYPICAL 1ST STORY HEADER STRAPPING DETAIL
SCALE: 1/2" = 1'-0"




GARAGE DOOR BUCK INSTALLATION DETAIL
SCALE: N.T.S.




BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.



BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.



BEAM CORNER CONNECTION DETAIL
SCALE: N.T.S.




BEAM MID-WALL CONNECTION DETAIL
SCALE: N.T.S.

ANCHOR TABLE

OBTAIN UPLIFT REQUIREMENTS FROM TRUSS MANUFACTURER'S ENGINEERING


UPLIFT LBS. SYP	UPLIFT LBS. SPF	TRUSS CONNECTOR*	TO PLATES	
-----------------	-----------------	------------------	-----------	--

REVISIONS	




F5 PORCH FOOTING
SCALE: 1/2" = 1'-0"

F9 SEM WALL FOOTING
SCALE: 1/2" = 1'-0"




F2 INTERIOR BEARING FOOTING
SCALE: 1/2" = 1'-0"

F12 AT-STEM WALL PORCH FOOTING
SCALE: 1/2" = 1'-0"



F3 INTERIOR BEARING STEP FOOTING
SCALE: 1/2" = 1'-0"

F4 ALT-STEM WALL GARAGE DOOR FOOTING
SCALE: 1/2" = 1'-0"




F6 TYPICAL NON-BEARING STEP FOOTING
SCALE: 1/2" = 1'-0"

TALL STEM WALL TABLE

The table assumes 60 ksi reinforcing bars with 6" hook in the footing and bent 24" into the reinforced slab at the top. Vertical steel is to be placed toward the tension side of the CMU wall (away from the screed). Within 2' of the exterior side of the wall, if the wall is over 8' high, add Durowall fiber reinforcement at 16" O.C. vertically or a horizontal bond beam with 185 continuous steel height. For higher parts of the wall 12" CMU may be used with reinforcement as shown in the table below.

STEM WALL HEIGHT (FEET)	UNBALANCE BACKFILL HEIGHT	VERTICAL REINFORCEMENT FOR 8" CMU STEM WALL (INCHES O.C.)			VERTICAL REINFORCEMENT FOR 12" CMU STEM WALL (INCHES O.C.)		
		#5	#7	#8	#5	#7	#8
3.3	3.0	96	96	96	96	96	96
4.0	3.7	96	96	96	96	96	96
4.7	4.3	88	96	96	96	96	96
5.3	5.0	56	96	96	96	96	96
6.0	5.7	40	80	96	80	96	96
6.7	6.3	32	56	80	56	96	96
7.3	7.0	24	40	56	40	80	96
8.0	7.7	16	32	48	32	64	80
8.7	8.3	8	24	32	24	48	64
9.3	9.0	8	16	24	16	40	48



FOUNDATION PLAN
SCALE: 1/4" = 1'-0"
DIMENSIONS ON STRUCTURAL SHEETS ARE NOT EXACT. REFER TO ARCHITECTURAL FLOOR PLAN FOR ACTUAL DIMENSIONS

WINDLOAD ENGINEER: Mark Disoway, P.E. No. 53815, PCB 868, Lake City, FL 32056, 386-754-5419

DIMENSIONS: Stated dimensions supercede scaled dimensions. Refer all questions to Mark Disoway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS: Mark Disoway, P.E. hereby expressly reserves its common law copyright and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without the express written permission and consent of Mark Disoway.

CERTIFICATION: I hereby certify that I have examined this plan, and find the applicable portions of the plan, relating to wind engineering comply with section F3012.1, Florida building code residential 2004, to the best of my knowledge.

LIMITATION: This design is valid for one building, at specified location.

MARK DISOWAY
P.E. 5315
09MAR07
SEAL

ERKINGER BUILDERS

Todd Manning

ADDRESS:
Columbia County, Florida

Mark Disoway P.E.
P.O. Box 868
Lake City, Florida 32056
Phone: (386)754 - 5419
Fax: (386) 259 - 4871

PRINTED DATE:
May 09, 2007

DRAWN BY: David Disoway

CHECKED BY:

VA QUALIFIER # 7882

MATTHEW ERKINGER

FINALS DATE:
09 / MAY / 07

JOB NUMBER:
703191


DRAWING NUMBER
S-2

OF 6 SHEETS



REVISIONS

SOFTPLAN
ARCHITECTURAL DESIGN SOFTWARE



ALTERNATE WALL TIE CONNECTION WHERE
THREADED ROD CANNOT BE PLACED IN WALL
SCALE: 1/2" = 1'-0"

WINDLOAD ENGINEER: Mark Disoway,
P.E. No. 53915, PCB 868, Lake City, FL
32056, 386-754-5419

DIMENSIONS:
Stated dimensions supersede scale
dimensions. Refer all questions to
Mark Disoway, P.E. for resolution.
Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:
Mark Disoway, P.E. hereby expressly reserves
its common law copyrights and property right in
these instruments of service. This document is
not to be reproduced, altered or copied in any
form or manner without first the express written
permission and consent of Mark Disoway.

CERTIFICATION: I hereby certify that I have
examined this plan, and that the applicable
portions of the plan, relating to wind engineering
comply with section R501.2.1, Florida building
code residential 2004, to the best of my
knowledge.

LIMITATION: This design is valid for one
building, at specified location.

MARK DISOWAY
P.E. 53915

09 MAY 07
SEAL

ERKINGER BUILDERS

Todd Manning

ADDRESS:
Columbia County, Florida

Mark Disoway P.E.
P.O. Box 868
Lake City, Florida 32056
Phone: (386) 754 - 5419
Fax: (386) 269 - 4371

PRINTED DATE:
May 08, 2007

DRAWN BY: David Disoway CHECKED BY:

VA QUALIFIER # 7882

MATTHEW ERKINGER

FINALS DATE:
09 / MAY / 07


JOB NUMBER:
703191

DRAWING NUMBER


S-3

OF 6 SHEETS

BLOCKING MUST BE PARALLEL TO TOP AND BOTTOM PLATES
WITH A MINIMUM OF 2-16d NAILS
NOTE: MUST STRAP EACH OUTLOOKER TO GABLE END-TRUSS
WITH SIMPSON H2.5 OR EQUIVALENT



OVERHANGS IN EXCESS OF 12" AND UP
TO 24" USE 2X4 SYR OUTLOOKER AT
24" OC CLIP TO DBL TOP PL. WITH (1)
H2.5 W/ (9) 8d. (12" OVERHANGS DO
NOT NEED OUTLOOKERS OR DROPPED
GABLE TRUSS)




NOTE: SEE STUD SIZING TABLE AND KING
STUD / JACK STUD CALCULATION FOR SPACING SIZE
AND NUMBER OF STUDS.

GABLE END WALL BALLOON FRAMING DETAIL

SCALE: 1/2" = 1'-0"

STRUCTURAL PLAN

SCALE: 1/4" = 1'-0"



12"x12" FRAMED PORCH COLUMN DETAIL

w/ THD. ROD HOLD DOWN

SCALE: N.T.S.

STRUCTURAL PLAN NOTES

- SI-1 ALL LOAD BEARING FRAME WALL & PORCH HEADERS
SHALL BE A MINIMUM OF (2) 2X12 SYP #2 (U.N.O.)
- SI-2 ALL LOAD BEARING FRAME WALL HEADERS
SHALL HAVE (1) JACK STUD & (1) KING STUD
EACH SIDE (U.N.O.)
- SI-3 DIMENSIONS ON STRUCTURAL SHEETS
ARE NOT EXACT. REFER TO ARCHITECTURAL
FLOOR PLAN FOR ACTUAL DIMENSIONS
- SI-4 PERMANENT TRUSS BRACING IS TO BE INSTALLED AT
LOCATIONS AS SHOWN ON THE SEALED TRUSS DRAWINGS.
LATERAL BRACING IS TO BE RESTRAINED PER BCSI-03,
BCSI-B1, BCSI-B2, & BCSI-B3. BCSI-B1, BCSI-B2, & BCSI-B3
ARE FURNISHED BY THE TRUSS SUPPLIER, WITH THE SEALED
TRUSS PACKAGE

THREADED ROD LEGEND

- INDICATES LOCATION OF:
1ST FLOOR 1/2" A307 ALL THREADED ROD
- ⊗ INDICATES LOCATION OF:
2ND FLOOR 1/2" A307 ALL THREADED ROD

HEADER LEGEND

- (2) 2X12X0',1J 1K → HEADER/BEAM CALL-OUT (U.N.O.)
- ↑ NUMBER OF KING STUDS (FULL LENGTH)
- ↑ NUMBER OF JACK STUDS (UNDER HEADER)
- ↑ SPAN OF HEADER
- ↑ SIZE OF HEADER MATERIAL
- ↑ NUMBER OF PLIES IN HEADER

TOTAL SHEAR WALL SEGMENTS

SWS = 0.0' INDICATES SHEAR WALL SEGMENTS

	REQUIRED	ACTUAL
TRANSVERSE	39.3'	49.0'
LONGITUDINAL	28.6'	44.0'

WALL LEGEND

SWS = 0.0'	1ST FLOOR EXTERIOR WALL
SWS = 0.0'	2ND FLOOR EXTERIOR
IBW	1ST FLOOR INTERIOR BEARING WALLS SEE DETAILS ON SHEET S-1
IBW	2ND FLOOR INTERIOR BEARING WALLS SEE DETAILS ON SHEET S-1

CONNECTIONS, WALL, & HEADER DESIGN IS BASED ON
ON REACTIONS & UPLIFTS FROM TRUSS ENGINEERING
FURNISHED BY BUILDER: ANDERSON TRUSS
JOB #7-092