

M390-A1F

390W

1000V

MITREX	BLACK HP M390-A1F
Nominal Max. Power (Pmax)	390W
MPP Operating Voltage (Vmp)	41.9V
MPP Operating Current (Imp)	9.31A
Open Circuit Voltage (Voc)	48.2V
Short Circuit Current (Isc)	9.97A
Module Efficiency	19.2%
Operating Temperature	-40°C ~ +85°C
Max. System Voltage	1000V (IEC/UL)
Max. Series Fuse Rating	20A
Application Classification	Class A

MECHANICAL DATA

SPECIFICATIONS	BLACK HP M390-A1F
Cell Type	Mono-crystalline
Cell Arrangement	72 [12x6]]
Dimensions	2036x996x40mm
Front Cover	3.2 mm tempered glass
Frame	Anodized aluminum alloy black frame
Weight	22kg
J-Box	IP68, 3 bypass diodes
Cable	4mm ² , 12 AWG (UL)
Cable Length (Including Connector)	500mm, 1000mm, 1200mm
Connector	MC4

TEMPERATURE CHARACTERISTICS

SPECIFICATIONS	BLACK HP M390-A1F
Temperature Coefficient Pmax	-0.36% / °C
Temperature Coefficient Voc	-0.30% / °C
Temperature Coefficient Isc	0.046% / °C
Nominal Module Operating Temperature	42 ± 3°C