

BEARING HEIGHT SCHEDULE

8'-0"

OVERHANG

2'-0"

ROOF PITCH(S)

6/12

NOTES:

- 1) REFER TO HB 91 (RECOMMENDATIONS FOR HANDLING INSTALLATION AND TEMPORARY BRACING) REFER TO ENGINEERED DRAWINGS FOR PERMANENT BRACINGS REQUIRED
- 2) ALL TRUSSES (INCLUDING TRUSSES UNDER VALLEY FRAMING) MUST BE COMPLETELY DECKED OR REFER TO DETAIL V03 FOR ALTERNATE BRACING REQUIREMENTS
- 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER
- 4) ALL TRUSSES ARE DESIGNED FOR 2' O.C. MAXIMUM SPACING, UNLESS OTHERWISE NOTED
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED
- 6) 5/4x2 TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP.
- 7) ALL ROOF TRUSSES HANGERS TO BE SHIP-SON H93/8 UNLESS OTHERWISE NOTED. ALL FLOOR TRUSSES HANGERS TO BE SHIP-SON TRAK412 UNLESS OTHERWISE NOTED
- 8) BEAMING ADHERE/INTEL (HBR) TO BE FURNISHED BY BUILDER

SHOP DRAWING APPROVAL

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND V005 ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS. REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

Accepted Drawing Date: _____

Approved By: _____



PHONE 904.437.3344 FAX 904.437.3444
Bunnell
JACKSONVILLE
PHONE 904.772.6100 FAX 904.772.1473
Lake City
PHONE 904.755.6844 FAX 904.755.7473
Sanford
PHONE 407.322.0094 FAX 407.322.9553

BUILDER: **MARTIN**
CANNON CREEK PLACE
LEGAL ADDRESS: **LOT 39**

MODEL: _____ REVISION: _____
DRAWN BY: **BENJAMIN** SCALE: **NTS**
DATE: **11/27/06** AM **L218303**

