



Donnelly Project #22027



CHALKLEY FAMILY RESIDENCE RENOVATION HIGH SPRINGS, FLORIDA CONSTRUCTION DOCUMENTS

CONTACT INFORMATION:

OWNER:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643

CONTRACTOR:
TANNER CONSTRUCTION
16407 NW 174TH DRIVE, SUITE E
ALACHUA, FLORIDA 32615
PHONE: 386.418.0001

ARCHITECT:
DONNELLY ARCHITECTURE, INCORPORATED
1384 NORTH CITRUS AVENUE
CRYSTAL RIVER, FLORIDA 34428
PHONE: 352.249.1166

PROJECT DESCRIPTION:

CREATION OF A NEW GARAGE IN HIGH SPRINGS, FLORIDA.

SHEET INDEX

A0.00 COVER SHEET AND CONTENTS
A0.05 GENERAL NOTES AND LEGENDS
A0.07 ARCHITECTURAL SITE PLAN
A0.09 DEMOLITION PLAN AND NOTES
A0.10 OVERALL FLOOR PLAN
A0.11 ROOF/ FRAMING/ SLAB PLANS
A0.13 FASTENER SCHEDULE, FRAMING DETAILS
A0.20 EXTERIOR ELEVATIONS
A0.25 BUILDING SECTIONS
A0.29 EXTERIOR WALL DETAILS
A0.35 EXTERIOR OPENING DETAILS
A0.45 ROOF DETAILS
A0.55 STAIR SECTIONS AND DETAILS

A1.05 DIMENSION FLOOR PLAN AND NOTES
A1.10 ENLARGED FLOOR PLANS AND NOTES
A1.21 REFLECTED CEILING PLAN AND NOTES
A3.00 INTERIOR OPENING TYPES AND NOTES

A9.01 OPENING DETAILS WOOD FRAMING
A9.02 OPENING DETAILS WOOD FRAMING
A9.90 PRODUCT APPROVALS
A9.91 PRODUCT APPROVALS
A9.95 TYVEK DETAILS



CHALKLEY FAMILY RESIDENCE RENOVATION *High Springs, Florida*


PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950

Digitally signed by Christopher M. Donnelly
Date: 2024.08.24 12:00:12
-04'00'
JULY 28, 2022

100% CONSTRUCTION
DOCUMENTS

COVER SHEET
AND CONTENTS


A0.00



1

Architectural Site Plan (For information only - site boundary, building location per owner provided survey)

Scale: 1/32" = 1'-0"



CHALKLEY FAMILY
RESIDENCE RENOVATION
High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950





JULY 28, 2022

100% CONSTRUCTION
DOCUMENTS

ARCHITECTURAL
SITE PLAN






A0.07



DEMOLITION PLAN NOTES

1.
- CLEAR AND PREP FOR NEW ADDITION.

DEMOLITION PLAN LEGEND

-  EXISTING WALL TO REMAIN
-  EXISTING DOOR TO REMAIN
-  EXISTING WINDOW TO REMAIN
-  EXISTING WALL, WINDOW, OR DOOR TO BE REMOVED AS SHOWN
-  HATCHED AREAS NOT INCLUDED IN THE SCOPE OF ARCHITECTURAL WORK


- NOTE:
1.
- OWNER HAS FIRST RIGHT OF REFUSAL FOR ALL MATERIALS, EQUIPMENT, AND/OR FIXTURES INDICATED TO BE REMOVED.
2.
- CAP EXISTING ABANDONED PLUMBING IN WALL, FLOOR, OR CEILING. COMPLETELY REMOVE OTHER UTILITIES AS NOTED FOR DEMOLITION. REMOVAL, RELOCATION OF APPLIANCES, EQUIPMENT, FIXTURES, WALLS AS SHOWN.
3.
- CUTTING OF STRUCTURAL MEMBERS AND BEARING WALLS NOT SHOWN ON THESE DRAWINGS SHALL ONLY BE DONE WITH WRITTEN APPROVAL OF THE ENGINEER. USE BRACING AND SHORING WHERE NECESSARY TO MAINTAIN STRUCTURAL INTEGRITY OF THE BUILDING.
4.
- KEEP BUILDING REASONABLY CLEAN AND SWEEP DAILY.
5.
- PROMPTLY REMOVE MATERIALS, RUBBISH, AND DEBRIS FROM THE BUILDING AND PROPERTY.
6.
- PROVIDE CUTTING AND PATCHING OF EXISTING WORK AS REQUIRED. VERIFY EXACT LOCATIONS AND MATERIALS OF EXISTING BEFORE PERFORMING WORK.

CHALKLEY FAMILY

RESIDENCE RENOVATION

High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950




JULY 28, 2022

100% CONSTRUCTION
DOCUMENTS

DEMOLITION PLAN
AND NOTES



A0.09



1

Overall Floor Plan (Shown without tags or dimensions to show completed design intent)

Scale: 1/4" = 1'-0"



**CHALKLEY FAMILY
RESIDENCE RENOVATION**
High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950



JULY 28, 2022


100% CONSTRUCTION
DOCUMENTS

OVERALL
FLOOR PLAN

A0.10


1 Slab Plan

Scale: 1/8" = 1'-0"




3 Roof Plan

Scale: 1/8" = 1'-0"



4 Roof Framing Plan

Scale: 1/8" = 1'-0"



ATTIC VENTILATION CALCULATIONS


ENCLOSED ATTIC SPACE
=1644 SQ FT

1644/300 (FBC-R 806.1) (FBC 1203.2)
=5.5 SQ FT / 2 = 2.75 SQ FT X 144 = 396 SQ IN

396 MINIMUM SQ. IN. OF NET FREE AREA OF EXHAUST NEEDED AT OR NEAR THE RIDGE
396 MINIMUM SQ. IN. OF NET FREE AREA OF INTAKE NEEDED AT OR NEAR THE SOFFIT

IN NO CASE SHOULD THE AMOUNT OF EXHAUST VENTILATION EXCEED THE AMOUNT OF INTAKE VENTILATION.

GAF COBRA RIDGE VENT = 12.5 SQ. IN. / LINEAL FOOT OF RIDGE VENT
OFF-RIDGE VENT = 105 SQ. IN./ 4' OFF-RIDGE VENT
HARDIE VENTED SOFFIT = 5 SQ. IN./ LINEAL FOOT
CERTAINTED VENTED VINYL SOFFIT = 9 SQ. IN./ LINEAL FOOT



ROOF SHEATHING NAILING ZONE:

ROOF SHEATHING NAILING PATTERN:
1. ZONE ① : USE 8D COMMON NAILS AT 6" O.C. AT EDGES AND 6" O.C. INTERMEDIATE.
2. ZONE ② : USE 8D COMMON NAILS AT 4" O.C. (ALL FIELDS)
3. ZONE ③ : USE 8D COMMON NAILS AT 4" O.C. (ALL FIELDS)

GABLE END WALL SHEATHING NAILING PATTERN:
1. SEE ROOF SYSTEM SPECIFICATIONS

ROOF FRAMING PLAN LEGEND:

— — — — — STANDARD WOOD TRUSS
- - - - - WOOD BEAM AS LABELED
- - - - - WOOD FRAMING AS NOTED

ROOF FRAMING PLAN NOTES:

1. THIS ROOF FRAMING PLAN MAY BE ALTERED WITH PRIOR APPROVAL OF ARCHITECT OF RECORD. FINAL ROOF TRUSS CONFIGURATION AND DESIGN WILL BE BY THE TRUSS MANUFACTURER.
2. ALL DIMENSIONS SHOWN ARE MEASURED FROM THE EXTERIOR FACE OF THE BEARING WALL.
3. COORDINATE LOCATION OF ATTIC ACCESS PANELS WITH ARCHITECTURAL FLOOR PLAN AND REFLECTED CEILING PLAN. PANELS SHALL BE A MINIMUM OF 3'-0" LONG X CLEAR WIDTH BETWEEN TRUSSES.

SLAB/ FOUNDATION PLAN NOTES

1. ALL EXTERIOR CONCRETE SLABS SHALL RECEIVE A LIGHT BROOM FINISH UNLESS NOTED OTHERWISE.
2. FIBER MESH REINFORCING MAY BE USED IN LIEU OF W.W.F.
3. STEP FOUNDATIONS WHERE SHOWN AND AS REQUIRED TO AVOID INTERFERENCE WITH OTHER TRADES. SEE TYPICAL STEPPED FOOTING DETAIL.
4. ALL FOOTINGS SHALL BE CENTERED BENEATH BEARING WALLS AND COLUMNS UNLESS OTHERWISE NOTED.

SLAB PLAN LEGEND

EXTERIOR CONCRETE SLAB:
SLOPE SLAB TO DRAIN IN DIRECTION INDICATED BY ARROW.

NOTE:
1. SEE A0.25 FOR FLOOR SYSTEM SPECIFICATIONS.

2020 FLORIDA BUILDING CODE
SECTION 1604 INFORMATION FOR
CHALKLEY RESIDENCE

1. ULTIMATE WIND DESIGN SPEED = 140
NOMINAL DESIGN WIND = 113 MPH
2. I = 1.00
BUILDING CATEGORY II
3. RISK EXPOSURE = C
4. INTERNAL PRESSURE COEFFICIENT= 0.18
5. C&C WIND PRESSURE
ZONE 1 = +15.98/-25.43 PSF
ZONE 2 = +15.98/-44.35 PSF
ZONE 3 = +15.98/-65.56 PSF
ZONE 4 = +17.63/-19.13 PSF
ZONE 5 = +17.63/-23.61 PSF


DESIGN NOTES:

ROOF SHEATHING: SEE ROOF SYSTEM SPECIFICATIONS

ROOF SHEATHING NAILS: SEE ROOF SHEATHING NOTES

GABLE END FASTENERS: SEE ROOF SYSTEM SPECIFICATIONS

TRUSS TO FRAME: SIMPSON H10A




A Plumbing Riser

Scale: NTS

CHALKLEY FAMILY
RESIDENCE RENOVATION
High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950




JULY 28, 2022


100% CONSTRUCTION
DOCUMENTS

ROOF/FRAMING
/SLAB PLANS


A0.11



1 Opening Framing Detail
Scale: 1/2" = 1'-0"



2 Wall Framing Detail
Scale: 1/2" = 1'-0"



A Roof Penetration Detail
Scale: 3/4" = 1'-0"

CONNECTOR SELECTION

SPAN	'A'	'B'	ANCHOR BOLTS
GARAGE DOORS 9'-0" AND UNDER OVER 9'-0"	(2) LSTA24 (1) LSTA24 (2) LSTA24	(2) SP4 * (1) SP4 * (2) SP4 *	(2) EACH END (1) EACH END (1) EACH END

* USE SP6 ON 2X6 WALLS

- NOTES:
- CONNECTORS INDICATED ARE BY SIMPSON STRONG TIE CO., INC. PRE-APPROVED EQUAL MAY BE USED.
 - STANDARD WALL HEIGHT SHOWN WITH PRECUT STUDS. WALL HEIGHT MAY VARY. ADJUST HEAD AND SILL HEIGHT WITH CRIPPLES AS REQUIRED.
 - REFER TO HEADER HOLD DOWN CHART FOR NUMBER OF FULL-LENGTH AND HEADER STUDS REQUIRED FOR DIFFERENT OPENING WIDTHS.

HEADER HOLD DOWNS

UNSUPPORTED WALL HEIGHT	STUD SPACING	MAXIMUM HEADER SPAN (FT.)					
		3	6	9	12	15	18
		NUMBER OF HEADER STUDS SUPPORTING END OF HEADER					
10'-0" OR LESS	12 IN.	2	2	3	3	3	3
	16 IN.	2	2	3	3	3	3
	24 IN.	1	2	2	2	2	2
GREATER THAN 10'-0"	12 IN.	2	2	3	4	5	5
	16 IN.	2	2	3	3	4	4
	24 IN.	1	2	2	2	3	3

TABLE 2304.9.1 FASTENING SCHEDULE (PARTIAL TABLE)		
CONNECTION	FASTENING ^{a,m}	LOCATION
6. SOLE PLATE TO JOIST OR BLOCKING	16d (3-1/2" x 0.135") AT 16" O.C.	TYPICAL FACE NAIL
	3" x 0.131" NAILS AT 8" O.C.	
	3" 14 GAGE STAPLES AT 12" O.C.	
SOLE PLATE TO JOIST OR BLOCKING AT BRACED	3 - 16d (3-1/2" x 0.135") AT 16" O.C.	BRACED WALL PANELS
	4 - 3" x 0.131" NAILS AT 16" O.C.	
	4 - 3" 14 GAGE STAPLES AT 16" O.C.	
7. TOP PLATE TO STUD	2 - 16d COMMON (3-1/2" x 0.162")	END NAIL
	3 - 3" x 0.131" NAILS	
	3 - 3" 14 GAGE STAPLES	
8. STUD TO SOLE PLATE	4 - 8d COMMON (2-1/2" x 0.131")	TOENAIL
	4 - 3" x 0.131" NAILS	
	3 - 3" 14 GAGE STAPLES	
	2 - 16d COMMON (3-1/2" x 0.162")	END NAIL
	3 - 3" x 0.131" NAILS	
	3 - 3" 14 GAGE STAPLES	
9. DOUBLE STUDS	16d (3-1/2" x 0.135") AT 24" O.C.	FACE NAIL
	3" x 0.131" NAIL AT 8" O.C.	
	3" 14 GAGE STAPLE AT 8" O.C.	
10. DOUBLE TOP PLATES	16d (3-1/2" x 0.135") AT 16" O.C.	TYPICAL FACE NAIL
	3" x 0.131" NAIL AT 12" O.C.	
	3" 14 GAGE STAPLE AT 12" O.C.	
DOUBLE TOP PLATES	8 - 16d COMMON (3-1/2" x 0.162")	LAP SPLICE
	12 - 3" x 0.131" NAILS	
	12 - 3" 14 GAGE STAPLES	
13. TOP PLATES, LAPS AND INTERSECTIONS	2 - 16d COMMON (3-1/2" x 0.162")	FACE NAIL
	3 - 3" x 0.131" NAILS	
	3 - 3" 14 GAGE STAPLES	
16. CONTINUOUS HEADER TO STUD	4 - 8d COMMON (2-1/2" x 0.131")	TOENAIL
19. RAFTER TO PLATE (SEE SECTION 2308.10.1, TABLE 2308.10.1)	3 - 8d COMMON (2-1/2" x 0.131")	TOENAIL
	3 - 3" x 0.131" NAILS	
	3 - 3" 14 GAGE STAPLES	
23. BUILT-UP CORNER STUDS	16d COMMON (3-1/2" x 0.162")	24" O.C.
	3" x 0.131" NAILS	16" O.C.
	3" 14 GAGE STAPLES	16" O.C.
24. BUILT-UP GIRDER AND BEAMS	20d COMMON (4" x 0.192") 32" O.C.	FACE NAIL AT TOP AND BOTTOM STAGGERED ON OPPOSITE SIDES
	3" x 0.131" NAIL AT 24" O.C.	
	3" 14 GAGE STAPLE AT 24" O.C.	
	2 - 20d COMMON (4" x 0.192")	FACE NAIL AT ENDS AND AT EACH SPLICE
	3 - 3" x 0.131" NAILS	
	3 - 3" 14 GAGE STAPLES	

- NOTES:
- FOR SI: 1 INCH = 25.4 MM.
- COMMON OR BOX NAILS ARE PERMITTED TO BE USED EXCEPT WHERE OTHERWISE STATED.
 - NAILS SPACED AT 6 INCHES ON CENTER AT EDGES, 12 INCHES AT INTERMEDIATE SUPPORTS EXCEPT 6 INCHES AT SUPPORTS WHERE SPANS ARE 48 INCHES OR MORE. FOR NAILING OF WOOD STRUCTURAL PANEL AND PARTICLEBOARD DIAPHRAGMS AND SHEAR WALLS, REFER TO SECTION 2305. NAILS FOR WALL SHEATHING ARE PERMITTED TO BE COMMON, BOX OR CASING.
 - COMMON OR DEFORMED SHANK (6D - 2" x 0.113"; 8D - 2 1/2" x 0.131"; 10D - 3" x 0.148").
 - COMMON (6D - 2" x 0.113"; 8D - 2 1/2" x 0.131"; 10D - 3" x 0.148").
 - DEFORMED SHANK (6D - 2" x 0.113"; 8D - 2 1/2" x 0.131"; 10D - 3" x 0.148").
 - CORROSION-RESISTANT SIDING (6D - 17/8" x 0.106"; 8D - 23/8" x 0.128") OR CASING (6D - 2" x 0.099"; 8D - 2 1/2" x 0.113") NAIL.
 - FASTENERS SPACED 3 INCHES ON CENTER AT EXTERIOR EDGES AND 6 INCHES ON CENTER AT INTERMEDIATE SUPPORTS, WHEN USED AS STRUCTURAL SHEATHING. SPACING SHALL BE 6 INCHES ON CENTER ON THE EDGES AND 12 INCHES ON CENTER AT INTERMEDIATE SUPPORTS FOR NONSTRUCTURAL APPLICATIONS.
 - CORROSION-RESISTANT ROOFING NAILS WITH 7/16-INCH-DIAMETER HEAD AND 11/2-INCH LENGTH FOR 1/2-INCH SHEATHING AND 13/4-INCH LENGTH FOR 25/32-INCH SHEATHING.
 - CORROSION-RESISTANT STAPLES WITH NOMINAL 7/16-INCH CROWN OR 1-INCH CROWN AND 11/4-INCH LENGTH FOR 1/2-INCH SHEATHING AND 11/2-INCH LENGTH FOR 25/32-INCH SHEATHING. PANEL SUPPORTS AT 16 INCHES (20 INCHES IF STRENGTH AXIS IN THE LONG DIRECTION OF THE PANEL, UNLESS OTHERWISE MARKED).
 - CASING (1 1/2" x 0.080") OR FINISH (1 1/2" x 0.072") NAILS SPACED 6 INCHES ON PANEL EDGES, 12 INCHES AT INTERMEDIATE SUPPORTS.
 - PANEL SUPPORTS AT 24 INCHES. CASING OR FINISH NAILS SPACED 6 INCHES ON PANEL EDGES, 12 INCHES AT INTERMEDIATE SUPPORTS.
 - FOR ROOF SHEATHING APPLICATIONS, 8D NAILS (21/2" x 0.113") ARE THE MINIMUM REQUIRED FOR WOOD STRUCTURAL PANELS.
 - STAPLES SHALL HAVE A MINIMUM CROWN WIDTH OF 7/16 INCH.
 - FOR ROOF SHEATHING APPLICATIONS, FASTENERS SPACED 4 INCHES ON CENTER AT EDGES, 8 INCHES AT INTERMEDIATE SUPPORTS.
 - FASTENERS SPACED 4 INCHES ON CENTER AT EDGES, 8 INCHES AT INTERMEDIATE SUPPORTS FOR SUBFLOOR AND WALL SHEATHING AND 3 INCHES ON CENTER AT EDGES, 6 INCHES AT INTERMEDIATE SUPPORTS FOR ROOF SHEATHING.
 - FASTENERS SPACED 4 INCHES ON CENTER AT EDGES, 8 INCHES AT INTERMEDIATE SUPPORTS.

SIMPSON CONNECTOR FASTENER SCHEDULE:		
CONNECTOR:	FASTENERS:	PRODUCT APPROVAL #:
H10A	(9) 10D X 1 1/2" AT RAFTER/TRUSS, AND AT PLATES	FL# 10456.5
H2.5	(5) 8D AT RAFTER/TRUSS, AND AT PLATES	FL# 10456.5
A35	(12) 8D X 1 1/2"	FL# 10446.1
LSTA 24	(18) 10D	FL# 10456.15
SP4	(6) 10D X 1 1/2"	FL# 13872.21
VTOR (VALLEY CONNECTOR)	(4) 10D AT SLEEPER, (3) 10D X 1 1/2" AT RAFTER	FL# 10447.18

CHALKLEY FAMILY
RESIDENCE RENOVATION
High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950




JULY 28, 2022

100% CONSTRUCTION
DOCUMENTS

FASTENER SCHEDULE,
FRAMING DETAILS


A0.13




1 North Elevation
Scale: 1/4" = 1'-0"



2 West Elevation
Scale: 1/4" = 1'-0"



3 South Elevation
Scale: 1/4" = 1'-0"



4 East Elevation
Scale: 1/4" = 1'-0"

ELEVATION NOTES:

1. PROVIDE MINIMUM 6" ADDRESS NUMBERS ON FRONT ELEVATION, VISIBLE FROM THE STREET.
2. SEE A0.25 FOR BUILDING SECTIONS AND EXTERIOR BUILDING SYSTEM SPECIFICATIONS.
3. WHERE EXTERIOR FINISHES AND COLORS ARE INDICATED, TRANSITIONS SHALL OCCUR AT INSIDE CORNERS OR TRIMS, UNLESS NOTED OTHERWISE.

CHALKLEY FAMILY
RESIDENCE RENOVATION
High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950



JULY 28, 2022

100% CONSTRUCTION
DOCUMENTS

EXTERIOR
ELEVATIONS

A0.20

CHALKLEY FAMILY
RESIDENCE RENOVATION
High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950




JULY 28, 2022

100% CONSTRUCTION
DOCUMENTS

BUILDING
SECTIONS

A0.25



ROOF SYSTEM SPECIFICATIONS							
CODE	SYSTEM	MANUFACTURER/ PRODUCT SELECTION	SUBSTRATE	FLASHING	ROOF/ ATTIC VENTILATION SYSTEM	SOFFIT SYSTEM	INSULATION SYSTEM
SH-1	SHINGLE ROOF SYSTEM	EQUAL TO GAF TIMBERLINE HDZ ON TWO LAYERS SELF-ADHERING SHEET WATERPROOFING. INSTALLED PER FL#10124.1. COLOR TO BE SELECTED FROM MANUFACTURER'S FULL LINE OF STANDARD COLORS. (LIFETIME MATERIAL DEFECT WARRANTY, 15 YEAR WIND COVERAGE, WIND COVERAGE WITH NO MAXIMUM WIND SPEED)	ROOF SHEATHING SHALL BE EXTERIOR EXPOSURE: 5/8" PLYWOOD OSB. 3/4" WITH H-CLIPS. SEE ROOF SHEATHING NOTES ON SHEET A0.41 FOR FASTENER TYPE AND SPACING. SEE EXTERIOR WALL SYSTEM SPECIFICATIONS FOR GABLE END SHEATHING AND FASTENER TYPE AND SPACING.	0.032 INCH (0.8 MM) ALUMINUM SHEET, COMPLYING WITH ASTM B 209. USE METAL FLASHINGS AT EAVE EDGES, RAKE EDGES, STEP FLASHING AT CHIMNEYS, SIDE WALLS AND DORMERS. VALLEYS SHALL HAVE LEAK BARRIER AT LEAST 36 INCHES WIDE CENTERED ON VALLEY; LAP ENDS 8 INCHES (203 MM) AND SEAL.	RIDGE VENT SHALL BE FLEXIBLE RIDGE VENTILATOR DESIGNED TO ALLOW THE PASSAGE OF AIR FROM ATTICS. COBRA RIDGE VENT, BY GAF-ELK OR APPROVED EQUAL.	VINYL SOFFIT EQUAL TO CERTAINTED VINYL SOFFIT (VENTED) INSTALLED PER FL#13389.1. CEMENTITIOUS SOFFIT EQUAL TO HARDIE SOFFIT PANELS NON-VENTED INSTALLED PER FL#13265.	R-38 BATTS (12" THICKNESS) EQUAL TO OWENS CORNING ECOTOUCH

- FASCIA:
1. PRESSURE TREATED 2X8.
 2. PROVIDE ALUMINUM PAINTED FASCIA WRAPS.

FLOOR SYSTEM SPECIFICATIONS				
CODE	SYSTEM	SPECIFICATION	VAPOR BARRIER	INSULATION
FS-1	CONCRETE SLAB ON GRADE	CONCRETE SLAB WITH 6"x6" W1.4XW1.4 W.W.F. OR FIBER MESH REINFORCING ON VAPOR BARRIER ON CLEAN, TREATED AND COMPACTED FILL. CAST IN PLACE CONCRETE SHALL HAVE A 28 DAY COMPRESSIVE STRENGTH OF 3,000 PSI AND SHALL BE REINFORCED AS SHOWN. CONCRETE REINFORCING BARS SHALL CONFORM TO ASTM615, GRADE 60. STEP FOUNDATIONS WHERE SHOWN AND AS REQUIRED TO AVOID INTERFERENCE WITH OTHER TRADES. SEE TYPICAL STEPPED FOOTING DETAIL.	MINIMUM 6 MIL. CONTINUOUS SHEET VAPOR BARRIER	N/A

EXTERIOR WALL SYSTEM SPECIFICATIONS						
CODE	SYSTEM	MANUFACTURER/ PRODUCT SELECTION	PAINT	WEATHER RESISTIVE BARRIER	SUBSTRATE	INSULATION
CS-1	CEMENTITIOUS SIDING	LAP SIDING EQUAL TO HARDIE 7 1/2" CEDARMILL PLANK WITH 6" EXPOSURE INSTALLED PER FL#13192.2.	EQUAL TO SHERWIN WILLIAMS 3 COAT SYSTEM. FIRST COAT: S-W LOXON EXTERIOR ACRYLIC MASONRY PRIMER. SECOND, THIRD COATS: S-W A-100 EXTERIOR LATEX SATIN	BUILDING WRAP EQUAL TO DUPONT TYVEK COMMERCIAL WRAP	WALL SHEATHING SHALL BE EXTERIOR EXPOSURE: 5/8" PLYWOOD OR 3/4" OSB. 3/4" WITH 6D COMMON NAILS AT 6" O.C. EDGES AND FIELD ON 2X4 FRAMING AT 16" O.C. WITH MID-HEIGHT BLOCKING "NO. 2" GRADE, STRESS RATED SOUTHERN PINE OR APPROVED EQUIVALENT.	MINIMUM R-13 (3 1/2" THICKNESS) EQUAL TO OWENS CORNING ECOTOUCH
CS-5	CEMENTITIOUS SIDING	PANEL SIDING EQUAL TO HARDIE PANEL SMOOTH INSTALLED PER FL#13223.2. PROVIDE 2 1/8" BATTEN STRIPS FOR BOARD AND BATTEN SIDING.			TREAT ALL ITEMS IN CONTACT WITH CONCRETE OR MASONRY, WOOD CANTS, NAILERS, CURBS, EQUIPMENT SUPPORT BASES, BLOCKING, STRIPPING, AND SIMILAR MEMBERS IN CONNECTION WITH ROOFING, FLASHING, VAPOR BARRIERS, AND WATERPROOFING. WOOD SILLS, SLEEPERS, BLOCKING, FURRING, STRIPPING, AND SIMILAR CONCEALED MEMBERS IN CONTACT WITH MASONRY OR CONCRETE. WOOD FRAMING MEMBERS LESS THAN 18 INCHES ABOVE GRADE. TREATED LUMBER IS NOT REQUIRED ABOVE TREATED BOTTOM PLATE FOR FRAMING WHICH IS BEARING ON CONCRETE FLOOR SLAB ON GRADE AND FOR WOOD FLOOR PLATES INSTALLED ON CONCRETE SLABS. IF CUT AFTER TREATMENT, COAT CUT SURFACES TO COMPLY WITH AWP4 M4.	INSULATION SUB CONTRACTOR SHALL PROVIDE ARCHITECT AN INSULATION CERTIFICATE STATING TYPE AND INSULATION R-VALUE OF INSTALLED INSULATION FOR ALL AREAS AND TYPES.

CHALKLEY FAMILY

RESIDENCE RENOVATION

High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950




JULY 28, 2022


100% CONSTRUCTION
DOCUMENTS

EXTERIOR OPENING
DETAILS


A0.35



1 Exterior Opening Detail - Pre-Hung Door
Scale: 1-1/2" = 1'-0"



2 Exterior Opening Detail - Vinyl Window
Scale: 1-1/2" = 1'-0"



4 Exterior Opening Detail - Garage Door
Scale: 1-1/2" = 1'-0"

CHALKLEY FAMILY
RESIDENCE RENOVATION
High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950




JULY 28, 2022


100% CONSTRUCTION
DOCUMENTS

ROOF
DETAILS


A0.45





A Roof Penetration Detail
Scale: 3/4" = 1'-0"




A Shingle Installation Detail
Scale: NTS




B Valley Flashing Detail
Scale: NTS




C Step Flashing Shingle Installation Detail
Scale: NTS



E Shingle Sealant Detail
Scale: NTS



D Wall Step Flashing Detail
Scale: NTS



CHALKLEY FAMILY
RESIDENCE RENOVATION
High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950



JULY 28, 2022

100% CONSTRUCTION
DOCUMENTS

DIMENSION FLOOR
PLAN AND NOTES

A1.01

CHALKLEY FAMILY
RESIDENCE RENOVATION
High Springs, Florida

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950




JULY 28, 2022


100% CONSTRUCTION
DOCUMENTS

ENLARGED FLOOR
PLANS AND NOTES


A1.10




1 Enlarged Floor Plan
Scale: 1/2" = 1'-0"




2 Interior Elevation
Scale: 1/2" = 1'-0"




3 Interior Elevation
Scale: 1/2" = 1'-0"



4 Interior Elevation
Scale: 1/2" = 1'-0"




5 Interior Elevation
Scale: 1/2" = 1'-0"





REFLECTED CEILING PLAN LEGEND:	
GB-1	SOFFIT PER ROOF SYSTEM SPECIFICATIONS
1'x4' SURFACE MOUNTED FIXTURE	RECESSED CAN LIGHT FIXTURE
FLOOD LIGHT	WALL MOUNTED LIGHT FIXTURE
SUPPLY GRILLE	CEILING MOUNTED LIGHT FIXTURE
RETURN GRILLE	EXHAUST FAN
ATTIC ACCESS	CEILING FAN
SMOKE DETECTOR	ELECTRICAL PANEL
CARBON MONOXIDE DETECTOR	

POWER/ SYSTEMS PLAN LEGEND:	
DUPLEX OUTLET	DATA/ TELEPHONE
DUPLEX OUTLET, MOUNT AT 42" AFF	CATV/ SATV
GFI GROUND FAULT INTERRUPTED OUTLET	WALL SWITCH

NOTE: PROVIDE ARC FAULT RECEPTACLES FOR ALL 15 AND 20 AMP BRANCH CIRCUITS





EXTERIOR OPENING NOTES:

- VINYL WINDOWS SHALL BE EQUAL TO PGT 5400, OR APPROVED EQUAL INSTALLED PER FL#1435.4 WITH A U-FACTOR OF 0.30 AND A SOLAR HEAT GAIN COEFFICIENT OF 0.25.
 - PRE HUNG EXTERIOR FIBERGLASS DOORS SHALL BE EQUAL TO THERMA-TRU SMOOTH STAR OR CLASSIC CRAFT SERIES INSTALLED PER FL#5891 (SINGLE DOOR) OR FL#7347 (DOUBLE DOOR). (U-VALUE 0.30, SHGC 0.28 MIN.)
 - GARAGE DOORS SHALL BE EQUAL TO WAYNE-DALTON THERMOSPAN 150 INSTALLED PER FL#10958 OR WAYNE DALTON MODEL 8300 INSTALLED PER FL#10737. (U-VALUE 0.08 MIN.)
- * NOTE: PROVIDE LABEL AT EACH EXTERIOR OPENING LISTING MANUFACTURER, MODEL, PRODUCT APPROVAL NUMBER, AND U-FACTOR

- NOTES:
- GLASS SHALL BE TEMPERED IN LOCATIONS REQUIRED BY FLORIDA BUILDING CODE SECTION 2406:
- GLAZING IN DOORS: GLAZING IN ALL FIXED AND OPERABLE PANELS OF SWINGING, SLIDING, AND BIFOLD DOORS SHALL BE CONSIDERED A HAZARDOUS LOCATION. EXCEPTIONS: DECORATIVE GLAZING; GLAZED OPENINGS OF A SIZE THROUGH WHICH A 3- INCH DIAMETER (76 MM) SPHERE IS UNABLE TO PASS.
 - GLAZING ADJACENT TO DOORS: GLAZING IN AN INDIVIDUAL FIXED OR OPERABLE PANEL ADJACENT TO A DOOR WHERE THE NEAREST VERTICAL EDGE OF THE GLAZING IS WITHIN A 24-INCH (610 MM) ARC OF EITHER VERTICAL EDGE OF THE DOOR IN A CLOSED POSITION AND WHERE THE BOTTOM EXPOSED EDGE OF THE GLAZING IS LESS THAN 60 INCHES (1524 MM) ABOVE THE WALKING SURFACE SHALL BE CONSIDERED A HAZARDOUS LOCATION. EXCEPTIONS: DECORATIVE GLAZING; WHERE THERE IS AN INTERVENING WALL OR OTHER PERMANENT BARRIER BETWEEN THE DOOR AND GLAZING; WHERE ACCESS THROUGH THE DOOR IS TO A CLOSET OR STORAGE AREA 3 FEET (914 MM) OR LESS IN DEPTH; GLAZING IN THIS APPLICATION SHALL COMPLY WITH SECTION 2406.4.3.
 - GLAZING IN WALLS: GLAZING IN WALLS ON THE LATCH SIDE OF AND PERPENDICULAR TO THE PLANE OF THE DOOR IN A CLOSED POSITION IN ONE- AND TWO-FAMILY DWELLINGS OR WITHIN DWELLING UNITS IN GROUP R-2.
 - GLAZING IN WINDOWS: GLAZING IN AN INDIVIDUAL FIXED OR OPERABLE PANEL THAT MEETS ALL OF THE FOLLOWING CONDITIONS SHALL BE CONSIDERED A HAZARDOUS LOCATION: THE EXPOSED AREA OF AN INDIVIDUAL PANE IS GREATER THAN 9 SQUARE FEET (0.84 M2); THE BOTTOM EDGE OF THE GLAZING IS LESS THAN 18 INCHES (457 MM) ABOVE THE FLOOR; THE TOP EDGE OF THE GLAZING IS GREATER THAN 36 INCHES (914 MM) ABOVE THE FLOOR; AND ONE OR MORE WALKING SURFACE(S) ARE WITHIN 36 INCHES (914 MM), MEASURED HORIZONTALLY AND IN A STRAIGHT LINE, OF THE PLANE OF THE GLAZING. EXCEPTIONS: DECORATIVE GLAZING; WHERE A HORIZONTAL RAIL IS INSTALLED ON THE ACCESSIBLE SIDE(S) OF THE GLAZING 34 TO 38 INCHES (864 TO 965 MM) ABOVE THE WALKING SURFACE (THE RAIL SHALL BE CAPABLE OF WITHSTANDING A HORIZONTAL LOAD OF 50 POUNDS PER LINEAR FOOT (730 N/M) WITHOUT CONTACTING THE GLASS AND BE A MINIMUM OF 1 1/2 INCHES (38 MM) IN CROSS-SECTIONAL HEIGHT); OUTBOARD PANES IN INSULATING GLASS UNITS OR MULTIPLE GLAZING WHERE THE BOTTOM EXPOSED EDGE OF THE GLASS IS 25 FEET (7620 MM) OR MORE ABOVE ANY GRADE, ROOF, WALKING SURFACE OR OTHER HORIZONTAL OR SLOPED (WITHIN 45 DEGREES OF HORIZONTAL) (0.78 RAD) SURFACE ADJACENT TO THE GLASS EXTERIOR.
 - GLAZING AND WET SURFACES: GLAZING IN WALLS, ENCLOSURES OR FENCES CONTAINING OR FACING HOT TUBS, SPAS, WHIRLPOOLS, SAUNAS, STEAM ROOMS, BATHTUBS, SHOWERS AND INDOOR OR OUTDOOR SWIMMING POOLS WHERE THE BOTTOM EXPOSED EDGE OF THE GLAZING IS LESS THAN 60 INCHES (1524 MM) MEASURED VERTICALLY ABOVE ANY STANDING OR WALKING SURFACE SHALL BE CONSIDERED A HAZARDOUS LOCATION. THIS SHALL APPLY TO SINGLE GLAZING AND ALL PANES IN MULTIPLE GLAZING. EXCEPTION: GLAZING THAT IS MORE THAN 60 INCHES (1524 MM), MEASURED HORIZONTALLY AND IN A STRAIGHT LINE, FROM THE WATER'S EDGE OF A BATHTUB, HOT TUB, SPA, WHIRLPOOL, OR SWIMMING POOL.
 - GLAZING ADJACENT TO STAIRS AND RAMPS: GLAZING WHERE THE BOTTOM EXPOSED EDGE OF THE GLAZING IS LESS THAN 60 INCHES (1524 MM) ABOVE THE PLANE OF THE ADJACENT WALKING SURFACE OF STAIRWAYS, LANDINGS BETWEEN FLIGHTS OF STAIRS, AND RAMPS SHALL BE CONSIDERED A HAZARDOUS LOCATION. EXCEPTIONS: THE SIDE OF A STAIRWAY, LANDING OR RAMP THAT HAS A GUARD COMPLYING WITH THE PROVISIONS OF SECTIONS 1013 AND 1607.8, AND THE PLANE OF THE GLASS IS GREATER THAN 18 INCHES (457 MM) FROM THE RAILING; GLAZING 36 INCHES (914 MM) OR MORE MEASURED HORIZONTALLY FROM THE WALKING SURFACE; GLAZING ADJACENT TO THE BOTTOM STAIR LANDING.
 - GLAZING ADJACENT TO THE LANDING AT THE BOTTOM OF A STAIRWAY WHERE THE GLAZING IS LESS THAN 36 INCHES (914 MM) ABOVE THE LANDING AND WITHIN 60 INCHES (1524 MM) HORIZONTALLY OF THE BOTTOM TREAD SHALL BE CONSIDERED A HAZARDOUS LOCATION. EXCEPTION: GLAZING THAT IS PROTECTED BY A GUARD COMPLYING WITH SECTIONS 1013 AND 1607.8 WHERE THE PLANE OF THE GLASS IS GREATER THAN 18 INCHES (457 MM) FROM THE GUARD.

CHALKLEY FAMILY RESIDENCE RENOVATION *High Springs, Florida*

PROJECT LOCATION:
CHALKLEY RESIDENCE
147 SOUTHWEST GREY WAY
HIGH SPRINGS, FLORIDA 32643
FLORIDA ARCHITECT AR 92950



JULY 28, 2022

100% CONSTRUCTION
DOCUMENTS

INTERIOR OPENING
TYPES AND NOTES

A3.00

6.3 PRE-WINDOW-INSTALLATION INSPECTION

6.3.1 Before window installation, the installer shall inspect the WRB to ensure that it is installed in accordance with this standard practice and the WRB manufacturer's instructions. Any tears, penetrations or defects within 305 mm (12 in) of the rough opening area shall be sealed per the WRB manufacturer's instructions.

6.3.2 The installer shall verify that the rough opening is plumb, level, square, and true. The installer shall notify the contractor to remedy any discrepancies per this standard practice.

6.3.3 Installer shall inspect the fenestration product for damage and repair or replace if necessary.

7.0 WINDOW INSTALLATION PROCEDURES

7.1 PREPARATION OF WRB

This practice recommends that the underside of the WRB be sealed at the rough opening, per discussion in Section 6.2.4. There are a variety of ways to do this successfully. Three representative methods are as follows:

7.1.1 WRB Method A

Box cut WRB around rough opening, seal with 100 mm or 150 mm (4 in or 6 in) self-adhered flashing between the jamb corner at the head, such that self-adhered flashing covers 50 mm (2 in) on the WRB as well as into the rough opening, return at least to the depth of the window, and the sill (see Figure 1). Apply sealant at jamb/head interface (see Figure 2). See Schematic 1 for jamb detail.




FIGURE 1





FIGURE 2



Schematic 1 (Top View)

FMA/AAMA 100-12

Page 6

7.3 INSTALLATION OF WINDOW INTO ROUGH OPENING

7.3.1 Inspect and clean the back side (interior surface) of the exterior window mounting flange. Look for any sealant gaps or misaligned welding (particularly for vinyl products) at the corner joinery. If corner seals of the flange are missing in whole or part, contact the window manufacturer for the recommended remedy.

7.3.2 After cleaning the mounting flange, carefully run a continuous 9 mm (3/8 in) nominal diameter bead of sealant on the back surface (interior face) of the mounting fin (see Figure 12) of window at the head and both jambs. Apply sealant in line with any pre-punched holes or slots in the mounting flange. Connect that bead of sealant across any joinery on the window frame at all four corners. As an option, the sealant shall be permitted to be applied to the wall surface as opposed to the back of the mounting flange.



FIGURE 12

7.3.3 Apply a discontinuous bead of sealant on the interior surface of the mounting flange at the sill. The bead of sealant shall be discontinuous, leaving two 50 mm (2 in) voids within 100 mm (4 in) of each jamb (see Figure 13). Any alternative to the discontinuity in the bead of sealant at the exterior sill area shall be approved by the window manufacturer.



FIGURE 13

FMA/AAMA 100-12

Page 11

7.5.5 Apply a continuous 9 mm (3/8 in) nominal diameter bead of sealant along the head. Apply an additional 9 mm (3/8 in) nominal diameter bead of sealant horizontally 216 mm (8 1/2 in) above the rough opening in line with the top of the jamb flashing (see Figure 22) or as a sloped roof design (see Figure 22A).

7.5.6 Apply mechanically attached flashing to head over sealant and secure with mechanical fasteners (see Figure 23).



FIGURE 22



FIGURE 22A

7.5.6.1 Use fasteners (in accordance with the flashing manufacturer's recommendations) to secure mechanically attached flashing at the head. (see Figure 23). Cover fasteners with WRB or sealant whenever possible.



FIGURE 23

7.6 The following steps apply when using both self-adhering and mechanically attached flashing.

Remove the previously applied tape which holds the flap of the water-resistive barrier at the head. Allow the flap to lay flat over the flashing. Apply a new piece of sheathing tape or 100 mm (4 in) self-adhering flashing over the WRB flap and the entire diagonal cut made in the water-resistive barrier. The tape should be compressed against the WRB and the head flashing, which extends over the jamb (see Figure 24). Placing discontinuous lengths of tape across the width of the head seam between the WRB and the head flashing is acceptable, but may result in increased air infiltration around the WRB.

FMA/AAMA 100-12

Page 16

7.1.2 WRB Method B Integration after Window is Installed (per Section 7.3.6)

Box cut WRB around rough opening and make cut 150 mm (6 in) onto the face of the wall at each jamb corner and fold back jamb as with head flap ensuring that the jamb cuts at the sill are angled upwards (Figure 3). After the window is installed (per Section 7.3.6), apply sealant along jamb and fold over the previously folded over WRB jamb flap allowing it to integrate with the window frame (see Figures 4 and 4A). Press down on sealant bead below WRB. Integrate WRB to the window with sheathing tape or self-adhering flashing. See Schematic 2 for jamb detail.




FIGURE 3



FIGURE 4





FIGURE 4A



Schematic 2

7.1.3 WRB Method C

Full I-Cut of WRB (see Figure 5) or modified I-Cut (Figure 5A), Apply sealant onto sheathing under WRB at jambs (Figure 6), and wrap into cavity and secure (Figure 7). Attach the WRB into position on the inside of the rough opening, and trim any excess as required (Figure 8). Press down on sealant bead below WRB. See Schematic 3 for jamb detail.

FMA/AAMA 100-12

Page 7

7.3.4 If a rigid or semi-rigid sill pan is used, apply a continuous bead of sealant to the outboard side of the upturned leg of the sill pan where it will integrate with the interior side of the window and form an air/water seal (Figure 14).



FIGURE 14

7.3.5 Immediately set the window in the opening (see Figure 15).



FIGURE 15

7.3.6 Hold the window temporarily into position and apply shims as required to ensure the window is set plumb, level, square and true. Fasten the window perimeter securely into position in accordance with the manufacturer's instructions.

NOTE 1: Additional fasteners may be required at locations such as locking mechanism or hinges, per manufacturer's instructions.

7.3.6.1 For proper sealant coverage, ensure squeeze out under flange and in fastener holes (see Figure 16).

7.3.7 Install shims in such a manner that they are not permitted to interfere with the application of the air seal, which will be applied on the interior side in the steps that follow.

FMA/AAMA 100-12

Page 12




FIGURE 24

7.7 At the interior, using a sealant recommended in Section 5.4 and appropriate bond breakers or backer rod, apply a bead of sealant (see Figures 25 and 26), or low expansion aerosol foam sealant conforming to Section 5.4.4 (see Figure 27), or other window manufacturer approved material between the window and the rough opening on all sides to form a continuous air seal.




FIGURE 25




FIGURE 26

FMA/AAMA 100-12

Page 17




FIGURE 5




FIGURE 5A




FIGURE 6




FIGURE 7



FIGURE 8



FIGURE 8A




FIGURE 8B




FIGURE 8C



FIGURE 8D



FIGURE 8E




FIGURE 8F




FIGURE 8G




FIGURE 8H




FIGURE 8I




FIGURE 8J




FIGURE 8K




FIGURE 8L




FIGURE 8M



FIGURE 8N



FIGURE 8O




FIGURE 8P




FIGURE 8Q



FIGURE 8R




FIGURE 8S




FIGURE 8T




FIGURE 8U

FMA/AAMA 100-12

Page 18





FIGURE 8



Schematic 3

7.1.4 For all WRB Wrap methods

At the head of the opening, starting at the top corner of the exterior window (rough) opening, measure from the corner horizontal and then vertical a distance equal to the roll width of the flashing to be applied. At a 45° angle, carefully cut the WRB on a diagonal (see Figure 9). Repeat this step on the opposite corner. Trim 25 mm (1 in) off the bottom of the WRB head flap for proper integration with the head flange of the window. Raise the bottom edge of the flap created in the WRB up and temporarily tape to the exterior face of the WRB above (Figure 10). This is done in order to allow for installation of the exterior window and head flashing later.

FMA/AAMA 100-12

Page 9

Do not interfere with the WRB flap at the head. Tuck the top of the jamb flashing under the flap of the water-resistive barrier at the head.

7.4.4 Use firm pressure to apply the self-adhering flashing to promote seal to window flange and WRB. Use of a J-Roller is recommended.

7.4.5 Apply a piece of flashing across the head of the rough opening. The head flashing shall be cut to the width of the rough opening plus two times the roll width of the flashing, plus 50 mm (2 in).

7.4.6 Adhere the self-adhering flashing with firm pressure (use of a J-Roller is recommended) across the head of the window on top of the mounting flange and beyond the rough opening on each side extending it 50 mm (2 in) over the outside edge of the flashing at the jambs (see Figure 18).



FIGURE 18

7.4.7 Remove the previously applied tape which holds the flap of the water-resistive barrier at the head. Allow the flap to lay flat over the head flashing. Apply a new piece of sheathing tape or 100 mm (4 in) self-adhering flashing over the WRB flap and the entire diagonal cut made in the water-resistive barrier. The tape should be compressed against the WRB and the head flashing, which extends over the jamb (see Figure 19). Placing discontinuous lengths of tape across the width of the head seam between the WRB and the head flashing is acceptable, but may result in increased air infiltration around the WRB.



FIGURE 19

FMA/AAMA 100-12

Page 14



FIGURE 29

7.7.3 To ensure adequate protection against extreme wind driven water, it is critical that the perimeter interior air and water seal between the window and the sill pan flashing is able to withstand this pressure load without air and water leakage. Special caution needs to be used when applying perimeter air and water seals to the interior corners.

8.0 POST INSTALLATION PROCEDURES

8.1 Verify that the window frame and sash are installed plumb, level, square and true, within the specified tolerances (see Section 6.0).

8.2 Check of Operable Elements - Verify that the operable sashes move freely within their frames and that weather stripping or compressible seals make full contact with mating surfaces.

8.3 Verify that operable hardware such as locks, cranks, latches and hinges operate smoothly and that all locking mechanisms engage and operate properly.

8.4 Verify that all accessories and other components of the fenestration product assembly are present, such as screens and hardware as applicable.

8.5 Verify that Drainage holes are free from any blockages or obstructions.

9.0 KEYWORDS

9.1 Flashing; Sealant; Sill pans; Water-resistive barrier (WRB); Window; Installation; Mount flanges; Air seal.

FMA/AAMA 100-12

Page 19




FIGURE 9




FIGURE 10

7.2 APPLYING A SILL PAN FLASHING

7.2.1 Ensure that the rough opening wood sill area is clean and free of debris.

7.2.2 There are a variety of sill pan systems available. The pan flashing shall direct water to the exterior or to the membrane drainage plane for subsequent drainage to the exterior of the building.

7.2.3 When self-adhering flashing is used as a sill pan, cut to a length equal to the rough opening width plus at least 300 mm (12 in), such that 150 mm (6 in) minimum is used at each jamb to form end dams (See Figure 11).




FIGURE 11

The self-adhering flashing sill pan system shall cover the sill to at least the depth of the window, plus at least 50 mm (2 in), but not more than 75 mm (3 in), which shall lap onto the face of the WRB drainage plane. The 75 mm (3 in) maximum is specified to ensure that jamb flashing of 100 mm (4 in) width will adequately lap over the sill flashing.

7.2.4 If a rigid or semi-rigid sill pan system is used, follow the manufacturer's instructions for installation details and integration with the WRB and flashing.

FMA/AAMA 100-12

Page 10

7.5 JAMB AND HEAD FLASHING USING MECHANICALLY ATTACHED FLASHING

7.5.1 Apply a continuous 9 mm (3/8 in) nominal diameter bead of sealant over sheathing (wall surface) and the exterior face of the mounting flange, starting 216 mm (8 1/2 in) above the rough opening (see Figure 20) continuing down the jambs to the bottom of the sill mounting flange.



FIGURE 20

7.5.2 Cut jamb flashing to a measurement equal to twice the roll width of the flashing being used, plus the height of the rough opening, minus 25 mm (1 in).

7.5.3 Apply jamb flashing in line with any pre-punched holes/slots in the mounting flange and cover any fastener heads (see Figure 21).



FIGURE 21

7.5.4 Cut a piece of head flashing that is the width of the rough opening, plus two times the roll width of the flashing, plus 50 mm (2 in).

FMA/AAMA 100-12

Page 15

FMA/AAMA 100-12

Page 16

FMA/AAMA 100-12

Page 17

FMA/AAMA 100-12

Page 18

FMA/AAMA 100-12

Page 19

FMA/AAMA 100-12

Page 15

6.3 SILLS
Sills in wood frame construction can consist of a concrete slab or wood frame flooring (sub floor). The preparation shall be followed for the specific sill system per Sections 7.3 and 7.4. The WRB shall lap over the sill preparation.

6.3.1 Sills shall be level to ensure a continuous flat surface to support the door. If necessary, leveling can be done with grinding and/or a non-shrinking, water-resistant cementitious mud, grout, or other continuous shimming material. If rough opening sills are sloped to exterior to promote drainage, then wedge shims shall be used to provide flat bearing as needed.

6.3.1.1 Concrete slab sills can be recessed or flush with the floor. Recessed sill dimensions depend on the specific door frame depth and profile. Consult with the door manufacturer for proper recess dimensions. The rough framing material shall not protrude into the recessed sill area.

NOTE 1: Recessed sills may not be practical for use with in-swing doors. Consult door manufacturer's instructions for guidance.

6.3.1.2 Wood sills are flush with the floor and may be sloped to the exterior to promote drainage.

6.3.2 Direct contact of aluminum surfaces with all incompatible materials shall be avoided. Aluminum shall be protected from incompatible materials by placing between the surfaces substances such as bituminous coatings of paint, caulking, non-absorptive plastic, elastomeric tapes, or gaskets.

6.4 PRE DOOR INSTALLATION INSPECTION

6.4.1 Before door installation, the installer shall inspect the WRB to ensure that it is installed in accordance with this standard practice and the WRB manufacturer's instructions. Any tears, penetrations, or defects within 305 mm (12 in) of the rough opening area shall be sealed per the WRB manufacturer's instructions.

6.4.2 The installer shall verify that the rough opening is plumb, level, square, and true. The installer shall notify the contractor to remedy any discrepancies per this standard practice.

6.4.3 Installer shall inspect the fenestration product for damage and repair or replace if necessary.

7.0 EXTERIOR DOOR INSTALLATION PROCEDURES


There are a number of floor variations that will impact installation details, such as concrete or wood and recessed or flush sill systems. This practice will address these different floor variations.

7.1 SILL PREPARATION OF WRB
For installations of doors at the base or termination of a wall, the WRB shall lap over the sill preparation (see Section 7.3). Thus, the WRB shall be pulled back from the sill area or applied after the sill preparation in order to enable sill cut at wall terminations.


7.2 WRB PREPARATION

7.2.1 This practice recommends that the underside of the WRB be sealed at the rough opening, per discussion in Section 6.2.4. There are a variety of ways to do this successfully. Three representative methods are as follows:


7.2.1.1 WRB Method A
Box cut WRB around rough opening (see Figure 1), seal with 100 mm or 150 mm (4 in or 6 in) self-adhered flashing between the jamb corner at the head (see Figure 2), such that self-adhered flashing covers 50 mm (2 in) on the WRB as well as into the rough opening return at least to the depth of the door, and the sill (see Figure 3). Apply sealant at jamb/head interface (see Figure 2). See Schematic 1 for jamb detail.




7.2.1.2 WRB Method B: Integration after Door is Installed (per Section 7.5)
For use with Mounting Flanged Doors Only: Box cut WRB around rough opening and make cut 150 mm (6 in) onto the face of the wall at each jamb corner and fold back jamb as with head flap (see Figure 4), ensuring that the jamb cuts at the sill are angled upwards (see Figure 5). After the door is installed (per Section 7.5), apply sealant along jamb and fold over the previously folded over WRB jamb flap allowing it to integrate with the door frame (see Figures 6 and 6A). Press down on sealant bead under WRB. Integrate WRB to the door with sheathing tape or self-adhering flashing. See Schematic 2 for jamb detail.



7.2.1.3 WRB Method C: Full I-Cut of WRB (see Figure 7)
Apply self-adhering flashing over the WRB at the head of the opening, starting at the top corner of the exterior door (rough) opening, measure from the corner horizontal and then vertical a distance equal to the roll width of the flashing to be applied. At a 45° angle, carefully cut the WRB on a diagonal (see Figure 9). Repeat this step on the opposite corner. Trim 25 mm (1 in) off the bottom of the WRB head flap for proper integration with the head flange of the door. Raise the bottom edge of the flap created in the WRB up and temporarily tape to the exterior face of the WRB above. This is done in order to allow for installation of the exterior door and head flashing later.



7.2.2 For all WRB Wrap methods) At the head of the opening, starting at the top corner of the exterior door (rough) opening, measure from the corner horizontal and then vertical a distance equal to the roll width of the flashing to be applied. At a 45° angle, carefully cut the WRB on a diagonal (see Figure 9). Repeat this step on the opposite corner. Trim 25 mm (1 in) off the bottom of the WRB head flap for proper integration with the head flange of the door. Raise the bottom edge of the flap created in the WRB up and temporarily tape to the exterior face of the WRB above. This is done in order to allow for installation of the exterior door and head flashing later.



7.3 CONCRETE SILL PREPARATION AND INSTALLATION

7.3.1 Ensure that the concrete sill area is clean and free of debris, crevices and cracks.

7.3.2 Treat the concrete sill area, whether recessed or flush, with a liquid applied flashing (LAF) to prevent absorption of liquid water. This application of the liquid applied flashing shall be carried out as follows:

- For a flat or non-recessed sill condition, lower surface of the concrete sill to the depth of the inside face of the wall, and the exterior face covering at least 100 mm (4 in) down from the exterior edge (see Figure 11).

- For a recessed sill, the end and rear returns, to form one continuous sealed area (see Figure 12).

The seal performance shall meet local wind exposure requirements and not interfere with adhesion of the exterior facade. The liquid applied flashing shall be applied in accordance with the manufacturer's recommendations and shall meet the requirements of AAMA 714.

7.3.3 For slab on grade sill conditions where a barrier type installation is used, apply continuous sealant beads across the full floor length of the framed opening (or along the bottom of the door frame) in a location where the sealant makes contact with the door sill and concrete slab. Two 10 mm (3/8 in) diameter beads shall be used. Deposit a sufficient amount of the sealant at the framed opening corners so the bottom door frame corners are embedded in sealant when the door is installed.

NOTE 2: Barrier type installations are not designed to manage incidental water intrusion through the door unit or at the interface with the wall.

7.3.4 For drainage installations that are designed to manage incidental water, a sill pan is used to promote drainage to the exterior. The sill pan shall not be sloped towards the interior. The water resistant recessed sill area described Sections 6.3.1.1 and 7.3.2 can serve as a sill pan. The door sill shall be supported consistent with Section 6.3.1.

7.4 WOOD SILL PREPARATION AND INSTALLATION

7.4.1 Ensure that the rough opening wood sill area is clean and free of debris.

7.4.2 Treat the rough opening wood sill area with a water resistant coating or a self-adhering flashing membrane to prevent absorption of liquid water. Cover the entire sill area and at least 100 mm (4 in) up the jambs and integrate with the WRB below the sill for non-grade doors (see Figure 13). The water resistant coating or flashing membrane shall provide a water resistant seal around nails or fasteners as described in Section 5.2 of AAMA 714 for liquid applied flashing or AAMA 711 for self-adhered flashing. The water resistant coating or membrane shall be applied in accordance with the manufacturer's recommendations.

7.5.1 Sill pan flashing shall be applied on wood floors. There are a variety of sill pan systems available; the waterproof coating or membrane can act as this sill pan flashing with manufacturer's approval. The pan flashing shall direct water to the exterior or to the membrane drainage plane for subsequent drainage to the exterior of the building. The sill pan flashing shall be sealed to the wood floor to prevent water intrusion under the sill pan flashing.

7.5.2 **Mounting Flange Door Frame Preparation**

7.5.2.1 Integral Flanged Doors

7.5.2.1.1 Inspect and clean the back side (interior surface) of the exterior door mounting flange. Look for any sealant gaps or misaligned welding (particularly for vinyl products) at the corner joinery. If corner seals of the flange are missing in whole or part, contact the exterior door manufacturer for the recommended remedy.

7.5.2.1.2 After cleaning the mounting flange, carefully run a continuous 9 mm (3/8 in) nominal diameter bead of sealant on the back surface (interior face) of the mounting fin of the exterior door at the head and both jambs. Apply sealant in line with any pre-punched holes or slots in the mounting flange. Connect that bead of sealant across any joinery on the exterior door frame at all four corners. As an option, the sealant shall be permitted to be applied to the wall surface as opposed to the back of the mounting flange.

7.5.2.2 Applied Flanges (Field-Applied/Mechanically Attached/Non-Integral Flange Systems)
Additional flashing and sealing detail is required in order to provide a waterproof seal at the interface between the flange and the door frame. When using applied flanges, refer to the manufacturer's instruction for sealing the applied flange to the frame.

7.5.3 Apply a single continuous bead of sealant onto the previously installed sill pan at a location closest to the innermost plane of the sill pan and up along each jamb, to serve as part of the interior air and water seal. The water performance integrity of the installation is dependent upon this critical seal.

7.5.4 If applied, an exterior bead of sealant shall be discontinuous, leaving two 50 mm (2 in) voids within 100 mm (4 in) of each jamb (see Figure 14). Any alternative to the discontinuity in the bead of sealant at the exterior sill area shall be approved by the fenestration product manufacturer.

7.5.5 **Door Frame Installation into the Rough Opening - Immediately after sealant application to the sill pan, set the exterior door into the opening (see Figure 15). Hold the exterior door temporarily into position and apply shims as required to ensure the exterior door is set plumb, level, square and true. Fasten the exterior door perimeter securely into position in accordance with the manufacturer's instructions.**

NOTE 3: For clarity, only the door frame is shown.

NOTE 4: Additional fasteners may be required at locations such as locking mechanism or hinges, per manufacturer's instructions.

7.5.5.1 For proper sealant coverage, ensure squeeze out under flange and in fastener holes.

7.5.5.2 Install shims in such a manner that they are not permitted to interfere with the application of the air seal, which will be applied on the interior side in the steps that follow.

7.5.5.3 For applications where the exterior door sill will be screwed down, pre-drill the fastener holes in the sill and apply appropriate sealant into the drilled hole. Install the fasteners and seal over the fastener head ensuring a water-tight condition.

7.5.6 Jamb and Head Flashing Installation using Self-Adhering Flashing

7.5.6.1 Apply flashing over the mounting flange of the exterior door at both jambs per manufacturer's instructions. The self-adhering flashing shall conform to the requirements of AAMA 711 and be a minimum of 100 mm (4 in) in width.

NOTE 5: Local job site conditions, application temperatures, or specific materials may require the application of primer to any exposed wood or concrete/masonry as required by the flashing manufacturer.

7.5.6.2 For grade level door installations, cut the jamb flashing 50 mm (2 in) longer than the rough opening height, including the recess sill. For non-grade level applications, cut the jamb flashing 100 mm (4 in) greater than the rough opening height to cover 50 mm (2 in) above and below the rough opening.

7.5.6.3 Adhere the top end of the flashing 50 mm (2 in) above the rough opening, such that the head flashing (applied later) will lap over the jamb flashing by at least 50 mm (2 in) (see Figure 16). Do not interfere with the WRB flap at the head. Tuck the top of the jamb flashing under the flap of the water-resistant barrier at the head.

7.5.6.4 Use firm pressure to apply the self-adhering flashing to promote seal to exterior door flange and WRB. Use of a J-Roller is recommended.

7.5.6.5 Use of a drip cap is strongly recommended at the head of the door frame or system (see Figure 16). See manufacturer's instructions for installation details.

7.5.6.6 Adhere the self-adhering flashing with firm pressure (use of a J-Roller is recommended) across the head of the exterior door on top of the mounting flange and beyond the rough opening on each side extending it 50 mm (2 in) over the outside edge of the flashing at the jambs (see Figure 17).

7.6 EXTERIOR CASING (BRICK MOLDING) DOOR INSTALLATION

7.6.1 Sealing the casing to the door frame. The interface between the exterior casing/brick mold and the door frame may not be a reliable water tight seal. Extra precautions shall be taken to seal this interface. This can be done with either self-adhering flashing designed for this purpose (see Figure 19) or a continuous 9 mm (3/8 in) nominal diameter bead of sealant around the entire perimeter of the casing/frame interface (see Figure 20). Tool sealant to ensure a proper seal between parts.

7.6.2 Apply a single continuous bead of sealant onto the previously installed sill pan at a location closest to the innermost plane of the sill pan and up along each jamb, to serve as part of the interior air and water seal. The water performance integrity of the installation is dependent upon this critical seal.

7.6.3 If applied, an exterior bead of sealant shall be discontinuous, leaving two 50 mm (2 in) voids within 100 mm (4 in) of each jamb (see Figure 14). Any alternative to the discontinuity in the bead of sealant at the exterior sill area shall be approved by the fenestration product manufacturer.

7.6.4 **Door Frame Installation into the Rough Opening**
Immediately after sealant application to the sill pan, set the exterior door into the opening (see Figure 21). Hold the exterior door temporarily into position and apply shims as required to ensure the exterior door is set plumb, level, square and true. Fasten the exterior door perimeter securely into position in accordance with the manufacturer's instructions.

7.6.4.1 Fasten the exterior casing/brick mold to the wall frame, making sure that this does not impact the trueness of the door.

NOTE 6: Additional fasteners may be required at locations such as locking mechanism or hinges, per manufacturer's instructions.

7.6.5 Install shims in such a manner that they are not permitted to interfere with the application of the air seal, which will be applied on the interior side in the steps that follow.

7.6.6 For applications where the exterior door sill will be screwed down, pre-drill the fastener holes in the sill and apply appropriate sealant into the drilled hole. Install the fasteners and seal over the fastener head ensuring a water-tight condition.

7.6.7 Integration between the door frame and the WRB. Use of self-adhering flashing that is designed for continuous integration between the door frame and the WRB is recommended for doors with exterior casing/brick mold (see Figure 23). Alternatively, apply a continuous 9 mm (3/8 in) nominal diameter bead of sealant around the entire perimeter of the exterior casing/brick molding interface with the WRB. The WRB shall be applied so that it is under the exterior casing/brick molding (WRB Wrap Method B per Section 7.2.1.2 is not permitted).

7.6.8 A drip cap shall be applied at the head of the exterior casing / brick mold door. The drip cap shall be applied under the WRB head flap and integrated to the sheathing with self-adhering flashing. See manufacturer's instructions for installation details.

7.6.9 Remove the previously applied tape which holds the flap of the water-resistant barrier at the head. Allow the flap to lay flat over the drip cap and flashing. Apply a new piece of sheathing tape or 100 mm (4 in) self-adhering flashing over the WRB flap and the entire diagonal cut made in the water-resistant barrier. The tape should be compressed against the WRB and the head flashing, which extends over the jamb. Placing discontinuous lengths of tape across the width of the head seam between the WRB and the head flashing is acceptable, but may result in increased air infiltration around the WRB (see Figure 18).

7.7 BOX FRAME (NON-FLANGED) DOOR INSTALLATION
The WRB shall be applied so that the rough opening return is protected per Method A or C (WRB Wrap Method B per Section 7.2.1.2 is not permitted).

7.7.1 Door frame preparation. Use of self-adhering flashing that is designed for continuous integration between the door frame and the WRB is recommended for box framed/non-flanged doors and, when used, shall be installed per door or frame manufacturer's instructions (see Figure 23). Alternatively, the door can be integrated to the WRB per Section 7.6.2. If the method per Section 7.6.2 is used, apply self-adhering flashing at the head of the rough opening and wrap into the rough opening return (see Figure 24). Ensure that the corners of the rough-opening jamb/head interface are fully protected with self-adhered flashing. Apply sealant to any overlapping seams in the self-adhered flashing.

7.7.2 Apply a single continuous bead of sealant onto the previously installed sill pan at a location closest to the innermost plane of the sill pan and up along each jamb, to serve as part of the interior air and water seal. The water performance integrity of the installation is dependent upon this critical seal.

7.7.3 If applied, an exterior bead of sealant shall be discontinuous, leaving two 50 mm (2 in) voids within 100 mm (4 in) of each jamb (see Figure 14). Any alternative to the discontinuity in the bead of sealant at the exterior sill area shall be approved by the fenestration product manufacturer.

7.7.4 **Door Frame Installation into the Rough Opening**
Immediately after sealant application to the sill pan, set the exterior door into the opening. Hold the exterior door temporarily into position and apply shims as required to ensure the exterior door is set plumb, level, square and true. Fasten the exterior door perimeter securely into position in accordance with the manufacturer's instructions.

NOTE 7: Additional fasteners may be required at locations such as locking mechanism or hinges, per manufacturer's instructions.

7.7.4.1 Install shims in such a manner that they are not permitted to interfere with the application of the air seal, which will be applied on the interior side in the steps that follow.

7.7.5 For applications where the exterior door sill will be screwed down, pre-drill the fastener holes in the sill and apply appropriate sealant into the drilled hole. Install the fasteners and seal over the fastener head ensuring a water-tight condition.

7.7.6 Integration Between the Door Frame and the WRB

7.7.6.1 Where self-adhering flashing designed for this application is used, the flashing can be integrated directly with the WRB at the jambs and the head (see Figure 25).

7.7.2 Apply a single continuous bead of sealant onto the previously installed sill pan at a location closest to the innermost plane of the sill pan and up along each jamb, to serve as part of the interior air and water seal. The water performance integrity of the installation is dependent upon this critical seal.

7.7.3 If applied, an exterior bead of sealant shall be discontinuous, leaving two 50 mm (2 in) voids within 100 mm (4 in) of each jamb (see Figure 14). Any alternative to the discontinuity in the bead of sealant at the exterior sill area shall be approved by the fenestration product manufacturer.

7.7.4 **Door Frame Installation into the Rough Opening**
Immediately after sealant application to the sill pan, set the exterior door into the opening. Hold the exterior door temporarily into position and apply shims as required to ensure the exterior door is set plumb, level, square and true. Fasten the exterior door perimeter securely into position in accordance with the manufacturer's instructions.

NOTE 7: Additional fasteners may be required at locations such as locking mechanism or hinges, per manufacturer's instructions.

7.7.4.1 Install shims in such a manner that they are not permitted to interfere with the application of the air seal, which will be applied on the interior side in the steps that follow.

7.7.5 For applications where the exterior door sill will be screwed down, pre-drill the fastener holes in the sill and apply appropriate sealant into the drilled hole. Install the fasteners and seal over the fastener head ensuring a water-tight condition.

7.7.6 Integration Between the Door Frame and the WRB

7.7.6.1 Where self-adhering flashing designed for this application is used, the flashing can be integrated directly with the WRB at the jambs and the head (see Figure 25).



7.7.6.2 For alternative method, apply a properly sized backup rod around the perimeter gap between the door frame and the rough opening. Apply a continuous 9 mm (3/8 in) nominal diameter bead of sealant around the entire perimeter of the door frame to bridge the interface with the WRB, leaving at least two 50 mm (2 in) gaps at the sill to allow drainage from the sill pan (see Figure 26).

7.7.7 A drip cap shall be applied at the head of the exterior casing / brick mold door. The drip cap shall be applied under the WRB head flap and integrated to the sheathing with self-adhering flashing. See manufacturer's instructions for installation details.

7.7.8 Remove the previously applied tape which holds the flap of the water-resistant barrier at the head. Allow the flap to lay flat over the drip cap and flashing. Apply a new piece of sheathing tape or 100 mm (4 in) self-adhering flashing over the WRB flap and the entire diagonal cut made in the water-resistant barrier. The tape should be compressed against the WRB and the head flashing, which extends over the jamb (see Figure 27). Placing discontinuous lengths of tape across the width of the head seam between the WRB and the head flashing is acceptable, but may result in increased air infiltration around the WRB.

7.8.1 For drainage sill pan methods, this interior seal effectively forms a back dam to prevent water intrusion into the interior, thus the integrity (adhesive bond strength) of this seal is critical. A raised upturned leg on the interior plane of the sill pan made from a rigid material can be also be used, if properly air sealed. If a rigid or semi-rigid sill pan was used, recess the seal between the sill of the door and the upturned leg of the sill pan and resal as needed.

7.8.2 In cases where shims, clips, or anchoring devices cause interference with the application of the interior air and water seal, trim, remove or take steps necessary to seal such obstructions to allow for a continuous air/water seal. In all cases make sure the entire perimeter joint has been sealed, creating an air/water tight condition.



Installation Details (Product Approval) - Therma-Tru Classic Craft (Non-Impact)

Scale: N/A

ITEM

DESCRIPTION

MATERIAL

A

1X BUCK SG=0.55

WOOD

B

2X BUCK SG=0.55

WOOD

C

MAX. 1/4" SHIM SPACE

WOOD

D

1/4" X 2-3/4" PHW ELCO OR TW CONCRETE SCREW

STEEL

E

MASONRY - 3000 PSI MIN. CONCRETE CONFORMING TO ACI 301 OR HOLLOW BLOCK CONFORMING TO ASTM OR

CONCRETE

F

3/16" X 3-1/4" PHW RW CONCRETE SCREW

STEEL

G

1/4" X 3-1/4" PHW RW CONCRETE SCREW

STEEL

H

1/4" X 3-3/4" PHW RW CONCRETE SCREW

STEEL

I

#8 X 2-1/2" PHW WOOD SCREW (1-1/2" MIN. EMBEDMENT)

STEEL

J

#10 X 2" PHW WOOD SCREW

STEEL

K

3/8" REACH COMPRESSION WEATHERSTRIP

STEEL

L

LONG REACH COMPRESSION WEATHERSTRIP

FOAM

M

1" X 4" HINGE, 89" THK.

STEEL

N

#10 X 3/4" PHW WOOD SCREW

STEEL

O

WINNET SIGNATURE SERIES PASSAGE LOCK

STEEL

P

LOW PROFILE OUTSWING BUMPER THRESHOLD

WOOD

Q

HEADER JAMB (PINE SG=0.62)

WOOD

R

SIDE JAMB (PINE SG=0.62)

WOOD

S

WINNET SIGNATURE SERIES (200) DEADBOLT

STEEL

T

LATCH STRIKE PLATE

STEEL

U

DRAGBOLT PLATE

STEEL

V

DOOR BOTTOM SWEEP

PVC

W

SELF ADJUSTING INSWING SADDLE THRESHOLD

ALUM.COMP.

X

FIBERGLASS DOOR PANEL - CLASSIC CRAFT

COMPOSITE

Y

CC DOOR SKIN .098" MIN. THK. FIBERGLASS BY THERMA-TRU WITH YIELD STRENGTH (MIN.) = 6000 PSI

SMC

Z

TOP RAIL

COMPOSITE

AA

LATCH STILE

LVL WOOD

AB

HINGE STILE

WOOD

AC

DOOR RAIL

COMPOSITE

AD

POLYURETHANE FOAM CORE - 1.9 LBS. DENSITY

FOAM

NOTE: WOOD/LEI COMPONENTS (OAK CAP, PINE CORE; SG=0.62)

PROJECT: THERMA-TRU FIBERGLASS DOOR

DATE: 4/23/08

SCALE: N.T.S.

DRAWN BY: AL

CHECKED BY: LFS

PROJECT NO.: FL-5891.3

SHEET: 7 OF 7

1

VERTICAL CROSS SECTION

Swing configuration

2

VERTICAL CROSS SECTION

Swing w/ 1x buck

3

VERTICAL CROSS SECTION

Swing configuration

4

VERTICAL CROSS SECTION

Swing configuration

PROJECT: THERMA-TRU FIBERGLASS DOOR

DATE: 4/23/08

SCALE: N.T.S.

DRAWN BY: AL

CHECKED BY: LFS

PROJECT NO.: FL-5891.3

SHEET: 8 OF 7

BUCK ANCHORING

STRIKE JAMB

FRAME ANCHORING

HINGE JAMB

1

CONCRETE ANCHOR NOTES:

1. Concrete anchor locations at the corners may be adjusted to maintain the min. edge distance to masonry joints.

2. Concrete anchor locations noted as "MAX. ON CENTER" must be adjusted to maintain the min. edge distance to masonry joints, additional concrete anchors may be required to ensure the "MAX. ON CENTER" dimension are not exceeded.

3. Concrete anchor table:

ANCHOR TYPE	ANCHOR SIZE	MIN. EMBEDMENT	MIN. CLEARANCE TO MASONRY EDGE	MIN. CLEARANCE TO ADJACENT ANCHOR
1" RW TAPCON	1/4"	1-1/4"	2"	4"
1" RW ELCO	1/4"	1-1/4"	1"	4"
1" RW ULTRACON	1/4"	1-1/4"	1"	4"

WOOD SCREW INSTALLATION NOTES:

1. Maintain a minimum 3/8" edge distance, 1" end distance, & 1" o.c. spacing of wood screws to prevent the splitting of wood.

PROJECT: THERMA-TRU FIBERGLASS DOOR

DATE: 4/23/08

SCALE: N.T.S.

DRAWN BY: AL

CHECKED BY: LFS

PROJECT NO.: FL-5891.3

SHEET: 9 OF 7

1

DOOR PANEL

DOOR PANEL

2

DOOR TOP RAIL

DOOR TOP RAIL

3

DOOR RAIL RAIL

DOOR RAIL RAIL

4

DOOR RAIL RAIL

DOOR RAIL RAIL

5

DOOR RAIL RAIL

DOOR RAIL RAIL

6

DOOR RAIL RAIL

DOOR RAIL RAIL

7

DOOR RAIL RAIL

DOOR RAIL RAIL

8

DOOR RAIL RAIL

DOOR RAIL RAIL

9

DOOR RAIL RAIL

DOOR RAIL RAIL

10

DOOR RAIL RAIL

DOOR RAIL RAIL

11

DOOR RAIL RAIL

DOOR RAIL RAIL

12

DOOR RAIL RAIL

DOOR RAIL RAIL

13

DOOR RAIL RAIL

DOOR RAIL RAIL

14

DOOR RAIL RAIL

DOOR RAIL RAIL

15

DOOR RAIL RAIL

DOOR RAIL RAIL

16

DOOR RAIL RAIL

DOOR RAIL RAIL

17

DOOR RAIL RAIL

DOOR RAIL RAIL

18

DOOR RAIL RAIL

DOOR RAIL RAIL

19

DOOR RAIL RAIL

DOOR RAIL RAIL

20

DOOR RAIL RAIL

DOOR RAIL RAIL

21

DOOR RAIL RAIL

DOOR RAIL RAIL

22

DOOR RAIL RAIL

DOOR RAIL RAIL

23

DOOR RAIL RAIL

DOOR RAIL RAIL

24

DOOR RAIL RAIL

DOOR RAIL RAIL

25

DOOR RAIL RAIL

DOOR RAIL RAIL

26

DOOR RAIL RAIL

DOOR RAIL RAIL

27

DOOR RAIL RAIL

DOOR RAIL RAIL

28

DOOR RAIL RAIL

DOOR RAIL RAIL

29

DOOR RAIL RAIL

DOOR RAIL RAIL

30

DOOR RAIL RAIL

DOOR RAIL RAIL

31

DOOR RAIL RAIL

DOOR RAIL RAIL

32

DOOR RAIL RAIL

DOOR RAIL RAIL

33

DOOR RAIL RAIL

DOOR RAIL RAIL

34

DOOR RAIL RAIL

DOOR RAIL RAIL

35

DOOR RAIL RAIL

DOOR RAIL RAIL

36

DOOR RAIL RAIL

DOOR RAIL RAIL

37

DOOR RAIL RAIL

DOOR RAIL RAIL

38

DOOR RAIL RAIL

DOOR RAIL RAIL

39

DOOR RAIL RAIL

DOOR RAIL RAIL

40

DOOR RAIL RAIL

DOOR RAIL RAIL

41

DOOR RAIL RAIL

DOOR RAIL RAIL

42

DOOR RAIL RAIL

DOOR RAIL RAIL

43

DOOR RAIL RAIL

DOOR RAIL RAIL

44

DOOR RAIL RAIL

DOOR RAIL RAIL

45

DOOR RAIL RAIL

DOOR RAIL RAIL

46

DOOR RAIL RAIL

DOOR RAIL RAIL

47

DOOR RAIL RAIL

DOOR RAIL RAIL

48

DOOR RAIL RAIL

DOOR RAIL RAIL

49

DOOR RAIL RAIL

DOOR RAIL RAIL

50

DOOR RAIL RAIL

DOOR RAIL RAIL

51

DOOR RAIL RAIL

DOOR RAIL RAIL

52

DOOR RAIL RAIL

DOOR RAIL RAIL

53

DOOR RAIL RAIL

DOOR RAIL RAIL

54

DOOR RAIL RAIL

DOOR RAIL RAIL

55

DOOR RAIL RAIL

DOOR RAIL RAIL

56

DOOR RAIL RAIL

DOOR RAIL RAIL

57

DOOR RAIL RAIL

DOOR RAIL RAIL

58

DOOR RAIL RAIL

DOOR RAIL RAIL

59

DOOR RAIL RAIL

DOOR RAIL RAIL

60

DOOR RAIL RAIL

DOOR RAIL RAIL

61

DOOR RAIL RAIL

DOOR RAIL RAIL

62

DOOR RAIL RAIL

DOOR RAIL RAIL

63

DOOR RAIL RAIL

DOOR RAIL RAIL

64

DOOR RAIL RAIL

DOOR RAIL RAIL

65

DOOR RAIL RAIL

DOOR RAIL RAIL

66

DOOR RAIL RAIL

DOOR RAIL RAIL

67

DOOR RAIL RAIL

DOOR RAIL RAIL

68

DOOR RAIL RAIL

DOOR RAIL RAIL

69

DOOR RAIL RAIL

DOOR RAIL RAIL

70

DOOR RAIL RAIL

DOOR RAIL RAIL

71

DOOR RAIL RAIL

DOOR RAIL RAIL

72

DOOR RAIL RAIL

DOOR RAIL RAIL

73

DOOR RAIL RAIL

DOOR RAIL RAIL

74

DOOR RAIL RAIL

DOOR RAIL RAIL

75

DOOR RAIL RAIL

DOOR RAIL RAIL

76

DOOR RAIL RAIL

DOOR RAIL RAIL

77

DOOR RAIL RAIL

DOOR RAIL RAIL

78

DOOR RAIL RAIL

DOOR RAIL RAIL

79

DOOR RAIL RAIL

DOOR RAIL RAIL

80

DOOR RAIL RAIL

DOOR RAIL RAIL

81

DOOR RAIL RAIL

DOOR RAIL RAIL

82

DOOR RAIL RAIL

DOOR RAIL RAIL

83

DOOR RAIL RAIL

DOOR RAIL RAIL

84

DOOR RAIL RAIL

DOOR RAIL RAIL

85

DOOR RAIL RAIL

DOOR RAIL RAIL

86

DOOR RAIL RAIL

DOOR RAIL RAIL

87

DOOR RAIL RAIL

DOOR RAIL RAIL

88

DOOR RAIL RAIL

DOOR RAIL RAIL

89

DOOR RAIL RAIL

DOOR RAIL RAIL

90

DOOR RAIL RAIL

DOOR RAIL RAIL

91

DOOR RAIL RAIL

DOOR RAIL RAIL

92

DOOR RAIL RAIL

DOOR RAIL RAIL

93

DOOR RAIL RAIL

DOOR RAIL RAIL

94

DOOR RAIL RAIL

DOOR RAIL RAIL

95

DOOR RAIL RAIL

DOOR RAIL RAIL

96

DOOR RAIL RAIL

DOOR RAIL RAIL

97

DOOR RAIL RAIL

DOOR RAIL RAIL

98

DOOR RAIL RAIL

DOOR RAIL RAIL

99

DOOR RAIL RAIL

DOOR RAIL RAIL

100

DOOR RAIL RAIL

DOOR RAIL RAIL

101

DOOR RAIL RAIL

DOOR RAIL RAIL

102

DOOR RAIL RAIL

DOOR RAIL RAIL

103

DOOR RAIL RAIL

DOOR RAIL RAIL

104

DOOR RAIL RAIL

DOOR RAIL RAIL

105

DOOR RAIL RAIL

DOOR RAIL RAIL

106

DOOR RAIL RAIL

DOOR RAIL RAIL

107

DOOR RAIL RAIL

DOOR RAIL RAIL

108

DOOR RAIL RAIL

DOOR RAIL RAIL

109

DOOR RAIL RAIL

DOOR RAIL RAIL

110

DOOR RAIL RAIL

DOOR RAIL RAIL

111

DOOR RAIL RAIL

DOOR RAIL RAIL

112

DOOR RAIL RAIL

DOOR RAIL RAIL

113

DOOR RAIL RAIL

DOOR RAIL RAIL

114

DOOR RAIL RAIL

DOOR RAIL RAIL

115

DOOR RAIL RAIL

DOOR RAIL RAIL

116

DOOR RAIL RAIL

DOOR RAIL RAIL

117

DOOR RAIL RAIL

DOOR RAIL RAIL

118

DOOR RAIL RAIL

DOOR RAIL RAIL

119

DOOR RAIL RAIL

DOOR RAIL RAIL

120

DOOR RAIL RAIL

DOOR RAIL RAIL

121

DOOR RAIL RAIL

DOOR RAIL RAIL

122

DOOR RAIL RAIL

DOOR RAIL RAIL

123

DOOR RAIL RAIL

DOOR RAIL RAIL

124

DOOR RAIL RAIL

DOOR RAIL RAIL

125

DOOR RAIL RAIL

DOOR RAIL RAIL

126

DOOR RAIL RAIL

DOOR RAIL RAIL

127

DOOR RAIL RAIL

DOOR RAIL RAIL

128

DOOR RAIL RAIL

DOOR RAIL RAIL

129

DOOR RAIL RAIL

DOOR RAIL RAIL

130

DOOR RAIL RAIL

DOOR RAIL RAIL

131

DOOR RAIL RAIL

DOOR RAIL RAIL

132

DOOR RAIL RAIL

DOOR RAIL RAIL

133

DOOR RAIL RAIL

DOOR RAIL RAIL

134

DOOR RAIL RAIL

DOOR RAIL RAIL

135

DOOR RAIL RAIL

DOOR RAIL RAIL

136

DOOR RAIL RAIL

DOOR RAIL RAIL

137

DOOR RAIL RAIL

DOOR RAIL RAIL

138

DOOR RAIL RAIL

DOOR RAIL RAIL

139

DOOR RAIL RAIL

DOOR RAIL RAIL

140

DOOR RAIL RAIL

DOOR RAIL RAIL

141

DOOR RAIL RAIL

DOOR RAIL RAIL

142

DOOR RAIL RAIL

DOOR RAIL RAIL

143

DOOR RAIL RAIL

DOOR RAIL RAIL

144

DOOR RAIL RAIL

DOOR RAIL RAIL

145

DOOR RAIL RAIL

DOOR RAIL RAIL

146

DOOR RAIL RAIL

DOOR RAIL RAIL

147

DOOR RAIL RAIL

DOOR RAIL RAIL

148

DOOR RAIL RAIL

DOOR RAIL RAIL

149

DOOR RAIL RAIL

DOOR RAIL RAIL

150

DOOR RAIL RAIL

DOOR RAIL RAIL

151

DOOR RAIL RAIL

DOOR RAIL RAIL

152

DOOR RAIL RAIL

DOOR RAIL RAIL

153

DOOR RAIL RAIL

DOOR RAIL RAIL

154

DOOR RAIL RAIL

DOOR RAIL RAIL

155

DOOR RAIL RAIL

DOOR RAIL RAIL

156

DOOR RAIL RAIL

DOOR RAIL RAIL

157

DOOR RAIL RAIL

DOOR RAIL RAIL

158

DOOR RAIL RAIL

DOOR RAIL RAIL

159

DOOR RAIL RAIL

DOOR RAIL RAIL

160

DOOR RAIL RAIL

DOOR RAIL RAIL

161

DOOR RAIL RAIL

DOOR RAIL RAIL

162

DOOR RAIL RAIL

DOOR RAIL RAIL

163

DOOR RAIL RAIL

DOOR RAIL RAIL

164

DOOR RAIL RAIL

DOOR RAIL RAIL

165

DOOR RAIL RAIL

DOOR RAIL RAIL

166

DOOR RAIL RAIL

DOOR RAIL RAIL

167

DOOR RAIL RAIL

DOOR RAIL RAIL

168

DOOR RAIL RAIL

DOOR RAIL RAIL

169

DOOR RAIL RAIL

DOOR RAIL RAIL

170

DOOR RAIL RAIL

DOOR RAIL RAIL

171

DOOR RAIL RAIL

DOOR RAIL RAIL

172

DOOR RAIL RAIL

DOOR RAIL RAIL

173

DOOR RAIL RAIL

DOOR RAIL RAIL

174

DOOR RAIL RAIL

DOOR RAIL RAIL

175

DOOR RAIL RAIL

DOOR RAIL RAIL

176

DOOR RAIL RAIL

DOOR RAIL RAIL

177

DOOR RAIL RAIL

DOOR RAIL RAIL

178

DOOR RAIL RAIL

DOOR RAIL RAIL

179

DOOR RAIL RAIL

DOOR RAIL RAIL

180

DOOR RAIL RAIL

DOOR RAIL RAIL

181

DOOR RAIL RAIL

DOOR RAIL RAIL

182

DOOR RAIL RAIL

DOOR RAIL RAIL

183

DOOR RAIL RAIL

DOOR RAIL RAIL

184

DOOR RAIL RAIL

DOOR RAIL RAIL

185

DOOR RAIL RAIL

DOOR RAIL RAIL

186

DOOR RAIL RAIL

DOOR RAIL RAIL

187

DOOR RAIL RAIL

DOOR RAIL RAIL

188

DOOR RAIL RAIL

DOOR RAIL RAIL

189

DOOR RAIL RAIL

DOOR RAIL RAIL

190

DOOR RAIL RAIL

DOOR RAIL RAIL

191

DOOR RAIL RAIL

DOOR RAIL RAIL

192

DOOR RAIL RAIL

DOOR RAIL RAIL

193

DOOR RAIL RAIL

DOOR RAIL RAIL

194

DOOR RAIL RAIL

DOOR RAIL RAIL

195

DOOR RAIL RAIL

DOOR RAIL RAIL

196

DOOR RAIL RAIL

DOOR RAIL RAIL

197

DOOR RAIL RAIL

DOOR RAIL RAIL

198

DOOR RAIL RAIL

DOOR RAIL RAIL

199

DOOR RAIL RAIL

DOOR RAIL RAIL

200

DOOR RAIL RAIL

DOOR RAIL RAIL

201

DOOR RAIL RAIL

DOOR RAIL RAIL

202

DOOR RAIL RAIL

DOOR RAIL RAIL

203

DOOR RAIL RAIL

DOOR RAIL RAIL

204

DOOR RAIL RAIL

DOOR RAIL RAIL

205

DOOR RAIL RAIL

DOOR RAIL RAIL

206

DOOR RAIL RAIL

DOOR RAIL RAIL

207

DOOR RAIL RAIL

DOOR RAIL RAIL

208

DOOR RAIL RAIL

DOOR RAIL RAIL

209

DOOR RAIL RAIL

DOOR RAIL RAIL

210

DOOR RAIL RAIL

DOOR RAIL RAIL

211

DOOR RAIL RAIL

DOOR RAIL RAIL

212

DOOR RAIL RAIL

DOOR RAIL RAIL

213

DOOR RAIL RAIL

DOOR RAIL RAIL

214

DOOR RAIL RAIL

DOOR RAIL RAIL

215

DOOR RAIL RAIL

DOOR RAIL RAIL

216

DOOR RAIL RAIL

DOOR RAIL RAIL

217

DOOR RAIL RAIL

DOOR RAIL RAIL

218

DOOR RAIL RAIL

DOOR RAIL RAIL

219

DOOR RAIL RAIL

DOOR RAIL RAIL

220

DOOR RAIL RAIL

DOOR RAIL RAIL

221

DOOR RAIL RAIL

DOOR RAIL RAIL

222

DOOR RAIL RAIL

DOOR RAIL RAIL

223

DOOR RAIL RAIL

DOOR RAIL RAIL

224

DOOR RAIL RAIL

DOOR RAIL RAIL

225

DOOR RAIL RAIL

DOOR RAIL RAIL

226

DOOR RAIL RAIL

DOOR RAIL RAIL

227

DOOR RAIL RAIL

DOOR RAIL RAIL

228

DOOR RAIL RAIL

DOOR RAIL RAIL

229

DOOR RAIL RAIL

DOOR RAIL RAIL

230

DOOR RAIL RAIL

DOOR RAIL RAIL

231

DOOR RAIL RAIL

DOOR RAIL RAIL

232

DOOR RAIL RAIL

DOOR RAIL RAIL

233

DOOR RAIL RAIL

DOOR RAIL RAIL

234

DOOR RAIL RAIL

DOOR RAIL RAIL

235

DOOR RAIL RAIL

DOOR RAIL RAIL

236

DOOR RAIL RAIL

DOOR RAIL RAIL

237

DOOR RAIL RAIL

DOOR RAIL RAIL

238

DOOR RAIL RAIL

DOOR RAIL RAIL

239

DOOR RAIL RAIL

DOOR RAIL RAIL

240

DOOR RAIL RAIL

DOOR RAIL RAIL

241

DOOR RAIL RAIL

DOOR RAIL RAIL

242

DOOR RAIL RAIL

DOOR RAIL RAIL

243

DOOR RAIL RAIL

DOOR RAIL RAIL

244

DOOR RAIL RAIL

DOOR RAIL RAIL

245

DOOR RAIL RAIL

DOOR RAIL RAIL

246

DOOR RAIL RAIL

DOOR RAIL RAIL

247

DOOR RAIL RAIL

DOOR RAIL RAIL

248

DOOR RAIL RAIL

DOOR RAIL RAIL

249

DOOR RAIL RAIL

DOOR RAIL RAIL

250

DOOR RAIL RAIL

DOOR RAIL RAIL

251

DOOR RAIL RAIL

DOOR RAIL RAIL

252

DOOR RAIL RAIL

DOOR RAIL RAIL

253

DOOR RAIL RAIL

DOOR RAIL RAIL

254

DOOR RAIL RAIL

DOOR RAIL RAIL

255

DOOR RAIL RAIL

DOOR RAIL RAIL

256

DOOR RAIL RAIL

DOOR RAIL RAIL

257

DOOR RAIL RAIL

DOOR RAIL RAIL

258

DOOR RAIL RAIL

DOOR RAIL RAIL

259

DOOR RAIL RAIL

DOOR RAIL RAIL

260

DOOR RAIL RAIL

DOOR RAIL RAIL

261

DOOR RAIL RAIL

DOOR RAIL RAIL

262

DOOR RAIL RAIL

DOOR RAIL RAIL

263

DOOR RAIL RAIL

DOOR RAIL RAIL

264

DOOR RAIL RAIL

DOOR RAIL RAIL

265

DOOR RAIL RAIL

DOOR RAIL RAIL

266

DOOR RAIL RAIL

DOOR RAIL RAIL

267

DOOR RAIL RAIL

DOOR RAIL RAIL

268

DOOR RAIL RAIL

DOOR RAIL RAIL

269

DOOR RAIL RAIL

DOOR RAIL RAIL

270

DOOR RAIL RAIL

DOOR RAIL RAIL

271

DOOR RAIL RAIL

DOOR RAIL RAIL

272

DOOR RAIL RAIL

DOOR RAIL RAIL

273

DOOR RAIL RAIL

DOOR RAIL RAIL

274

DOOR RAIL RAIL

DOOR RAIL RAIL

275

DOOR RAIL RAIL

DOOR RAIL RAIL

276

DOOR RAIL RAIL

DOOR RAIL RAIL

277

DOOR RAIL RAIL

DOOR RAIL RAIL

278

DOOR RAIL RAIL

DOOR RAIL RAIL

279

DOOR RAIL RAIL

DOOR RAIL RAIL

280

DOOR RAIL RAIL

DOOR RAIL RAIL

281

DOOR RAIL RAIL

DOOR RAIL RAIL

282

DOOR RAIL RAIL

DOOR RAIL RAIL

283

DOOR RAIL RAIL

DOOR RAIL RAIL

284

DOOR RAIL RAIL

DOOR RAIL RAIL

285

DOOR RAIL RAIL

DOOR RAIL RAIL

286

DOOR RAIL RAIL

DOOR RAIL RAIL

287

DOOR RAIL RAIL

DOOR RAIL RAIL

288

DOOR RAIL RAIL

DOOR RAIL RAIL

289

DOOR RAIL RAIL

DOOR RAIL RAIL

290

DOOR RAIL RAIL

DOOR RAIL RAIL

291

DOOR RAIL RAIL

DOOR RAIL RAIL

292

DOOR RAIL RAIL

DOOR RAIL RAIL

293

DOOR RAIL RAIL

DOOR RAIL RAIL

294

DOOR RAIL RAIL

DOOR RAIL RAIL

295

DOOR RAIL RAIL

DOOR RAIL RAIL

296

DOOR RAIL RAIL

DOOR RAIL RAIL

297

DOOR RAIL RAIL

DOOR RAIL RAIL

298

DOOR RAIL RAIL

DOOR RAIL RAIL

299

DOOR RAIL RAIL

DOOR RAIL RAIL

300

DOOR RAIL RAIL

DOOR RAIL RAIL

301

DOOR RAIL RAIL

DOOR RAIL RAIL

302

DOOR RAIL RAIL

DOOR RAIL RAIL

<


DuPont™ Tyvek® Water-Resistive and Air Barriers Installation Guidelines

DuPont Flashing Systems Integration


If windows and doors have not been installed, reference the DuPont™ Self-Adhered Flashing Systems Installation Guidelines, Installation Instructions for Windows and Doors AFTER Water-Resistive Barrier (WRB) is installed to prepare the rough opening.

If windows and doors will be installed before the WRB, then follow these last 4 integration steps to tie the DuPont™ Tyvek® WRB into the flashing.

STEP 1
A. Install flashing and the window or door following the steps detailed in the DuPont™ Self-Adhered Flashing Systems Installation Guidelines, Installation Instructions for Windows and Doors BEFORE Water-Resistive Barrier (WRB) is installed.




STEP 2
A. Install the DuPont™ Tyvek® WRB. Do not install fasteners within 4" of the window frame at jambs and head, and within 12" of the window frame at sill or location of apron.
B. Mark a perimeter on the DuPont™ Tyvek® WRB around the rough opening a minimum of 1" from the jambs and head of the window frame, and 6" below the sill of the window frame.




DuPont™ Tyvek® Water-Resistive and Air Barriers Installation Guidelines

STEP 3
A. Cut the DuPont™ Tyvek® WRB along perimeter marking to expose window. Do not cut through the DuPont™ Self-Adhered Flashing products or DuPont™ Tyvek® WRB apron underneath.
ALTERNATE STEP A: If apron extends far enough below the sill rough opening to overlap the sill plate, base of wall flashing, or the DuPont™ Tyvek® WRB below, the DuPont™ Tyvek® WRB can be cut along jambs and head only to overlap apron.

B. Create horizontal slits in the DuPont™ Tyvek® WRB at each lower corner of the perimeter cut that extend a minimum of 2" beyond DuPont™ Tyvek® WRB apron.



STEP 4
A. Bring the bottom portion of the DuPont™ Tyvek® WRB apron through the sill perimeter cut and horizontal slits so it laps over the top layer of DuPont™ Tyvek® WRB.
B. Working from bottom to top, install DuPont™ Tyvek® Tape to secure horizontal and vertical seams of DuPont™ Tyvek® WRB apron.
C. Install DuPont™ Tyvek® Tape along jambs and head to seal DuPont™ Tyvek® WRB around window.




DuPont™ Tyvek® Water-Resistive and Air Barriers Installation Guidelines

Penetrations

Seal around plumbing pipes, HVAC components, electrical outlets, exterior lights, flashing panels, and other objects that penetrate the DuPont™ Tyvek® WRB. Always use positive shingling by installing DuPont™ Tyvek® WRBs and Self-Adhered Flashing products from bottom to top, with upper layer installed over lower layer.

Flashing Integral Flanged Products Installed AFTER DuPont™ Tyvek® WRB

Method 1



STEP 1
Install DuPont™ Tyvek® WRB and cut as necessary to accommodate integral flanged product.

STEP 2
Install integral flanged product per manufacturer's instructions.

STEP 3
Install DuPont™ Self-Adhered Flashing onto sides and top flange, extending onto DuPont™ Tyvek® WRB by a minimum of 2". **NOTE:** Also install at bottom flange as a recommended best practice and for air barrier installations.

STEP 4 (OPTIONAL)
Install a piece of DuPont™ Tyvek® WRB to overlap the top edge of the DuPont™ Self-Adhered Flashing. Seal sides and top with DuPont™ Tyvek® Tape.

OPTIONAL LAST STEP FOR ALL INSTALLATIONS: Install a piece of DuPont™ Tyvek® WRB and seal with DuPont™ Tyvek® Tape to overlap the top edge of the DuPont™ Self-Adhered Flashing product (shown in Method 1 below).

*Use DuPont™ Self-Adhered Flashing products with DuPont™ Adhesive/Primer (or recommended primer) as applicable to seal the DuPont™ Tyvek® WRB directly to concrete, wood, or other rough surfaces. The DuPont™ Tyvek® WRB can also be sealed to rough surfaces using DuPont™ Residential Sealant (or recommended sealant).

**Except when installing DuPont™ Tyvek® WRB over foam and other non-nail-base sheathings.

Installation Instructions


Start at bottom corner of structure to ensure proper shingling throughout the installation. Proper shingling is required to shed water and to prevent water from entering the wall system. Printed stud marks are available on some DuPont™ Tyvek® WRBs to aid in aligning with the studs (e.g. studmarks are 8" apart for DuPont™ Tyvek® HomeWrap®).

STEP 1
Align roll at bottom corner of structure. Roll should be plumb. Bottom edge of roll must:
• extend over sill plate interface by at least 1" (2" or greater is recommended)
• extend to bottom of sill plate for slab on grade foundations, etc.
• be properly integrated with water drainage components such as kick-out flashing or weep screed (for stucco exteriors).
When bottom edge of roll is less than 2" over the sill plate interface, it is recommended to seal or skip-seal the DuPont™ Tyvek® WRB at the bottom of the wall.*


STEP 2
UNWRAP roll starting at corner. Overlap all vertical seams by 6-12".

STEP 3
Secure DuPont™ Tyvek® WRB to the stud or other nail-base material (i.e., wood sheathing). Fasteners should be placed no closer than 6" and no farther than 16" on vertical stud lines. Securing along stud lines will assist in maintaining fastening pattern. Penetrating bandboard or other horizontal members may be necessary to maintain fastening pattern. Do not install fasteners within 6" of the sills and jambs and within 3" of the head of the window rough openings. Use one or more of the recommended fasteners below for use with DuPont™ Tyvek® WRBs:
• DuPont™ Tyvek® Wrap Cap Nails
• DuPont™ Tyvek® Wrap Cap screws
• DuPont™ Tyvek® Wrap Cap staples or other cap staples for Slinger™ Cap Stapler**
• Other manufacturers' equivalent fasteners.

Please see "Special Considerations" section above for equivalent fastener requirements and "Temporary Fastening" section below for more information on alternative fastening schedules and requirements.



Examples of Sealing DuPont™ Tyvek® WRB at Bottom of Wall




STEP 8
After DuPont™ Tyvek® WRB is installed refer to the DuPont™ Self-Adhered Flashing Systems Installation Guidelines, Installation Instructions for Windows and Doors AFTER Water-Resistive Barrier (WRB) is installed to prepare and flash windows and doors.


DuPont™ Tyvek® Water-Resistive and Air Barriers Installation Guidelines

Flashing Non-Flanged Products - Installed AFTER DuPont™ Tyvek® WRB

Method 1: Flashing Non-Flanged Products Using DuPont™ FlexWrap™ EZ



For non-flanged products with OD GREATER than 2"



STEP 1
Install DuPont™ Tyvek® WRB over non-flanged product and cut around penetration.

STEP 2
Cut a piece of DuPont™ FlexWrap™ EZ the length of 1/2 the circumference of the non-flanged product. Adhere onto bottom section and fan out onto DuPont™ Tyvek® WRB.


STEP 3
Cut a second piece of DuPont™ FlexWrap™ EZ the length of 1/2 the circumference of the pipe circumference. Adhere onto top section and fan out onto face of wall with a minimum of 1" overlap of the edges of

DuPont™ Tyvek® Water-Resistive and Air Barriers Installation Guidelines

Proper Overlap for Water Management

A. Lap all components from bottom of the wall to the top of the wall.
B. Treat the walls of the building just like a roof.

NOTE: In order to make a claim under the DuPont 10-Year Limited Product and Labor Warranty on DuPont Weatherization Products, you must have met all of the terms and conditions of the warranty, including use of the applicable DuPont Installation Guidelines. In the event that a specific detail or installation technique is not covered in the DuPont Installation Guidelines at the time you are building, then the Key Installation Requirements outlined in this document must have been followed in order to make a claim under the warranty. Compliance prior, during and post construction with the Key Installation Requirements are at the sole discretion of DuPont. Please contact DuPont or a DuPont™ Tyvek® Specialist if you have any questions in connection with any DuPont Installation Guideline.



Copyright ©2019 E. I. du Pont de Nemours and Company. All Rights Reserved. K16282 Rev. 01/19

22