COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2014 EFFECTIVE 1 JULY 2015 AND THE NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT 2014 FLORIDA BUILDING CODES RESIDENTIAL, EFFECTIVE 1 JULY 2015. NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609-A THROUGH 1609-C ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES

Revised 12/2016 GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as Applicable
	Select From the Dropbox
1 Two (2) complete sets of plans containing the following: 2 All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void 3 Condition space (Sq. Ft.) 2413 Total (Sq. Ft.) under roof 2080	YES NO N/A

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.2.1

S	ite Plan information including:	- VBS
4	Dimensions of lot or parcel of land	- ves
5	Dimensions of all building set backs	1100
6	Dimensions of all building set backs Location of all other structures (include square footage of structures) on parcel, existing or proposed	- 425
L	well and septic tank and all utility easements.	-UPS
7	Provide a full legal description of property.	7.1

W	nd-load Engineering Summary, calculations and any details are required. GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Marked as Applicable		
25	Plans or specifications must show compliance with FBCR Chapter 3	(YES)	NO	N/A	
8	Plans or specifications must show obe-p	Select Fr		Topuo	
9	Basic wind speed (3-second gust), miles per hour	- 4	75		
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated)		RS		
1	Wind importance factor and nature of occupancy	- U	es		
	Components and Cladding	- 1	K>		
12	The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component,		Politica and Sale		
13	The design wind pressure in terms of psi (kivili), to be used for the cladding materials not specifally designed by the registered design professional.	- U	es		

Elev	rations Drawing including:	I- ues
14	All side views of the structure	- ues
15	Roof pitch	- yes
16	Overhang dimensions and detail with attic ventilation	- 462
17	Location, size and height above roof of chimneys	- 495
18	Location and size of skylights with Florida Product Approval	- Vec
18	Number of stories	- 1100
20A	Building height from the established grade to the roofs highest peak	

FI	oor Plan including:	
	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck,	- 480
20		-103
21	Raised floor surfaces located more than 30 inches above the floor or grade	- hla
22	All exterior and interior shear walls indicated	- yes
23	Cheer well enoning shows (Windows Doors and Garage doors)	- yes
24	Show compliance with Section FRCR 310 Emergency escape and rescue opening snown in each	
1 -	hadroom (not clear eneming shown) and Show compliance with Section FBC 1405.13.2 where the	
1	I more than // inches above the fillished grade of surface 1	
1	1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t	- yes
	the finished floor of the room in which the window is located. Glazing between the floor and 24	4
1	inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass.	
25	Safety glazing of glass where needed	- na
-	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth	250
26		-
27	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails	- nia
28	Identify accessibility of bathroom (see FBCR SECTION 320)	- nta
		ave Florida product
AL	I materials placed within opening or onto/into exterior walls, soffits or roofs shall be materials placed within opening or onto/into exterior walls, soffits or roofs shall be materials placed with the plans (see Fig.	rida product approv
	proval number and mfg. installation information submitted with the plans (see Flo	riua product approv
for	rm)	
	The second secon	Items to Include-
2.3	GENERAL REQUIREMENTS:	Each Box shall be
	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Marked as
		Applicable
A-1204500		
5 KT 9/8/		CONTROL DE LA CO
1.17%		YES / NO / N/A
FB	CR 403: Foundation Plans	YES / NO / N/A
	S	CONTROL DE LA CO
FB 29	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size	YES / NO / N/A
29	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	YES / NO / N/A elect From the Dropbox
29	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing	YES / NO / N/A elect From the Dropbox
29 30 31	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling.	YES / NO / N/A elect From the Dropbox
30 31 32	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot	YES / NO / N/A elect From the Dropbox - Yes - Nes - Nes
29 30 31	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system.	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32 33	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32 33	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32 33 FB	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32 33 FB	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32 33 33 FB6 34 35	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32 33 33 FB6 34 35	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32 33 FBC 34 35	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	YES / NO / N/A elect From the Dropbox - YES - NES - NIA - NA
30 31 32 33 FB6 FB6	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered	YES / NO / N/A elect From the Dropbox - YES - NES - NIA
30 31 32 33 FBC 34 35	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	YES / NO / N/A elect From the Dropbox - YES - NES - NIA - NIA
30 31 32 33 34 35 FB6 36	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides	YES / NO / N/A elect From the Dropbox - YES - NES - NIA - NIA
30 31 32 33 34 35 FB6 36	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)	YES / NO / N/A elect From the Dropbox - YES - NES - NIA - NIA
30 31 32 33 34 35 FB6 36	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type	YES / NO / N/A elect From the Dropbox - YES - NES - NIA - NA
30 31 32 33 34 35 FBC 36	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as pilling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement	YES / NO / N/A elect From the Dropbox - YES - NES - NIA - WES
30 31 32 33 34 35 FBC 36	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as pilling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement	YES / NO / N/A elect From the Dropbox - 1985 - 1985 - 1985 - 1985 - 1985 - 1985 - 1985 - 1985 - 1985
30 31 32 33 33 FB6 34 35 FB6 37 38 Met	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement and sealed by Florida Pro	YES / NO / N/A elect From the Dropbox - YES - NES - NIA - WES
30 31 32 33 33 FB6 34 35 FB6 37 38 Met	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement and sealed by Florida Pro	YES / NO / N/A elect From the Dropbox - YES - NES - NIA - WES
30 31 32 33 33 FBC 34 35 FBC 37 38 Met	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement and frame shear wall and roof systems shall be designed, signed and sealed by Florida Proof or Framing System: First and/or second story	YES / NO / N/A elect From the Dropbox - YES - NES - NE
30 31 32 33 33 FBC 34 35 FBC 37 38 Met	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement and sealed by Florida Pro	YES / NO / N/A elect From the Dropbox - YES - NES - NIA - WES

	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls,	- ues
40		
41	Girder type, size and spacing to load bearing walls, stem wall and/or priers	- 1162
42	Attachment of joist to girder	- UPS
	Wind load requirements where applicable	- yer
	Show required under-floor crawl space	- h/a.
4:	Show required amount of ventilation opening for under-floor spaces	- 11-a
47	Show required covering of ventilation opening Show the required access opening to access to under-floor spaces	- Ma
4/	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &	
48		- yes
_	Show Draftstopping, Fire caulking and Fire blocking	- u-e.s
50	Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6	- U-P?
51		- Leg
		YES / NO / N/A
Н	BCR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION	9.00 - 10 To - 7 - 7 - 1 To -
	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as
300		Applicable
2		lect From the Dropbo
2	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls Fastener schedule for structural members per table IRC 602.3 are to be shown	- 425
_		- yes
4	Show Wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	- yes
5	Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	- yes
6	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per IRC Table 502.5 (1)	- Utes
7	Indicate where pressure treated wood will be placed	- ues
3	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing edges & intermediate areas	- yes
9	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	- hes
R	CR :ROOF SYSTEMS:	
v		
-	Two docion describe shall most section EDCD 902 1 6 1 Was demanded	11144
T	Truss design drawing shall meet section FBCR 802.1.6.1 Wood trusses	- Ues
I	Include a layout and truss details, signed and sealed by Florida Professional Engineer	-1123
	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	- 1128 - 429
	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	- 1125 - 426 - 1125
	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	- 1128 - 479
	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses	- 1125 - 426 - 1125
B	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout	- 425 - 425 - 425
B	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout Rafter and ridge beams sizes, span, species and spacing	- 425 - 425 - 425
B	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout Rafter and ridge beams sizes, span, species and spacing Connectors to wall assemblies' include assemblies' resistance to uplift rating	- 425 - 425 - 425 - 425
B	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout Rafter and ridge beams sizes, span, species and spacing	- 425 - 425 - 425
B	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout Rafter and ridge beams sizes, span, species and spacing Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system	- 1125 - 1125 - 1125 - 1125 - 1125
B 1	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout Rafter and ridge beams sizes, span, species and spacing Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING	- 1125 - 1125 - 1125 - 1125 - 1125
B	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout Rafter and ridge beams sizes, span, species and spacing Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING Include all materials which will make up the roof decking, identification of structural panel	- 425 - 425 - 425 - 425 - 425
B 1 1 1 S 1 S	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout Rafter and ridge beams sizes, span, species and spacing Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING Include all materials which will make up the roof decking, identification of structural panel heathing, grade, thickness	- 405 - 405 - 405 - 405 - 405 - 405 - 405
B 1 1 1 1 S S S S S S S S S S S S S S S	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout Rafter and ridge beams sizes, span, species and spacing Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING Include all materials which will make up the roof decking, identification of structural panel heathing, grade, thickness Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas OF ASSEMBLIES FRC Chapter 9	- 1125 - 1125 - 1125 - 1125 - 1125 - 1125
BC	Include a layout and truss details, signed and sealed by Florida Professional Engineer Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details Provide dead load rating of trusses CR 802:Conventional Roof Framing Layout Rafter and ridge beams sizes, span, species and spacing Connectors to wall assemblies' include assemblies' resistance to uplift rating Valley framing and support details Provide dead load rating of rafter system CR 803 ROOF SHEATHING Include all materials which will make up the roof decking, identification of structural panel heathing, grade, thickness	- 1125 - 1125 - 1125 - 1125 - 1125 - 1125

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

YES / NO / N/A

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as Applicable
		Select From the Dropbox
73	Show the insulation R value for the following areas of the structure	- LIES
	Attic space	- LIPS
	Exterior wall cavity	- ues
76	Crawl space	- N/W
H	AC information	w A
77	Submit two copies of a Manual J sizing equipment or equivalent computation study	- 1162
78	Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or 20 cfm continuous required	- UPS
79	Show clothes dryer route and total run of exhaust duct	- 1125
80 81	All fixtures waste water lines shall be shown on the foundation plan Show the location of water heater	- CHES
82		-
	Reservoir pressure tank gallon capacity	-
84	Rating of cycle stop valve if used	-
85	Show Switches, receptacles outlets, lighting fixtures and Ceiling fans Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A	- U.ES
87	Show the location of smoke detectors & Carbon monoxide detectors	- 445
88		- 445
89	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a	- 4
di di	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3	Marie Commence of
90	Appliances and HVAC equipment and disconnects	- 11-67
91	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter, Protection device.	- thes

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

		YES	NO	N/A
92	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted. There is a \$15.00 application fee. The completed application with attached documents and application fee can be mailed.	NO		
93	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	NO	ye.	Ž
94	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	NO		
***	BELOW ITEMS ONLY NEEDED AFTER ZONING APPROVAL HAS GIVEN.	404500	44.4	*** ****
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	NO	ijes	2
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031	NO		
97	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations	NO		
98	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required.			2
99	A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00			
100	Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size and length of every culvert before instillation and completes a final inspection before permanent power is granted. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.	NO		
101	911 Address: An application for a 911 address must be applied for and received through the Columbia	NO	\$	

TOILET FACILITIES SHALL BE PROVIDED FOR ALL CONSTRUCTION SITES. NO

<u>Disclosure Statement for Owner Builders</u> If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form recorded in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code shall govern the administration and enforcement of the Florida Building Code, Residential.