

COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST REQUIRMENTS

MINIMUM PLAN REQUIREMENTS FOR THE FLORIDA BUILDING CODE RESIDENTIAL 2007 ONE (1) AND TWO (2) FAMILY DWELLINGS

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE with the Current 2007 FLORIDA BUILDING CODES RESIDENTIAL. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FIGURE R301.2(4) of the FLORIDA BUILDING CODES RESIDENTIAL (Florida Wind speed map) SHALL BE USED.

WIND SPEED LINE SHALL BE DEFINED AS FOLLOWS: THE CENTERLINE OF INTERSTATE 75.

ALL BUILDINGS CONSTRUCTED EAST OF SAID LINE SHALL BE ------ 100 MPH ALL BUILDINGS CONSTRUCTED WEST OF SAID LINE SHALL BE ------110 MPH NO AREA IN COLUMBIA COUNTY IS IN A WIND BORNE DEBRIS REGION

	APPLICANT - PLE		REQUIREMENTS: APPLICABLE BOXES BEFORE SUBMITTAL		Circled as Applicable		
			A STATE OF THE STA	1	Yeş	No	N/A
1	Two (2) complete sets of p	lans containing the fo	llowing:		X		
2	All drawings must be clear	r, concise, drawn to sc	ale, details that are not used shall be marked void		X		
3	Condition space (Sq.	1715	Total (Sq. Ft.) under roof 235 6	II	imm	HIIIIIII	ШШ

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.2.1

S	ite Plan information including:	/	
4	Dimensions of lot or parcel of land	X	
5	Dimensions of all building set backs	N	
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	X	
7	Provide a full legal description of property.	X	

Items to Include-Each Box shall be

Wind-load Engineering Summary, calculations and any details required

1. 强能	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each C	to Inclu Box shal ircled as olicable	
8	Plans or specifications must show compliance with FBCR Chapter 3	IIIIII	IIIII	ШШ
-		YES	NO	N/A
9	Basic wind speed (3-second gust), miles per hour	V		
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated)	X		
11	Wind importance factor and nature of occupancy	X		
12	The applicable internal pressure coefficient, Components and Cladding	X		
13	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional.	X		
				-

Elevations Drawing including:

14	All side views of the structure			
15	Roof pitch	X)°		
16	Overhang dimensions and detail with attic ventilation	V		
17	Location, size and height above roof of chimneys	X)		
18	Location and size of skylights with Florida Product Approval	Mr.	W	X
18	Number of stories	No.	/	X
20A	Building height from the established grade to the roofs highest peak	. V		1

Floor Plan including:

20	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, balconies	M		
21	Raised floor surfaces located more than 30 inches above the floor or grade	X		
22	All exterior and interior shear walls indicated	X.		
23	Shear wall opening shown (Windows, Doors and Garage doors)	X		1.
24	Emergency escape and rescue opening shown in each bedroom (net clear opening shown)	The same of the sa		X
25	Safety glazing of glass where needed	X		
26	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 of FBCR)	A		
27	Stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails (see FBCR SECTION 311)	/	*	X
28	Identify accessibility of bathroom (see FBCR SECTION 322)	V	1	1

All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the pla (see Florida product approval form)

Items to Include-GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Each Box shall be Circled as Applicable FBCR 403: Foundation Plans YES NO N/A Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. 31 Pound Per Square Foot 32 Assumed load-bearing valve of soil Location of horizontal and vertical steel, for foundation or walls (include # size and type) FBCR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports FBCR 320: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or submit other approved termite protection methods. 36 Protection shall be provided by registered termiticides FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect Floor Framing System: First and/or second story Floor truss package shall including layout and details, signed and sealed by Florida Registered Professional Engineer 39 Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or priers 40 Girder type, size and spacing to load bearing walls, stem wall and/or priers 42 Attachment of joist to girder Wind load requirements where applicable 43 44 Show required under-floor crawl space 45 Show required amount of ventilation opening for under-floor spaces Show required covering of ventilation opening 46 Show the required access opening to access to under-floor spaces Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &

48	intermediate of the areas structural panel sheathing	X
49	Show Draftstopping, Fire caulking and Fire blocking	X
50	Show fireproofing requirements for garages attached to living spaces, per FBCR section 309	N
	Provide live and dead load rating of floor framing systems (psf).	X

FBCR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION

	Fastener schedule for structural members per table FBCR 602.3 are to be shown Show Wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	Items to Inclu Each Box sha Circled as Applicabl		
		YES	NO	N/A
52	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	X		
53	Fastener schedule for structural members per table FBCR 602.3 are to be shown	M		
54	panel sheathing	X		
55	Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	X		
56	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per FBCR Table 502.5 (1)	X		
57	Indicate where pressure treated wood will be placed	X		
58	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing edges & intermediate areas	8		
59	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	N		L

FBCR:ROOF SYSTEMS:

60	Truss design drawing shall meet section FBCR 802.10 Wood trusses	X	
61	Include a layout and truss details, signed and sealed by Florida Professional Engineer	X/	
62	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	V	
	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	X	
64	Provide dead load rating of trusses	\otimes	
_		/	

FBCR 802:Conventional Roof Framing Layout

			1/1
65	Rafter and ridge beams sizes, span, species and spacing		V2
66	Connectors to wall assemblies' include assemblies' resistance to uplift rating	W	K
67	Valley framing and support details		Y
68	Provide dead load rating of rafter system		Y _

FBCR Table 602,3(2) & FBCR 803 ROOF SHEATHING

69	Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness	X		
70	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	y		

FBCR ROOF ASSEMBLIES FRC Chapter 9

71	Include all materials which will make up the roof assembles covering	X	
72	Submit Florida Product Approval numbers for each component of the roof assembles covering	N)	

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, showing dimensions condition area equal to the total condition living space area

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITT.	Each I	Items to Include- Each Box shall be Circled as Applicable	
	YĘS	NO	N/A
73 Show the insulation R value for the following areas of the structure	y y		
74 Attic space	N		
75 Exterior wall cavity	Ŋ		
76 Crawl space	V		
78 Exhaust fans locations in bathrooms 79 Show clothes dryer route and total run of exhaust duct	<u> </u>		
Plumbing Fixture layout shown			
	1 10		
80 All fixtures waste water lines shall be shown on the foundation plan			
81 Show the location of water heater	V		
Private Potable Water			
82 Pump motor horse power	X		
83 Reservoir pressure tank gallon capacity	- X		
84 Rating of cycle stop valve if used			-
Electrical layout shown including			
Switches, outlets recentacles, lighting and all required GECI outlets identified	V		

85	Switches, outlets/receptacles, lighting and all required GFCI outlets identified	y	
86	Ceiling fans	W.	
87	Smoke detectors & Carbon dioxide detectors	y	
88	Service panel, sub-panel, location(s) and total ampere ratings	y	
89	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.		

90	Appliances and HVAC equipment and disconnects	V.	
91	Arc Fault Circuits (AFCI) in bedrooms	,XV	

<u>Disclosure Statement for Owner Builders</u> If you as the applicant will be acting as an owner builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form **recorded** in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

The state of the second of	Items to Include-
GENERAL REQUIREMENTS:	Each Box shall be
APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Circled as
。17 的是"不够好"。由于"连生"等。20 等。在20 新年,第122 第122 第122 第122 第122 第122 第122 第122	Applicable

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

		YES	NO	N/A
92	Building Permit Application A current Building Permit Application form is to be completed and submitted for all residential projects			1
93			-	-
93	Parcel Number The parcel number (Tax ID number) from the Property Appraiser			
	(386) 758-1084 is required. A copy of property deed is also requested		-	-
94	Environmental Health Permit or Sewer Tap Approval A copy of a approved			
	Columbia County Environmental Health (386) 758-1058			
95	City of Lake City A permit showing an approved waste water sewer tap			
96	Toilet facilities shall be provided for all construction sites			
97	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is			
	within the Corporate city limits of Fort White an approval land use development letter issued by the			
	Town of Fort is required to be submitted with the application for a building permit.			
	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers			
NO CONTROL OF	shall require permitting through the Suwannee River Water Management District, before			
98	submitting a application to this office. Any project located within a flood zone where the base flood			
	elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the			
	Columbia County Land Development Regulations. Any project located within a flood zone			
	where the base flood elevation has not been established (Zone A) shall meet the requirements of			
	Section 8.5.3 of the Columbia County Land Development Regulations			
99	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project			
	where the base flood elevation (100 year flood) has been established			
100	A development permit will also be required. Development permit cost is \$50.00			
	Driveway Connection: If the property does not have an existing access to a public road,			
	then an application for a culvert permit (\$25.00) must be made. If the applicant feels that a			
101	culvert is not needed, they may apply for a culvert waiver (\$50.00).			
	All culvert waivers are sent to the Columbia County Public Works Department for approval			
	or denial.			
	911 Address: If the project is located in an area where a 911 address has not been issued,			
102	then application for a 911address must be applied for and received through the Columbia County			
	Emergency Management Office of 911 Addressing Department (386) 758-1125			

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code, Building shall govern the administration and enforcement of the Florida Building Code, Residential.

Section 105 of the Florida Building Code defines the:

Time limitation of application.

An application for a permit for any proposed work shall be deemed to have been abandoned 180 days after the date of filing, unless such application has been pursued in good faith or a permit has been issued; except that the building official is authorized to grant one or more extensions of time for additional periods not exceeding 90 days each. The extension shall be requested in writing and justifiable cause demonstrated.

Single-family residential dwelling.

Section 105.3.4 A building permit for a single-family residential dwelling must be issued within 30 working days of application therefor unless unusual circumstances require a longer time for processing the applica or unless the permit application fails to satisfy the Florida Building Code or the enforcing agency's laws of ordinances.

Permit intent.

Section 105.4.1: A permit issued shall be constructed to be a license to proceed with the work and not as authority to violate, cancel, alter or set aside any of the provisions of the technical codes, nor shall issuance a permit prevent the building official from thereafter requiring a correction of errors in plans, construction or violations of this code. Every permit issued shall become invalid unless the work authorized by such permit is commenced within six months after its issuance, or if the work authorized by such permit is suspended or abandoned for a period of six months after the time the work is commenced.

If work has commenced.

Section 105.4.1.1: If work has commenced and the permit is revoked, becomes null and void, or expires because of lack of progress or abandonment, a new permit covering the proposed construction shall be obtained before proceeding with the work.

New Permit.

Section 105.4.1.2: If a new permit is not obtained within 180 days from the date the initial permit became and void, the building official is authorized to require that any work which has been commenced or completed be removed from the building site. Alternately, a new permit may be issued on application, providing the work in place and required to complete the structure meets all applicable regulations in effe at the time the initial permit became null and void and any regulations which may have become effective between the date of expiration and the date if issuance of the new permit.

Work Shall Be:

Section 105.4.1.3: Work shall be considered to be in active progress when the permit has received an approved inspection within 180 days. This provision shall not be applicable in case of civil commotion or strike or when the building work is halted due directly to judicial injunction, order or similar process.

The Fee:

Section 105.4.1.4: The fee for renewal reissuance and extension of a permit shall be set forth by the administrative authority.

When the submitted application is approved for permitting the applica will be notified by phone as to the date and time a building permit will prepared and issued by the Columbia County Building & Zoning Department