




SQUARE FOOTAGES	
AREA	SQ. FT.
ENTRY	131 SF
GARAGE	541 SF
LANAI	154 SF
LIVING 1	2071 SF
LIVING 2	280 SF
TOTAL	3111 SF



BONUS ROOM ELEVATION



BUILDING SECTION

- GENERAL NOTES:**
- ALL WINDOWS TO HAVE FLUSH SILLS. PITCH TOP OF SILL FIN AWAY FROM WINDOW FRAME.
 - VERIFY ALL WINDOW & DR. ROUGH OPENINGS W/ MFR SPECS. SEE PLAN FOR WINDOW HEADS.
 - VERIFY DEPTH AND WIDTH OF SLAB RECESS AT ALL DOORS TO ACCOMMODATE PROPER ALIGNMENT WITH THRESHOLDS AND DOOR TRACKS WITH MFR. REQUIREMENTS IN RELATION TO FINISH FLOOR MATERIALS.
 - REG. CLG SURFACES, BOTH HORIZONTAL AND VERTICAL, SHALL HAVE SMOOTH FIN.
 - PROVIDE SOLID FILLED CONG. BLOCK AT ALL SHOWER SEATS.
 - SEE SHEET 6 FOR SPECIFIC ELEV DETAILS.
 - 3000 PSI CONCRETE DRIVEWAY UP TO 750 SF.
 - ALL EXTERIOR FRENCH DOORS & SERVICE DOORS TO BE FIBERGLASS; ENTRY DOOR STYLE & MATERIAL TBD; ALL EXTERIOR DOORS WILL HAVE FRAME DEFENSE OR FRAME SAVER JAMBS.
 - ALL INTERIOR DOORS TO BE CARRARA SMOOTH OR EQUAL HARDBOARD 1 1/2\"/>
- INSULATION:**
- ATTIC - R-30 "BLOWN" INSULATION.
 - ATTIC WALLS - R-30 "BATT" INSULATION.
 - 4" FRAME WALLS - R-13 "BATT" INSULATION.
 - 6" FRAME WALLS - R-14 "BATT" INSULATION.
- INTERIOR MOULDING:**
- BASE, EMPIRE 620 OR EQUAL 1 1/4" FINGER JOINT BASE MOULDING.
 - DOOR CASINGS, 5/8" 201 OR EQUAL 2 1/4" FINGER JOINT DOOR CASING.
 - WINDOW SILLS, FJ PINE STOOD & 2 1/4" APRON TRIM.





01/04/14 P.E.C. - A
 01/04/14 P.E.C. - A
 01/04/14 P.E.C. - B

ARTHUR RUTENBERG HOMES, INC. THE DESIGNER IS RESPONSIBLE FOR THE AESTHETIC DESIGN ONLY AS SHOWN ON THESE PLANS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR OBTAINING ALL APPLICABLE FEDERAL, STATE AND LOCAL BUILDING CODES, ORDINANCES, AND LAWS, AND FOR OBTAINING ALL NECESSARY INSURANCE COVERAGE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR OBTAINING ALL APPLICABLE FEDERAL, STATE AND LOCAL BUILDING CODES, ORDINANCES, AND LAWS, AND FOR OBTAINING ALL NECESSARY INSURANCE COVERAGE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR OBTAINING ALL APPLICABLE FEDERAL, STATE AND LOCAL BUILDING CODES, ORDINANCES, AND LAWS, AND FOR OBTAINING ALL NECESSARY INSURANCE COVERAGE.

THE HEATHER 1202F - R - JONES/GOODSON RESIDENCE
 BUILDER: BRYAN ZECHER HOMES, INC.
 AN INDEPENDENTLY OWNED AND OPERATED FRANCHISE

34X36: 1/4" = 1'-0"
 18X24: 1/8" = 1'-0"





FLOOR PLAN
 PLAN 1202F-2F-01-B




- GENERAL NOTES:**
- FLAT SOFFIT AT PERIMETER OF HOUSE UNLESS NOTED OTHERWISE.
 - VERIFY ALL HDW & DR ROUGH OPNGS W/ MFR SPECS.
 - LOCATE ALL PLUMBING STACKS BEYOND THE FRONT ELEV ROOF RIDGES, IF ALLOWABLE PER CODE.
 - ROOF VENTS SHOWN FOR LOCATION PURPOSE ONLY.
 - NUMBER OF ROOF VENTS TO BE DETERMINED BY BUILDER.

FRAMING PLAN DISCLAIMER


THE FRAMING PLANS REPRESENTED IN THESE DRAWINGS ARE INTENDED TO ESTABLISH PROPOSED FRAMING MEMBER LOCATIONS AND ELEVATIONS AND IS IN NO WAY INTENDED TO BE INTERPRETED AS STRUCTURAL ENGINEERED DRAWINGS. THE CONTRACTOR (BUILDER) SHALL ENSURE THAT THE STRUCTURE CONFORMS TO THOSE STANDARDS IN ALL RESPECTS INCLUDING STRENGTH, STIFFNESS, STRAINS, LOADS, CONNECTIONS AND STABILITY. REFER TO PLAN DISCLAIMER LOCATED ON THIS SHEET FOR ADDITIONAL STIPULATIONS AND REQUIREMENTS.



FRAMING PLAN DISCLAIMER
 THE FRAMING PLANS REPRESENTED IN THESE DRAWINGS ARE INTENDED TO ESTABLISH PROPOSED FRAMING MEMBER LOCATIONS, FRAMING MEMBER DEPTH, POTENTIAL BEARING LOCATIONS AND ELEVATIONS, AND IS IN NO WAY INTENDED TO BE INTERPRETED AS STRUCTURAL ENGINEERED DRAWINGS. THE CONTRACTOR (BUILDER) SHALL ENSURE THAT THE STRUCTURE CONFORMS TO THOSE STANDARDS IN ALL RESPECTS INCLUDING STRENGTH, STRESSES, STRAINS, LOADS, CONNECTIONS, AND STABILITY. REFER TO PLAN DISCLAIMER LOCATED ON THIS SHEET FOR ADDITIONAL STIPULATIONS AND REQUIREMENTS.



PLAN DISCLAIMER
 SIDE ELEVATIONS / BLDG SECTION
 24X36 - 1/4"=1'-0"
 1/8"=1'-0"
 1/8"X24



5/8\"/>

NOTE: ALIGN FASCIA AND SOFFIT BETWEEN 6:12 AND 6:12 ROOF SLOPES.

NOTE: ALIGN FASCIA AND SOFFIT BETWEEN 6:12 AND 6:12 ROOF SLOPES.



ROOF PLAN

FRAMING PLAN DISCLAIMER

THE FRAMING PLANS REPRESENTED IN THESE DRAWINGS ARE INTENDED TO ESTABLISH PROPOSED FRAMING MEMBER LOCATIONS, FRAMING MEMBER DEPTH, POTENTIAL BEARING LOCATIONS AND ELEVATIONS, AND IS IN NO WAY INTENDED TO BE INTERPRETED AS STRUCTURAL ENGINEERED DRAWINGS. THE CONTRACTOR (BUILDER) SHALL ENSURE THAT THE STRUCTURE CONFORMS TO THOSE STANDARDS IN ALL RESPECTS INCLUDING STRENGTH, STIFFNESS, STRAINS, LOADS, CONNECTIONS, AND STABILITY. REFER TO PLAN DISCLAIMER LOCATED ON THIS SHEET FOR ADDITIONAL STIPULATIONS AND REQUIREMENTS.

MECHANICAL DISCLAIMER

THE DUCT ROUTING AND HVAC EQUIPMENT SHOWN ON THESE DRAWINGS ARE DIAGRAMATIC ONLY. THE BUILDER IS SOLELY RESPONSIBLE FOR COORDINATING ALL ASPECTS OF MECHANICAL INSTALLATION WITH ALL TRADES. THE BUILDER SHALL COORDINATE BETWEEN THE PRE-ENGINEERED TRUSS MFR. AND/OR FRAMING REQUIREMENTS WITH THE MECHANICAL CONTRACTOR TO ENSURE ADEQUATE SPACE FOR DUCT ROUTING AND EQUIPMENT PLACEMENT AND SUPPORT. HVAC INSTALLATION SHALL BE INSTALLED ACCORDING TO ALL CURRENT STATE AND LOCAL MECHANICAL CODES.



SHINGLE ROOF

ALL OVERHANGS TO BE 1'-4\"/>



PROVIDE SOLID BLOCKING BELOW ALL KNEEWALLS AND OVER FRAMING PER TRUSS MFR. AND STRUCT. ENG.

MECHANICAL DISCLAIMER

THE DUCT ROUTING AND HVAC EQUIPMENT SHOWN ON THESE DRAWINGS ARE DIAGNOSTIC ONLY. THE BUILDER IS SOLELY RESPONSIBLE FOR COORDINATING ALL ASPECTS OF MECHANICAL INSTALLATION WITH ALL TRADES. THE BUILDER SHALL COORDINATE BETWEEN THE PRE-ENGINEERED TRUSS MFR. AND/OR FRAMING REQUIREMENTS WITH THE MECHANICAL CONTRACTOR TO ENSURE ADEQUATE SPACE FOR DUCT ROUTING AND EQUIPMENT PLACEMENT AND SUPPORT. HVAC INSTALLATION SHALL BE INSTALLED ACCORDING TO ALL CURRENT STATE AND LOCAL MECHANICAL CODES.

FLOOR OUTLET NOTE:
RECESSED FLOOR OUTLET (FULLY CONCEALED BELOW FLOOR LEVEL) #60-P IW COVER PLATE BY: THOMAS & BETTS, INC OR EQUAL

RECESSED CAN NOTE:
ALL RECESSED CANS MUST HAVE HALOGEN FLOOD LAMPS, SEE ELECTRICAL LEGEND FOR WATTAGE.




GENERAL NOTES:

- 200AMP SERVICE W/ COPPER WIRING FROM BREAKER FNL THROUGHOUT HOME, MIN 200AMP SINGLE PHASE 120/240 V SERVICE
- GREAT ROOM & LANAI - PRE-WIRE FOR SPEAKER SYSTEM.
- SECURITY: INSTALL AT ALL WINDOWS/DOORS W/ CONTACTS, (1) MOTION DETECTOR, (2) KEY PADS, MONITORING BY OWNER.
- ELECTRICAL SWITCHES: SWITCHES TO BE TOGGLE, DIMMERS TO BE SLIDE, 4 OUTLETS TO BE STANDARD.
- HVAC: CARRIER 14-SEER OR EQUAL W/ DUCT WORK, GRILLS, EQUIPMENT & THERMOSTAT.
- 50 GAL ELECTRIC WATER HEATER.
- PEST CONTROL: UNDER SLAB TERMITE PREVENTION TREATMENT.

ELECTRICAL LEGEND

- ⊕ DUPLEX OUTLET (110V AT 12" OR AS NTD)
- ⊕ DUPLEX OUTLET (110V AT 34")
- ⊕ DUPLEX OUTLET (110V AT 43")
- ⊕ DUPLEX OUTLET (110V AT 45")
- ⊕ SPLIT DPLX OUTLET (110V AT 12") TOP 15 "HOT"
- ⊕ WEATHERPROOF DPLX OUTLET (110V AT 12")
- ⊕ WEATHERPROOF DPLX OUTLET (110V AT 12") TOP PLUG IS HOT
- ⊕ 220V OUTLET AT 30"
- ⊕ RECESS FLOOR OUTLET
- ⊕ SPECIAL PURPOSE CONN
- ⊕ TELEPHONE OUTLET AT 12" OR AS NTD
- ⊕ STRUCTURED WIRE COMBO OUTLET WALL OR FL MOUNT
- ⊕ STRUCTURED WIRE QUAD COMBO OUTLET
- ⊕ SW SEE ELEC DTL
- ⊕ 3-WAY SW SEE ELEC DTL
- ⊕ 4-WAY SW SEE ELEC DTL
- ⊕ 1-GANG COMBINATION FAN / LIGHT SWITCH
- ⊕ PUSH-BUTTON FOR GARAGE DOOR AT 60"
- ⊕ DIMMER SW AT 36"
- ⊕ PUSH-BUTTON DOORBELL (DELETE W/ INTERCOM)
- ⊕ CL6 MNT LT FIXTURE
- ⊕ CL6 MNT PREWIRE - FIXTURE BY OWNER
- ⊕ SURFACE MNT FIXTURE
- ⊕ WALL MNT FIXTURE
- ⊕ ROUND RECESS FOR TUB/SHOWER
- ⊕ ROUND RECESS OPEN BAFFLE TRIM W/ TSW HALOGEN FLOOD (INTERIOR FLAT CL6)
- ⊕ MINI ROUND RECESS OPEN BAFFLE TRIM W/ 50W HALOGEN FLOOD (BAR LOCATIONS)
- ⊕ MINI ROUND RECESS EYEBALL TRIM W/ 50W HALOGEN FLOOD
- ⊕ ROUND RECESS REGRESSED EYEBALL W/ TSW HALOGEN FLOOD (INTERIOR SLOPED CL6)
- ⊕ MINI HALOGEN (CABINET LOCATIONS)
- ⊕ CL6 FAN/LIGHT PREWIRE AND SWITCHES
- ⊕ SMOKE & CARBON MONOXIDE DETECTOR
- ⊕-12" UNDER CABT 12"
- ⊕-24" UNDER CABT 24"
- ⊕-36" UNDER CABT 36"
- ⊕-48" UNDER CABT 48"
- ⊕-5-24" SINGLE 24" FLUOR STRIP
- ⊕-5-36" SINGLE 36" FLUOR STRIP
- ⊕-5-48" SINGLE 48" FLUOR STRIP
- ⊕-D-24" DOUBLE 24" FLUOR STRIP
- ⊕-D-36" DOUBLE 36" FLUOR STRIP
- ⊕-D-48" DOUBLE 48" FLUOR STRIP
- ⊕ 24" CL6 MNT FLUOR. LT, WRAPPED
- ⊕ 48" CL6 MNT FLUOR. LT, WRAPPED
- ⊕ 24" VANITY LIGHTING (SEE SPECS)
- ⊕ 36" VANITY LIGHTING (SEE SPECS)
- ⊕ EXHAUST FAN / LIGHT FIXTURE COMBO
- ⊕ SOFFIT MNT FLOOD LIGHT
- ⊕ CL6 MNT SPEAKER
- ⊕ CHIMES (DELETE W/ INTERCOM)
- ⊕ ELEC PANEL
- ⊕ STRUCTURED WIRING PANEL
- ⊕ CL6 RETURN AIR
- ⊕ A/C REGISTER
- ⊕ THERMOSTAT
- ⊕ SECURITY PAD
- ⊕ INTERCOM
- ⊕ MASTER STATION
- ⊕ LIGHTING OR ELECTRONICS (LCD DISPLAY OR LIGHTING AUTOMATION PUSH BUTTON CONTROLLER)
- ⊕ VOLUME CONTROL KNOB
- ⊕ USE MAX OF 6 GANG BOXES, FOR GANG BOXES OF 3 OR MORE THAT ARE LOCATED ON BLOCK WALL, CHIP OUT THE BLOCK TO ACCOMMODATE DEEPER BOX.
- ⊕ NOTE: ALL DIMENSIONS ARE FOR ROUGH FRAMING.




THE ITEMS BELOW ARE SHOWN FOR LOCATION PURPOSES ONLY. PLEASE REFER TO LOCAL SPECS TO DETERMINE WHETHER OR NOT THE FOLLOWING ITEMS ARE INCLUDED:

⊕ INTERCOM
⊕ MASTER STATION
⊕ LIGHTING OR ELECTRONICS (LCD DISPLAY OR LIGHTING AUTOMATION PUSH BUTTON CONTROLLER)
⊕ VOLUME CONTROL KNOB

• USE MAX OF 6 GANG BOXES, FOR GANG BOXES OF 3 OR MORE THAT ARE LOCATED ON BLOCK WALL, CHIP OUT THE BLOCK TO ACCOMMODATE DEEPER BOX.


NOTE: ALL DIMENSIONS ARE FOR ROUGH FRAMING.

ELECTRICAL DETAILS
SCALE: 1/2"=1'-0"




GREAT ROOM

GREAT ROOM




GREAT ROOM

CASUAL DINING




KITCHEN




KITCHEN

GENERAL NOTES:
 CABINET ELEVATIONS AND LIGHTING ARE GRAPHIC REPRESENTATIONS ONLY. REFERENCE SHOULD BE MADE TO THE ELECTRICAL SHEET, CABINET MFR DRAWINGS AND SPECS FOR FURTHER INFORMATION.
 REFER TO CABINET SHOP DRAWINGS FOR CABINET & VANITY TOP DIMENSIONS.
 FOR STEPPED UPPER CABINETS, IF MODULAR CABINETS ARE SELECTED AND NOT AVAILABLE IN SPECIFIED DEPTHS THE WALLS BEHIND CABINETS WILL NEED TO BE BUILT OUT TO OBTAIN SPECIFIED DEPTH.
 THE TOE KICK IS 4".
 PLUMBING, TILE, BASE MLDG, DOOR CASING, & DECORATIVE LIGHTING & DECORATIVE MIRRORS ARE ILLUSTRATED FOR LOCATION PURPOSES ONLY. PLEASE REFER TO COMMUNITY STANDARDS FOR SIZES & SPECS.


CASUAL DINING




KITCHEN ISLAND



DEN




M. SUITE




ENSURE TUB/SHOWER VALVES DO NOT INTERFERE WITH TILE DESIGN - IF FIELD CONFLICT EXISTS, NOTIFY THE DESIGNER

M. BATH





SHOWER WALL


M. BATH WC



BATH 2



UTILITY




GENERAL NOTES:
 CABINET ELEVATIONS AND LIGHTING ARE GRAPHIC REPRESENTATIONS ONLY. REFERENCE SHOULD BE MADE TO THE ELECTRICAL SHEET, CABINET MFR DRAWINGS AND SPECS FOR FURTHER INFORMATION.
 REFER TO CABINET SHOP DRAWINGS FOR CABINET & VANITY TOP DIMENSIONS.
 FOR STEPPED UPPER CABINETS, IF MODULAR CABINETS ARE SELECTED AND NOT AVAILABLE IN SPECIFIED DEPTHS THE WALLS BEHIND CABINETS WILL NEED TO BE BUILT OUT TO OBTAIN SPECIFIED DEPTH.
 THE TOE KICK IS 4".
 PLUMBING, TILE, BASE MLDG, DOOR CASING, & DECORATIVE LIGHTING & DECORATIVE MIRRORS ARE ILLUSTRATED FOR LOCATION PURPOSES ONLY. PLEASE REFER TO COMMUNITY STANDARDS FOR SIZES & SPECS.


01/24/14 PEG - A
 01/24/14 PEG - B
 THESE DRAWINGS ARE THE PROPERTY OF THE DESIGNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND CONSTRUCTION OF THE PROJECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND CONSTRUCTION OF THE PROJECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND CONSTRUCTION OF THE PROJECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND CONSTRUCTION OF THE PROJECT.

THE HEATHER 1262F - R - JONES/GOODSON RESIDENCE
 BUILDER: BRYAN ZECHER HOMES, INC.
 AN INDEPENDENTLY OWNED AND OPERATED FRANCHISE


24X36: 1/2" = 1'-0"
 18X24: 1/4" = 1'-0"
 MASTER BATH, BATH 2, UTILITY
 PLAN 1262F-STD-01-17




1 MONOLITHIC FOOTING SECTION
 IF GROUND ADJACENT TO FTG SLOPES DOWN AND AWAY FROM STRUCTURE STEEPER THAN 1'-0" VERTICALLY PER 3'-0" HORIZONTALLY, CONTRACTOR HAS TWO CHOICES:
 1. PRIOR TO CONSTRUCTION, SEEK GUIDANCE OF EOR TO PREVENT EROSION OF SOIL.
 2. USE STEMWALL FOOTING




5 GARAGE EXT WALL CURB SECTION




6 BEARING CURB STEP SECTION




8 DOUBLE CMU STEMWALL SECTION




9 GARAGE ENTRY CMU STEMWALL SECTION
 1. SPECIAL CARE SHOULD BE EXERCISED BY CONTRACTOR WHEN BACK FILLING BEHIND A STEM WALL, PARTICULARLY WHEN IT IS OVER 4 COURSES HIGH. SHOULD THIS CONDITION EXIST, RECOMMENDATIONS MAY BE OBTAINED FROM THE ENGINEER OF RECORD.
 2. SCREW IN ANCHORS ALLOWED IN MONOLITHIC FOOTINGS ONLY. EPOXY ANCHORS MUST BE USED IN STEMWALL FOUNDATIONS.




1A MONOLITHIC FOOTING SECTION - 36" MAX DEPTH
 IF GROUND ADJACENT TO FTG SLOPES DOWN AND AWAY FROM STRUCTURE STEEPER THAN 1'-0" VERTICALLY PER 3'-0" HORIZONTALLY, CONTRACTOR HAS TWO CHOICES:
 1. PRIOR TO CONSTRUCTION, SEEK GUIDANCE OF EOR TO PREVENT EROSION OF SOIL.
 2. USE STEMWALL FOOTING




2 CMU STEMWALL SECTION
 1. SPECIAL CARE SHOULD BE EXERCISED BY CONTRACTOR WHEN BACK FILLING BEHIND A STEM WALL, PARTICULARLY WHEN IT IS OVER 4 COURSES HIGH. SHOULD THIS CONDITION EXIST, RECOMMENDATIONS MAY BE OBTAINED FROM THE ENGINEER OF RECORD.
 2. SCREW IN ANCHORS ALLOWED IN MONOLITHIC FOOTINGS ONLY. EPOXY ANCHORS MUST BE USED IN STEMWALL FOUNDATIONS.



3 BEARING WALL FOOTING SECTION



4 CURB STEP SECTION



FOUNDATION KEYNOTES:

- A 8"x8" DEEP THICKENED EDGE W/ (1) #4 CONT.
- B 12" DEEP FTG W/ #4 @ 12" EW UNDER BOX COLUMN
- C 16"x12" DEEP FTG W/ (3) #4 EW
- D 24"x20" DEEP FTG W/ (3) #4 EW
- E 30"x20" DEEP FTG W/ (4) #4 EW
- F 36"x20" DEEP FTG W/ (4) #4 EW
- G 48"x24" DEEP FTG W/ (5) #4 EW, T&B


CONTROL JOINTS (CJ)

- TIMING**
- a. CUTS MUST BE MADE THE SAME DAY AS PLACEMENT. AS SOON AS THE CONCRETE HAS SET ENOUGH TO ALLOW SAWCUTS WITHOUT RAVELING THE COARSE AGGREGATE FROM THE CUT, MAKE THE CUT.
 - b. CUTS MADE THE NEXT DAY OR AT SUBSEQUENT TIMES DO NOT PROVIDE ADEQUATE PROTECTION AGAINST "RANDOM" CRACKING.
- DEPTH**
- a. THE CUT SHOULD BE AT LEAST 1" DEEP, BUT NOT MORE THAN 1 1/2" DEEP.




THIS FOUNDATION PLAN WAS PREPARED BY ARTHUR RUTENBURG HOMES. THE STRUCTURAL FOUNDATION REQUIREMENTS WERE INCLUDED BY APEX TECHNOLOGY AFTER THE DRAWING WAS GENERATED. BY ACCEPTING THIS DRAWING, BRYAN ZECHEER HOMES RELEASES APEX TECHNOLOGY FROM ANY RESPONSIBILITY OF THE LAYOUT OF THE FOUNDATION WITH REGARD TO THE DIMENSIONS AND THE LOCATION OF MISCELLANEOUS PLUMBING, ELECTRICAL, AND MECHANICAL WORK REQUIREMENTS. ANY MODIFICATION BY APEX TO THE INFORMATION PROVIDED BY ARTHUR RUTENBURG HOMES MUST HAVE WRITTEN CONSENT FROM BRYAN ZECHEER HOMES PRIOR TO THE RELEASE OF CONSTRUCTION DRAWINGS.

EQUIPMENT/SERVICE PAD: ACTUAL PADS AND/OR WALLS MUST BE VERIFIED WITH BUILT SET ARCHITECTURAL PLANS AS LAYOUT AND/OR DIMENSIONS ON THESE STRUCTURAL PLANS ARE SUBJECT TO CHANGE.

POOL NOTE: ACTUAL POOL AREA OUTLINE MUST BE VERIFIED WITH BUILT SET ARCHITECTURAL PLANS AS LAYOUT AND/OR DIMENSIONS ON THESE PLANS ARE SUBJECT TO CHANGE.



7 CMU STEMWALL SECTION
 1. SPECIAL CARE SHOULD BE EXERCISED BY CONTRACTOR WHEN BACK FILLING BEHIND A STEM WALL, PARTICULARLY WHEN IT IS OVER 4 COURSES HIGH. SHOULD THIS CONDITION EXIST, RECOMMENDATIONS MAY BE OBTAINED FROM THE ENGINEER OF RECORD.
 2. SCREW IN ANCHORS ALLOWED IN MONOLITHIC FOOTINGS ONLY. EPOXY ANCHORS MUST BE USED IN STEMWALL FOUNDATIONS.



BOTTOM PLATE ANCHOR OPTIONS

1. The engineering data and details contained herein are the property of Apex Technology and are not to be reproduced in any manner, except as approved in writing by Apex Technology.
 2. The information represented in this package is intended for the residence or structure indicated in the title block alone. Application of these details to any other structure is not intended.
 3. Dimensions should not be scaled from the drawings. If a dimension is unclear or indeterminate from adjacent dimensions, contact the engineer of record for clarification.



FL00014 D.A.E.-A
 FL00014 D.A.E.-B
 FL00014 D.A.E.-C

DISCLAIMER
 ARTHUR RUTENBURG HOMES INC. THE DESIGNER, IS RESPONSIBLE FOR THE ARCHITECTURAL DESIGN ONLY AS REPRESENTED IN THESE DRAWINGS. THE ENGINEER OF RECORD IS RESPONSIBLE FOR THE STRUCTURAL DESIGN ONLY AS REPRESENTED IN THESE DRAWINGS. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR OBTAINING THE RESISTANCE TO ALL APPLICABLE LOCAL, STATE AND FEDERAL CODES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING THE RESISTANCE TO ALL APPLICABLE LOCAL, STATE AND FEDERAL CODES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING THE RESISTANCE TO ALL APPLICABLE LOCAL, STATE AND FEDERAL CODES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING THE RESISTANCE TO ALL APPLICABLE LOCAL, STATE AND FEDERAL CODES.

the Heather 1262F - r - Jones/Goodson residence
 Builder: bryan zecher homes, inc.
 An Independently owned and Operated Franchise

24x36: 1/4"=1'-0"
 18x24: 1/8"=1'-0"

APEX TECHNOLOGY IS A FICTITIOUS NAME OWNED BY JAX APEX TECHNOLOGY INC., A REGISTERED PROFESSIONAL ENGINEER BUSINESS NO. 7142-4746 SUTTON PARK COURT, SUITE 402 JACKSONVILLE, FL 32224 - 904.821.5200

APEX TECHNOLOGY IS A FICTITIOUS NAME OWNED BY JAX APEX TECHNOLOGY INC., A REGISTERED PROFESSIONAL ENGINEER BUSINESS NO. 7142-4746 SUTTON PARK COURT, SUITE 402 JACKSONVILLE, FL 32224 - 904.821.5200

APEX TECHNOLOGY IS A FICTITIOUS NAME OWNED BY JAX APEX TECHNOLOGY INC., A REGISTERED PROFESSIONAL ENGINEER BUSINESS NO. 7142-4746 SUTTON PARK COURT, SUITE 402 JACKSONVILLE, FL 32224 - 904.821.5200





BRICK LINTEL SCHEDULE AND INSTALLATION SPECIFICATIONS

LINTEL DIMENSION	MINIMUM BEARING	MAXIMUM TOTAL SPAN
3" V x 3 1/2" H x 1/2" T	4 INCHES	6 FEET
4" V x 3 1/2" H x 1/2" T	6 INCHES	8 FEET
5" V x 3 1/2" H x 1/2" T	6 INCHES	10 FEET
6" V x 3 1/2" H x 1/2" T	6 INCHES	12 FEET
7" V x 4" H x 1/2" T	6 INCHES	16 FEET

GENERAL NOTES:
 1. STEEL LINTELS TO BE MIN 36 KSI.
 2. LINTEL MUST HAVE CORROSION RESISTENT COATING OF EPOXY BASED PAINT.
 3. ALL LINTELS GREATER THAN 8 FEET SHOULD BE LATERALLY SUPPORTED AT A NO GREATER THAN 6 FEET ON CENTER W/ (1) 1/2" x 3" WOOD SCREW INTO HEADER. PROVIDE A 1/2" VERTICALLY SLOTTED HOLD FOR SCREW.

- ### FRAMING KEYNOTES (CUP)
- NOTES APPLICABLE ONLY WHERE SPECIFIED ON PLAN
- MIN (2) INTERMEDIATE JACK STUDS REQUIRED BETWEEN OPENINGS.
 - SEE INTERIOR SHEARWALL DETAIL ON DETAIL SHEET. IN LOCATIONS WHERE INTERIOR SHEARWALLS HAVE VAULTED TOP PLATES, ALSO SEE INTERIOR SHEARWALL AT VAULTED TOP PLATE ON DETAIL SHEET.
 - ATTACH SW TO FLOOR DIAPHRAGM PER ONE OF THE FOLLOWING:
 - IF FLOOR TRUSS ALIGNS ABOVE SW, ATTACH FLOOR TRUSS BOTTOM CHORD TO SW DBL TOP PLATE W/ 10d @ 3" O.C.
 - FRAME AND SHEATH SW TO FLOOR DECK ABOVE. ATTACH FLOOR DECK TO SW DBL TOP PLATE W/ 10d @ 3" O.C.
 - PORCH BEAM FRAMING NOTES
 - BEAM POCKET PORCH BEAMS AT TOP PLT ELEV. NOTCH TOP OF PORCH BEAM 3" FOR BEAM PKT CONNECTION AT WALL. TOP OF BEAM ELEVATION EQUALS TOP OF PLT ELEVATION. 3 1/2" MINIMUM BEARING REQUIRED IN WALL. PORCH BEAM TO STUDS W/ HTS20 OR MSTA24.
 - SHIM BELOW PORCH BEAMS JUST ABOVE TOP PLT ELEV. PORCH BEAM TO TOP PLT W/ MTS12 OR MSTA24.
 - POST DOWN PORCH BEAMS ABOVE TOP PLT ELEV. PROVIDE DOUBLE STUD POST DOWN SUPPORT AT WALL FOR PORCH BEAM. BEAM TO POST DOWN STUDS W/ HTS20 OR MSTA24. POST DOWN STUDS TO STUDS BELOW W/ HTS20 OR MSTA24.
 - BEAM ATTACHED TO EXISTING FRAMING ATTACH PORCH BEAM TO EXISTING STUDS OR KING/JACK STUDS W/ SIMPSON HUC HANGER MATCHING PORCH BEAM DIMENSIONS.
 - SHEATH WALL CONTINUOUS TO SECOND FLOOR TOP PLATE PER TYPICAL WALL SECTION SHEET.
 - CONVENTIONAL METAL UPLIFT CONNECTION
 - ATTACH DOUBLE TOP PLATE TO EVERY STUD W/ TSP.
 - ATTACH EVERY STUD TO BOTTOM PLATE W/ TSP.
 - AT ALL HEADERS:
 - HEADER TO JACK W/ MSTA24 EACH END.
 - KING/JACK STUD GROUP TO SLAB W/ DTT22.
 - TRUSS TO PORCH BEAM CONNECTION: USE (2) SIMPSON H2 5A OR SDWC1560
 - BALLOON FRAME WALLS W/ 2x8 @ 16" O.C.
 - (2) AND (3) PLY BEAMS:
 - ATTACH PLYS W/ (3) ROWS 12d COMMON @ 12" O.C. STAGGERED
 - (4) PLY LVL BEAMS.
 - ATTACH PLYS W/ (2) ROWS 1/2" DIAMETER THROUGH BOLTS W/ NUT AND WASHER @ 24" O.C. STAGGERED.
 - BALLOON FRAME FRONT ENTRY WALL TO 10' PLATE W/ 2x4 NO.2 SPF OR BETTER @ 16" O.C. MAX



1. The engineering data and details contained herein are the property of Apex Technology and are not to be reproduced in any manner, except as approved in writing by Apex Technology, Inc.
 2. The information represented in this package is intended for the residence or structure indicated in the title block above. Application of these details to any other structure is expressly forbidden.
 3. Dimensions should not be scaled from the drawings. If a dimension is unclear or indeterminate from adjacent dimensions, contact the engineer of record for clarification.


APEX TECHNOLOGY IS A FICTITIOUS NAME OWNED BY JAX APEX TECHNOLOGY INC., A FLORIDA CORPORATION FLORIDA ENGINEER BUSINESS NO. 75474745 SUTTON PARK COURT, SUITE 402 JACKSONVILLE, FL 32224 - 904.821.5200



Arthur Rutenberg Homes
 010074 P.A.C. - A
 010374 P.A.C. - AT
 012574 P.A.C. - B

the Heather 1262F - r - Jones/Goodson residence
 Builder: bryan zecher homes, inc.
 Lake City, FLORIDA
 An Independently Owned and Operated Franchise

24x36: 1/4"=1'-0"
 18x24: 1/8"=1'-0"
 Structural Plan
 Plan 1262F-201-B*
 ST-3



ROOF FRAMING KEYNOTES

- NOTES APPLICABLE ONLY WHERE SPECIFIED ON PLAN
- PRE-MAUFACTURED SHEAR PANEL**
 - INSTALL AS SHOWN ON LAYOUT ABOVE SW SPECIFIED ON FRAMING PLAN
 - SHEAR PANEL TO SW DBL TOP PLT W/ 10d @ 3" O.C.
 - FLOOR DECK TO SHEAR PANEL W/ 10d @ 3" O.C.
 - TYPICAL BEARING BLOCK**
 - BEARING BLOCK TO BE NO 2 SYP, MIN 48" LONG AND TO MATCH DIMENSION OF TRUSS MEMBER.
 - ATTACH BEARING BLOCK TO TRUSS VERTICAL OR TRUSS BOTTOM CHORD W/ (3) ROWS 10d @ 4" O.C. STAGGERED.
 - LEDGER FRAMING NOTES:**
 - FASTEN LEDGER TO FRAMING/TRUSS VERTICALS AT EVERY SUPPORT WITH FASTENING SHOWN BELOW (MAX 24" O.C. SPACING)
 - ADDITIONAL FASTENERS MAY BE REQUIRED AT SPECIFIED LOCATIONS ON PLAN
 - SEE TABLE 3 ON SHEET ST-1/S1 FOR FASTENER PROTECTION AGAINST CORROSION
 - IN ACCORDANCE W/ FRC 502.2.1, EXTERIOR DECK LEDGERS SHALL BE SECURE TO WALL FRAMING WITH WOOD SCREWS AS INDICATED ABOVE. COMMON NAILS AT FLOOR FRAMING LEDGERS ARE FOR INTERIOR USE ONLY.

ROOF FRAMING LEDGER:

2x6	(4) 12d COMMON
2x8	(6) 12d COMMON
2x10	(8) 12d COMMON
2x12	(10) 12d COMMON

FLOOR FRAMING LEDGER (W/ NAILS):

PT 2x6	(3) 16d COMMON
PT 2x8	(5) 16d COMMON
PT 2x10	(7) 16d COMMON
PT 2x12	(9) 16d COMMON

FLOOR FRAMING LEDGER (W/ SCREWS):

PT 2x6	(3) 1/2" x 4-1/2" LONG #14 WOOD SCREWS
PT 2x8	(5) 1/2" x 4-1/2" LONG #14 WOOD SCREWS
PT 2x10	(7) 1/2" x 4-1/2" LONG #14 WOOD SCREWS
PT 2x12	(9) 1/2" x 4-1/2" LONG #14 WOOD SCREWS

- OVERFRAMING NOTES**
 - ALL RAFTERS TO BE MIN. 2x6 NO 2 SYP @ 24" O.C. MAX.
 - ALL "SLEEPERS" TO BE PLANK-ORIENTED 2x8 NO 2 SYP MIN.
 - FASTEN "SLEEPERS" TO EACH TRUSS/RAFTER W/ (3) 16d COMMONS MIN.
 - EACH RAFTER TO "SLEEPER" W/ SIMPSON I3 UPLIFT CONNECTOR.
 - ALL RIDGE BOARDS TO BE 2x8 NO 2 SYP MIN.
 - FASTEN 2x8 NO 2 SYP COLLAR TIES FROM RAFTER TO RAFTER WHERE APPLICABLE W/ (5) 10d COMMONS MIN.

RAFTER SPAN SCHEDULE

O.C. SPACING	LUMBER SIZE			
12"	2x6	2x8	2x10	2x12
15"	15'-5"	19'-11"	23'-9"	26'-0"
16"	13'-4"	17'-3"	20'-7"	22'-0"
24"	10'-11"	14'-1"	16'-10"	19'-9"

20 L.L./15 D.L. #2 SYP

CEILING JOIST SPAN SCHEDULE

O.C. SPACING	LUMBER SIZE		
12"	2x4	2x6	2x8
15"	12'-5"	19'-6"	25'-8"
16"	11'-3"	17'-8"	23'-4"
24"	9'-10"	15'-6"	20'-1"


10 L.L./5 D.L. #2 SYP


CONVENTIONAL FRAMING NOTES

- RIDGE #2 SYP TYP:**
- 2x8 RIDGES
 - (8) 12d COMMON TOENAILS @ VALLEY TO ADJACENT MEMBER.
 - (1) MTS12 STRAP @ VALLEY TO PLATE. 2x10 RIDGES
 - (10) 12d COMMON TOENAILS @ VALLEY TO ADJACENT MEMBER.
 - (2) MTS12 STRAPS @ VALLEY TO PLATE. 2x12 RIDGES
 - (12) 12d COMMON TOENAILS @ VALLEY TO ADJACENT MEMBER.
 - (2) MTS12 STRAPS @ VALLEY TO PLATE.
- RAFTERS #2 SYP TYP:**
- 2x6 RAFTERS
 - (1) H5 OR (1) H8 @ EACH RAFTER TO PLATE.
 - (6) 12d COMMON TOENAILS @ RAFTERS TO RIDGE/VALLEY/LEDGER.
 - 2x8 RAFTERS
 - (2) H5'S OR (1) H8 @ EACH RAFTER TO PLATE.
 - (8) 12d COMMON TOENAILS @ RAFTERS TO RIDGE/VALLEY/LEDGER.
 - 2x10 RAFTERS
 - (1) H16 OR (1) MST12 @ EACH RAFTER TO PLATE.
 - (10) 12d COMMON TOENAILS @ RAFTERS TO RIDGE/VALLEY/LEDGER.
- CLG. JOIST #2 SYP TYP:**
- 2x JOIST
 - (3) 10d COMMON TOENAILS @ CLG. JOIST TO TOP PLATE/RAFTERS.

1. The engineering data and details contained herein are the property of Apex Technology and are not to be reproduced in any manner, except as approved in writing by APEX TECHNOLOGY, INC. 2. The information presented in this package is intended for the residence or structure indicated in the title block above. Application of these details to other structure is expressly forbidden. 3. Dimensions should not be scaled from the drawings. If a dimension is unclear or indeterminate from adjacent dimensions, contact the engineer of record for clarification.


APEX TECHNOLOGY IS A FICTITIOUS NAME OWNED BY JAX APEX TECHNOLOGY INC. A FLORIDA CORPORATION FLORIDA ENGINEER BUSINESS NO. 7547-4745 SUITON PARK COURT, SUITE 402, JACKSONVILLE, FL 32224-5042/5200






WALL SECTION AT ROOF (COMMON HEEL CONDITION)

(THIS SECTION IS TYPICAL FOR ONE AND TWO STORY APPLICATIONS)




WALL SECTION AT ROOF (RAISED HEEL CONDITION)

(THIS SECTION IS TYPICAL FOR ONE AND TWO STORY APPLICATIONS)



WALL SECTION AT ROOF (CANTILEVER CONDITION)

(THIS SECTION IS TYPICAL FOR ONE AND TWO STORY APPLICATIONS)



WALL SECTION AT FOUNDATION

(THIS SECTION IS TYPICAL FOR ONE AND TWO STORY APPLICATIONS)

GENERAL NOTES APPLICABLE TO ALL:

1. ALL TOP PLATES ARE TO BE BUILT WITH (2)2x NO 2 SYP FASTENED W/(2) ROWS 10d @ 8" O.C. STAGGERED (UNO). MINIMUM 48" LAP W/ MINIMUM (20)10d IN LAP. ADJUST TYPICAL NAIL SPACING AS NEEDED.
2. ALL BOTTOM PLATES ARE TO BE 2x NO 2 SYP PT.
3. ALL INTERIOR LOAD BEARING WALL STUDS ARE TO BE MINIMUM 2X4 NO 2 SPF AT 16" O.C. UNLESS NOTED OTHERWISE ON FRAMING PLAN.
4. FOR EXTERIOR WALL STUD SIZE AND SPACING, REFER TO TABLE 3: MINIMUM EXTERIOR WALL STUD SIZES ON SHEET ST-1.
5. FOR SHEATHING SIZE AND FASTENING REFER TO TABLE 2: WOOD STRUCTURAL PANEL SHEATHING REQUIREMENTS ON SHEET ST-1.
6. FOUNDATION INFORMATION ON THIS PAGE IS FOR GRAPHICAL DEPICTION ONLY. REFER TO FOUNDATION PLAN AND SECTIONS FOR FOUNDATION INFORMATION.
7. WALL SECTION AT FOUNDATION AND WALL SECTION AT ROOF ARE TYPICAL FOR ONE AND TWO STORY APPLICATIONS.
8. STUD TO BOTTOM PLATE CONNECTION MAY BE OMITTED IF 1/2" ANCHOR W/ 3" SQUARE BY 1/4" WASHER INSTALLED @ 24" O.C. (WASHER NOT REQUIRED W/ MASA)

ALTERNATE WALL SECTIONS

APEX TECHNOLOGY IS A FICTITIOUS NAME OWNED BY JAX APEX TECHNOLOGY INC., A FLORIDA CORPORATION, FLORIDA 32224 SUTTON PARK COURT, SUITE 402, JACKSONVILLE, FL 32224 • 904.821.5200

24x36: 1/4" = 1'-0"
18x24: 1/8" = 1'-0"

APEX JOB NO. B210085
ADDRESS: LAKE CITY, FL



Typical Wall Sections
ST-5















Arthur Rutenberg Homes
An independently owned and operated franchise

010914 P.A.C. - A
011314 P.A.C. - AT
012314 P.A.C. - B

ARTHUR RUTENBERG HOMES INC. THE DESIGNER IS RESPONSIBLE FOR THE ALTERNATE DESIGN ONLY AS REPRESENTED IN THESE DRAWINGS (IF ANY), BUT NOT FOR ANY STRUCTURAL INFORMATION INCLUDED OR OMITTED. THE CONTRACTOR (BUILDER) IS RESPONSIBLE FOR VERIFYING ALL INFORMATION REPRESENTED IN THIS PACKAGE IS INTENDED FOR THE RESIDENCE OR STRUCTURE INDICATED IN THE TITLE BLOCK ALONE. APPLICATION OF THESE DETAILS TO ANY OTHER STRUCTURE IS EXPRESSLY FORBIDDEN. REPRESENTED IN THIS PACKAGE IS FOR GRAPHICAL DEPICTION ONLY. REFER TO FOUNDATION PLAN AND SECTIONS FOR FOUNDATION INFORMATION. IF A DIMENSION IS UNCLEAR OR INDETERMINATE FROM ADJACENT DIMENSIONS, CONTACT THE ENGINEER OF RECORD FOR CLARIFICATION.

the Heather 1262F - r - Jones/Goodson residence
Builder: bryan zecher homes, inc.
Lake City, FL 32024

COMBINED USE PANEL (CUP) ENGINEERING



The engineering data and details contained herein are the property of Apex Technology and are not to be reproduced in any manner, except as approved in writing by Apex Technology, Inc. The information represented in this package is intended for the residence or structure indicated in the title block alone. Application of these details to any other structure is expressly forbidden. Dimensions should not be scaled from the drawings. If a dimension is unclear or indeterminate from adjacent dimensions, contact the engineer of record for clarification.