



ALL METAL PARTS SPECIFIED IN DOCUMENTS MUST BE OBTAINED FROM
A QUALITY CONTROL SOURCE AND MUST BE ASSEMBLED CORRECTLY.
THE QUALITY CONTROL SOURCE HAS A DUTY TO THE DEPARTMENT OF THE
NAVY TO CONDUCT VISUAL INSPECTION OF THE COMPONENTS, AND
LISTED PARTS ARE CONSIDERED AS SUCH. THE LISTED PARTS ARE
CONSIDERED AS SUCH FOR THE PURPOSES OF THE DEPARTMENT OF THE
NAVY AND MUST BE USED IN THE SAME MANNER AS THE PARTS
FOR A FIRST INSPECTION FROM THE VENDOR FOR THE PURPOSES.

THE STRUCTURAL ROOSTERING STEEL OF A CONCRETE PERMANENTLY INSTALLED POOL, CLIMBER, OR OUTDOOR HOT TUB, TIES TOGETHER BY THE LOCAL STEEL TRIMMER.

THE METAL WALL OF A RECENTLY INSTALLED POOL
OUTDOOR SPA, GO OUT TO ENJOY THE

THE EARTH POTENTIAL SYSTEM (EPS) CAN BE LINKED TOGETHER WITH FIVE BARRIERS OF COPPER-GOLD-SILVER COMBINED TO EXIST AT ALL POINTS OF CROSSING BY BROTHERHOOD WELDRING, LIMITED PRESSURE CUSHIONING OF THE SET POINT OR DIFFERENTIAL TIE, LISTED CLAIMS, OR OTHER LISTED ATTACHES (COP).

THE EARTH POTENTIAL BONDING GRID MUST COVER THE ENTIRE SURFACE OF THE PERMANENTLY INSTALLED POOL, OUTDOOR SPAS AND TUBS. EXTENDING 3 FEET HORIZONTALLY FROM THE VERTICAL, THE EARTH POTENTIAL BONDING GRID MUST BE ARRANGED IN A 4-FOOT BY 4-FOOT SQUARE OF 8-KG COILS, WITH A CLEARANCE OF 4 FEET.

INSTALLATION: THE ROOFING METAL SHEETING MUST BE SECURED TO BE INSTALLED UNDER THE ROOFING OR OTHERWISE ADHESIVE TO THE WALL OF METAL LINED TUNNEL WALL. FLEXIBLE COMPOSITE OR OTHER POLYMER MATERIALS OF NON-CONDUCTIVE MATERIALS.

1. ALL WORK IS TO COMPLY WITH ALL APPLICABLE CODES & ORDINANCES.
2. CONSTRUCTED OF 3000 PSI CONCRETE OR EQUAL, WITH #3 REBAR 12" O.C. EACH WAY, TIE AT EVERY OTHER INTERSECTION. MIN COVER FOR REBAR IS 2". MIN OVERLAP IS 18".

4. ASSUMED SOIL BEARING = 2850 PSF
5. CIRCULATION SYSTEM, COMPONENTS, AND
6. EQUIPMENT SHALL COMPLY WITH NSF 50
7. INSTALL CONTROL JOINTS AS SHOWN
8. ON CENTER IN POOL DECKING
9. FINISH TO CONFORM TO NEC 2014
10. FSC RESIDENTIAL 2017 6th EDITION
11. 6.1
12. CONCRETE STAIRS ARE 32" TREAD X 10" RISE
13. 48" TO 60" MAXIMUM HEIGHT
14. ALL CONSTRUCTION ON STAIRS COMPLY WITH
15. 4231-5-03, 2014 NEC ARTICLE 400, 5, &
16. 4231-5-01 3-22 IN-SERVICE 10-4 COMPLY

TOOLS MUST COMPLY WITH FEDERAL CONSTRUCTION STANDARDS
DESIGN CONSTRUCTION AND MODIFICATION SHALL BE
COMPLETED BY THE DESIGNER'S SPECIALTY SUBS
(E.G., HIGHWAY, AIRPORT, MARINE, SPECIALTIES, AND ETC.)

EXERCISE 10.10.11. $\square$

FENCE REQUIREMENTS:

1. MINIMUM 42" HEIGHT
2. 2" MAX VERTICAL CLEARANCE BETWEEN BRACE & RAISED BOTTOM
3. MAX OPENING SHALL NOT ALLOW PASSAGE OF 4" SPHERE.
4. FENCE POSTS WILL BE LOCATED ON POOL SIDE OF FENCE.
5. GATE WILL BE SELF-CLOSING WITH APPROVED LOCKING DEVICE.

NOTE: IF ANY PART OF THE POOL
ENCROACHES UPON THE ANGLE OF
REPOSE, PLACE STEEL @ 6' O.C. EA WAY
IN AREAS OF QUESTION