

BEARING HEIGHT SCHEDULE

	10' 1-1/8"
	9' 1-1/8"

NOTES:

- 1) REFER TO MB Q1 RECOMMENDATIONS FOR HANDING INSTALLATION AND TEMPORARY BRACING. REFER TO ENGINEERED DRAWINGS FOR PERMANENT BRACING REQUIRED
- 2) ALL TRUSSES (INCLUDING TRUSSES UNDER VALLEY FRAMING) MUST BE COMPLETELY DECKED OR REFER TO DECKING VIDS FOR ALTERNATE BRACING REQUIREMENTS
- 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER
- 4) ALL TRUSSES ARE DESIGNED FOR 2 OC MAXIMUM SPACING, UNLESS OTHERWISE NOTED
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED
- 6) 5X12 TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP
- 7) DECKING ADDED/INTEL. (HOK) TO BE FURNISHED BY BUILDER



Jacksonville
PHONE 904-772-6100 FAX: 904-772-1973
Tampa
PHONE 813-621-0931 FAX: 813-628-0766
Lake City
PHONE 386-755-6044 FAX: 386-755-1973

BUILDER
BLAKE CONST.

OWNER
LUNDE RES.

DATE:	DESIGNED BY:	DATE:	DESIGNED BY:
11-5-19	KLH	2150579	
11-5-19	KLH	2150579	

FL Approval Codes - Mitek Plates #'s 2197.2 - 2197.4, Versa-Lam #1644-R4 & BCI Joists #1392-R4

