Roof Replacement or Repair Application #72971

Friday, August 29, 2025 1:16 PM



Checklist:				
AddressDrive/ROWSepticSite Use ApprovedDocs Reviewed/Accepted	ApplicationZoning RevieuPlans RevieuRequired Ins	ew	Legal Lot of Flood Zone dFDEP Need	
APPLICANT: Tanesha Bouthner			PHONE : (863) 42	24-8607
ADDRESS: 1130 1st Street South Winte	er Haven FL 33880			
OWNER: SMITH KERMIT A, SMITH RITA A			PHONE : (386) 243-1796	
ADDRESS: 218 SE ANASTASIA ST LA	KE CITY, FL 32025			
PARCEL ID: 15-4S-17-08360-164	s	SUBDIVISION: EAST	TWOOD UNIT 1	
LOT: 14 BLOCK:	PHASE:		UNIT:	ACRES : 0.43
CONTRACTOR	TYPE	LIC#	BUSINESS NAME	
Tanesha Bouthner	General	CCC1335469	Solar Roofing & Co	onstruction Specialist Corp
ROOFING JOB DETAILS				
Type Roofing Job			Replac	ement - Tear off Existing and Replace
Further Job Details (Explain if decking is b	eing replaced and or Repa	airs are being done.)		Replace plywood decking as needed
Type of structure				House
Further Structure Details (if needed)				Single family residential
Total Estimated Cost				19401.91
Commercial or Residential				Residential
Roof Area (for this job) Sq Ft				2736
No. of Stories				1
Ventilation:				Ridge Vent
Flashing:				Replace All
Drip Edge:				Replace All
Valley Treatment:				New Mineral Surface
Roof Pitch				4:12 or Greater
Second Roof Pitch (if applicable)				
Any cable and/or race-way wiring located	on or within the roof assem	nbly?		
Is the existing roof being removed?				Yes
Explain if not removing the existing roofing	y material?			
Type of New Roofing Product				Asphalt Shingles
Florida Product Approval Number				18355.1
Product Manufacturer				TAMKO Building Products LLC
Product Description				Titan XT Shingles
Other Poofing Product Type Not Listed				

Sealed roof decking options: (Must select an option.)	a minimum 4-inch wide strip of selfadhering polymer- modified bitumen complying with ASTM D1970 or a minimum 3 3/4 - inch wide strip of selfadhering flexible flashing tape complying with AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the performance requirements specified, is required to be applied over the strips/tape over the entire roof.
Sealed roof decking explanation for other option.	
Review Notes:	