



8/12 PITCH  
18" O/H

# BEARING HEIGHT SCHEDULE

9' 1-1/8"

- NOTES:**
- 1) REFER TO HD 91 (RECOMMENDATIONS FOR HANDLING INSTALLATION AND TEMPORARY BRACING). REFER TO ENGINEERED DRAWINGS FOR PERMANENT BRACING REQUIRED.
  - 2) ALL TRUSSES (INCLUDING TRUSSES UNDER VALLEY FRAMING) MUST BE COMPLETELY DECKED OR REFER TO DETAIL V105 FOR ALTERNATE BRACING REQUIREMENTS.
  - 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER.
  - 4) ALL TRUSSES ARE DESIGNED FOR 2" o.c. MAXIMUM SPACING, UNLESS OTHERWISE NOTED.
  - 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED.
  - 6) 5Y42 TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP.
  - 7) BEAM/HEADER/INTEL (HDR) TO BE FURNISHED BY BUILDER.



Jacksonville  
PHONE: 904-772-6100 FAX: 904-772-1973

Tampa  
PHONE: 813-621-9831 FAX: 813-628-8956

Lake City  
PHONE: 386-755-6844 FAX: 386-755-7973

BUILDER:  
**LIPSCOMB EAGLE**

LEGAL ADDRESS:  
**LOT 29 TURKEY CREEK**

MODEL: Revision:

DATE: **3-15-21** DESIGNED BY: **KLH**

Original Reference #: **2714464**

Inst. Level Job #: Inst. Level Job #: **2714464**

FL Approval Codes - Mitek Plates #'s 2197.2 - 2197.4, Versa-Lam #1644-R4 & BCI Joists #1392-R4