

DATE 09/14/2010

Columbia County Building Permit

PERMIT

This Permit Must Be Prominently Posted on Premises During Construction

000028856

APPLICANT BARBARA WEBSTER PHONE 386.719.7143

ADDRESS 125 SW MIDTOWN PL.,STE 101 LAKE CITY FL 32025

OWNER ANTHONY & MAGDA SINISI PHONE _____

ADDRESS 1500 SW LEGION DRIVE LAKE CITY FL 32024

CONTRACTOR ISAAC BRATKOVICH PHONE 386.719.7143

LOCATION OF PROPERTY 90-W TO SR. 247-S TO TAMARACK LN,TR TO LEGION DR.,TL 2ND TO
LAST LOT ON L TOWARDS END OF CUL-DE-SAC.

TYPE DEVELOPMENT SFD/UTILITY ESTIMATED COST OF CONSTRUCTION 185150.00

HEATED FLOOR AREA 2458.00 TOTAL AREA 3703.00 HEIGHT 20.10 STORIES 1

FOUNDATION CONC WALLS FRAMED ROOF PITCH 5'12 FLOOR CONC

LAND USE & ZONING A-3 MAX. HEIGHT 35

Minimum Set Back Requirments: STREET-FRONT 30.00 REAR 25.00 SIDE 25.00

NO. EX.D.U. 0 FLOOD ZONE X DEVELOPMENT PERMIT NO. _____

PARCEL ID 20-4S-16-03051-206 SUBDIVISION LEGION PLACE

LOT 6 BLOCK _____ PHASE _____ UNIT _____ TOTAL ACRES 5.01

000001848 CBC059323 *Barbara Webster*

Culvert Permit No. _____ Culvert Waiver _____ Contractor's License Number _____ Applicant/Owner/Contractor _____

18"X32'MITERED 10-0390 BLK TC Y

Driveway Connection _____ Septic Tank Number _____ LU & Zoning checked by _____ Approved for Issuance _____ New Resident _____

COMMENTS: 1 FOOT ABOVE ROAD.Check # or Cash 2593

FOR BUILDING & ZONING DEPARTMENT ONLY

(footer/Slab)

Temporary Power _____ Foundation _____ Monolithic _____
date/app. by _____ date/app. by _____ date/app. by _____

Under slab rough-in plumbing _____ Slab _____ Sheathing/Nailing _____
date/app. by _____ date/app. by _____ date/app. by _____

Framing _____ Insulation _____
date/app. by _____ date/app. by _____

Rough-in plumbing above slab and below wood floor _____ Electrical rough-in _____
date/app. by _____ date/app. by _____

Heat & Air Duct _____ Peri. beam (Lintel) _____ Pool _____
date/app. by _____ date/app. by _____ date/app. by _____

Permanent power _____ C.O. Final _____ Culvert _____
date/app. by _____ date/app. by _____ date/app. by _____

Pump pole _____ Utility Pole _____ M/H tie downs, blocking, electricity and plumbing _____
date/app. by _____ date/app. by _____ date/app. by _____

Reconnection _____ RV _____ Re-roof _____
date/app. by _____ date/app. by _____ date/app. by _____

BUILDING PERMIT FEE \$ 930.00 CERTIFICATION FEE \$ 18.52 SURCHARGE FEE \$ 18.52

MISC. FEES \$ 0.00 ZONING CERT. FEE \$ 50.00 FIRE FEE \$ 0.00 WASTE FEE \$ _____

FLOOD DEVELOPMENT FEE \$ _____ FLOOD ZONE FEE \$ 25.00 CULVERT FEE \$ 25.00 **TOTAL FEE** 1067.04

INSPECTORS OFFICE *COO* CLERKS OFFICE *CH*

NOTICE: IN ADDITION TO THE REQUIREMENTS OF THIS PERMIT, THERE MAY BE ADDITIONAL RESTRICTIONS APPLICABLE TO THIS PROPERTY THAT MAY BE FOUND IN THE PUBLIC RECORDS OF THIS COUNTY. AND THERE MAY BE ADDITIONAL PERMITS REQUIRED FROM OTHER GOVERNMENTAL ENTITIES SUCH AS WATER MANAGEMENT DISTRICTS, STATE AGENCIES, OR FEDERAL AGENCIES.

"WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOUR PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR AN ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT."


EVERY PERMIT ISSUED SHALL BECOME INVALID UNLESS THE WORK AUTHORIZED BY SUCH PERMIT IS COMMENCED WITHIN 180 DAYS AFTER ITS ISSUANCE, OR IF THE WORK AUTHORIZED BY SUCH PERMIT IS SUSPENDED OR ABANDONED FOR A PERIOD OF 180 DAYS AFTER THE TIME THE WORK IS COMMENCED. A VALID PERMIT RECIEVES AN APPROVED INSPECTION EVERY 180 DAYS. WORK SHALL BE CONSIDERED NOT SUSPENDED, ABANDONED OR INVALID WHEN THE PERMIT HAS RECIEVED AN APPROVED INSPECTION WITHIN 180 DAYS OT THE PREVIOUS INSPECTION.

The Issuance of this Permit Does Not Waive Compliance by Permittee with Deed Restrictions.

611
- "No" ^{TS} Verification form
on Ricky Allen.

! Ron David was originally
the contractor..

We said 2 other people were
out there w/ him. (What about
their exemption status.) I told
him we will check it out for
him.



2

SUBCONTRACTOR VERIFICATION FORM

APPLICATION NUMBER _____ CONTRACTOR Isaac Construction PHONE _____

THIS FORM MUST BE SUBMITTED PRIOR TO THE ISSUANCE OF A PERMIT

In Columbia County one permit will cover all trades doing work at the permitted site. It is **REQUIRED** that we have records of the subcontractors who actually did the trade specific work under the permit. Per Florida Statute 440 and Ordinance 89-6, a contractor shall require all subcontractors to provide evidence of workers' compensation or exemption, general liability insurance and a valid Certificate of Competency license in Columbia County.

Any changes, the permitted contractor is responsible for the corrected form being submitted to this office prior to the start of that subcontractor beginning any work. Violations will result in stop work orders and/or fines.

ELECTRICAL 234 ✓ OK	Print Name <u>Conner Electric</u> License #: <u>ER13013192</u>	Signature <u>Michael S. C.</u> Phone #: <u>386 965 9905</u>
MECHANICAL/A/C 563 ✓ OK	Print Name <u>David Hallis</u> License #: <u>CACU 57424</u>	Signature <u>[Signature]</u> Phone #: <u>386-755-9792</u>
PLUMBING/GAS 1623 ✓ OK	Print Name <u>Express Plumbing</u> License #: <u>CFC1428640</u>	Signature <u>[Signature]</u> Phone #: <u>386-867-0269</u>
ROOFING 494 ✓ OK	Print Name <u>Precision Exteriors</u> License #: <u>CCC1327718</u>	Signature <u>[Signature]</u> Phone #: <u>386-752-4022</u>
SHEET METAL	Print Name _____ License #: _____	Signature _____ Phone #: _____
FIRE SYSTEM/SPRINKLER	Print Name _____ License #: _____	Signature _____ Phone #: _____
SOLAR	Print Name _____ License #: _____	Signature _____ Phone #: _____

Specialty License	License Number	Sub-Contractors Printed Name	Sub-Contractors Signature
MASON ✓ OK	000 720	Donald Roberts	[Signature]
CONCRETE FINISHER OK	0000 48	hofstrom Builders	[Signature]
FRAMING OK	CBC059323	Isaac Construction	[Signature]
INSULATION 421 OK	CBC059323	Isaac Construction	[Signature]
STUCCO OK	000256	Ron Dewitt	[Signature]
DRYWALL OK	000345	Heitzman Drywall	[Signature]
PLASTER			
CABINET INSTALLER OK	CBC059323	Isaac Construction	[Signature]
PAINTING OK	000 219	Hart's Painting	[Signature]
ACOUSTICAL CEILING			
GLASS OK	000618	Lake City Glass	[Signature]
CERAMIC TILE OK	000071	SESTile	[Signature]
FLOOR COVERING			
ALUM/VINYL SIDING			
GARAGE DOOR OK	000619	Lake City Glass	[Signature]
METAL BLDG ERECTOR			

F. S. 440.103 Building permits; identification of minimum premium policy.--Every employer shall, as a condition to applying for and receiving a building permit, show proof and certify to the permit issuer that it has secured compensation for its employees under this chapter as provided in ss. 440.10 and 440.38, and shall be presented each time the employer applies for a building permit.

09-13-10;03:14PM;

;386 758-2187

1/ 2

STATE OF FLORIDA
DEPARTMENT OF HEALTH AND REHABILITATIVE SERVICES
ON-SITE SEWAGE DISPOSAL SYSTEM
APPLICATION FOR CONSTRUCTION PERMIT
Authority: Chapter 381, FS & Chapter 10D-6, FAC

PERMIT #
DATE PAID
FEE PAID \$
RECEIPT #
CR #

10-0390
9254161
872110
310.83
1755240
08-4655

APPLICATION FOR:

[X] New System [] Existing System [] Holding Tank [] Temporary/Experimental System
[] Repair [] Abandonment [] Other (Specify)

APPLICANT: ANTHONY SINISI

TELEPHONE: 719-7143

AGENT: ISAAC CONSTRUCTION

MAILING ADDRESS: 125 SW MIDTOWN PL. STE 101 CITY: LAKE CITY STATE: FL ZIP: 32025

TO BE COMPLETED BY APPLICANT OR APPLICANT'S AUTHORIZED AGENT. ATTACH BUILDING PLAN AND TO-SCALE SITE PLAN SHOWING PERTINENT FEATURES REQUIRED BY CHAPTER 10D-6, FLORIDA ADMINISTRATIVE CODE.

PROPERTY INFORMATION [IF LOT IS NOT IN A RECORDED SUBDIVISION, ATTACH LEGAL DESCRIPTION OR DEED]

LOT: 6 BLOCK: SUBDIVISION: LEGION PLACE DATESUBD: 1-22-01

PROPERTY ID #: 20-4S-16-03051-206 [Section/Township/Range/Parcel] ZONING: RES

PROPERTY SIZE: 5.01 ACRES [Sqft/43560] PROPERTY WATER SUPPLY: [X] PRIVATE [] PUBLIC

PROPERTY STREET ADDRESS: LEGION DR.

DIRECTIONS TO PROPERTY: 90 WEST TL ON CR 247 TR ON TAMARACK TL ON LEGION DR. LOT LAST ON LEFT.

BUILDING INFORMATION

[X] RESIDENTIAL

[] COMMERCIAL

Unit No.	Type of Establishment	No. of Bedrooms	Building Area Sqft	# Persons Served	Business Activity For Commercial Only
1	HOUSE	4	2458	4	
2					
3					
4					

[N] Garbage Grinders/Disposals
[N] Ultra-low Volume Flush Toilets

[N] Spas/Hot Tubs
[N] Other (Specify)

[N] Floor/Equipment Drains

APPLICANT'S SIGNATURE:

Barbara Webster

DATE: 8/12/10


09-13-10:03:14PM;

;386 758-2187

2/ 2

**Application for Onsite Sewage Disposal System
Construction Permit. Part II Site Plan**
Permit Application Number: 10-0390-N

ALL CHANGES MUST BE APPROVED BY THE COUNTY HEALTH UNIT



1A OF 5.01
shown see
attached for
full dimensions

Site Plan Submitted By: Paul Lloyd Date: 8/8/10
Plan Approved X Not Approved Date: 8-18-10
By: Sally Ford - EH Director Columbia CHD CPHT
Notes:

Prepared by:
Michael H. Harrell
Abstract & Title Services, Inc.
382 SW Baya Drive
Lake City, Florida 32025

Inst: [REDACTED] Date: 10/22/2004 Time: 15:57
Doc Stamp-Deed : 280.00
[Signature] DC, P. DeWitt Cason, Columbia County B: 1028 P: 2700

Warranty Deed

Individual to Individual

THIS WARRANTY DEED made the 15th day of October, 2004 by

Daniel P. Shackelford, and his wife, Judith A. Shackelford
hereinafter called the grantor, to

Anthony Sinisi, and his wife, Magda Bondi-Sinisi
whose post office address is: 8300 NW 17th Court, Pembroke Pines, Florida 33024
hereinafter called the grantee:

(Wherever used herein the terms "grantor" and "grantee" include all the parties to this instrument and the heirs, legal representatives and assigns of individuals, and the successors and assigns of corporation)

Witnesseth: That the grantor, for and in consideration of the sum of \$10.00 and other valuable considerations, receipt whereof is hereby acknowledged, hereby grants, bargains, sells, aliens, remises, releases, conveys, and confirms unto the grantee, all that certain land situate in COLUMBIA County, FLORIDA, viz: Parcel ID#

Lot 6, Legion Place, a subdivison according to the plat thereof filed in Plat Book 7, Page 67,
Public Records of Columbia County, Florida.

TOGETHER with all tenements, hereditaments and appurtenances thereto belonging or in anywise appertain

TO HAVE AND TO HOLD, the same in fee simple forever.

AND the grantor hereby covenants with said grantee that the grantor is lawfully seized of said land in fee simple; that the grantor has good right and lawful authority to sell and convey said land; that the grantor hereby fully warrants the title to said land and will defend the same against the lawful claims of all persons whomsoever; and that said land is free of all encumbrances, except taxes accruing subsequent to December 31, 2003.

IN WITNESS WHEREOF, the said grantor has signed and sealed these presents the day and year first above written.

Signed, sealed and delivered in our presence:

[Signature] Megan Maravelle
Witness

[Signature] Rhonda B. Green
Witness

[Signature] Daniel P. Shackelford
Daniel P. Shackelford
[Signature] Judith A. Shackelford
Judith A. Shackelford

STATE OF FLORIDA
COUNTY OF COLUMBIA

The foregoing instrument was acknowledged before me this 15th day of October, 2004 by Daniel P. Shackelford, and his wife, Judith A. Shackelford personally known to me or, if not personally known to me, who produced Driver's License No. [REDACTED] for identification and who did not take an oath.

(SEAL)

[Signature] Rhonda B. Green
Notary Public
RHONDA B. GREEN
MY COMMISSION # DO 001827
EXPIRES: February 12, 2008
1-800-6HONEY FL. Notary Service & Bonding, Inc.

COLUMBIA COUNTY 9-1-1 ADDRESSING

P. O. Box 1787, Lake City, FL 32056-1787

PHONE: (386) 758-1125 * FAX: (386) 758-1365 * Email: ron_croft@columbiacountyfla.com

Addressing Maintenance

To maintain the Countywide Addressing Policy you must make application for a 9-1-1 Address at the time you apply for a building permit. The established standards for assigning and posting numbers to all principal buildings, dwellings, businesses and industries are contained in Columbia County Ordinance 2001-9. The addressing system is to enable Emergency Service Agencies to locate you in an emergency, and to assist the United States Postal Service and the public in the timely and efficient provision of services to residents and businesses of Columbia County.

DATE REQUESTED: 6/22/2009 DATE ISSUED: 6/23/2009

ENHANCED 9-1-1 ADDRESS:

1500 SW LEGION DR

LAKE CITY FL 32024

PROPERTY APPRAISER PARCEL NUMBER:

20-4S-16-03051-206

Remarks:

LOT 6 LEGION PLACE S/D

Address Issued By:



Columbia County 9-1-1 Addressing / GIS Department

NOTICE: THIS ADDRESS WAS ISSUED BASED ON LOCATION INFORMATION RECEIVED FROM THE REQUESTER. SHOULD, AT A LATER DATE, THE LOCATION INFORMATION BE FOUND TO BE IN ERROR, THIS ADDRESS IS SUBJECT TO CHANGE.

1463

Columbia County Property Appraiser

DB Last Updated: 4/27/2009

2009 Preliminary Values

Tax Record

Property Card

Interactive GIS Map

Print

Parcel: 20-4S-16-03051-206

Search Result: 1 of 4

Next >>

Owner & Property Info

Owner's Name	SINISI ANTHONY &		
Site Address			
Mailing Address	MAGDA BONDI-SINISI 8300 NW 17TH CT PEMBROKE PINES, FL 33024		
Use Desc. (code)	VACANT (000000)		
Neighborhood	017416.00	Tax District	3
UD Codes	MKTA01	Market Area	01
Total Land Area	5.010 ACRES		
Description	LOT 6 LEGION PLACE S/D. WD 1009-329, WD 1028-2700.		

GIS Aerial



Property & Assessment Values

SOUTHPOINTE SUBDIVISION
OFF OF 247

Mkt Land Value	cnt: (1)	\$51,300.00
Ag Land Value	cnt: (0)	\$0.00
Building Value	cnt: (0)	\$0.00
XFOB Value	cnt: (0)	\$0.00
Total Appraised Value		\$51,300.00

Just Value	\$51,300.00
Class Value	\$0.00
Assessed Value	\$51,300.00
Exemptions	\$0.00
Total Taxable Value	County: \$51,300.00 City: \$51,300.00 Other: \$51,300.00 School: \$51,300.00

Sales History

Sale Date	Book/Page	Inst. Type	Sale VImp	Sale Qual	Sale RCode	Sale Price
10/15/2004	1028/2700	WD	V	Q		\$40,000.00
3/5/2004	1009/329	WD	V	Q		\$37,400.00

Building Characteristics

Bldg Item	Bldg Desc	Year Blt	Ext. Walls	Heated S.F.	Actual S.F.	Bldg Value
			NONE			

Extra Features & Out Buildings

Code	Desc	Year Blt	Value	Units	Dims	Condition (% Good)
						NONE

Land Breakdown

Lnd Code	Desc	Units	Adjustments	Eff Rate	Lnd Value
000000	VAC RES (MKT)	0000001.000 LT - (0000005.010AC)	1.00/1.00/1.00/1.00	\$51,300.00	\$51,300.00

Columbia County Property Appraiser

DB Last Updated: 4/27/2009



COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST REQUIREMENTS

MINIMUM PLAN REQUIREMENTS FOR THE FLORIDA BUILDING CODE RESIDENTIAL 2007 ONE (1) AND TWO (2) FAMILY DWELLINGS

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE with the Current 2007 FLORIDA BUILDING CODES RESIDENTIAL. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FIGURE R301.2(4) of the FLORIDA BUILDING CODES RESIDENTIAL (Florida Wind speed map) SHALL BE USED.

WIND SPEED LINE SHALL BE DEFINED AS FOLLOWS: THE CENTERLINE OF INTERSTATE 75.

ALL BUILDINGS CONSTRUCTED EAST OF SAID LINE SHALL BE ----- 100 MPH
ALL BUILDINGS CONSTRUCTED WEST OF SAID LINE SHALL BE -----110 MPH
NO AREA IN COLUMBIA COUNTY IS IN A WIND BORNE DEBRIS REGION

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable		
---	--	--	--	--

			Yes	No	N/A
1	Two (2) complete sets of plans containing the following:		<input checked="" type="checkbox"/>		
2	All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void		<input checked="" type="checkbox"/>		
3	Condition space (Sq. Ft.)	Total (Sq. Ft.) under roof	IIIIIIII <input checked="" type="checkbox"/>	IIIIIIII	IIII
	2458	3703			

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.2.1

Site Plan information including:

4	Dimensions of lot or parcel of land	<input checked="" type="checkbox"/>		
5	Dimensions of all building set backs	<input checked="" type="checkbox"/>		
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	<input checked="" type="checkbox"/>		
7	Provide a full legal description of property.	<input checked="" type="checkbox"/>		

Wind-load Engineering Summary, calculations and any details required

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable		
		IIIIII	IIII	IIIIII
		YES	NO	N/A
8	Plans or specifications must show compliance with FBCR Chapter 3			
9	Basic wind speed (3-second gust), miles per hour	✓		
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated)	✓		
11	Wind importance factor and nature of occupancy	✓		
12	The applicable internal pressure coefficient, Components and Cladding	✓		
13	The design wind pressure in terms of psf (kN/m ²), to be used for the design of exterior component, cladding materials not specifically designed by the registered design professional.	✓		

Elevations Drawing including:

14	All side views of the structure	✓		
15	Roof pitch	✓		
16	Overhang dimensions and detail with attic ventilation	✓		
17	Location, size and height above roof of chimneys			✓
18	Location and size of skylights with Florida Product Approval			✓
18	Number of stories	✓		
20A	Building height from the established grade to the roofs highest peak	✓		

Floor Plan including:

20	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, balconies	✓		
21	Raised floor surfaces located more than 30 inches above the floor or grade	✓		
22	All exterior and interior shear walls indicated	✓		
23	Shear wall opening shown (Windows, Doors and Garage doors)	✓		
24	Emergency escape and rescue opening shown in each bedroom (net clear opening shown)	✓		
25	Safety glazing of glass where needed	✓		
26	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 of FBCR)	✓		
27	Stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails (see FBCR SECTION 311)			✓
28	Identify accessibility of bathroom (see FBCR SECTION 322)			✓

All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plan (see Florida product approval form)

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable		
---	--	--	--	--

FBCR 403: Foundation Plans

		YES	NO	N/A
29	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
30	All posts and/or column footing including size and reinforcing	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
31	Any special support required by soil analysis such as piling.	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
32	Assumed load-bearing value of soil _____ Pound Per Square Foot	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
33	Location of horizontal and vertical steel, for foundation or walls (include # size and type)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

FBCR 506: CONCRETE SLAB ON GRADE

34	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
35	Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

FBCR 320: PROTECTION AGAINST TERMITES

36	Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or submit other approved termite protection methods. Protection shall be provided by registered termiticides	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
----	---	-------------------------------------	--------------------------	--------------------------

FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls)

37	Show all materials making up walls, wall height, and Block size, mortar type	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
38	Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect

Floor Framing System: First and/or second story

39	Floor truss package shall including layout and details, signed and sealed by Florida Registered Professional Engineer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
40	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or piers	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
41	Girder type, size and spacing to load bearing walls, stem wall and/or piers	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
42	Attachment of joist to girder	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
43	Wind load requirements where applicable	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
44	Show required under-floor crawl space	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
45	Show required amount of ventilation opening for under-floor spaces	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
46	Show required covering of ventilation opening	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
47	Show the required access opening to access to under-floor spaces	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

48	intermediate of the areas structural panel sheathing	<input checked="" type="checkbox"/>		
49	Show Draftstopping, Fire caulking and Fire blocking	<input checked="" type="checkbox"/>		
50	Show fireproofing requirements for garages attached to living spaces, per FBCR section 309	<input checked="" type="checkbox"/>		
51	Provide live and dead load rating of floor framing systems (psf).	<input checked="" type="checkbox"/>		

FBCR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable		
		YES	NO	N/A

52	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	<input checked="" type="checkbox"/>		
53	Fastener schedule for structural members per table FBCR 602.3 are to be shown	<input checked="" type="checkbox"/>		
54	Show Wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	<input checked="" type="checkbox"/>		
55	Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	<input checked="" type="checkbox"/>		
56	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per FBCR Table 502.5 (1)	<input checked="" type="checkbox"/>		
57	Indicate where pressure treated wood will be placed	<input checked="" type="checkbox"/>		
58	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing edges & intermediate areas	<input checked="" type="checkbox"/>		
59	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	<input checked="" type="checkbox"/>		

FBCR :ROOF SYSTEMS:

60	Truss design drawing shall meet section FBCR 802.10 Wood trusses	<input checked="" type="checkbox"/>		
61	Include a layout and truss details, signed and sealed by Florida Professional Engineer	<input checked="" type="checkbox"/>		
62	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	<input checked="" type="checkbox"/>		
63	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	<input checked="" type="checkbox"/>		
64	Provide dead load rating of trusses	<input checked="" type="checkbox"/>		

FBCR 802:Conventional Roof Framing Layout

65	Rafter and ridge beams sizes, span, species and spacing	<input checked="" type="checkbox"/>		
66	Connectors to wall assemblies' include assemblies' resistance to uplift rating	<input checked="" type="checkbox"/>		
67	Valley framing and support details	<input checked="" type="checkbox"/>		
68	Provide dead load rating of rafter system	<input checked="" type="checkbox"/>		

FBCR Table 602,3(2) & FBCR 803 ROOF SHEATHING

69	Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness	<input checked="" type="checkbox"/>		
70	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	<input checked="" type="checkbox"/>		

FBCR ROOF ASSEMBLIES FRC Chapter 9

71	Include all materials which will make up the roof assembles covering	<input checked="" type="checkbox"/>		
72	Submit Florida Product Approval numbers for each component of the roof assembles covering	<input checked="" type="checkbox"/>		

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. *Two of the required forms are to be submitted, showing dimensions condition area equal to the total condition living space area*

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable		
		YES	NO	N/A
73	Show the insulation R value for the following areas of the structure	<input checked="" type="checkbox"/>		
74	Attic space	<input checked="" type="checkbox"/>		
75	Exterior wall cavity	<input checked="" type="checkbox"/>		
76	Crawl space	<input checked="" type="checkbox"/>		

HVAC information

77	Submit two copies of a Manual J sizing equipment or equivalent computation study	<input checked="" type="checkbox"/>		
78	Exhaust fans locations in bathrooms	<input checked="" type="checkbox"/>		
79	Show clothes dryer route and total run of exhaust duct	<input checked="" type="checkbox"/>		

Plumbing Fixture layout shown

80	All fixtures waste water lines shall be shown on the foundation plan	<input checked="" type="checkbox"/>		
81	Show the location of water heater	<input checked="" type="checkbox"/>		

Private Potable Water

82	Pump motor horse power	<input checked="" type="checkbox"/>		
83	Reservoir pressure tank gallon capacity	<input checked="" type="checkbox"/>		
84	Rating of cycle stop valve if used	<input checked="" type="checkbox"/>		

Electrical layout shown including

85	Switches, outlets/receptacles, lighting and all required GFCI outlets identified	<input checked="" type="checkbox"/>		
86	Ceiling fans	<input checked="" type="checkbox"/>		
87	Smoke detectors & Carbon dioxide detectors	<input checked="" type="checkbox"/>		
88	Service panel, sub-panel, location(s) and total ampere ratings	<input checked="" type="checkbox"/>		
89	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	<input checked="" type="checkbox"/>		

90	Appliances and HVAC equipment and disconnects	✓		
91	Arc Fault Circuits (AFCI) in bedrooms	✓		

Disclosure Statement for Owner Builders If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form **recorded** in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable
---	--	--

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

		YES	NO	N/A
92	Building Permit Application A current Building Permit Application form is to be completed and submitted for all residential projects			
93	Parcel Number The parcel number (Tax ID number) from the Property Appraiser (386) 758-1084 is required. A copy of property deed is also requested	✓		
94	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058			
95	City of Lake City A permit showing an approved waste water sewer tap			✓
96	Toilet facilities shall be provided for all construction sites	✓		
97	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.			✓
98	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations			✓
99	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the base flood elevation (100 year flood) has been established			✓
100	A development permit will also be required. Development permit cost is \$50.00			
101	Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00). All culvert waivers are sent to the Columbia County Public Works Department for approval or denial.	✓		
102	911 Address: If the project is located in an area where a 911 address has not been issued, then application for a 911 address must be applied for and received through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125	✓		

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code, Building shall govern the administration and enforcement of the Florida Building Code, Residential.

Section 105 of the Florida Building Code defines the:

Time limitation of application.

An application for a permit for any proposed work shall be deemed to have been abandoned 180 days after the date of filing, unless such application has been pursued in good faith or a permit has been issued; except that the building official is authorized to grant one or more extensions of time for additional periods not exceeding 90 days each. The extension shall be requested in writing and justifiable cause demonstrated.

Single-family residential dwelling.

Section 105.3.4 A building permit for a single-family residential dwelling must be issued within 30 working days of application therefor unless unusual circumstances require a longer time for processing the application or unless the permit application fails to satisfy the Florida Building Code or the enforcing agency's laws or ordinances.

Permit intent.

Section 105.4.1: A permit issued shall be constructed to be a license to proceed with the work and not as authority to violate, cancel, alter or set aside any of the provisions of the technical codes, nor shall issuance of a permit prevent the building official from thereafter requiring a correction of errors in plans, construction or violations of this code. Every permit issued shall become invalid unless the work authorized by such permit is commenced within six months after its issuance, or if the work authorized by such permit is suspended or abandoned for a period of six months after the time the work is commenced.

If work has commenced.

Section 105.4.1.1: If work has commenced and the permit is revoked, becomes null and void, or expires because of lack of progress or abandonment, a new permit covering the proposed construction shall be obtained before proceeding with the work.

New Permit.

Section 105.4.1.2: If a new permit is not obtained within 180 days from the date the initial permit became null and void, the building official is authorized to require that any work which has been commenced or completed be removed from the building site. Alternately, a new permit may be issued on application, providing the work in place and required to complete the structure meets all applicable regulations in effect at the time the initial permit became null and void and any regulations which may have become effective between the date of expiration and the date of issuance of the new permit.

Work Shall Be:

Section 105.4.1.3: Work shall be considered to be in active progress when the permit has received an approved inspection within 180 days. This provision shall not be applicable in case of civil commotion or strike or when the building work is halted due directly to judicial injunction, order or similar process.

The Fee:

Section 105.4.1.4: The fee for renewal reissuance and extension of a permit shall be set forth by the administrative authority.

When the submitted application is approved for permitting the applicant will be notified by phone as to the date and time a building permit will be prepared and issued by the Columbia County Building & Zoning Department

PRODUCT APPROVAL SPECIFICATION SHEET

Location: Legion Place S/D Lot 6 **Project Name:** Sinisi

As required by Florida Statute 553.842 and Florida Administrative Code 9B-72, please provide the information and the product approval number(s) on the building components listed below if they will be utilized on the construction project for which you are applying for a building permit on or after April 1, 2004. We recommend you contact your local product supplier should you not know the product approval number for any of the applicable listed products. More information about statewide product approval can be obtained at www.floridabuilding.org

Category/Subcategory	Manufacturer	Product Description	Approval Number(s)
A. EXTERIOR DOORS			
1. Swinging	Phst Pro Inc	Opaque fiberglass-inswing/out	4760.1, 4760.2
2. Sliding	Pella Corp	Vinyle sliding glass door	1824.1
3. Sectional	Raynor	Over lay Carriage House Garage Dr	8645.1, 8645.2
4. Roll up	Sanus	Rollup flat stat door	11025.1
5. Automatic			
6. Other			
B. WINDOWS			
1. Single hung	Phillips Product	single hung 48x96 w/insulated	5300.4
2. Horizontal Slider	Alenco	aluminum xox horizontal slider	7673.1
3. Casement			
4. Double Hung	Kawneer	aluminum non-impact double hung	7912.1
5. Fixed	Phillips Product	96x72 extruded vinyle twin	1935.3
6. Awning			
7. Pass-through			
8. Projected			
9. Mullion			
10. Wind Breaker			
11 Dual Action			
12. Other			
C. PANEL WALL			
1. Siding	Alcoa	structure vinyle	5544.6
2. Soffits	Variform	D5 standard vinyle, T4 aluminum	11176.3, 11176.6
3. EIFS			
4. Storefronts			
5. Curtain walls			
6. Wall louver			
7. Glass block			
8. Membrane			
9. Greenhouse			
10. Other			
D. ROOFING PRODUCTS			
1. Asphalt Shingles	Tamko	heavy weight dimensional	7154.1
2. Underlayments	Tamko	self adhering rubberized membrane	3664.1
3. Roofing Fasteners	OMG	fasteners for base sheet/insulation	699.1, 699.2
4. Non-structural Metal Rf			
5. Built-Up Roofing			
6. Modified Bitumen			
7. Single Ply Roofing Sys			
8. Roofing Tiles			
9. Roofing Insulation			
10. Waterproofing			
11. Wood shingles /shakes			
12. Roofing Slate			

Category/Subcategory (cont.)	Manufacturer	Product Description	Approval Number(s)
13. Liquid Applied Roof Sys			
14. Cements-Adhesives – Coatings			
15. Roof Tile Adhesive			
16. Spray Applied Polyurethane Roof			
17. Other			
E. SHUTTERS			
1. Accordion			
2. Bahama			
3. Storm Panels			
4. Colonial			
5. Roll-up			
6. Equipment			
7. Others			
F. SKYLIGHTS			
1. Skylight			
2. Other			
G. STRUCTURAL COMPONENTS			
1. Wood connector/anchor	Simpson	double stud to plate tie, universal	10456.1, 5621.1
2. Truss plates	PTW	metal connector plate	1999.1, 1999.2
3. Engineered lumber	GPWPS	laminated lumber, I-joist	10009.1, 10005.1
4. Railing			
5. Coolers-freezers			
6. Concrete Admixtures			
7. Material			
8. Insulation Forms			
9. Plastics			
10. Deck-Roof			
11. Wall	Huber	zip system w/ sheathing	10565.1
12. Sheds			
13. Other			
H. NEW EXTERIOR ENVELOPE PRODUCTS			
1.			
2.			

The products listed below did not demonstrate product approval at plan review. I understand that at the time of inspection of these products, the following information must be available to the inspector on the jobsite; 1) copy of the product approval, 2) the performance characteristics which the product was tested and certified to comply with, 3) copy of the applicable manufacturers installation requirements.

I understand these products may have to be removed if approval cannot be demonstrated during inspection

Samantha Harrington
 Contractor or Contractor's Authorized Agent Signature
Legion Place Lot 6
 Location

Samantha Harrington 6/22/09
 Print Name Date

Permit # (FOR STAFF USE ONLY)

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Community Affairs Residential Performance Method A

Project Name: Sinisi Residence
 Street:
 City, State, Zip: Lake City, FL, 32024-
 Owner: Tony & Magda Sinisi
 Design Location: FL, Gainesville

Builder Name: Isaac Construction
 Permit Office: Columbia County
 Permit Number:
 Jurisdiction:

1. New construction or existing	New (From Plans)	
2. Single family or multiple family	Single-family	
3. Number of units, if multiple family	1	
4. Number of Bedrooms	4	
5. Is this a worst case?	No	
6. Conditioned floor area (ft ²)	2458	
7. Windows	Description	Area
a. U-Factor:	Dbl, U=0.30	426.00 ft ²
SHGC:	SHGC=0.50	
b. U-Factor:	N/A	ft ²
SHGC:		
c. U-Factor:	N/A	ft ²
SHGC:		
d. U-Factor:	N/A	ft ²
SHGC:		
e. U-Factor:	N/A	ft ²
SHGC:		
8. Floor Types	Insulation	Area
a. Slab-On-Grade Edge Insulation	R=5.0	2458.00 ft ²
b. N/A	R=	ft ²
c. N/A	R=	ft ²

9. Wall Types	Insulation	Area
a. Frame - Wood, Exterior	R=19.0	2047.50 ft ²
b. Frame - Wood, Adjacent	R=19.0	171.04 ft ²
c. N/A	R=	ft ²
d. N/A	R=	ft ²
10. Ceiling Types	Insulation	Area
a. Under Attic (Vented)	R=30.0	2704.00 ft ²
b. N/A	R=	ft ²
c. N/A	R=	ft ²
11. Ducts		
a. Sup: Attic Ret: Attic AH: Garage Sup. R= 6, 614.5 ft ²		
12. Cooling systems		
a. Central Unit	Cap: 67.7 kBtu/hr	SEER: 14
13. Heating systems		
a. Electric Heat Pump	Cap: 67.7 kBtu/hr	HSPF: 7.7
14. Hot water systems		
a. Electric	Cap: 80 gallons	EF: 0.9
b. Conservation features		
None		
15. Credits		None

Glass/Floor Area: 0.173

Total As-Built Modified Loads: 40.69

Total Baseline Loads: 50.84

PASS

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: 

DATE: 6/19/09

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: _____

DATE: _____

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.



BUILDING OFFICIAL: _____

DATE: _____

- Compliance requires an envelope leakage test report, by a Florida Class 1 Rater, in accordance with N1113.A.1.

PROJECT

Title:	Sinisi Residence	Bedrooms:	4	Adress Type:	Lot Information
Building Type:	FLAsBuilt	Bathrooms:	0	Lot #	6
Owner:	Tony & Magda Sinisi	Conditioned Area:	2458	SubDivision:	Legion Place
# of Units:	1	Total Stories:	1	PlatBook:	
Builder Name:	Isaac Construction	Worst Case:	No	Street:	
Permit Office:	Columbia County	Rotate Angle:	0	County:	Columbia
Jurisdiction:		Cross Ventilation:		City, State, Zip:	Lake City ,
Family Type:	Single-family	Whole House Fan:			FL , 32024-
New/Existing:	New (From Plans)				
Comment:					

CLIMATE

✓	Design Location	TMY Site	IECC Zone	Design Temp 97.5 %	Design Temp 2.5 %	Int Design Temp Winter	Int Design Temp Summer	Heating Degree Days	Design Moisture	Daily Temp Range
_____	FL, Gainesville	FL_GAINESVILLE_REGI	2	32	92	75	70	1305.5	51	Medium

FLOORS

✓	#	Floor Type	Perimeter	R-Value	Area	Tile	Wood	Carpet
_____	1	Slab-On-Grade Edge Insulatio	246.5 ft	5	2458 ft²	0	0	1

ROOF

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Solar Absor.	Tested	Deck Insul.	Pitch
_____	1	Hip	Composition shingles	2662 ft²	0 ft²	Dark	0.96	No	0	22.6 deg

ATTIC

✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
_____	1	Full attic	Vented	303	2458 ft²	N	N

CEILING

✓	#	Ceiling Type	R-Value	Area	Framing Frac	Truss Type
_____	1	Under Attic (Vented)	30	2704 ft²	0.11	Wood

WALLS

✓	#	Ornt	Adjacent To	Wall Type	Cavity R-Value	Area	Sheathing R-Value	Framing Fraction	Solar Absor.
_____	1	N	Exterior	Frame - Wood	19	344.56 ft²	0	0.23	0.75
_____	2	S	Exterior	Frame - Wood	19	311.25 ft²	0	0.23	0.75
_____	3	E	Exterior	Frame - Wood	19	370.92 ft²	0	0.23	0.75
_____	4	W	Exterior	Frame - Wood	19	435.92 ft²	0	0.23	0.75
_____	5	NW	Exterior	Frame - Wood	19	302.92 ft²	0	0.23	0.75
_____	6	SW	Exterior	Frame - Wood	19	281.92 ft²	0	0.23	0.75
_____	7	E	Garage	Frame - Wood	19	171.04 ft²		0.23	0.01

DOORS

✓	#	Ornt	Door Type	Storms	U-Value	Area
✓	1	E	Insulated	None	0.46	20 ft²
✓	2	W	Insulated	None	0.46	20 ft²

WINDOWS

Window orientation below is as entered. Actual orientation is modified by rotate angle shown in "Project" section above.

✓	#	Ornt	Frame	Panes	NFRC	U-Factor	SHGC	Storms	Area	Overhang		Int Shade	Screening
										Depth	Separation		
✓	1	E	Metal	Double (Clear)	Yes	0.3	0.5	N	72 ft²	0 ft 78 in	0 ft 18 in	HERS 2006	None
✓	2	E	Metal	Double (Clear)	Yes	0.3	0.5	N	12 ft²	0 ft 78 in	0 ft 0 in	HERS 2006	None
✓	3	E	Metal	Double (Clear)	Yes	0.3	0.5	N	20 ft²	0 ft 12 in	0 ft 24 in	HERS 2006	None
✓	4	N	Metal	Double (Clear)	Yes	0.3	0.5	N	6 ft²	0 ft 18 in	0 ft 12 in	HERS 2006	None
✓	5	N	Metal	Double (Clear)	Yes	0.3	0.5	N	8 ft²	0 ft 18 in	0 ft 12 in	HERS 2006	None
✓	6	NW	Metal	Double (Clear)	Yes	0.3	0.5	N	15 ft²	0 ft 30 in	0 ft 24 in	HERS 2006	None
✓	7	W	Metal	Double (Clear)	Yes	0.3	0.5	N	30 ft²	0 ft 188 in	0 ft 36 in	HERS 2006	None
✓	8	SW	Metal	Double (Clear)	Yes	0.3	0.5	N	15 ft²	0 ft 192 in	0 ft 36 in	HERS 2006	None
✓	9	W	Metal	Double (Clear)	Yes	0.3	0.5	N	48 ft²	0 ft 228 in	0 ft 12 in	HERS 2006	None
✓	10	N	Metal	Double (Clear)	Yes	0.3	0.5	N	21 ft²	0 ft 180 in	0 ft 12 in	HERS 2006	None
✓	11	NW	Metal	Double (Clear)	Yes	0.3	0.5	N	21 ft²	0 ft 168 in	0 ft 12 in	HERS 2006	None
✓	12	W	Metal	Double (Clear)	Yes	0.3	0.5	N	21 ft²	0 ft 138 in	0 ft 12 in	HERS 2006	None
✓	13	N	Metal	Double (Clear)	Yes	0.3	0.5	N	42.67 ft²	0 ft 54 in	0 ft 12 in	HERS 2006	None
✓	14	W	Metal	Double (Clear)	Yes	0.3	0.5	N	35 ft²	0 ft 18 in	0 ft 24 in	HERS 2006	None
✓	15	W	Metal	Double (Clear)	Yes	0.3	0.5	N	15 ft²	0 ft 18 in	0 ft 12 in	HERS 2006	None
✓	16	S	Metal	Double (Clear)	Yes	0.3	0.5	N	30 ft²	0 ft 18 in	0 ft 12 in	HERS 2006	None
✓	17	S	Metal	Double (Clear)	Yes	0.3	0.5	N	5.33 ft²	0 ft 18 in	0 ft 12 in	HERS 2006	None
✓	18	S	Metal	Double (Clear)	Yes	0.3	0.5	N	9 ft²	0 ft 18 in	0 ft 12 in	HERS 2006	None

INFILTRATION & VENTING

✓	Method	SLA	CFM 50	ACH 50	ELA	EqLA	--- Forced Ventilation ---		Run Time	Fan
							Supply CFM	Exhaust CFM	Fraction	Watts
✓	Proposed ACH	0.00036	2321	6.30	127.4	239.6	0 cfm	0 cfm	0	0

GARAGE

✓	#	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg. Wall Height	Exposed Wall Insulation
✓	1	569.763 ft²	569.763 ft²	77.33 ft	8 ft	13

COOLING SYSTEM

✓	#	System Type	Subtype	Efficiency	Capacity	Air Flow	SHR	Ductless
✓	1	Central Unit	None	SEER: 14	67.7 kBtu/hr	cfm	0.75	

HEATING SYSTEM

✓	#	System Type	Subtype	Efficiency	Capacity	Ductless
✓	1	Electric Heat Pump	None	HSPF: 7.7	67.7 kBtu/hr	

HOT WATER SYSTEM

✓	#	System Type	EF	Cap	Use	SetPnt	Conservation
✓	1	Electric	0.9	80 gal	70 gal	120 deg	None

SOLAR HOT WATER SYSTEM

✓	FSEC	Company Name	System Model #	Collector Model #	Collector Area	Storage Volume	FEF
✓	None	None				ft ²	

DUCTS

✓	#	Location	Supply R-Value	Supply Area	Location	Return Area	Leakage Type	Air Handler	CFM 25	Percent Leakage	QN	RLF
✓	1	Attic	6	614.5 ft ²	Attic	122.9 ft ²	Default Leakage	Garage				

TEMPERATURES

Programable Thermostat: N				Ceiling Fans:									
Cooling	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input checked="" type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec	
Heating	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input checked="" type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec	
Venting	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input checked="" type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec	
Thermostat Schedule: HERS 2006 Reference													
Schedule Type		1	2	3	4	5	6	7	8	9	10	11	12
Cooling (WD)	AM PM	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78
Cooling (WEH)	AM PM	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78
Heating (WD)	AM PM	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68
Heating (WEH)	AM PM	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68	68 68

Code Compliance Checklist

Residential Whole Building Performance Method A - Details

ADDRESS:

Lake City, FL, 32024-

PERMIT #:

INFILTRATION REDUCTION COMPLIANCE CHECKLIST

COMPONENTS	SECTION	REQUIREMENTS FOR EACH PRACTICE	CHECK
Exterior Windows & Doors	N1106.AB.1.1	Maximum: .3 cfm/sq.ft. window area; .5 cfm/sq.ft. door area.	
Exterior & Adjacent Walls	N1106.AB.1.2.1	Caulk, gasket, weatherstrip or seal between: windows/doors & frames, surrounding wall; foundation & wall sole or sill plate; joints between exterior wall panels at corners; utility penetrations; between wall panels & top/bottom plates; between walls and floor. EXCEPTION: Frame walls where a continuous infiltration barrier is installed that extends from, and is sealed to, the foundation to the top plate.	
Floors	N1106.AB.1.2.2	Penetrations/openings > 1/8" sealed unless backed by truss or joint members. EXCEPTION: Frame floors where a continuous infiltration barrier is installed that is sealed to the perimeter, penetrations and seams.	
Ceilings	N1106.AB.1.2.3	Between walls & ceilings; penetrations of ceiling plane to top floor; around shafts, chases, soffits, chimneys, cabinets sealed to continuous air barrier; gaps in gyp board & top plate; attic access. EXCEPTION: Frame ceilings where a continuous infiltration barrier is installed that is sealed at the perimeter, at penetrations and seams.	
Recessed Lighting Fixtures	N1106.AB.1.2.4	Type IC rated with no penetrations, sealed; or Type IC or non-IC rated, installed inside a sealed box with 1/2" clearance & 3" from insulation; or Type IC with < 2.0 cfm from conditioned space, tested.	
Multi-story Houses	N1106.AB.1.2.5	Air barrier on perimeter of floor cavity between floors.	
Additional Infiltration reqts	N1106.AB.1.3	Exhaust fans vented to outdoors, dampers; combustion space heaters comply with NFPA, have combustion air.	

OTHER PRESCRIPTIVE MEASURES (must be met or exceeded by all residences.)

COMPONENTS	SECTION	REQUIREMENTS	CHECK
Water Heaters	N1112.AB.3	Comply with efficiency requirements in Table N112.ABC.3. Switch or clearly marked circuit breaker (electric) or cutoff (gas) must be provided. External or built-in heat trap required.	
Swimming Pools & Spas	N1112.AB.2.3	Spas & heated pools must have covers (except solar heated). Non-commercial pools must have a pump timer. Gas spa & pool heaters must have a minimum thermal efficiency of 78%. Heat pump pool heaters shall have a minimum COP of 4.0.	
Shower heads	N1112.AB.2.4	Water flow must be restricted to no more than 2.5 gallons per minute at 80 PSIG.	
Air Distribution Systems	N1110.AB	All ducts, fittings, mechanical equipment and plenum chambers shall be mechanically attached, sealed, insulated and installed in accordance with the criteria of Section N1110.AB. Ducts in unconditioned attics: R-6 min. insulation.	
HVAC Controls	N1107.AB.2	Separate readily accessible manual or automatic thermostat for each system.	
Insulation	N1104.AB.1 N1102.B.1.1	Ceilings-Min. R-19. Common walls-frame R-11 or CBS R-3 both sides. Common ceiling & floors R-11.	

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 80

The lower the EnergyPerformance Index, the more efficient the home.

1. New construction or existing	New (From Plans)	9. Wall Types	Insulation	Area
2. Single family or multiple family	Single-family	a. Frame - Wood, Exterior	R=19.0	2047.50 ft ²
3. Number of units, if multiple family	1	b. Frame - Wood, Adjacent	R=19.0	171.04 ft ²
4. Number of Bedrooms	4	c. N/A	R=	ft ²
5. Is this a worst case?	No	d. N/A	R=	ft ²
6. Conditioned floor area (ft ²)	2458	10. Ceiling Types	Insulation	Area
7. Windows**	Description	a. Under Attic (Vented)	R=30.0	2704.00 ft ²
a. U-Factor:	Dbl, U=0.30	b. N/A	R=	ft ²
SHGC:	SHGC=0.50	c. N/A	R=	ft ²
b. U-Factor:	N/A	11. Ducts		
SHGC:		a. Sup: Attic Ret: Attic AH: Garage Sup. R= 6, 614.5 ft ²		
c. U-Factor:	N/A	12. Cooling systems		
SHGC:		a. Central Unit	Cap: 67.7 kBtu/hr	SEER: 14
d. U-Factor:	N/A	13. Heating systems		
SHGC:		a. Electric Heat Pump	Cap: 67.7 kBtu/hr	HSPF: 7.7
e. U-Factor:	N/A	14. Hot water systems		
SHGC:		a. Electric	Cap: 80 gallons	EF: 0.9
8. Floor Types	Insulation	b. Conservation features		
a. Slab-On-Grade Edge Insulation	R=5.0	None		
b. N/A	R=	15. Credits		None
c. N/A	R=			

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: _____ Date: _____

Address of New Home: _____ City/FL Zip: _____



*Note: The home's estimated Energy Performance Index is only available through the EnergyGauge USA - FlaRes2008 computer program. This is not a Building Energy Rating. If your Index is below 100, your home may qualify for incentives if you obtain a Florida Energy Gauge Rating. Contact the Energy Gauge Hotline at (321) 638-1492 or see the Energy Gauge web site at energygauge.com for information and a list of certified Raters. For information about Florida's Energy Efficiency Code for Building Construction, contact the Department of Community Affairs at (850) 487-1824.

**Label required by Section 13-104.4.5 of the Florida Building Code, Building, or Section B2.1.1 of Appendix G of the Florida Building Code, Residential, if not DEFAULT.

Residential System Sizing Calculation

Summary

Tony & Magda Sinisi

Project Title:
Sinisi Residence

Code Only
Professional Version
Climate: North


6/19/2009

Location for weather data: Gainesville - User customized: Latitude(29) Altitude(152 ft.) Temp Range(M)					
Humidity data: Interior RH (50%) Outdoor wet bulb (78F) Humidity difference(54gr.)					
Winter design temperature	33	F	Summer design temperature	95	F
Winter setpoint	70	F	Summer setpoint	75	F
Winter temperature difference	37	F	Summer temperature difference	20	F
Total heating load calculation			43736	Btuh	
Submitted heating capacity	% of calc	Btuh	Submitted cooling capacity	% of calc	Btuh
Total (Electric Heat Pump)	154.8	67700	Sensible (SHR = 0.75)	102.0	50775
Heat Pump + Auxiliary(0.0kW)	154.8	67700	Latent	143.5	16925
			Total (Electric Heat Pump)	109.9	67700

WINTER CALCULATIONS

Winter Heating Load (for 2458 sqft)


Load component		Load	
Window total	426 sqft	13713	Btuh
Wall total	1753 sqft	5011	Btuh
Door total	40 sqft	518	Btuh
Ceiling total	2704 sqft	3186	Btuh
Floor total	247 sqft	4031	Btuh
Infiltration	295 cfm	11948	Btuh
Duct loss		5330	Btuh
Subtotal		43736	Btuh
Ventilation	0 cfm	0	Btuh
TOTAL HEAT LOSS		43736	Btuh



SUMMER CALCULATIONS

Summer Cooling Load (for 2458 sqft)

Load component		Load	
Window total	426 sqft	24320	Btuh
Wall total	1753 sqft	3005	Btuh
Door total	40 sqft	434	Btuh
Ceiling total	2704 sqft	4736	Btuh
Floor total		0	Btuh
Infiltration	258 cfm	5651	Btuh
Internal gain		4240	Btuh
Duct gain		7406	Btuh
Sens. Ventilation	0 cfm	0	Btuh
Total sensible gain		49793	Btuh
Latent gain(ducts)		765	Btuh
Latent gain(infiltration)		9432	Btuh
Latent gain(ventilation)		0	Btuh
Latent gain(internal/occupants/other)		1600	Btuh
Total latent gain		11797	Btuh
TOTAL HEAT GAIN		61590	Btuh



Version 8
For Florida residences only

EnergyGauge® System Sizing

PREPARED BY:

DATE: 6/19/09

System Sizing Calculations - Winter

Residential Load - Whole House Component Details

Tony & Magda Sinisi

Project Title:
Sinisi Residence

Code Only
Professional Version
Climate: North

Lake City, FL 32024-

Reference City: Gainesville (User customized) Winter Temperature Difference: 37.0 F

6/19/2009

WHOLE HOUSE TOTALS

	Subtotal Sensible	43736 Btuh
	Ventilation Sensible	0 Btuh
	Total Btuh Loss	43736 Btuh

EQUIPMENT

1. Electric Heat Pump	#	67700 Btuh
-----------------------	---	------------

Key: Window types (SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)
(Frame types - metal, wood or insulated metal)
(U - Window U-Factor or 'DEF' for default)
(HTM - ManualJ Heat Transfer Multiplier)
Key: Floor size (perimeter(p) for slab-on-grade or area for all other floor types)



Version 8
For Florida residences only

System Sizing Calculations - Winter

Residential Load - Room by Room Component Details

Tony & Magda Sinisi

Project Title:
Sinisi Residence

Code Only
Professional Version
Climate: North

Lake City, FL 32024-

Reference City: Gainesville (User customized) Winter Temperature Difference: 37.0 F

6/19/2009

Component Loads for Zone #1: Main

Window	Panes/SHGC/Frame/U	Orientation	Area(sqft)	X	HTM=	Load
1	2, Clear, Metal, 0.87	E	72.0		32.2	2318 Btuh
2	2, Clear, Metal, 0.87	E	12.0		32.2	386 Btuh
3	2, Clear, Metal, 0.87	E	20.0		32.2	644 Btuh
4	2, Clear, Metal, 0.87	N	6.0		32.2	193 Btuh
5	2, Clear, Metal, 0.87	N	8.0		32.2	258 Btuh
6	2, Clear, Metal, 0.87	NW	15.0		32.2	483 Btuh
7	2, Clear, Metal, 0.87	W	30.0		32.2	966 Btuh
8	2, Clear, Metal, 0.87	SW	15.0		32.2	483 Btuh
9	2, Clear, Metal, 0.87	W	48.0		32.2	1545 Btuh
10	2, Clear, Metal, 0.87	N	21.0		32.2	676 Btuh
11	2, Clear, Metal, 0.87	NW	21.0		32.2	676 Btuh
12	2, Clear, Metal, 0.87	W	21.0		32.2	676 Btuh
13	2, Clear, Metal, 0.87	N	42.7		32.2	1374 Btuh
14	2, Clear, Metal, 0.87	W	35.0		32.2	1127 Btuh
15	2, Clear, Metal, 0.87	W	15.0		32.2	483 Btuh
16	2, Clear, Metal, 0.87	S	30.0		32.2	966 Btuh
17	2, Clear, Metal, 0.87	S	5.3		32.2	172 Btuh
18	2, Clear, Metal, 0.87	S	9.0		32.2	290 Btuh
Window Total			426(sqft)			13713 Btuh
Walls	Type	R-Value	Area	X	HTM=	Load
1	Frame - Wood - Ext(0.08)	19.0	1602		2.9	4579 Btuh
2	Frame - Wood - Adj(0.08)	19.0	151		2.9	432 Btuh
Wall Total			1753			5011 Btuh
Doors	Type		Area	X	HTM=	Load
1	Insulated - Adjacent		20		12.9	259 Btuh
2	Insulated - Exterior		20		12.9	259 Btuh
Door Total			40			518 Btuh
Ceilings	Type/Color/Surface	R-Value	Area	X	HTM=	Load
1	Vented Attic/D/Shin	30.0	2704		1.2	3186 Btuh
Ceiling Total			2704			3186 Btuh
Floors	Type	R-Value	Size	X	HTM=	Load
1	Slab On Grade	5	246.5 ft(p)		16.4	4031 Btuh
Floor Total			247			4031 Btuh
Zone Envelope Subtotal:						26459 Btuh
Infiltration	Type	ACH X Volume(cuft)	walls(sqft)	CFM=		Load
	Natural	0.80	22122	1753	295.0	11948 Btuh
Ductload	Pro. leak free, Supply(R6.0-Attic), Return(R6.0-Attic) (DLM of 0.139)					5330 Btuh

Manual J Winter Calculations

Residential Load - Component Details (continued)

Tony & Magda Sinisi

Project Title:
Sinisi Residence

Code Only
Professional Version
Climate: North

Lake City, FL 32024-

6/19/2009

Zone #1	Sensible Zone Subtotal	43736 Btuh
----------------	-------------------------------	-------------------

WHOLE HOUSE TOTALS

	Subtotal Sensible	43736 Btuh
	Ventilation Sensible	0 Btuh
	Total Btuh Loss	43736 Btuh

EQUIPMENT

1. Electric Heat Pump	#	67700 Btuh
-----------------------	---	------------

Key: Window types (SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)
(Frame types - metal, wood or insulated metal)
(U - Window U-Factor or 'DEF' for default)
(HTM - ManualJ Heat Transfer Multiplier)

Key: Floor size (perimeter(p) for slab-on-grade or area for all other floor types)



Version 8
For Florida residences only

System Sizing Calculations - Summer

Residential Load - Whole House Component Details

Tony & Magda Sinisi

Project Title:
Sinisi Residence

Code Only
Professional Version
Climate: North

Lake City, FL 32024-

Reference City: Gainesville (User customized) Summer Temperature Difference: 20.0 F 6/19/2009

The following window Excursion will be assigned to the system loads.

~~2450~~ 87, None, N, N
~~400~~ 87, None, N, N
~~1000~~ 87, None, N, N
~~600~~ 87, None, N, N
~~200~~ 87, None, N, N
~~500~~ 87, None, N, N
~~300~~ 87, None, N, N
~~400~~ 87, None, N, N
~~400~~ 87, None, N, N
~~600~~ 87, None, N, N
~~1000~~ 87, None, N, N
~~200~~ 87, None, N, N
~~1000~~ 87, None, N, N
~~2000~~ 87, None, N, N
~~1000~~ 87, None, N, N
~~300~~ 87, None, N, N
1.6666666666666666 87, None, N, N
~~200~~ 87, None, N, N

	Window Total		426 (sqft)		19408 Btuh
Walls	Type	R-Value/U-Value	Area(sqft)	HTM	Load
1	Frame - Wood - Ext	19.0/0.08	1601.5	1.7	2772 Btuh
2	Frame - Wood - Adj	19.0/0.08	151.0	1.5	233 Btuh
	Wall Total		1753 (sqft)		3005 Btuh
Doors	Type		Area (sqft)	HTM	Load
1	Insulated - Adjacent		20.0	10.8	217 Btuh
2	Insulated - Exterior		20.0	10.8	217 Btuh
	Door Total		40 (sqft)		434 Btuh
Ceilings	Type/Color/Surface	R-Value	Area(sqft)	HTM	Load
1	Vented Attic/DarkShingle	30.0	2704.0	1.8	4736 Btuh
	Ceiling Total		2704 (sqft)		4736 Btuh
Floors	Type	R-Value	Size	HTM	Load
1	Slab On Grade	5.0	247 (ft(p))	0.0	0 Btuh
	Floor Total		246.5 (sqft)		0 Btuh
Windows	July excursion for System 1				4912 Btuh
	Excursion Subtotal:				13088 Btuh
Duct load	(DGMs vary for Mixed ducts)				7406 Btuh
	Sensible Load All Zones				20494 Btuh

Manual J Summer Calculations

Residential Load - Component Details (continued)

Tony & Magda Sinisi

Project Title:
Sinisi Residence

Code Only
Professional Version
Climate: North

Lake City, FL 32024-

6/19/2009

WHOLE HOUSE TOTALS

Whole House Totals for Cooling	Sensible Envelope Load All Zones	42387 Btuh
	Sensible Duct Load	7406 Btuh
	Total Sensible Zone Loads	49793 Btuh
	Sensible ventilation	0 Btuh
	Blower	0 Btuh
	Total sensible gain	49793 Btuh
	Latent infiltration gain (for 54 gr. humidity difference)	9432 Btuh
	Latent ventilation gain	0 Btuh
	Latent duct gain	765 Btuh
	Latent occupant gain (8 people @ 200 Btuh per person)	1600 Btuh
	Latent other gain	0 Btuh
	Latent total gain	11797 Btuh
	TOTAL GAIN	61590 Btuh

EQUIPMENT

1. Central Unit	#	67700 Btuh
-----------------	---	------------

*Key: Window types (Pn - Number of panes of glass)

(SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)

(U - Window U-Factor or 'DEF' for default)

(InSh - Interior shading device: none(N), Blinds(B), Draperies(D) or Roller Shades(R))

(ExSh - Exterior shading device: none(N) or numerical value)

(BS - Insect screen: none(N), Full(F) or Half(H))

(Ornt - compass orientation)



Version 8
For Florida residences only

System Sizing Calculations - Summer

Residential Load - Room by Room Component Details

Tony & Magda Sinisi

Project Title:
Sinisi Residence

Code Only
Professional Version
Climate: North

Lake City, FL 32024-

Reference City: Gainesville (User customized) Summer Temperature Difference: 20.0 F 6/19/2009

The following window Excursion will be assigned to the system loads.

Windows	July excursion for System 1	Excursion Subtotal:	4912 Btuh 4912 Btuh
Duct load			858 Btuh
		Sensible Excursion Load	5770 Btuh

Component Loads for Zone #1: Main

Window	Type*	Ornt	Overhang		Window Area(sqft)			HTM		Load
			Len	Hgt	Gross	Shaded	Unshaded	Shaded	Unshaded	
1	2, Clear, 0.87, None,N,N	E	6.5ft	7.5ft	72.0	46.7	25.3	32	82	3550 Btuh
2	2, Clear, 0.87, None,N,N	E	6.5ft	6ft.	12.0	10.8	1.2	32	82	440 Btuh
3	2, Clear, 0.87, None,N,N	E	1ft.	7ft.	20.0	0.0	20.0	32	82	1643 Btuh
4	2, Clear, 0.87, None,N,N	N	1.5ft	4ft.	6.0	0.0	6.0	32	32	189 Btuh
5	2, Clear, 0.87, None,N,N	N	1.5ft	3ft.	8.0	0.0	8.0	32	32	253 Btuh
6	2, Clear, 0.87, None,N,N	NW	2.5ft	7ft.	15.0	0.0	15.0	32	63	940 Btuh
7	2, Clear, 0.87, None,N,N	W	15.6	8ft.	30.0	30.0	0.0	32	82	947 Btuh
8	2, Clear, 0.87, None,N,N	SW	16ft.	8ft.	15.0	15.0	0.0	32	65	474 Btuh
9	2, Clear, 0.87, None,N,N	W	19ft.	9ft.	48.0	48.0	0.0	32	82	1515 Btuh
10	2, Clear, 0.87, None,N,N	N	15ft.	8ft.	21.0	0.0	21.0	32	32	663 Btuh
11	2, Clear, 0.87, None,N,N	NW	14ft.	8ft.	21.0	0.0	21.0	32	63	1316 Btuh
12	2, Clear, 0.87, None,N,N	W	11.5f	8ft.	21.0	21.0	0.0	32	82	663 Btuh
13	2, Clear, 0.87, None,N,N	N	4.5ft	9ft.	42.7	0.0	42.7	32	32	1347 Btuh
14	2, Clear, 0.87, None,N,N	W	1.5ft	9ft.	35.0	0.0	35.0	32	82	2874 Btuh
15	2, Clear, 0.87, None,N,N	W	1.5ft	6ft.	15.0	0.7	14.3	32	82	1195 Btuh
16	2, Clear, 0.87, None,N,N	S	1.5ft	6ft.	30.0	30.0	0.0	32	36	947 Btuh
17	2, Clear, 0.87, None,N,N	S	1.5ft	1.66	5.3	5.3	0.0	32	36	168 Btuh
18	2, Clear, 0.87, None,N,N	S	1.5ft	4ft.	9.0	9.0	0.0	32	36	284 Btuh
	Window Total				426 (sqft)					19408 Btuh
Walls	Type		R-Value/U-Value		Area(sqft)			HTM		Load
1	Frame - Wood - Ext		19.0/0.08		1601.5			1.7		2772 Btuh
2	Frame - Wood - Adj		19.0/0.08		151.0			1.5		233 Btuh
	Wall Total				1753 (sqft)					3005 Btuh
Doors	Type				Area (sqft)			HTM		Load
1	Insulated - Adjacent				20.0			10.8		217 Btuh
2	Insulated - Exterior				20.0			10.8		217 Btuh
	Door Total				40 (sqft)					434 Btuh
Ceilings	Type/Color/Surface		R-Value		Area(sqft)			HTM		Load
1	Vented Attic/DarkShingle		30.0		2704.0			1.8		4736 Btuh
	Ceiling Total				2704 (sqft)					4736 Btuh
Floors	Type		R-Value		Size			HTM		Load
1	Slab On Grade		5.0		247 (ft(p))			0.0		0 Btuh
	Floor Total				246.5 (sqft)					0 Btuh
								Zone Envelope Subtotal:		27584 Btuh

Manual J Summer Calculations

Residential Load - Component Details (continued)

Tony & Magda Sinisi

Project Title:
Sinisi Residence

Code Only
Professional Version
Climate: North

Lake City, FL 32024-

6/19/2009

Infiltration	Type	ACH	Volume(cuft)	wall area(sqft)	CFM=	Load
	SensibleNatural	0.70	22122	1753	258.1	5651 Btuh
Internal gain		Occupants	Btuh/occupant	Appliance		Load
		8	X 230 +	2400		4240 Btuh
				Sensible Envelope Load:		37475 Btuh
Duct load	Prop. leak free, Supply(R6.0-Attic), Return(R6.0-Attic)			(DGM of 0.175)		6548 Btuh
				Sensible Zone Load		44023 Btuh

Manual J Summer Calculations

Residential Load - Component Details (continued)

Tony & Magda Sinisi

Project Title:
Sinisi Residence

Code Only
Professional Version
Climate: North

Lake City, FL 32024-

6/19/2009

WHOLE HOUSE TOTALS

Whole House Totals for Cooling	Sensible Envelope Load All Zones	42387 Btuh
	Sensible Duct Load	7406 Btuh
	Total Sensible Zone Loads	49793 Btuh
	Sensible ventilation	0 Btuh
	Blower	0 Btuh
	Total sensible gain	49793 Btuh
	Latent infiltration gain (for 54 gr. humidity difference)	9432 Btuh
	Latent ventilation gain	0 Btuh
	Latent duct gain	765 Btuh
	Latent occupant gain (8 people @ 200 Btuh per person)	1600 Btuh
	Latent other gain	0 Btuh
	Latent total gain	11797 Btuh
	TOTAL GAIN	61590 Btuh

EQUIPMENT

1. Central Unit	#	67700 Btuh
-----------------	---	------------

*Key: Window types (Pn - Number of panes of glass)

(SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)

(U - Window U-Factor or 'DEF' for default)

(InSh - Interior shading device: none(N), Blinds(B), Draperies(D) or Roller Shades(R))

(ExSh - Exterior shading device: none(N) or numerical value)

(BS - Insect screen: none(N), Full(F) or Half(H))

(Ornt - compass orientation)



Version 8
For Florida residences only

Residential Window Diversity

MidSummer

Tony & Magda Sinisi

Lake City, FL 32024-

Project Title:
Sinisi Residence


Code Only
Professional Version
Climate: North

6/19/2009

Weather data for: Gainesville - User customized

Summer design temperature	95 F	Average window load for July	19352 Btu
Summer setpoint	75 F	Peak window load for July	31292 Btu
Summer temperature difference	20 F	Excursion limit(130% of Ave.)	25157 Btu
Latitude	29 North	Window excursion (July)	6135 Btuh

WINDOW Average and Peak Loads



This application has glass areas that produce large heat gains for part of the day. Variable air volume devices are required to overcome spikes in solar gain for one or more rooms. Install a zoned system or provide zone control for problem rooms. Single speed equipment may not be suitable for the application.

EnergyGauge® System Sizing for Florida residences only

PREPARED BY: _____

DATE: _____

EnergyGauge® FLRCPB v4.5.2



OMB Approval No. 2502-0525
(exp. 02/29/2012)

Public reporting burden for this collection of information is estimated to average 15 minutes per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. This information is required to obtain benefits. HUD may not collect this information, and you are not required to complete this form, unless it displays a currently valid OMB control number.

All contracts for services are between the Pest Control Company and builder, unless stated otherwise.

duct #2581 From • CROWNMAX • 1-800-252-4011

28856

**NOTICE OF COMMENCEMENT FORM
COLUMBIA COUNTY, FLORIDA**

**THIS DOCUMENT MUST BE RECORDED AT THE COUNTY
CLERKS OFFICE BEFORE YOUR FIRST INSPECTION**

THE UNDERSIGNED hereby gives notice that improvement will be made to certain real property, and in accordance with Chapter 713, Florida Statutes, the following information is provided in this Notice of Commencement.

IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR AN ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT.

Tax Parcel ID Number 20-45-16-03051-206 Permit Number _____

1. Description of property: (legal description of the property and street address or 911 address)

LOT # 6 hearon Place, a subdivision according to the
plat thereof filed in Plat Book 7, Page 67, Public Record
of Columbia County, Florida

2. General description of improvement: Construction of a Single Family Home

3. Owner Name & Address Anthony & Magda Sinisi

Interest In Property _____

4. Name & Address of Fee Simple Owner (if other than owner): AAA

5. Contractor Name Isaac Construction Phone Number 386-719-7143

Address 125 SW N. ctown Pl, Suite #

6. Surety Holders Name N/A

Phone Number _____

Address _____

Amount of Bond _____

7. Lender Name N/A

Phone Number _____

Address _____

8. Persons within the State of Florida designated by the Owner upon whom notices or other documents may be served as provided by section 718.13 (1)(a) 7; Florida Statutes:

Name N/A

Address _____

Inst: 201012014781 Date: 9/14/2010 Time: 1:13 PM
DC, P. DeWitt Cason, Columbia County Page 1 of 1 B: 1201 P: 780

9. In addition to himself/herself the owner designates 16 of

_____ to receive a copy of the Lien Notice as provided in Section 713.13 (1) -

(a) 7. Phone Number of the designee N/A

10. Expiration date of the Notice of Commencement (the expiration date is 1 (one) year from the date of recording, (Unless a different date is specified) _____

THE OWNER MUST SIGN THE NOTICE OF COMMENCEMENT AND NO ONE ELSE MAY BE PERMITTED TO SIGN IN HIS/HER STEAD.

Anthony Sinisi
Magda Sinisi
Signature of Owner


Sworn to (or affirmed) and subscribed before day of 28th of July, 2010

Barbara Webster
Signature of Notary

NOTARY STAMP/SEAL



BARBARA C. WEBSTER
MY COMMISSION # DD 800888
EXPIRES: July 2, 2012
Bonded Thru Budget Notary Services



SOUTH POINTE

POINT OF BEGINNING

4"x4" L.L. LEE #1950
CONCRETE MONUMENT FOL

ALEX STEVENS

EAST LINE SECTION 20

SEVEN
DIVIDED FOR
IMAGE
BOUNDARY

RDS

IE
DIVIDED,
ISION
OR OTHER
A PUBLIC

2E:
PLAT AS RECORDED IN ITS GRAPHICAL FORM, IS THE
IAL DEPICTION OF THE SUBDIVIDED LANDS DESCRIBED IN
IN AND WILL IN NO CIRCUMSTANCES BE SUPPLANTED IN
ORITY BY OTHER GRAPHICAL OR DIGITAL FORM OF THE
THERE MAY BE ADDITIONAL RESTRICTIONS THAT ARE NOT
RDED ON THIS PLAT THAT MAY BE FOUND IN THE PUBLIC
RDS OF THIS COUNTY.

ALEX STEVENS, JR 37.73 AC
UNPLATTED LANDS

4"x4" L.E. BRITT #1079
CONCRETE MONUMENT SET
SE CORNER OF THE NE 1/4,
OF THE NE 1/4, SECTION 20,
TOWNSHIP 4 SOUTH, RANGE
16 EAST.


DEVELOPER:

PETER W. GIEBEIG
P.O. BOX 1384
LAKE CITY, FLORIDA 32056
904-752-7968



TELEPHONE: 69





1008-07

Columbia County Building Permit Application

2593

For Office Use Only Application # 1008-17 Date Received 8/12/10 By LS Permit # 1848/28856
Zoning Official B2K Date 03.09.10 Flood Zone X Land Use A-3 Zoning A-3
FEMA Map # N/A Elevation N/A MFE 1' above R River N/A Plans Examiner J.C. Date 9-2-10
Comments
☐ NOC ☐ EH ☐ Deed or PA ☐ Site Plan ☐ State Road Info ☐ Parent Parcel #
☐ Dev Permit # ☐ In Floodway ☐ Letter of Auth. from Contractor ☐ F W Comp. letter
IMPACT FEES: EMS _____ Fire _____ Corr _____ Road/Code _____
School _____ = TOTAL N/A Suspended VF

Septic Permit No. 10-0390Fax 386-719-4757Name Authorized Person Signing Permit Barbara Webster Phone 386-719-7143Address 125 SW Midtown Pl Ste #101 Lake City, FL 32025Owners Name Anthony and Magda Sinisi

Phone _____

911 Address 1500 SW Legion Dr. Lake City, FL 32024Contractors Name Isaac Construction, LLCPhone 386-719-7143Address 125 SW Midtown Pl Ste #101 Lake City, FL 32025

Fee Simple Owner Name & Address _____

Bonding Co. Name & Address _____

Architect/Engineer Name & Address Mark Disosway, PE PO Box 868 Lake City, FL 32026Mortgage Lenders Name & Address First FederalCircle the correct power company - FL Power & Light - Clay Elec. - Suwannee Valley Elec. - Progress EnergyProperty ID Number 20-45-16-03051-206 Estimated Cost of Construction 165,000.00Subdivision Name Legion PlaceLot 6 Block _____ Unit _____ Phase _____Driving Directions Hwy 90 to Branford Hwy turn R on to Tamara Lane, follow the road around the R, turn L on to Tamara Lane, follow it to S. Pointe on Legion Dr. lot 6 on L near the end of the cul-de-sac 2nd to last on leftNumber of Existing Dwellings on Property 0Construction of new home SFDTotal Acreage 5.01 Lot Size _____Do you need a Culvert Permit or Culvert Waiver or Have an Existing DriveTotal Building Height 20'-1"Actual Distance of Structure from Property Lines - Front 100'-0" Side 175'-8" Side 167'-4" Rear 296'-0"Number of Stories 1 Heated Floor Area 2458 Total Floor Area 3703 Roof Pitch 5/12

Application is hereby made to obtain a permit to do work and installations as indicated. I certify that no work or installation has commenced prior to the issuance of a permit and that all work be performed to meet the standards of all laws regulating construction in this jurisdiction.

Spoke
w/ BARBARA
9/3/10

Columbia County Building Permit Application

TIME LIMITATIONS OF APPLICATION : An application for a permit for any proposed work shall be deemed to have been abandoned 180 days after the date of filing, unless such application has been pursued in good faith or a permit has been issued; except that the building official is authorized to grant one or more extensions of time for additional periods not exceeding 90 days each. The extension shall be requested in writing and justifiable cause demonstrated.

TIME LIMITATIONS OF PERMITS: Every permit issued shall become invalid unless the work authorized by such permit is commenced within 180 days after its issuance, or if the work authorized by such permit is suspended or abandoned for a period of 180 days after the time work is commenced. A valid permit receives an approved inspection every 180 days. Work shall be considered not suspended, abandoned or invalid when the permit has received an approved inspection within 180 days of the previous approved inspection.



FLORIDA'S CONSTRUCTION LIEN LAW: Protect Yourself and Your Investment: According to Florida Law, those who work on your property or provide materials, and are not paid-in-full, have a right to enforce their claim for payment against your property. This claim is known as a construction lien. If your contractor fails to pay subcontractors or material suppliers or neglects to make other legally required payments, the people who are owed money may look to your property for payment, even if you have paid your contractor in full. This means if a lien is filed against your property, it could be sold against your will to pay for labor, materials or other services which your contractor may have failed to pay.

NOTICE OF RESPONSIBILITY TO BUILDING PERMITEE: **YOU ARE HEREBY NOTIFIED** as the recipient of a building permit from Columbia County, Florida, you will be held responsible to the County for any damage to sidewalks and/or road curbs and gutters, concrete features and structures, together with damage to drainage facilities, removal of sod, major changes to lot grades that result in ponding of water, or other damage to roadway and other public infrastructure facilities caused by you or your contractor, subcontractors, agents or representatives in the construction and/or improvement of the building and lot for which this permit is issued. No certificate of occupancy will be issued until all corrective work to these public infrastructures and facilities has been corrected.

WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOU PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. A NOTICE OF COMMENCEMENT MUST BE RECORDED AND POSTED ON THE JOB SITE BEFORE THE FIRST INSPECTION. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT.

OWNERS CERTIFICATION: I CERTIFY THAT ALL THE FOREGOING INFORMATION IS ACCURATE AND THAT ALL WORK WILL BE DONE IN COMPLIANCE WITH ALL APPLICABLE LAWS REGULATING CONSTRUCTION AND ZONING.

NOTICE TO OWNER: There are some properties that may have deed restrictions recorded upon them. These restrictions may limit or prohibit the work applied for in your building permit. It may be to your advantage to check and see if your property is encumbered by any restrictions.



Owners Signature

(Owners Must Sign All Applications Before Permit Issuance.)

****OWNER BUILDERS MUST PERSONALLY APPEAR AND SIGN THE BUILDING PERMIT.**

CONTRACTORS AFFIDAVIT: By my signature I understand and agree that I have informed and provided this written statement to the owner of all the above written responsibilities in Columbia County for obtaining this Building Permit including all application and permit time limitations.


Contractor's Signature (Permitee)

Contractor's License Number 46059323
Columbia County
Competency Card Number _____

Affirmed under penalty of perjury to by the Contractor and subscribed before me this 28 day of July 2010.

Personally known X or Produced Identification _____


State of Florida Notary Signature (For the Contractor)

SEAL:



BARBARA C. WEBSTER
MY COMMISSION # DD 800888
EXPIRES: July 2, 2012
Bonded Thru Budget Notary Services

Date	Inspection	Inspect.	Owner	Pass	Location	Permit
03/16/11	Nailing	Randy	Isaac Bratkovich - Sinisi	OK	Legion Place Lot 6	28856
04/05/11	Framing	Troy	Isaac Bratkovich	Not Right	Legion Place Lot 6	28856
04/05/11	Electrical	Troy	Isaac Bratkovich	OK	Legion Place Lot 6	28856
04/05/11	Plumbing	Troy	Isaac Bratkovich	Not Right	Legion Place Lot 6	28856
04/05/11	A/C	Troy	Isaac Bratkovich	Ok	Legion Place Lot 6	28856
05/12/11	Recheck Framing	TC-RJ	Isaac Bratkovich - Sinisi	Not Right	Legion Place Lot 6	28856
05/12/11	Recheck Plumbing	TC-RJ	Isaac Bratkovich - Sinisi	OK	Legion Place Lot 6	28856

25% of \$930.00
\$232.50

SUBCONTRACTOR VERIFICATION FORM

APPLICATION NUMBER

28856

CONTRACTOR

ISAAC BRATKOVICH

PHONE

867-0134

THIS FORM MUST BE SUBMITTED PRIOR TO THE ISSUANCE OF A PERMIT

In Columbia County one permit will cover all trades doing work at the permitted site. It is **REQUIRED** that we have records of the subcontractors who actually did the trade specific work under the permit. Per Florida Statute 440 and Ordinance 89-6, a contractor shall require all subcontractors to provide evidence of workers' compensation or exemption, general liability insurance and a valid Certificate of Competency license in Columbia County.

Any changes, the permitted contractor is responsible for the corrected form being submitted to this office prior to the start of that subcontractor beginning any work. Violations will result in stop work orders and/or fines.

ELECTRICAL	Print Name _____ License #: _____	Signature _____ Phone #: _____
MECHANICAL/ A/C _____	Print Name _____ License #: _____	Signature _____ Phone #: _____
PLUMBING/ GAS	Print Name _____ License #: _____	Signature _____ Phone #: _____
ROOFING	Print Name _____ License #: _____	Signature _____ Phone #: _____
SHEET METAL	Print Name _____ License #: _____	Signature _____ Phone #: _____
FIRE SYSTEM/ SPRINKLER	Print Name _____ License #: _____	Signature _____ Phone #: _____
SOLAR	Print Name _____ License #: _____	Signature _____ Phone #: _____

Specialty License	License Number	Sub-Contractors Printed Name	Sub-Contractors Signature
MASON			
CONCRETE FINISHER			
FRAMING			
INSULATION			
STUCCO	1194	Ricky LAUER	Ricky Lauer
DRYWALL			
PLASTER			
CABINET INSTALLER			
PAINTING			
ACOUSTICAL CEILING			
GLASS			
CERAMIC TILE			
FLOOR COVERING			
ALUM/VINYL SIDING			
GARAGE DOOR			
METAL BLDG ERECTOR			

F. S. 440.103 Building permits; identification of minimum premium policy.--Every employer shall, as a condition to applying for and receiving a building permit, show proof and certify to the permit issuer that it has secured compensation for its employees under this chapter as provided in ss. 440.10 and 440.38, and shall be presented each time the employer applies for a building permit.

SUBCONTRACTOR VERIFICATION FORM

APPLICATION NUMBER _____

CONTRACTOR

Isaac Construction

PHONE _____

THIS FORM MUST BE SUBMITTED PRIOR TO THE ISSUANCE OF A PERMIT

In Columbia County one permit will cover all trades doing work at the permitted site. It is REQUIRED that we have records of the subcontractors who actually did the trade specific work under the permit. Per Florida Statute 440 and Ordinance 89-6, a contractor shall require all subcontractors to provide evidence of workers' compensation or exemption, general liability insurance and a valid Certificate of Competency license in Columbia County.

Any changes, the permitted contractor is responsible for the corrected form being submitted to this office prior to the start of that subcontractor beginning any work. Violations will result in stop work orders and/or fines.

ELECTRICAL ✓ 234 OK	Print Name <u>Conner Electric</u> License #: <u>ER13013192</u>	Signature <u>Michael S. Conner</u> Phone #: <u>386 265 9905</u>
MECHANICAL/A/C ✓ 563 OK	Print Name <u>David Hallis</u> License #: <u>CAC 57424</u>	Signature <u>[Signature]</u> Phone #: <u>386-755-9792</u>
PLUMBING/GAS ✓ 623 OK	Print Name <u>Express Plumbing</u> License #: <u>CFC142840</u>	Signature <u>Mark Ganskop</u> Phone #: <u>386-867-0269</u>
ROOFING ✓ 494 OK	Print Name <u>Precision Exteriors</u> License #: <u>CCC132711</u>	Signature <u>[Signature]</u> Phone #: <u>386-752-4022</u>
SHEET METAL	Print Name _____ License #: _____	Signature _____ Phone #: _____
FIRE SYSTEM/SPRINKLER	Print Name _____ License #: _____	Signature _____ Phone #: _____
SOLAR	Print Name _____ License #: _____	Signature _____ Phone #: _____

Specialty License	License Number	Sub-Contractors Printed Name	Sub-Contractors Signature
MASON ✓ OK	000720	Donald Roberts	[Signature]
CONCRETE FINISHER ✓ OK	000048	Hofstrom Builders	[Signature]
FRAMING ✓ OK	CBC059323	Isaac Construction	[Signature]
INSULATION 421 OK	CBC059323	Isaac Construction	[Signature]
STUCCO ✓ OK	000256	Gon Dowd	[Signature]
DRYWALL ✓ OK	000345	Heitzman Drywall	[Signature]
PLASTER			
CABINET INSTALLER ✓ OK	CBC059323	Isaac Construction	[Signature]
PAINTING ✓ OK	000219	Hart's Painting	[Signature]
ACOUSTICAL CEILING			
GLASS ✓ OK	000618	Lake City Glass	[Signature]
CERAMIC TILE ✓ OK	000071	JS Tile	[Signature]
FLOOR COVERING			
ALUM/VINYL SIDING			
GARAGE DOOR ✓ OK	000619	Lake City Glass	[Signature]
METAL BLDG ERECTOR			

F. S. 440.103 Building permits; identification of minimum premium policy.--Every employer shall, as a condition to applying for and receiving a building permit, show proof and certify to the permit issuer that it has secured compensation for its employees under this chapter as provided in ss. 440.10 and 440.38, and shall be presented each time the employer applies for a building permit.

Laurie Hodson

From: Troy Crews
Sent: Wednesday, November 09, 2011 10:02 AM
To: asinisi@msn.com
Cc: Randy Jones; Laurie Hodson
Subject: permit # 28856 1500 S.W. Legion Dr.

Mr. Sinisi per our phone conversation this am I am sending you this e mail to inform you the status of inspections on you're hs.. A framing inspection was Scheduled and performed on 5-12-11, the framing of the house was disapproved the contractor was informed that due to the multiple violations with the framing that he needed to contact the engineer of record for a plan to make repairs to meet code. If you have any questions feel free to call me.



M. Troy Crews
Building Official II
Columbia County
Fax 386-758-2160
Phone 386-758-1040
troy_crews@columbiacountyfla.com

**Columbia County Building Department
Culvert Permit**

**Culvert Permit No.
000001848**

DATE 09/14/2010 PARCEL ID # 20-4S-16-03051-206
APPLICANT BARBARA WEBSTER PHONE 386.719.7143
ADDRESS 125 SW MIDTOWN PL.,STE 101 LAKE CITY FL 32025
OWNER ANTHONY & MAGDA SINISI PHONE _____
ADDRESS 1500 SW LEGION DRIVE LAKE CITY FL 32024
CONTRACTOR ISAAC BRATKOVICH PHONE 386.719.7143
LOCATION OF PROPERTY 90-W TO SR. 247-S TO TAMARACK LN,TR TO LEGION DR.,TL 2ND TO
LAST LOT ON L TOWARDS END OF CUL-DE-SAC.

SUBDIVISION/LOT/BLOCK/PHASE/UNIT LEGION PLACE 6

SIGNATURE Barbara Webster

INSTALLATION REQUIREMENTS



Culvert size will be 18 inches in diameter with a total length of 32 feet, leaving 24 feet of driving surface. Both ends will be mitered 4 foot with a 4 : 1 slope and poured with a 4 inch thick reinforced concrete slab.

INSTALLATION NOTE: Turnouts will be required as follows:

- a) a majority of the current and existing driveway turnouts are paved, or;
- b) the driveway to be served will be paved or formed with concrete.

Turnouts shall be concrete or paved a minimum of 12 feet wide or the width of the concrete or paved driveway, whichever is greater. The width shall conform to the current and existing paved or concreted turnouts.



Culvert installation shall conform to the approved site plan standards.



Department of Transportation Permit installation approved standards.



Other _____

**ALL PROPER SAFETY REQUIREMENTS SHOULD BE FOLLOWED
DURING THE INSTALATION OF THE CULVERT.**

135 NE Hernando Ave., Suite B-21
Lake City, FL 32055
Phone: 386-758-1008 Fax: 386-758-2160

Amount Paid 25.00



ITW Building Components Group, Inc.

1950 Marley Drive Haines City, FL 33844
Florida Engineering Certificate of Authorization Number: 0 278
Florida Certificate of Product Approval # FL1999
Page 1 of 1 Document ID:1TSF8228Z0111134328

Truss Fabricator: Anderson Truss Company
Job Identification: 9-121--Isaac Construction Sinisi -- , **
Truss Count: 55
Model Code: Florida Building Code 2007 and 2009 Supplement
Truss Criteria: FBC2007Res/TPI-2002(STD)
Engineering Software: Alpine Software, Version 8.07.
Structural Engineer of Record: The identity of the structural EOR did not exist as of
Address: the seal date per section 61615-31.003(5a) of the FAC
Minimum Design Loads: Roof - 40.0 PSF @ 1.25 Duration
Floor - N/A
Wind - 110 MPH ASCE 7-05 -Closed



Seal Date: 06/11/2009

Notes:

1. Determination as to the suitability of these truss components for the structure is the responsibility of the building designer/engineer of record, as defined in ANSI/TPI 1
2. The drawing date shown on this index sheet must match the date shown on the individual truss component drawing.
3. As shown on attached drawings; the drawing number is preceded by: HCUSR8228

-Truss Design Engineer-
Doug Fleming


Florida License Number: 66648
1950 Marley Drive
Haines City, FL 33844

Details: A1101505-GBLLETIN-

#	Ref	Description	Drawing#	Date
1	35510--	H7A	09162077	06/11/09
2	35511--	H9A	09162039	06/11/09
3	35512--	H11A	09162040	06/11/09
4	35513--	H13A	09162041	06/11/09
5	35514--	H15A	09162001	06/11/09
6	35515--	H17A	09162002	06/11/09
7	35516--	H7AA	09162042	06/11/09
8	35517--	H9AA	09162043	06/11/09
9	35518--	H11AA	09162044	06/11/09
10	35519--	H13AA	09162045	06/11/09
11	35520--	H15AA	09162046	06/11/09
12	35521--	H17AA	09162047	06/11/09
13	35522--	H19AA	09162048	06/11/09
14	35523--	H21AA	09162049	06/11/09
15	35524--	H23AA	09162050	06/11/09
16	35525--	H25AA	09162051	06/11/09
17	35526--	A1	09162052	06/11/09
18	35527--	A2	09162053	06/11/09
19	35528--	A3	09162054	06/11/09
20	35529--	H27A	09162055	06/11/09
21	35530--	H21A	09162056	06/11/09
22	35531--	H23A	09162003	06/11/09
23	35532--	H25A	09162004	06/11/09
24	35533--	H19A	09162057	06/11/09
25	35534--	H7B	09162058	06/11/09
26	35535--	H7BB	09162059	06/11/09
27	35536--	H9B	09162005	06/11/09
28	35537--	H9BB	09162006	06/11/09
29	35538--	B3	09162007	06/11/09
30	35539--	B2	09162008	06/11/09
31	35540--	B1	09162009	06/11/09
32	35541--	H4C	09162060	06/11/09
33	35542--	D-GE	09162061	06/11/09
34	35543--	E1	09162010	06/11/09
35	35544--	E-GE	09162062	06/11/09
36	35545--	E2	09162011	06/11/09

#	Ref	Description	Drawing#	Date
37	35546--	E3-GDR	09162063	06/11/09
38	35547--	J1	09162064	06/11/09
39	35548--	HJ7	09162065	06/11/09
40	35549--	HJ4	09162066	06/11/09
41	35550--	J3	09162012	06/11/09
42	35551--	EJ4	09162067	06/11/09
43	35552--	J5	09162013	06/11/09
44	35553--	HJ3	09162068	06/11/09
45	35554--	EJ7	09162014	06/11/09
46	35555--	EJ7A	09162069	06/11/09
47	35556--	EJ7B	09162070	06/11/09
48	35557--	EJ9	09162071	06/11/09
49	35558--	EJ9A	09162072	06/11/09
50	35559--	EJ9B	09162073	06/11/09
51	35560--	EJ9E	09162015	06/11/09
52	35561--	EJ9F	09162074	06/11/09
53	35562--	EJ9G	09162016	06/11/09
54	35563--	EJ9D	09162075	06/11/09
55	35564--	EJ9C	09162076	06/11/09





Top chord 2x6 SP #2 :T1 2x4 SP #2 Dense:
Bot chord 2x6 SP #2 :B2, B3 2x6 SP #1 Dense:
Webs 2x4 SP #3 :W4, W14 2x4 SP #2 Dense:

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $G_{CPI}(+/-)=0.18$

Wind reactions based on MWFRS pressures.

Roof overhang supports 2.00 psf soffit load.

Deflection meets L/240 live and L/180 total load.

SPECIAL LOADS

----- (LUMBER DUR.FAC.=1.25 / PLATE DUR.FAC.=1.25)
TC - From 64 PLF at -1.50 to 64 PLF at 0.00
TC - From 60 PLF at 0.00 to 60 PLF at 2.20
TC - From 126 PLF at 2.20 to 126 PLF at 44.67
BC - From 20 PLF at 0.00 to 20 PLF at 2.20
BC - From 44 PLF at 2.20 to 44 PLF at 44.67
BC - 353 LB Conc. Load at 2.20

2 COMPLETE TRUSSES REQUIRED


Nailing Schedule: (0.131"x3" Gun_nails)

Top Chord: 1 Row @12.00" o.c.
Bot Chord: 1 Row @12.00" o.c.
Webs : 1 Row @ 4" o.c.
Use equal spacing between rows and stagger nails in each row to avoid splitting.

End verticals not exposed to wind pressure.

In lieu of structural panels use purlins to brace all flat TC @ 24" o.c.

Calculated vertical deflection is 0.62" due to live load and 0.63" due to dead load at $X = 23-5-3$.



PLT TYP. 20 Gauge HS.Wave

Design Crit: FBC2007Res/TPI-2002(STD)

FT/RT=10%(0%)/0(0)

8.07.00



QTY:1

FL/-/4/-/R/-

Scale = .125"/ft.

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO RESC (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6300 WOODBRIDGE AVENUE, SUITE 100, FARMINGTON, CT, 06031) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, ALL DIMENSIONS SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE RESC, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH THE DESIGN, OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES, SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AIA/AIA) AND TPI. THE RESC CONNECTOR PLATES ARE MADE OF 2018/1664 (H/H/SS/2) ASTM A653 GRADE 40/60 (H, K/H/SS) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A-2. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TPI-2002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.




TC LL	20.0 PSF	REF R8228- 35510
TC DL	10.0 PSF	DATE 06/11/09
BC DL	10.0 PSF	DRW HCUR8228 09162077
BC LL	0.0 PSF	HC-ENG DF/DF
TOT.LD.	40.0 PSF	SEON- 28397
DUR.FAC.	1.25	FROM AH
SPACING	SEE ABOVE	DIFF- 1TCE8228701

Deflection meets L/240 live and L/180 total load.

Bottom chord checked for 10.00 psf non-concurrent live load.



AS SHOWN, THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/IFP 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228- 35511
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162039
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28407
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF -	1TSF8228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3 :M14 2x4 SP #2 Dense:

Roof overhang supports 2.00 psf soffit load.

Calculated horizontal deflection is 0.18" due to live load and 0.18" due to dead load.

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

Deflection meets L/240 live and L/180 total load.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCPI (+/-)=0.18


Wind reactions based on MWFRS pressures.

Right end vertical not exposed to wind pressure.


(A) 1x4 #3SRB SP-F-S or better "T" brace, 80% length of web member. Attach with 8d Box or Gun (0.113"x2.5".min.) nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

Calculated vertical deflection is 0.55" due to live load and 0.57" due to dead load at X = 22-2-11.



Note: All Plates Are 3X4 Except As Shown.
PLT TYP. 20 Gauge HS, 18 Gauge HS, Design Crit: F8C2007Res/TPI-2002(STD)
Wave FT/RT=10%(0%)/0(0%) 8.07.00



TC LL	20.0 PSF	REF	R8228- 35513
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCSR8228 09162041
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT. LD.	40.0 PSF	SEQN-	28428
DUR. FAC.	1.25	FROM	AH
SPACING	24 0"	DATE	11/28/09

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, closed bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcpl (+/-)=0.18

Wind reactions based on MFRS pressures.


Right end vertical not exposed to wind pressure.

(A) 1x4 #33KB SPF-S or better "T" brace. 80% length of web member. Attach with 8d Box or Gun (0.113"x2.5",min.)nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.



Scale = .125"/ft.



110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, Iw=1.00 Gcpl (+/-)=0.18

Wind reactions based on MMFRS pressures.

Bottom chord checked for 10.00 psf non-concurrent live load.

Deflection meets L/240 live and L/180 total load.



Scale = .125"/Ft.

DOUGLAS FLEMING
LICENSE
No. 66648

TC LL	20.0 PSF	REF	R8228 - 35515
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DBM	WCHSP8228 09162002

BC LL	0.0 PSF	HC-ENG DF/DF
TOT.LD.	40.0 PSF	SEON- 28445
DUR.FAC.	1.25	FROM AH
SPACING	24 0"	JPEF- 1TSE8228701

Top chord 2x6 SP #2 :T1, T5 2x4 SP #2 Dense:
Bot chord 2x6 SP #2
Webs 2x4 SP #3 :W5, W14, W15 2x4 SP #2 Dense:

Trusses or components connecting to this girder have been modified by the truss designer. The loading for this girder requires verification for accuracy.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART-ENC. bldg. located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCpl(+/-)=0.55

Roof overhang supports 2.00 psf soffit load.

Girder supports 9-0-0 span to TC/BC split one face and 2-0-0 span to TC/BC split opposite face.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.

2 COMPLETE TRUSSES REQUIRED

Nailing Schedule: (0.131"x3" Gun_nails)

Top Chord: 1 Row @12.00" o.c.
Bot Chord: 1 Row @12.00" o.c.
Webs : 1 Row @ 4" o.c.
Use equal spacing between rows and stagger nails in each row to avoid splitting.


Wind reactions based on MMFRS pressures.

Right end vertical not exposed to wind pressure.

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

Deflection meets L/240 live and L/180 total load.

(2)



PLT TYP. 20 Gauge HS,Wave


Design Cnt: FBC2007Res/TP1-2002(STD)

8.07.00

QTY:1

FL/-/4/-/-/R/-

Scale = .125"/ft.



ALPINE Building Components Group, Inc.
Haines City, FL 33844



TC LL	20.0 PSF	REF R8228 - 35516
TC DL	10.0 PSF	DATE 06/11/09
BC DL	10.0 PSF	DRW HCU8R8228 09162042
BC LL	0.0 PSF	HC-ENG DF/DF
TOT. LD.	40.0 PSF	SEQN- 28633
DUR. FAC.	1.25	FROM AH
SPACING	SFF ABOVE	JRRF - TTSF8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART. ENC. bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI (+/-)=0.55

Wind reactions based on MWFRS pressures.

Right end vertical not exposed to wind pressure.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



Scale = .125"/ft.

DOUGLAS FLEMING
LICENSE
No. 66648

TC LL	20.0 PSF	REF	R8228 - 3551/
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162043

A circular professional engineer seal for Douglas Fleming, No. 66648, State of Florida. The seal features the text "DOUGLAS FLEMING" at the top, "LICENSE" on the right, "No. 66648" in the center, "STATE OF" below the number, "FLORIDA" on the left, and "PROFESSIONAL ENGINEER" at the bottom. A signature is written over the center text. The seal is stamped on a document with a grid background.

DATE	09/22/05
BC DL	10.0 PSF
BC DL	10.0 PSF
BC LL	0.0 PSF
TOT.LD.	40.0 PSF
DUR.FAC.	1.25
SPACING	24.0"
DRW	HCSUR8228 09162043
HC-ENG	DF/DF
SEQN-	28652
FROM	AH
JREF-	1TSF8228Z01

110 mph wind; 15.00 ft mean hgt, ASCE 7-05, PART, ENC. bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI (+/-)=0.55

Wind reactions based on MFRS pressures.

Right end vertical not exposed to wind pressure.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.

Design Crit: FBC2007Res/TP1-2002(STD,
FT/RT=10%(0%)/0(0))

QTY:1

FL/-/4/-/-/R/-

Scale = .125"/ft.

[illegible]

7.00
QT
DOUGLAS FLEMING
LICENSE
No. 86648

TC LL	20.0 PSF	REF R8228- 35518
TC DL	10.0 PSF	DATE 06/11/09
BC DL	10.0 PSF	DRW HCHSR8228 09162044



ALPINE

ITW Building Components Group Inc.
Haines City, FL 33844

[illegible]

A circular professional engineer seal for Douglas Fleming, No. 86648, State of Florida. The seal features the text "DOUGLAS FLEMING" at the top, "LICENSE" on the right, "No. 86648" in the center, "STATE OF FLORIDA" at the bottom, and "PROFESSIONAL ENGINEER" on the left. There are stars at the top and bottom of the seal.

BC LL	0.0 PSF	HC-ENG DF/DF
TOT.LD.	40.0 PSF	SEQN- 28675
DUR.FAC.	1.25	FROM AH
SPACING	24.0"	JREF- 1TSF828201


110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART. ENC. bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCPI (+/-)=0.55

Wind reactions based on MMFRS pressures.

(A) 2x6 #3 or better "T" brace, 80% length of web member. Attach with 16d Box or Gun (0.135"x3.5", min.) nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.
Deflection meets L/240 live and L/180 total load.

Deflection meets $L/240$ live and $L/180$ total load.



Design Crit: FBC2007Res/TPI-2002(STD,
FT/RT=10%(0%)/0(0))

QTY:1

FL/-/4/-/-/R/-


Scale = .125" / Ft.

WARNING: THESE PRODUCTS REQUIRE CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO NCSP (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY FBI (FIBERGLASS PANEL INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND NFCA (WOOD TRUSS COUNCIL OF AMERICA, 6500 ENTERPRISE LANE, MADISON, WI, 53719) FOR SAFETY PRACTICES, TIPS TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED FOR CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE BCG, INC., SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TROSS IN CONFORMANCE WITH THE FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TROSSES.

ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF IPT-1-2002 SEC.3.
DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENTS.

DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/PP1 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228- 35519
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162045
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28672
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228Z01

110 mph wind; 15.00 ft mean hgt, ASCE 7-05, PART_ENC. bldg, not located within 6.50 ft from roof edge, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCPI(+/-)=0.55


Wind reactions based on MFRS pressures.

In lieu of structural panels use purlins to brace all flat TC @ 24 OC.

Deflection meets $L/240$ live and $L/180$ total load.



Scale = .125" / ft.



110 mph wind; 15.00 ft mean hgt, ASCE / -0.5, PAR1, ENC. bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI (+/-)=0.55

Wind reactions based on MWRS pressures.

Right end vertical not exposed to wind pressure.

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



8.07.00

QTY: 1

FL/-/4/-/-/R/-

Scale = .125"/ft.

7.00
DOUGLAS FLEMING
LICENSE
No. 66648
QTY

TC LL	20.0 PSF	REF	R8228 - 35521
TC DL	10.0 PSF	DATE	06/11/09
RC DL	10.0 PSF	DRW	HCUSSA8228 09162047

A circular professional engineer seal for Douglas S. Fleming, No. 66648, State of Florida. The seal features the text "DOUGLAS FLEMING" at the top, "LICENSE" on the right, "No. 66648" in the center, "STATE OF FLORIDA" on the left, and "PROFESSIONAL ENGINEER" at the bottom. A signature is written over the center text.

TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162047
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28690
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228201

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Roof overhang supports 2.00 psf soffit load.

(A) 1x4 #3SR8 SPF-S or better "T" brace. 80% length of web member.
Attach with 8d Box or Gun (0.113"x2.5",min.)nails @ 6" OC.

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

Deflection meets L/240 live and L/180 total load.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART. ENC. bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcpl(+/-)=0.55


Wind reactions based on MWFRS pressures.

Right end vertical not exposed to wind pressure.

(B) 2x4 #3 or better "T" brace. 80% length of web member. Attach with 16d Box or Gun (0.135"x3.5",min.)nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002 (STD)


FT/RT=10%(0%)/0(0)

8.07.00

QTY: 1

FL/-/4/-/-/R/-

Scale = .125"/Ft.



****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCSS (BOUTLIDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE), 210 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22304 AND TCA (TRUSS CONSTRUCTION AND BRACING) 500 ENTERPRISE LANE, HANNOVER, NH 03033. DO NOT EXCEED THE MAXIMUM ALLOWED DEFLECTIONS, UNLESS OTHERWISE INDICATED. WHEN SHOWN, TRUSSES MUST BE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH THE TPI: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

CONNECTION PLATES ARE MADE OF 20/18/16GA (40/35/30) ASTM A653 GRADE 40/60 (40, K/H, SS) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A-Z. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TPI-2002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228- 35522
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162048
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28702
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228201

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART, ENC. bldg, not located within 6.50 ft from roof edge, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI (+/-)=0.55

Wind reactions based on MWFRS pressures.

Right end vertical not exposed to wind pressure.

(A) 2x6 #3 or better "T" brace. 80% length of web member. Attach with 16d Box or Gun (0.135"x3.5".min.) nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



QTY:1 FL/-/4/-/-/R/-

Scale = .125" / Ft.

No. 66648

TC DL	10.0 PSF	DATE	06/11/09
RC DL	10.0 PSF	DRW	HCUSR328 09162

TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 091622
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28710
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	IRREF-	1TSE822820

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART. ENC. bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCpi (+/-)=0.55


Wind reactions based on MWFRS pressures.

Right end vertical not exposed to wind pressure.

(A) 2x6 #3 or better "T" brace. 80% length of web member. Attach with 16d Box or Gun (0.135"x3.5".min.)nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



Scale = .125"/Ft.

7.00
DOUGLAS FLEMING
LICENSE
No. 66648
CITY

ITW Building Components Group Inc.
Haines City, FL 33844

TC LL	20.0 PSF	REF	R8228- 35524
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCSUR8228 09162050
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28716
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART. ENC. bldg, not located within 6.50 ft from roof edge, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI (+/-)=0.55


Wind reactions based on MMFRS pressures.

Right end vertical not exposed to wind pressure.

(A) 2x4 #3 or better "T" brace, 80% length of web member. Attach with 16d Box or Gun (0.135"x3.5".min.) nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



110 mph wind, 15.05 ft mean hgt, ASCE 7-05, PART. ENC. bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI (+/-)=0.55

Wind reactions based on MWFRS pressures.


Right end vertical not exposed to wind pressure.

(B) 2x4 #3 or better "T" brace. 80% length of web member. Attach with 16d Box or Gun (0.135"x3.5", min.) nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.




R=1644 U=159 W=6

Design Crit: FBC2007Res/TPI-2002(STD)

Scale = .125"/Ft.

DOUGLAS FLEMING
LICENSE
No. 66648



ALPINE

ITW Building Components Group Inc

Haines City, FL 33844

[illegible]

60. 11.09

TC LL	20.0 PSF	REF	R8228- 35526
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCSR8228 09162052
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28739
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSR8228Z01

JREF - 1TSF822870

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Roof overhang supports 2.00 psf soffit load.

(A) 1x4 #3SRB SPF-S or better "T" brace. 80% length of web member.
Attach with 8d Box or Gun (0.113"x2.5",min.)nails @ 6" OC.

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

Deflection meets L/240 live and L/180 total load.

110 mph wind, 15.05 ft mean hgt, ASCE 7-05, PART. ENC. bldg, not located within 6.50 ft from roof edge, CAT II, Exp B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. 1w=1.00 GCPI(+/-)-0.55


Wind reactions based on MMFRS pressures.

Right end vertical not exposed to wind pressure.

(B) 2x4 #3 or better "T" brace. 80% length of web member. Attach with 16d Box or Gun (0.135"x3.5",min.)nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



R=289 U=32 W=3.496"
R=208/-194 R=2075 U=265 W=6"

R=1655 U=156 W=6"

Note: All Plates Are 3x4 Except As Shown.

Design Crit: FBC2007Res/TP1-2002(STD)

PLT TYP. Wave

8.07.00

QTY:1

FL/-/4/-/-/R/-

Scale = .125"/Ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING & BRACING. REFER TO DETAIL (INCLUDING COMPONENTS) AND ALL APPLICABLE PROVISIONS OF AISC 360, 360M, 360S, 360T, 360U, 360V, 360W, 360X, 360Y, 360Z, 360AA, 360AB, 360AC, 360AD, 360AE, 360AF, 360AG, 360AH, 360AI, 360AJ, 360AK, 360AL, 360AM, 360AN, 360AO, 360AP, 360AQ, 360AR, 360AS, 360AT, 360AU, 360AV, 360AW, 360AX, 360AY, 360AZ, 360BA, 360BB, 360BC, 360BD, 360BE, 360BF, 360BG, 360BH, 360BI, 360BJ, 360BK, 360BL, 360BM, 360BN, 360BO, 360BP, 360BQ, 360BR, 360BS, 360BT, 360BU, 360BV, 360BW, 360BX, 360BY, 360BZ, 360CA, 360CB, 360CC, 360CD, 360CE, 360CF, 360CG, 360CH, 360CI, 360CJ, 360CK, 360CL, 360CM, 360CN, 360CO, 360CP, 360CQ, 360CR, 360CS, 360CT, 360CU, 360CV, 360CW, 360CX, 360CY, 360CZ, 360DA, 360DB, 360DC, 360DD, 360DE, 360DF, 360DG, 360DH, 360DI, 360DJ, 360DK, 360DL, 360DM, 360DN, 360DO, 360DP, 360DQ, 360DR, 360DS, 360DT, 360DU, 360DV, 360DW, 360DX, 360DY, 360DZ, 360EA, 360EB, 360EC, 360ED, 360EE, 360EF, 360EG, 360EH, 360EI, 360EJ, 360EK, 360EL, 360EM, 360EN, 360EO, 360EP, 360EQ, 360ER, 360ES, 360ET, 360EU, 360EV, 360EW, 360EX, 360EY, 360EZ, 360FA, 360FB, 360FC, 360FD, 360FE, 360FF, 360FG, 360FH, 360FI, 360FJ, 360FK, 360FL, 360FM, 360FN, 360FO, 360FP, 360FQ, 360FR, 360FS, 360FT, 360FU, 360FV, 360FW, 360FX, 360FY, 360FZ, 360GA, 360GB, 360GC, 360GD, 360GE, 360GF, 360GG, 360GH, 360GI, 360GJ, 360GK, 360GL, 360GM, 360GN, 360GO, 360GP, 360GQ, 360GR, 360GS, 360GT, 360GU, 360GV, 360GW, 360GX, 360GY, 360GZ, 360HA, 360HB, 360HC, 360HD, 360HE, 360HF, 360HG, 360HH, 360HI, 360HJ, 360HK, 360HL, 360HM, 360HN, 360HO, 360HP, 360HQ, 360HR, 360HS, 360HT, 360HU, 360HV, 360HW, 360HX, 360HY, 360HZ, 360IA, 360IB, 360IC, 360ID, 360IE, 360IF, 360IG, 360IH, 360II, 360IJ, 360IK, 360IL, 360IM, 360IN, 360IO, 360IP, 360IQ, 360IR, 360IS, 360IT, 360IU, 360IV, 360IW, 360IX, 360IY, 360IZ, 360JA, 360JB, 360JC, 360JD, 360JE, 360JF, 360JG, 360JH, 360JI, 360JJ, 360JK, 360JL, 360JM, 360JN, 360JO, 360JP, 360JQ, 360JR, 360JS, 360JT, 360JU, 360JV, 360JW, 360JX, 360JY, 360JZ, 360KA, 360KB, 360KC, 360KD, 360KE, 360KF, 360KG, 360KH, 360KI, 360KJ, 360KK, 360KL, 360KM, 360KN, 360KO, 360KP, 360KQ, 360KR, 360KS, 360KT, 360KU, 360KV, 360KW, 360KX, 360KY, 360KZ, 360LA, 360LB, 360LC, 360LD, 360LE, 360LF, 360LG, 360LH, 360LI, 360LJ, 360LK, 360LL, 360LM, 360LN, 360LO, 360LP, 360LQ, 360LR, 360LS, 360LT, 360LU, 360LV, 360LW, 360LX, 360LY, 360LZ, 360MA, 360MB, 360MC, 360MD, 360ME, 360MF, 360MG, 360MH, 360MI, 360MJ, 360MK, 360ML, 360MN, 360MO, 360MP, 360MQ, 360MR, 360MS, 360MT, 360MU, 360MV, 360MW, 360MX, 360MY, 360MZ, 360NA, 360NB, 360NC, 360ND, 360NE, 360NF, 360NG, 360NH, 360NI, 360NJ, 360NK, 360NL, 360NM, 360NN, 360NO, 360NP, 360NQ, 360NR, 360NS, 360NT, 360NU, 360NV, 360NW, 360NX, 360NY, 360NZ, 360OA, 360OB, 360OC, 360OD, 360OE, 360OF, 360OG, 360OH, 360OI, 360OJ, 360OK, 360OL, 360OM, 360ON, 360OO, 360OP, 360OQ, 360OR, 360OS, 360OT, 360OU, 360OV, 360OW, 360OX, 360OY, 360OZ, 360PA, 360PB, 360PC, 360PD, 360PE, 360PF, 360PG, 360PH, 360PI, 360PJ, 360PK, 360PL, 360PM, 360PN, 360PO, 360PP, 360PQ, 360PR, 360PS, 360PT, 360PU, 360PV, 360PW, 360PX, 360PY, 360PZ, 360QA, 360QB, 360QC, 360QD, 360QE, 360QF, 360QG, 360QH, 360QI, 360QJ, 360QK, 360QL, 360QM, 360QN, 360QO, 360QP, 360QQ, 360QR, 360QS, 360QT, 360QU, 360QV, 360QW, 360QX, 360QY, 360QZ, 360RA, 360RB, 360RC, 360RD, 360RE, 360RF, 360RG, 360RH, 360RI, 360RJ, 360RK, 360RL, 360RM, 360RN, 360RO, 360RP, 360RQ, 360RR, 360RS, 360RT, 360RU, 360RV, 360RW, 360RX, 360RY, 360RZ, 360SA, 360SB, 360SC, 360SD, 360SE, 360SF, 360SG, 360SH, 360SI, 360SJ, 360SK, 360SL, 360SM, 360SN, 360SO, 360SP, 360SQ, 360SR, 360SS, 360ST, 360SU, 360SV, 360SW, 360SX, 360SY, 360SZ, 360TA, 360TB, 360TC, 360TD, 360TE, 360TF, 360TG, 360TH, 360TI, 360TJ, 360TK, 360TL, 360TM, 360TN, 360TO, 360TP, 360TQ, 360TR, 360TS, 360TT, 360TU, 360TV, 360TW, 360TX, 360TY, 360TZ, 360UA, 360UB, 360UC, 360UD, 360UE, 360UF, 360UG, 360UH, 360UI, 360UJ, 360UK, 360UL, 360UM, 360UN, 360UO, 360UP, 360UQ, 360UR, 360US, 360UT, 360UU, 360UV, 360UW, 360UX, 360UY, 360UZ, 360VA, 360VB, 360VC, 360VD, 360VE, 360VF, 360VG, 360VH, 360VI, 360VJ, 360VK, 360VL, 360VM, 360VN, 360VO, 360VP, 360VQ, 360VR, 360VS, 360VT, 360VU, 360VV, 360VW, 360VX, 360VY, 360VZ, 360WA, 360WB, 360WC, 360WD, 360WE, 360WF, 360WG, 360WH, 360WI, 360WJ, 360WK, 360WL, 360WM, 360WN, 360WO, 360WP, 360WQ, 360WR, 360WS, 360WT, 360WU, 360WV, 360WW, 360WX, 360WY, 360WZ, 360XA, 360XB, 360XC, 360XD, 360XE, 360XF, 360XG, 360XH, 360XI, 360XJ, 360XK, 360XL, 360XM, 360XN, 360XO, 360XP, 360XQ, 360XR, 360XS, 360XT, 360XU, 360XV, 360XW, 360XX, 360XY, 360XZ, 360YA, 360YB, 360YC, 360YD, 360YE, 360YF, 360YG, 360YH, 360YI, 360YJ, 360YK, 360YL, 360YM, 360YN, 360YO, 360YP, 360YQ, 360YR, 360YS, 360YT, 360YU, 360YV, 360YW, 360YX, 360YY, 360YZ, 360ZA, 360ZB, 360ZC, 360ZD, 360ZE, 360ZF, 360ZG, 360ZH, 360ZI, 360ZJ, 360ZK, 360ZL, 360ZM, 360ZN, 360ZO, 360ZP, 360ZQ, 360ZR, 360ZS, 360ZT, 360ZU, 360ZV, 360ZW, 360ZX, 360ZY, 360ZZ.

ALPINE

ITW Building Components Group Inc.

Haines City, FL 33844



TC LL	20.0 PSF	REF	R8228- 35527
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162053
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT. LD.	40.0 PSF	SEQN-	28766
DUR. FAC.	1.25	FROM	AH
SPACING	24.0"	UREF-	1TSF8228Z01

110 mph wind, 15.05 ft mean hgt, ASCE 7-05, PART_ENC, bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCPI(+/-)=0.55

Wind reactions based on MWFRS pressures.


Right end vertical not exposed to wind pressure.

(B) 2x4 #3 or better "T" brace. 80% length of web member. Attach with 16d Box or Gun (0.135"x3.5", min.) nails @ 6" OC.

with 16d Box or Gun (0.135"x3.5", min.) nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



Design Crit: FBC2007Res/TPI-2002(STD)

$$FT/RT=10\%(0\%)/0(0)$$

8.07.00

QTY:1

FL/-/4/-/-/R/-

Scale = .125" / ft.

WARNING: TRUSS BRIDGE EXTREMELY DANGEROUS IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO DCSS (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY THE TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND NFCA (WOOD TRUSS COUNCIL OF AMERICA, 6500 CRIMMIE LANE, MAINTON, VA, 53719) FOR SAFETY PRACTICES WRITERS FOR DETERMINING THESE PROCEEDINGS. ONE-SIDEDLY INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED BRIDG CELLING.

ITW Building Components Group Inc

Haines City, FL 33844
FL COA #0070



11.09

SPACING 24.0"

JREF - 1TSF8228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Roof overhang supports 2.00 psf soffit load.

(A) 1x4 #3SRB SPF-S or better "T" brace. 80% length of web member.
Attach with 8d Box or Gun (0.113"x2.5",min.)nails @ 6" OC.

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

Deflection meets L/240 live and L/180 total load.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART-ENC. bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. 1w=1.00 GCPI(+/-)=0.55


Wind reactions based on MWFRS pressures.

Right end vertical not exposed to wind pressure.

(B) 2x4 #3 or better "T" brace. 80% length of web member. Attach with 16d Box or Gun (0.135"x3.5",min.)nails @ 6" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



PLT TYP. Wave

Design Crit: FBC2007Res/TP1-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00


QTY:1

FL/-/4/-/-/R/-

Scale = .125"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22304) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF 2010/10/1004 (U.S.S.A.) ASH A653 (2004) OR 40/60 (U.S.S.A.) G.A.V. (2004) PLATES TO EACH FACE OF TRUSS AND UNLESS OTHERWISE INDICATED, ALL TRUSSES SHALL BE MANUFACTURED TO THE DESIGN INDICATED. ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TP1 1 SEC. 2.




TC LL	20.0 PSF	REF	R8228- 35529
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162055
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28778
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228Z01


Deflection meets $L/240$ live and $L/180$ total load

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.




DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENTS



TC LL	20.0 PSF	REF	R8228- 35530
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162056
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28800
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	ITSF8228Z01

Deflection meets L/240 live and L/180 total load.



Deflection meets $L/240$ live and $L/180$ total load.

Bottom chord checked for 10.00 psf non-concurrent live load.

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



© 1996 by Blackwell Science Ltd, *Journal of Internal Medicine* 240: 395–401



TC LL	20.0 PSF	REF	R8228- 35533
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCSR8228 09162057
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEON-	28972
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Roof overhang supports 2.00 psf soffit load.


In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCFI (+/-)=0.18

Wind reactions based on MMFRS pressures.

#1 hip supports 7-0-0 jacks with no webs.

Deflection meets L/240 live and L/180 total load.



PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00

QTY: 1


FL/-/4/-/-/R/-

Scale = .3125"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCSEI (BUILDING COMPONENT SAFETY INFORMATION) PUBLISHED BY TPI (TRUSS PLATE INSTITUTE), 6200 ENTERPRISE LANE, MADISON, WI 53719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI, OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

DESIGN CONDITIONS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY AIAA) AND TPI. THE BCG CONNECTOR PLATES ARE MADE OF 20/18/16GA (20/H/18/16) ASH OR 20/18/16GA (20/H/18/16) GALV. STEEL. APPLY THE FOLLOWING DESIGN CONDITIONS: 1. ALL TRUSSES SHOWN ARE LOCATED ON THIS DESIGN. POSITION PER DRAWING 1600-2. ANY INSPECTION OF PLATES, JOINTS, AND BRACING SHALL BE DONE BY A QUALIFIED PERSON. 2. THE DESIGN CONDITIONS SHOWN, ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSSES SHOWN. 3. THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



TC LL	20.0 PSF	REF R8228- 35534
TC DL	10.0 PSF	DATE 06/11/09
BC DL	10.0 PSF	DRW HCUSR8228 09162058
BC LL	0.0 PSF	HC-ENG DF/DF
TOT.LD.	40.0 PSF	SEON- 28319
DUR.FAC.	1.25	FROM AH
SPACING	SFF ABOVE	JREF- 1TSF8228201

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, located anywhere in roof, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, $I_w=1.00$ GCp1 (+/-)=0.18

Wind reactions based on MMFRS pressures.

In lieu of structural panels use purtins to brace all flat TC @ 24" OC.

Left side jacks have 0-0-0 setback with 0-0-0 cant and 0-0-0 overhang. End jacks have 7-0-0 setback with 0-0-0 cant and 1-6-0 overhang. Right side jacks have 7-0-0 setback with 0-0-0 cant and 1-6-0 overhang.


$$FT/RT=10\%(0\%)/0(0)$$

QTY:1 FL/-/4/-/-/R/-/

Scale = .3125"/ft.

WARNING: THESE REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO DESIGNS (BUILDING COMPONENT SAFETY INFORMATION), WHICH LIE STRAIGHT, SUFFLE 312, ALEXANDRIA, VA, 22314) AND MFC (WOOD FORMS COUNCIL OF AMERICA, ENTERPRISE LANE, MALDEN, MA 02148) FOR SAFETY PRACTICES AND GUIDANCE TO IMPROVING THESE CONDITIONS. UNLESS OTHERWISE INDICATED, THE CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CELLING.

ITW Building Components Group Inc.

Haines City, FL 33844
FL COA #0078



TC LL	20.0 PSF	REF	R8228- 35535
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162059
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEON-	28340
DUR.FAC.	1.25	FROM	AH
SPACING	SEE ABOVE	UREF -	1TSF8228701

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

Roof overhang supports 2.00 psf soffit load.


In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. lw=1.00 GCpl(+/-)-0.18

Wind reactions based on MWFRS pressures.

Bottom chord checked for 10.00 psf non-concurrent live load.

Deflection meets L/240 live and L/180 total load.



PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0.(0)

8.07.00

QTY: 1

FL/-/4/-/-/R/-

Scale = .3125"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. NORTH LEE STREET, SUITE 112, ALEXANDRIA, VA 22304 AND WICKHAM TRUSS COMPANY, INC. 1000 ENTERPRISE LANE, MOORESVILLE, NC 28557 FOR SAFETY PRECAUTIONS PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE OF TRUSS OR BRACING OF TRUSSES.

DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC. BY NDS) AND TPI.

ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PERFORMED AS OF TPI 2002, SEC. 3. A SEAL ON THIS

DESIGN SHALL BE AFFIXED TO THE BOTTOM CHORD OF THE TRUSS. THE SEAL SHALL BE THE PROPERTY OF THE

BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.

ALPINE

ITW Building Components Group Inc.


Haines City, FL 33844
FL COA #0778



TC LL	20.0 PSF	REF R8228- 35536
TC DL	10.0 PSF	DATE 06/11/09
BC DL	10.0 PSF	DRW HCUR8228 09162005
BC LL	0.0 PSF	HC-ENG DF/DF
TOT. LD.	40.0 PSF	SEON- 28323
DUR. FAC.	1.25	FROM AH
SPACING	24.0"	JREF- 1TSF8228Z01

Bottom chord checked for 10.00 psf non-concurrent live load.

Deflection meets $L/240$ live and $L/180$ total load.



Haines City, FL 33844
FL COA #0078




TC LL	20.0 PSF	REF	R8228- 35537
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162006
BC LL	0.0 PSF	HC-ENG DF/DF	*
TOT.LD.	40.0 PSF	SEQN-	28344
DUR.FAC.	1.25	FROM AH	
SPACING	24.0"	JREF-	1TSF8228201

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL-5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI (+/-)=0.18

Wind reactions based on MMFRS pressures.

In lieu of structural panels use purlins to brace all flat TC @ 24"

Deflection meets L/240 live and L/180 total load.



DOUGLAS FLEMING
LICENSE
No. 66648

ITW Building Components Group Inc.

Haines City, FL 33844

FLC05A #00778

11.09

SPACING 24.0"

JREF - 1TSF8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcpl (+/-)=0.18

Wind reactions based on MFRS pressures.

Bottom chord checked for 10.00 psf non-concurrent live load.

Deflection meets L/240 live and L/180 total load.


$$FT/RT=10\%(0\%)/0(0)$$

8.07.00

QTY:1

FL/-/4/-/-/R/-/-

Scale = .3125"/Ft.

DOUGLAS
LICENSE
No. 66648

****IMPORTANT***FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT

ALPINE

ITW Building Components Group Inc.

Haines City, FL 33844

FLCQ 40-278



11, 09

TC LL	20.0 PSF	REF	R8228 - 35539
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162008
BC LL	0.0 PSF	HC-ENG	DF/DF *
TOT. LD.	40.0 PSF	SEQN-	28353
DUR. FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228Z01

REF - 1TSF8228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3


Roof overhang supports 2.00 psf soffit load.

Bottom chord checked for 10.00 psf non-concurrent live load.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, lw=1.00 gcpl(+/-)=0.18

Wind reactions based on MMFRS pressures.

Deflection meets L/240 live and L/180 total load.



PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00

QTY:1


FL/-/4/-/-/R/-

Scale = .3125"/ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BC31 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6500 REVERE DRIVE, SUITE 200, FARMERS BRANCH, TX 75442) FOR SAFETY PRECAUTIONS. THE TRUSS MANUFACTURER SHALL BE RESPONSIBLE FOR THE PROPER ATTACHMENT OF THE TRUSS TO THE STRUCTURE. THE TRUSS MANUFACTURER SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED BRIDG CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TPI: OR FABRICATING, HANDLING, SHIPPING, INSTALLING, BRACING OR TRUSSES.

DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF AIA 605.0 GRADE 40/60 (4, K/H, SS) GAV, STEEL, APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 1604-Z. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TPI-2002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOCIETY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228- 35540
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162009
BC LL	0.0 PSF	HC-ENG DF/DF	*
TOT. LD.	40.0 PSF	SEQN-	28357
DUR. FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228Z01

(9-121--Isaac Construction Sinist -- ** - HAC)

Top chord 2x4 SP #2 Dense :T2, T3 2x6 SP #1 Dense:
Bot chord 2x6 SP #1 Dense
Webs 2x4 SP #3 :W2, W8 2x4 SP #2 Dense:

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.



Left side jacks have 4-0-0 setback with 0-0-0 cant and 1-6-0 overhang. End jacks have 4-0-0 setback with 0-0-0 cant and 1-6-0 overhang. Right side jacks have 4-0-0 setback with 0-0-0 cant and 1-6-0 overhang.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART. ENC. bldg. located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $G_{CPI}(+/-)=0.55$

Wind reactions based on MWFRS pressures.
#1 hip supports 4-0-0 jacks with no webs.

Deflection meets L/240 live and L/180 total load.

Calculated vertical deflection is 0.57" due to live load and 0.62" due to dead load at X = 15-11-0.



PLT TYP. 20 Gauge HS, Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0) 8.07.00

WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCST (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 46300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, ALL DIMENSIONS SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT: A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE REG. INC. SHALL NOT BE RESPONSIBLE FOR THE CONSTRUCTION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH THE SPECIFICATIONS OF THE TRUSS MANUFACTURER SHALL BE THE RESPONSIBILITY OF THE INSTALLATION CONTRACTOR. THE REG. INC. SHALL NOT BE RESPONSIBLE FOR THE CONSTRUCTION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH THE SPECIFICATIONS OF THE TRUSS MANUFACTURER SHALL BE THE RESPONSIBILITY OF THE INSTALLATION CONTRACTOR.



TC LL	20.0 PSF	REF R8228- 35541
TC DL	10.0 PSF	DATE 06/11/09
BC DL	10.0 PSF	DRW HCUR8228 09162060
BC LL	0.0 PSF	HC-ENG DF/DF
TOT. LD.	40.0 PSF	SEQN- 28301
DUR. FAC.	1.25	FROM AH
SPACING	SEE ABOVE	JREF- 1TSF8228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3

:Stack Chord SC1 2x4 SP #2 Dense:::Stack Chord SC2 2x4 SP #2 Dense:

Roof overhang supports 2.00 psf soffit load.

See DWGS A11015050109 & GBLLETIN0109 for more requirements.

Stacked top chord must NOT be notched or cut in area (NML). Attach stacked top chord (SC) to dropped top chord in noticable area using 3x4 tie-plates 24" o.c. Center plate on stacked/dropped chord interface, plate length perpendicular to chord length. Splice top chord in noticable area using 3x6.

THE BUILDING DESIGNER IS RESPONSIBLE FOR THE DESIGN OF THE ROOF, FLOOR AND CEILING DIAPHRAGMS, GABLE END SHEAR WALLS, AND SUPPORTING SHEAR WALLS. DIAPHRAGMS AND SHEAR WALLS MUST PROVIDE CONTINUOUS LATERAL RESTRAINT TO THE GABLE END. ALL CONNECTIONS ARE TO BE PROVIDED BY THE BUILDING DESIGNER.

(**) 4 plate(s) require special positioning. Refer to scaled plate plot details for special positioning requirements.


110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 GCpi (+/-)=0.18

Wind reactions based on MWFRS pressures.

In lieu of structural panels use purlins to brace TC @ 24" OC.

Bottom chord checked for 10.00 psf non-concurrent live load.

Deflection meets L/240 live and L/180 total load.



R=121 PLF U=83 PLF W=6-8-0
RL=8/-8 PLF

PLT TYP. Wave

Design Crit: FBC2007Res/TP1-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00

QTY:1

FL/-/4/-/-/R/-

Scale =.5"/Ft.

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BC51 (BUILDING COMPONENT SAFETY INFORMATION), PROVIDED BY TPI (TRUSS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WICA (WOOD TRUSS CONDUCTOR OF AMERICA, 6500 ENTERPRISE LANE, MADISON, MI 48071) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, ALL DIMENSIONS SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

IMPORTANT OBTAIN A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE REG. INC. SHALL NOT BE RESPONSIBLE FOR DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH THIS DESIGN OR FABRICATING, HANDLING, SHIPPING, INSTALLING A BRACING OF TRUSSES.

DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (NATIONAL DESIGN SPEC., BY AF&PA) AND TPI.

TRUSS CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE FOLLOWING: ASTM A563 GRADE 40/60 (40, KSI) GALV. STEEL, APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A-Z.


ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TPI-2002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY. SOCIETY FOR THE TRUSS CONFORMANCE DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.

ALPINE

ITW Building Components Group Inc.

Haines City, FL 33844

FL C-100-778



TC LL	20.0 PSF	REF R8228- 35542
TC DL	10.0 PSF	DATE 06/11/09
BC DL	10.0 PSF	DRW HCUR8228 09162061
BC LL	0.0 PSF	HC-ENG DF/DF
TOT. LD.	40.0 PSF	SEON- 28369
DUR. FAC.	1.25	FROM AH
SPACING	SEE ABOVE	JREF- 1TSF8228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3


110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, Iw=1.00 GCPI(+/-)=0.18

Roof overhang supports 2.00 psf soffit load.

Wind reactions based on MMFRS pressures.

Bottom chord checked for 10.00 psf non-concurrent live load.

Deflection meets L/240 live and L/180 total load.



PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)

FT/RT=10%(0%)/0(0)

8.07.00

QTY:1

FL/-/4/-/-/R/-

Scale = .375"/Ft.

ALPINE

NTW Building Components Group Inc.

Haines City, FL 33844

FL 06-000078

DOUBLE FLEMING

PROFESSIONAL ENGINEER

No. 66648

STATE OF FLORIDA

11 '09

TC LL	20.0 PSF	REF	R8228- 35543
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162010
BC LL	0.0 PSF	HC-ENG DF/DF	*
TOT. LD.	40.0 PSF	SEQN-	28371
DUR. FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3


Roof overhang supports 2.00 psf soffit load.

Bottom chord checked for 10.00 psf non-concurrent live load.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located
within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf,
wind BC DL=5.0 psf, IW=1.00 GCPI(+/-)=0.18

Wind reactions based on MMFRS pressures.

Deflection meets L/240 live and L/180 total load.



PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00

QTY:2 FL-/4/-/-R/-

Scale =.5"/ft.

****WARNING**** BRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 2100 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, HOUSTON, TX 77037) FOR SAFETY PRACTICES PRIOR TO REFORMING THESE INSTRUCTIONS. UNLESS OTHERWISE INDICATED, ALL DIMENSIONS SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID JOINT.

****IMPORTANT**** BRUSSES A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR, THE BCG, INC. SHALL NOT BE RESPONSIBLE FOR THE DESIGN OF THE TRUSS IN CONFORMANCE WITH THE TPI OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES. THE TRUSS IN CONFORMANCE WITH THE DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF BCS (NATIONAL DESIGN SPEC. BY AIA/ASA AND TPI. THE BCG CONNECTOR PLATES ARE MADE OF 2018/1664 (W/AL/SS/2) ASIN ASS 6040/60 (W/AL/SS) GALV. STEEL. APPLY PLATES TO EACH FACE OF TRUSS AND, UNLESS OTHERWISE LOCATED ON THIS DESIGN, POSITION PER DRAWINGS 160A-2. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TPI-2002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.

ALPINE

NTW Building Components Group Inc.

Haines City, FL 33844

FL CG 11-09



11 '09

TC LL	20.0 PSF	REF	R8228- 35545
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCSUR8228 09162011
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT. LD.	40.0 PSF	SEON-	28386
DUR. FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228201


2 COMPLETE TRUSSES REQUIRED
Nailing Schedule: (0.131"x3" Gun_nails)

2 COMPLETE TRUSSES REQUIRED
Nailing Schedule: (0.131"x3"
Gun_nails)

110 mph wind, 15.00 ft mean ht, ASCE 7-05, CLOSED bldg, not located within 6.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ Gcpi (+/-)=0.18

Wind reactions based on MWFRS pressures.

Deflection meets $L/240$ live and $L/180$ total load.


$$4 \times 8(A1) \equiv$$

—1-6-0—

Diagram showing the elevation view of a bridge deck. The deck is supported by two supports, with dimensions indicating the span and overhangs.

Dimensions (from left to right):

- 4 - 4 - 6
- 7 - 4 - 0
- 2 - 11 - 10
- 2 - 11 - 10
- 7 - 4 - 0
- 4 - 4 - 6

Supports are indicated by vertical lines with arrows pointing outwards.

Overall dimensions:

- 14 - 8 - 0 over 2 Supports
- R=4943 U=1084 W=6"
- R=2485 U=509

R=2485 U=509 W=6"

Design Crit: FBC2007Res/TPI-2002(STD),
FT/RT=10%(0%)/0(0)

$$FT/RT=10\%(0\%)/0(0)$$

8.07.00

QTY:1

FL/-/4/-/-/R/-/

Scale = .5"/Ft.

WARNING: THESE BUILDING EXISTENCE CASE, HANDLING, SHIPPING, INSTALLING AND REACTING REFER TO SC-1 (BUILDING COMPONENT SAFETY INFORMATION). PUBLISHED BY THE CROSS-PALE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND WICK GOOD TRUSS COMPANY, 6500 RENO ROAD, INTERSTATE LANE, MIDDLETON, WI 53519 FOR SAFETY PRACTICES PRELIMINARY TO FORMING THESE STRUCTURES. UNDESIGNED INDICATED TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CELLING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT

TP1: OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

CORRELATOR PLATES ARE MADE OF 20/10/1066 (W, H/SS/K) WITH A653 GRADE 40/60 (H, K/H, SS) GALV. STEEL. APPLY

ANY REQUESTS FOR COPIES FOLLOWED BY (1) SMALL DE PER ANNEA AS OF 17-11-2002 SEC.3, A SEAL ON THE

[illegible]

ALPINE

ITW Building Components Group Inc

Haines City, FL 33844

FLCQ 100378




TC LL	20.0 PSF	REF	R8228- 35546
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162063
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28678
DUR.FAC.	1.25	FROM	AH
SPACING	SEE ABOVE	JREF-	1TSF8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART-ENC. bldg, located anywhere in roof, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, Iw=1.00 GCp1(+/-)=0.55


Wind reactions based on MIFRS pressures.

Deflection meets L/240 live and L/180 total load.



Scale = .5"/Ft.

IMPORTANT TURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT



ALPINE


Professional Engineer Seal for Douglas Fleming, State of Florida, License No. 66648. The seal is circular with a double-lined border. The outer ring contains the text "DOUGLAS FLEMING" at the top and "PROFESSIONAL ENGINEER" at the bottom, separated by two stars. The inner circle contains the text "STATE OF FLORIDA" and "LICENSE" on the left and right respectively, with "No. 66648" in the center. A stylized graphic of a person holding a torch is positioned in the center of the seal.

TC LL	20.0 PSF	REF	R8228- 35547
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCSR8228 09162064
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28270
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSR8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART. ENC. bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ GCPI (+/-)=0.55


Wind reactions based on MFRS pressures.

Deflection meets L/240 live and L/180 total load.



Scale = .5" / ft.

IMPORTANT FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. TIM BCG, INC. SHALL NOT



ALPINE

Haines City, FL 33844

FLC 78




TC LL	20.0 PSF	REF	R8228- 35549
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162066
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28284
DUR.FAC.	1.25	FROM	AH
SPACING	SEE ABOVE	JREF-	1TSF828201

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART_ENC, bldg, located anywhere in roof, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, lw=1.00 gcpt(+/-)=0.55

Wind reactions based on MWFRS pressures.

Deflection meets L/240 live and L/180 total load.



0-6-1

3-0-0 Over 3 Supports

R=259 U=45 W=6"
RL=43

PLT TYP. Wave

Design Crit: FBC2007Res/TP1-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00

QTY:10 FL/-/4/-/-/R/-

Scale = .5" / ft.

WARNING: THESE REINFORCING STEEL CAGE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND DRACING REFER TO DC-1 (BUILT-UP COMPONENTS) AND C-1 (CONCRETE). PUBLISHED BY THE STEEL INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA. 22314 AND WICK, 6000 TRUSS COUNCIL OF AMERICA, 6500 ENTERPRISE LANE, MOBILE, AL 36619 FOR SAFETY PRACTICES PERTAINING TO THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TWO CORDS SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT****FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITM BCG, INC. SHALL NOT

BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TP1; OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

DESIGN COMFORMS WITH APPLICABLE PROVISIONS OF AISC TENSIONAL DESIGN SPEC., BY AISC/AAS AND THE
CONCRETE PLATES ARE MADE OF 70/18/1664 (H.M./SS/K) ASTM A653 GRADE 40/60 (H. K/H.SS) GALV. STEEL.
APPLY TO EACH CASE. PROVIDES AND WELDS ATTACHED OR THIS IS SIGN POSITION PER DRAWINGS. EVID-2

PLATES TO EACH OF TRUSS JOINTS, UNLESS OTHERWISE SPECIFIED ON THIS SECTION, POSITIONED PER DRAWING INDICATES. ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOCIETY FOR THE TRUSS CORPORATION. ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TP11-2002 SEC.3.3. A SEAL ON THIS

DESIGN SHOWN. THE SUSTAINABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/SPR 1 SEC. 2.




TC LL	20.0 PSF	REF	R8228- 35550
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162012
BC LL	0.0 PSF	HC-ENG	DF/DF *
TOT.LD.	40.0 PSF	SEON-	28275
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JRFF-	1TSF8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, PART_ENC, bldg, located anywhere in roof, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, lw=1.00 gcpt(+/-)=0.55

Wind reactions based on MWFRS pressures.

Deflection meets $L/240$ live and $L/180$ total load.



← 4-0-0 over 3 Supports →

R=292 U=40 W=3.5"
RL=35

Design Crit: FBC2007Res/TP1-2002(STD)
FT/RT=10%(0%)/0(0)

QTY:13 FL/-/4/-/-/R/-

Scale = .5"/ft.

WARNING: TRUSSES BEING EXTREMELY CARE IN FABRICATION, HANDLING, SHIPMENT, INSTALLING AND BRACING. REFER TO DCSI (GEOBLINDING COMPONENTS INCORPORATION), PUBLISHED BY THE EARTH PRESSURE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314, (800) 768-6000 THROUGH THESE CONSULTING OFFICES, 6300 ENTERPRISE LANE, MADISON, WI 53719, FOR SAFETY PRACTICES AND PRELIMINARY DESIGN. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CILLING.

****IMPORTANT****FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITR BCG, INC. SHALL NOT

BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH TP1, OR FABRICATING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF NDS (TRADITIONAL DESIGN SPEC. BY AIA/CES) AND TPI. CONNECTOR PLATES ARE MADE OF 20/18/1664 (U/M/SS/K) ASTM A653 GRADE 40/60 (U, K/M, SS) GALV. STEEL. 11% BECAUSE OF EACH FACE OF STUDS AND UNITS ATTACHED OR WELDED ON THIS POSITION PER DRAWINGS 1604-2

PLATES TO EACH OF TRUSS AND, (CIRCLES OTHERWISE LOCATED ON THIS SECTION, POSITION FOR DRILLING 100%
ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TP11-2002 SEC.3. A SEAL ON THIS
DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLLEY FOR THE TRUSS COMPONENT

DESIGN SHOW. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



ALPINE

ITW Building Components Group Inc.
Haines City, FL 33844
FL 888-888-8888



TC LL	20.0 PSF	REF	R8228- 35551
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162067
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEON-	28280
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense



Roof overhang supports 2.00 psf soffit load.

Bottom chord checked for 10.00 psf non-concurrent live load.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, lw=1.00 GCPI (+/-)=0.18

Wind reactions based on MWFRS pressures.

Deflection meets L/240 live and L/180 total load.



PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00 QTY:7 FL/-/4/-/1/R/-

Scale =.5"/Ft.

ALPINE		No. 66648		TC LL	20.0 PSF	REF	R8228 - 35552
ITW Building Components Group Inc.		FLORIDA		TC DL	10.0 PSF	DATE	06/11/09
Haines City, FL 33844		ENGINEER		BC DL	10.0 PSF	DRW	HCUSR8228 09162013
FLC 78		11 '09		BC LL	0.0 PSF	HC-ENG	DF/DF
				TOT. LD.	40.0 PSF	SEQN-	28303
				DUR. FAC.	1.25	FROM	AH
				SPACING	24.0"	JREF -	ITSF8228Z01

Top chord 2x4 SP #2 Dense
Bot chord 2x4 SP #2 Dense
Webs 2x4 SP #3



Left end vertical not exposed to wind pressure.

Hipjack supports 2-2-6 setback jacks with no webs.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, located
anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0
psf, lw=1.00 GCPI (+/-)=0.18

Wind reactions based on MMFRS pressures.

Deflection meets L/240 live and L/180 total load.



PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00

QTY:1

FL/-/4/-/-/R/-


Scale =.5"/Ft.

****WARNING**** TRUSSES REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCST (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY TPI (TRUSS PLATE INSTITUTE, 210 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22304) AND WCA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LANE, MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PREPARING THESE TRUSSES. UNLESS OTHERWISE INDICATED FOR GROUND SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE BCG, INC. SHALL NOT BE RESPONSIBLE FOR ANY DAMAGE TO THE TRUSS OR TO THE BUILDING OR TO THE PERSONS OR PROPERTY DURING THE TRUSS INSTALLATION. THE TRUSS IS TO BE INSTALLED IN ACCORDANCE WITH THE DESIGN SPECIFICATIONS AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS DESIGN AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS FABRICATION AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS SHIPPING AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS INSTALLATION. THE TRUSS IS TO BE INSTALLED IN ACCORDANCE WITH THE DESIGN SPECIFICATIONS AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS DESIGN AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS FABRICATION AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS SHIPPING AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS INSTALLATION.

DESIGN CONFORMS WITH APPLICABLE PROVISIONS OF BOB (NATIONAL DESIGN SPEC. BY AREA) AND TPI. THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS DESIGN AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS FABRICATION AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS SHIPPING AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS INSTALLATION. THE TRUSS IS TO BE INSTALLED IN ACCORDANCE WITH THE DESIGN SPECIFICATIONS AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS DESIGN AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS FABRICATION AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS SHIPPING AND THE BCG, INC. SHALL BE RESPONSIBLE FOR THE TRUSS INSTALLATION.

ANY INSPECTION OF PLATES FOLLOWED BY (1) SHALL BE PER ANNEX A3 OF TPI 2002 SEC.3. A SEAL ON THIS DRAWING INDICATES ACCEPTANCE OF PROFESSIONAL ENGINEERING RESPONSIBILITY SOLELY FOR THE TRUSS COMPONENT DESIGN SHOWN. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



FLC 078



TC LL	20.0 PSF	REF	R8228 - 35553
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162068
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT. LD.	40.0 PSF	SEON-	28359
DUR. FAC.	1.25	FROM	AH
SPACING	SEE ABOVE	UREF-	ITSF8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, closed bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcpl(+/-)=0.18

Wind reactions based on MWFRS pressures.


$$FT/RT=10\%(0\%)/0(0)$$

QTY:2

Scale = .5" / ft.

*IMPORTANT-TO OBTAIN A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR, THE RCG, INC., SHALL NOT BE RESPONSIBLE FOR ANY DEVIATION FROM THIS DESIGN; ANY FAILURE TO BUILD THE TROSS IN CONFORMANCE WITH THE DESIGN, OR FABRICATING, HANDLING, SHIPPING, INSTALLING OR BRACING OF PROSSES.

DESIGN SHOWN, THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/TPI 1 SEC. 2.



TC LL	20.0 PSF	REF	R8228- 35556
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162070
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28331
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	TTSF8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, located anywhere in roof, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf, Iw=1.00 Gcpl (+/-)=0.18

Wind reactions based on MWFRS pressures.

Deflection meets $L/240$ live and $L/180$ total load.




8.07.00

QTY:31 FL/-/4/-/-/R/-

Scale = .5"/Ft.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. THE BCG, INC. SHALL NOT



ALPINE

Haines City, FL 33844

FLC# 0000078




TC LL	20.0 PSF	REF	R8228- 35554
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCU8R8228 09162014
BC LL	0.0 PSF	HC-ENG	DF/DF *
TOT.LD.	40.0 PSF	SEQN-	28307
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF -	1TSF8228Z01

Top	chord	2x6	SP	#2	:T2	2x4	SP	#2	Dense:
Bot	chord	2x4	SP	#2	Dense				
	Weds	2x4	SP	#3					

In lieu of structural panels use purlins to brace all flat TC @ 24" OC.

Deflection meets $L/240$ live and $L/180$ total load.

Bottom chord checked for 10.00 psf non-concurrent live load.



9-0-0 Over 3 Supports

PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

$$FT/RT=10\%(0\%)/0(0)$$

8.07.00

QTY:1

FL/-/4/-/-/R/-/

Scale = .5"/Ft.

WARNING THESE BUILDING EXTERIOR CASES IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACKETING TO BE USED TO BRIDGE THE EXISTING COMPROMISED SAFETY INFORMATION. PUBLISHED BY THE STRESS PLATE INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND ALSO 6000 TRUSS COMPANY OF AMERICA, 65000 INTERSTATE LAKE, SUITE 312, ALEXANDRIA, VA, 53709 FOR SAFETY PRACTICES AND PRIOR TO PERFORMING THESE FUNCTIONS. OTHERWISE INDICATED FOR GOOD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

****IMPORTANT**** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT BE RESPONSIBLE FOR DEVIATION FROM THIS DESIGN. ANY FAILURE TO BUILD THE TRUSS IN CONFORMANCE WITH IT11 OR FALCRAFTING, HANDLING, SHIPPING, INSTALLING & BRACING OF TRUSSES.

[illegible]

DESIGN SHOP. THE SUITABILITY AND USE OF THIS COMPONENT FOR ANY BUILDING IS THE RESPONSIBILITY OF THE BUILDING DESIGNER PER ANSI/AP1 1 SEC. 2.



11.09

DUR.FAC


1.25

FROM AH

JREF - 1TSF8228Z01

Bottom chord checked for 10.00 psf non-concurrent live load.
Deflection meets L/240 live and L/180 total load.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 gcpi (+/-)=0.18



9-0-0 Over 3 Supports
R=380 U=12 W=3.5"
RL=97/-22

PLT TYP. Wave


Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00

QTY:1

FL/-/4/-/-/R/-/-

Scale = .5"/Ft.


[illegible]

Haines City, FL 33844
FL CO, 4078



TC LL	20.0 PSF	REF	R8228- 35558
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCUSR8228 09162072
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28480
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1TSF8228201

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 gcpi(+/-)=0.18



R=380 U=11 W=3.5"
RL=98/-22

PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

$$FT/RT=10\%(0\%)/0(0)$$

8.07.00

QTY:5

FL/-/4/-/-/R/-/-

Scale = .5" / Ft.

WARNING: FIRE RESISTING RIGID CEILING CASE IN FABRICATION, HANDLING, SHIPPING, INSTALLING AND BRACING REFER TO RC-31 (BUILDING COMPONENT SAFETY INFORMATION). PUBLISHED BY FPI (FIBER PASTE INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314, AND WICK GORD TRUSS COUNCIL OF AMERICA, 65000 ENTERPRISE LANE, MADISON, WI, 53719 FOR SAFETY PRACTICES AND TIPS TO PERFORMING THESE FUNCTIONS. UNLESS INDICATED TOP GORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM GORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

ALPINE

ITW Building Components Group Inc.

Haines City, FL 33844

FLCQ, 110-278



11 '09

SPACING 24.0"

JREF - 1TSF8228Z01


110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcpl(+/-)=0.18

Roof overhang supports 2.00 psf soffit load.

Wind reactions based on MFRS pressures.

Bottom chord checked for 10.00 psf non-concurrent live load

Deflection meets $L/240$ live and $L/180$ total load.



PLT TYP. Wave

Design Crit: FBC2007Res/TP1-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00


QTY: 5

$$FL/-/4/-/-/R/-$$

Scale = .5" / ft.

WARNING: THESE PROCESSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO GC-51 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY THE GIBBS PAPER INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND AFCA (WOOD BRASS COUNCIL OF AMERICA, 6500 ROCKFORD ENTERPRISE LANE, SUITE 401, 53719) FOR SAFETY PRACTICES PERTAINING TO PERFORMING THESE FUNCTIONS. UNDESIRABLE INDICATED FOR GIBBS SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM GIRD SHALL HAVE A PROPERLY ATTACHED GIRD CELLING.

ALPINE



ALPINE

Haines City, FL 33844
FL CC, 10-278



11.09

SPACING 24.0"

JREF- 1TSF8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $G_{CPI}(+/-)=0.18$



8.07.00

QTY:1

FL/-/4/-/-/R/-/

Scale = .5"/Ft.

WARNING: ALL FRIBES REQUIRING EXTERIOR CASE IN EMERGO, HANDLING, UNWRAPPING, INSTALLING, AND BRACING REFER TO GC51 (BUILDING COMPONENT SAFETY INFORMATION). PUBLISHED BY THE FIBER PAPER INSTITUTE, 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND PICA (6000 TRUSS CONSULTING OF AMERICA, 62000 INTERSTATE LANE, MANDALAY, AZ, 57319) FOR SAFETY PRACTICES PERTAINING TO PENETRATING THESE STRUCTURES. UNDESIRABLE CONDITIONS INDICATED FOR CORDS SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

ALPINE

ITW Building Components Group Inc.

Haines City, FL 33844
FL CO 33844




11.09

SPACING 24.0"

JREF - 1TSF8228Z01

Calculated horizontal deflection is 0.13" due to live load and 0.13" due to dead load.

Bottom chord checked for 10.00 psf non-concurrent live load.
Deflection meets L/240 live and L/180 total load.


$$FT/RT=10\%(0\%)/0(0)$$

8.07.00


QTY:1

FL/-/4/-/-/R/-/

Scale = .5" / Ft.

****IMPORTANT*** FURNISH A COPY OF THIS DESIGN TO THE INSTALLATION CONTRACTOR. ITW BCG, INC. SHALL NOT

ALPINE



Haines City, FL 33844

FLCC 2007-278




11.09

SPACING 24.0"

JREF - 1TSF8228Z01

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT 11, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. $I_w=1.00$ $G_{CPI}(+/-)=0.18$

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

QTY:8

FL/-/4/-/-/R/-/-

Scale = .5"/Ft.

MARINER™ FIBERS REQUIRE EXTREME CARE IN FABRICATION, HANDLING, SHIPPING, INSTALLING, AND BRACING. REFER TO RCSI (BIOLOGICALLY COMPATIBLE SAFETY INFORMATION) - PUBLISHED BY TPI (FIBERS PAPER INSTITUTE), 218 NORTH LEE STREET, SUITE 312, ALEXANDRIA, VA, 22314 AND AFCA (AMERICAN FIBERS COUNCIL OF AMERICA), 65000 ROCKY HILL ENTERPRISE LANE, MOBILE, AL 36619 FOR SAFETY PRACTICES PERTAINING TO PERFORMANCE, HOUSE FUNCTIONS, UNDESIRABLE INDICATED (TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING).

ITW Building Components Group Inc.

Haines City, FL 33844

FL CGA No. 378



TC LL	20.0 PSF	REF	R8228- 35563
TC DL	10.0 PSF	DATE	06/11/09
BC DL	10.0 PSF	DRW	HCHSR8228 09162075
BC LL	0.0 PSF	HC-ENG	DF/DF
TOT.LD.	40.0 PSF	SEQN-	28574
DUR.FAC.	1.25	FROM	AH
SPACING	24.0"	JREF-	1T5F8228Z01

Bottom chord checked for 10.00 psf non-concurrent live load.


Laterally brace BC above filler @ 24" O.C.
Including a lateral brace at chord ends.

110 mph wind, 15.00 ft mean hgt, ASCE 7-05, CLOSED bldg, not located within 4.50 ft from roof edge, CAT II, EXP B, wind TC DL=5.0 psf, wind BC DL=5.0 psf. Iw=1.00 Gcpi (+/-)=0.18

Wind reactions based on MWFRS pressures.

Right end vertical not exposed to wind pressure.

Deflection meets L/240 live and L/180 total load.



PLT TYP. Wave

Design Crit: FBC2007Res/TPI-2002(STD)
FT/RT=10%(0%)/0(0)

8.07.00

QTY:1

FL/-/4/-/-/R/-/


Scale = .5" / Ft.



ITW Building Components Group Inc

Haines City, FL 33844

FLCQA 200378

[illegible]

11.09

SPACING

24.0"


JREF - 1T

8228701

ASCE 7-05: 110 MPH WIND SPEED, 15' MEAN HEIGHT, ENCLOSED, 1 = 1.00, EXPOSURE C, Kzt = 1.00

CABLE STUD REINFORCEMENT DETAIL

MAX GABLE VERTICAL LENGTH		2x4		BRACE		NO		BRACES		(1) 1x4 "L" BRACE *		(1) 2x4 "L" BRACE *		(2) 2x4 "L" BRACE **		(1) 2x6 "L" BRACE *		(2) 2x6 "L" BRACE **	
GABLE VERTICAL SPECIES	GRADE	SPACING	BRACE	NO	BRACES	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B
12" O.C.	SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 5"	12' 9"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	STUD	#3	3' 9"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 3"	12' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	HF	STANDARD	3' 9"	5' 2"	5' 2"	6' 9"	6' 9"	9' 1"	9' 1"	10' 7"	10' 7"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	SP	#1	4' 3"	6' 8"	7' 2"	7' 11"	8' 6"	9' 5"	10' 2"	12' 5"	13' 5"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
16" O.C.	SPF	#2	4' 0"	6' 2"	6' 2"	7' 11"	8' 1"	9' 5"	9' 11"	12' 5"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	STUD	#3	4' 0"	6' 1"	6' 1"	7' 11"	8' 0"	9' 5"	9' 11"	12' 5"	12' 6"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	HF	STANDARD	3' 10"	5' 3"	5' 3"	6' 11"	6' 11"	9' 4"	9' 4"	10' 10"	10' 10"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	SP	#1 / #2	4' 5"	7' 8"	7' 8"	9' 1"	9' 4"	10' 10"	11' 1"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
24" O.C.	SPF	#3	4' 4"	7' 4"	7' 4"	9' 1"	9' 1"	10' 10"	10' 10"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	STUD	#3	4' 4"	7' 4"	7' 4"	9' 1"	9' 1"	10' 10"	10' 10"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	HF	STANDARD	4' 4"	6' 4"	6' 4"	8' 4"	8' 4"	10' 10"	10' 10"	12' 11"	12' 11"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	SP	#1	4' 10"	7' 8"	8' 3"	9' 1"	9' 9"	10' 10"	11' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
MAX GABLE VERTICAL LENGTH	SP	#2	4' 9"	7' 8"	8' 3"	9' 1"	9' 9"	10' 10"	11' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	STUD	#3	4' 6"	7' 6"	7' 6"	9' 1"	9' 6"	10' 10"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	HF	STANDARD	4' 5"	6' 5"	6' 5"	8' 6"	8' 6"	10' 10"	11' 1"	13' 3"	13' 3"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	SP	#1 / #2	4' 11"	8' 5"	8' 5"	10' 0"	10' 3"	11' 11"	12' 3"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
MAX GABLE VERTICAL LENGTH	STUD	#3	4' 9"	8' 5"	8' 5"	10' 0"	10' 0"	11' 11"	11' 11"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	HF	STANDARD	4' 8"	8' 5"	8' 5"	10' 0"	10' 0"	11' 11"	11' 11"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	SP	#1	4' 9"	7' 3"	7' 3"	9' 7"	9' 7"	11' 11"	11' 11"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	STUD	#2	5' 4"	8' 5"	9' 1"	10' 0"	10' 9"	11' 11"	12' 10"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
MAX GABLE VERTICAL LENGTH	SP	#3	5' 3"	8' 5"	8' 5"	10' 0"	10' 6"	11' 11"	12' 6"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	STUD	#3	5' 0"	8' 5"	8' 5"	10' 0"	10' 6"	11' 11"	12' 6"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	HF	STANDARD	4' 11"	7' 5"	7' 5"	9' 10"	9' 10"	11' 11"	12' 3"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"
	SP	STANDARD	4' 11"	7' 5"	7' 5"	9' 10"	9' 10"	11' 11"	12' 3"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"



GABLE VERTICAL PLATE SIZES	
VERTICAL LENGTH	NO SPLICE
LESS THAN 4' 0"	1x4 OR 2x3
GREATER THAN 4' 0" BUT LESS THAN 11' 6"	2.5x4
GREATER THAN 11' 6"	3x4
+ REFER TO COMMON TRUSS DESIGN FOR PEAK, SPLICE, AND HEEL PLATES.	


BRACING GROUP SPECIES AND GRADES:	
GROUP A:	
SPRUCE-PINE-FIR	HEM-FIR
#1 / #2 STANDARD	#2 STUD
#3 STUD	#3 STANDARD
DOUGLAS FIR-LARCH	
#3 STUD	#3 STUD
STANDARD	STANDARD
GROUP B:	
HEM-FIR	DOUGLAS FIR-LARCH
#1 & BTR	#1
SOUTHERN PINE	#2

GABLE TRUSS DETAIL NOTES:

LIVE LOAD DEFLECTION CRITERIA IS $L/240$.
 PROVIDE UPLIFT CONNECTIONS FOR 80 PLF OVER CONTINUOUS BEARING (5 PSF TC DEAD LOAD).
 CABLE END SUPPORTS LOAD FROM 4' 0" OUTLOOKERS WITH 2' 0" OVERHANG, OR 12" PLYWOOD OVERHANG.
 ATTACH EACH "L" BRACE WITH 10d NAILS.
 * FOR (1) "L" BRACE: SPACE NAILS AT 2' 0" O.C. IN 18" END ZONES AND 4' 0" O.C. BETWEEN ZONES.
 ** FOR (2) "L" BRACES: SPACE NAILS AT 3' 0" O.C. IN 18" END ZONES AND 6' 0" O.C. BETWEEN ZONES.
 "L" BRACING MUST BE A MINIMUM OF 80% OF WEB MEMBER LENGTH.




Building Components Group Inc.
 WARNING READ AND FOLLOW ALL NOTES ON THIS SHEET.
 Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow BCSI Building Component Safety Information, by TPI and WCA for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural panels and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections 85 & 87. See this job's general notes page for more information.
 IMPORTANT FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR.
 ITW Building Components Group Inc. (ITWBC) shall not be responsible for any deviation from this design, any failure to build the truss in conformance with TPI, or fabricating, handling, shipping, installing & bracing of trusses. ITWBC connector plates are made of 20/18/16GA (H/S/R) ASTM A653 grade 37/40/60 (K/R/H/S) galv. steel. Apply plates to each face of truss, positioned as shown above and on joint details. ITWBC connector plates shall be installed in accordance with the manufacturer's instructions and the responsibility of the Building Designer per ANSI/TPI 1 Sec. 2.
 ITW-BCSI: www.itwbc.com, TPI: www.tpi.net, WCA: www.abundant.com, ICC: www.iccsafe.org



REF	ASCE7-05-CAB1015
DATE	1/1/09
DRWG	A11015050109
MAX. TOT. LD.	60 PSF
MAX. SPACING	24' 0"


CABLE DETAIL FOR LET-IN VERTICALS



GABLE TRUSS PLATE SIZES

- REFER TO APPROPRIATE ITW GABLE DETAIL FOR MINIMUM PLATE SIZES FOR VERTICAL STUDS.
- REFER TO ENGINEERED TRUSS DESIGN FOR PEAK SPLICE, WEB AND HEEL PLATES.
- IF GABLE VERTICAL PLATES OVERLAP, USE A SINGLE PLATE THAT COVERS THE TOTAL AREA OF THE OVERLAPPED PLATES TO SPAN THE WEB.

EXAMPLE:



PROVIDE CONNECTIONS FOR UPLIFT SPECIFIED ON THE ENGINEERED TRUSS DESIGN.

ATTACH EACH "T" REINFORCING MEMBER WITH

END DRIVEN NAILS:

- 10d COMMON (0.148" X 3" MIN) NAILS AT 4" O.C. PLUS
- (4) NAILS IN TOP AND BOTTOM CHORD.

TOENAILED NAILS:

- 10d COMMON (0.148" X 3" MIN) TOENAILS AT 4" O.C. PLUS
- (4) TOENAILS IN TOP AND BOTTOM CHORD.

THIS DETAIL TO BE USED WITH THE APPROPRIATE ITW GABLE DETAIL FOR ASCE

WIND LOAD.

ASCE 7-98 GABLE DETAIL DRAWINGS

A13015980109, A12015980109, A11015980109,

A13030980109, A12030980109, A11030980109

ASCE 7-02 GABLE DETAIL DRAWINGS

A13015020109, A12015020109, A11015020109,

A13030020109, A12030020109, A11030020109


ASCE 7-05 GABLE DETAIL DRAWINGS

A13015050109, A12015050109, A11015050109,

A13030050109, A12030050109, A11030050109,

SEE APPROPRIATE ITW GABLE DETAIL FOR MAXIMUM

UNREINFORCED GABLE VERTICAL LENGTH.



WARNING READ AND FOLLOW ALL NOTES ON THIS SHEET.

Truss components shall be installed in accordance with the ITW Building Components Group Inc. (ITWBCG) Building Component Safety Information, by TPI and WTC. For safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural panels and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3 & B7. See this job's general notes page for more information.

IMPORTANT FURNISH COPY OF THIS DESIGN TO INSTALLATION CONTRACTOR.


ITW Building Components Group Inc. (ITWBCG) shall not be responsible for any deviation from this design, any failure to build the truss in conformance with TPI or fabricating, handling, shipping, installing & bracing of trusses. ITWBCG connector plates are made of 20/18/16GA (W/H/S/R) ASTM A653 grade 37/40/50 (K/W/H/S) galv. steel. Apply plates to each face of truss, positioned as shown above and on Joint Details. Seal on this drawing or cover page indicates acceptance and professional engineering responsibility solely for the design and use of this component for any building is the responsibility of the Building Designer per ANSI/TPI 1, Sec. 2.

ITW-BGC: www.itwbcg.com; TPI: www.tpi.net; WTC: www.abendustry.com; ICC: www.iccsafe.org



Building Components Group Inc.

Earth City, MO 63045



TO CONVERT FROM "L" TO "T" REINFORCING MEMBERS, MULTIPLY "T" INCREASE BY LENGTH (BASED ON APPROPRIATE ITW GABLE DETAIL).

MAXIMUM ALLOWABLE "T" REINFORCED GABLE VERTICAL LENGTH IS 14' FROM TOP TO BOTTOM CHORD.

WEB LENGTH INCREASE W/ "T" BRACE

WIND SPEED AND MRH	"T" REINFORCING MEMBER SIZE	"T" INCREASE
140 MPH	2x4	10 %
15 FT	2x6	50 %
140 MPH	2x4	10 %
30 FT	2x6	50 %
130 MPH	2x4	10 %
15 FT	2x6	50 %
130 MPH	2x4	10 %
30 FT	2x6	50 %
120 MPH	2x4	10 %
15 FT	2x6	50 %
120 MPH	2x4	10 %
30 FT	2x6	50 %
110 MPH	2x4	10 %
15 FT	2x6	50 %
110 MPH	2x4	10 %
30 FT	2x6	50 %
100 MPH	2x4	20 %
15 FT	2x6	30 %
100 MPH	2x4	10 %
30 FT	2x6	40 %
90 MPH	2x4	20 %
15 FT	2x6	20 %
90 MPH	2x4	20 %
30 FT	2x6	30 %

EXAMPLE:

ASCE WIND SPEED = 100 MPH

MEAN ROOF HEIGHT = 30 FT, K_{z1} = 1.00

GABLE VERTICAL = 24" O.C. SP #3

"T" REINFORCING MEMBER SIZE = 2X4

"T" BRACE INCREASE (FROM ABOVE) = 10% = 1.10

(1) 2X4 "T" BRACE LENGTH = 6' 7"

MAXIMUM "T" REINFORCED GABLE VERTICAL LENGTH

1.10 x 6' 7" = 7' 3"

REF LET-IN VERT

DATE 1/1/09

DRWG GILLETINO109

MAX TOT. LD. 60 PSF

DUR. FAC. ANY

MAX SPACING 24.0"