COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2023 EFFECTIVE 1 JANUARY 2024 AND THE NATIONAL ELECTRICAL 2020 EFFECTIVE 1 JANUARY 2024

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT FLORIDA BUILDING CODES RESIDENTIAL AND THE NATIONAL ELECTRICAL CODE. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA. OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS, FBC 1609.1 THRU 1609.6.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609.3(1) THROUGH 1609.3(4) ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES **Revised 7/1/20**

Items to Include-Submit Online at- http://www.columbiacountyfla.com/BuildingandZoning.asp Each Box shall be GENERAL REQUIREMENTS: Circled as APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Applicable Select From Drop down Two (2) complete sets of plans containing the following: 2 All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void ~ NA Total (Sq. Ft.) under roof 3168 Condition space (Sq. Ft.) 2240

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES BUILDING 107.1.

Site Plan information including:

4	Dimensions of lot or parcel of land	Yes	
	Dimensions of all building set backs	Yes	
б	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	Yes	
	Provide a full legal description of property.	Yes	

Wind-load Engineering Summary, calculations and any details are required.

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each C	Box sha lircled as plicable	ll be
8	Plans or specifications must show compliance with FBCR Chapter 3	Yes	No	NA
		Select Fro	om Drop	down
9	Basic wind speed (3-second gust), miles per hour	Yes		1
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated)	Yes		
11	Wind importance factor and nature of occupancy	Yes		
12	The applicable internal pressure coefficient, Components and Cladding	Yes		
13	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional.	Yes		
Ele	evations Drawing including:			
14	All side views of the structure	Yes		-
15	Roof pitch	Yes Yes		
16	Overhang dimensions and detail with attic ventilation	No	_	
17	Location, size and height above roof of chimneys	No	+	_
18	Location and size of skylights with Florida Product Approval	Yes	-	
19	Number of stories			-
20	Building height from the established grade to the roofs highest peak	Yes		

Itama to Include

Floor Plan Including: Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, Yes 21 deck, balconies No Raised floor surfaces located more than 30 inches above the floor or grade 22 Yes All exterior and interior shear walls indicated 23 Yes Shear wall opening shown (Windows, Doors and Garage doors) 24 Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each 25 bedroom (net clear opening shown) and Show compliance with Section FBCR 312.2.1 where the opening of an operable window is located more than 72 inches above the finished grade or surface Yes below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass. Yes Safety glazing of glass where needed 26 Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR) Yes 27 Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails 28 No Yes Identify accessibility of bathroom (see FBCR SECTION 320)

All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plans (see Florida product approval form)

CENERAL REQUIREMENTS:

	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box shall Circled as Applicable	
FB		Select From Dr	op dov
30	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	Yes	
31	All posts and/or column footing including size and reinforcing	Yes	
32	Any special support required by soil analysis such as piling.	No	
3	Assumed load-bearing valve of soil Pound Per Square Foot	NA	
34	Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system.	Yes	
	Per the National Electrical Code article 250.52.3		
FB	Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE		
\$5	Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed)	Yes	
35	Per the National Electrical Code article 250.52.3	Yes Yes	
35 36	Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES		
35 36	Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	Yes	
35 36	Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports		
35 36 37	Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides	Yes	
35 36 FB 37	Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered	Yes	

Items to Include-

Floor Framing System: First and/or second story

	Floor truss package shall including layout and details, signed and sealed by Florida Registered	No	
40	Professional Engineer		
44	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls,	No	
41	stem walls and/or priers		
42	Girder type, size and spacing to load bearing walls, stem wall and/or priers	No	
43		No	
44	Wind load requirements where applicable	No	
45	Show required under-floor crawl space	No	
46	Show required amount of ventilation opening for under-floor spaces	No	
47	Show required covering of ventilation opening	No	
48	Show the required access opening to access to under-floor spaces	No	
	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &	No	
49	intermediate of the areas structural panel sheathing	INO	
50	Show Draftstopping, Fire caulking and Fire blocking	No	
51	Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6	No	
52	Provide live and dead load rating of floor framing systems (psf).	No	

FBCR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION

GENERAL REQUIREMENTS:
APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

	5	Select from	Drop down
53	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	Yes	
54	Fastener schedule for structural members per table FBC 2304.10.1 are to be shown	Yes	
55	Show wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	Yes	
56	Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	Yes	
57	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per FBC 2304.3.	Yes	
58	Indicate where pressure treated wood will be placed	Yes	
59	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing edges & intermediate areas	Yes	
60	A detail showing gable truss bracing, wall balloon framing details or/and wall hinge bracing detail	-	

FBC :ROOF SYSTEMS:

61	Truss design drawing shall meet section FBC 2303.1 Wood trusses	Yes	
	Include a layout and truss details, signed and sealed by Florida Professional Engineer	Yes	
	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	Yes	
	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	Yes	
	Provide dead load rating of trusses	Yes	

FBC 2304.4: Conventional Roof Framing Layout

66	Rafter and ridge beams sizes, span, species and spacing	Yes	
	Connectors to wall assemblies' include assemblies' resistance to uplift rating	Yes	
		Yes	
	Provide dead load rating of rafter system	Yes	

FBC 2304.8 ROOF SHEATHING

Sheathing, grade, thickness The Street of t	70	Include all materials which will make up the roof decking, identification of structural panel	Yes	
1 71 Show togreper Size and schedule for structural daties sugarified on the cures of interinculate areas	71	sheathing, grade, thickness Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	Yes	

ROOF ASSEMBLIES FRC Chapter 9

72	Include all materials which will make up the roof assembles covering	Yes	
73	Submit Florida Product Approval numbers for each component of the roof assembles covering	Yes	

FBC Energy Chapter 4

Residential construction shall comply with this code by using the following compliance methods in the FBC Chapter 4, Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600 A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to In Each Box Circle Applic	shall be d as able
	Se	elect from Di	op Down
74	Show the insulation R value for the following areas of the structure	Yes	
75	Attic space	Yes	
76	Exterior wall cavity	Yes	
77	Crawl space	NA	
H	VAC information		
78	Submit two copies of a Manual J sizing equipment or equivalent computation study	Yes	
79	Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or	V	
	20 cfm continuous required	Yes	
80		Yes	
-		I.	
Plu	umbing Fixture layout shown		
81	All fixtures waste water lines shall be shown on the foundationplan	Yes	
82	Show the location of water heater	Yes	
84	Pump motor horse power Reservoir pressure tank gallon capacity Rating of cycle stop valve if used	Yes Yes Yes	
00	Rating of cycle stop varve if used	165	
Ele	ectrical layout shown including		
86	Show Switches, receptacles outlets, lighting fixtures and Ceiling fans	Yes	
87	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A	Yes	
88	Show the location of smoke detectors & Carbon monoxide detectors	Yes	
89	Show service panel, sub-panel, location(s) and total ampere ratings	Yes	
90	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	Yes	
	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3		
91	Appliances and HVAC equipment and disconnects	Yes	
92	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter, Protection device.	Yes	

Notice Of Commencement:

A notice of commencement form RECORDED in the Columbia County Clerk Office is required to be filed with the Building Department BEFORE ANY INSPECTIONS can be performed.

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

ITEMS 95, 96, & 98 Are Required After APPROVAL from the ZONING DEPT.

Select from Drop down

	56	elect from Dro	p aowi
93	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted.	Yes	
94	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	Yes	
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	Yes	
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031	No	
97	Toilet facilities shall be provided for all construction sites	Yes	
98	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	No	
99	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations (Municode.cpm)	No	
100	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required.	Yes	
101	A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00	-	
102	Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size and length of every culvert before instillation and completes a final inspection before permanent power is granted. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.	NA	
103	911 Address: An application for a 911 address must be applied for and received through the Columbia County Office of 911 Addressing Department online.	Yes	
			-

Ordinance Sec. 90-75. - Construction debris. (e) It shall be unlawful for any person to dispose of or discard solid waste, including construction or demolition debris at any place within the county other than on an authorized disposal site or at the county's solid waste facilities. The temporary storage, not to exceed seven days of solid waste (excluding construction and demolition debris) on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance, shall not be deemed a violation of this section. The temporary storage of construction and demolition debris on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance shall not be deemed in violation of this section; provided, however, such construction and demolition debris must be disposed of in accordance with this article prior to the county's issuance of a certificate of occupancy for the premises. The burning of lumber from a construction or demolition project or vegetative trash when done so with legal and proper permits from the authorized agencies and in accordance with such agencies' rules and regulations, shall not be deemed a violation of this section. No person shall bury, throw, place, or deposit, or cause to be buried, thrown, placed, or deposited, any solid waste, special waste, or debris of any kind into or on any of the public streets, road right-of-way, highways, bridges, alleys, lanes, thoroughfares, waters, canals, or vacant lots or lands within the county. No person shall bury any vegetative trash on any of the public streets, road right-of-way, highways, bridges, lanes, within the county.