

REQUIRED ROOF VENTILATION:
AS PER FLORIDA BUILDING CODE 2308.7

RIDGE VENT
MIN. 50% TOTAL VENT AREA
LOCATED IN THE UPPER PORTION OF ATTIC (MIN. 3" ABOVE EAVE)
4285 S.F. / 300 : 50% = 8 S.F. RIDGE VENT AREA REQUIRED
73 FEET OF RIDGE VENT REQUIRED

SOFFIT VENT
4285 S.F. / 300 : 50% = 8 S.F. SOFFIT VENT AREA REQUIRED
267 FEET OF SOFFIT VENT REQUIRED


BUILDER MUST VERIFY THE FOLLOWING MINIMUM NET FREE VENT AREAS:

1. RIDGE VENTS = 16 IN²/FT (.11 FT²/FT)
2. OFF-RIDGE VENTS = .70 FT² PER 4' UNIT
3. SOFFIT VENTS = 4.3 IN²/FT (.03 FT²/FT)


FRONT ELEVATION
SCALE: 1/4" = 1'-0"



RIGHT ELEVATION
SCALE: 3/16" = 1'-0"



REAR ELEVATION
SCALE: 3/16" = 1'-0"



SECTION THROUGH
SCALE: 1/4" = 1'-0"



LEFT ELEVATION
SCALE: 3/16" = 1'-0"

REVISIONS	
05/01/2006	

SOFTPLAN
ARCHITECTURAL DESIGN SOFTWARE

WINDLOAD ENGINEER: Mark Disosway,
P.E. No. 53915, P.O. Box 868, Lake City, FL
32056, 386-754-5419

DIMENSIONS:
Stated dimensions supercede scaled
dimensions. Refer all questions to
Mark Disosway, P.E. for resolution.
Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:
Mark Disosway, P.E. hereby expressly reserves
its common law copyrights and property right in
these instruments of service. This document is
not to be reproduced, altered or copied in any
form or manner without first the express written
permission and consent of Mark Disosway.

CERTIFICATION: I hereby certify that I have
examined this plan, and that the applicable
portions of the plan, relating to wind engineering
comply with section F301.2.1, Florida building
code residential 2004, to the best of my
knowledge.

LIMITATION: This design is valid for one
building, at specified location.

MARK DISOSWAY
P.E. 53915

Mark Disosway
05/04/06
SEAL

**LYN & LYNNETTE
BURKS**

ADDRESS:
Blue Bird Landing S/D
Columbia County Florida

Mark Disosway P.E.
P.O. Box 868
Lake City, Florida 32056
Phone: (386) 754 - 5419
Fax: (386) 269 - 4871

PRINTED DATE:
May 05, 2006

DRAWN BY: Ben Sparks
STRUCTURAL BY: Ben Sparks

FINALS DATE:
05 / May / 06


JOB NUMBER:
602175

DRAWING NUMBER
A-1
OF 6 SHEETS

BUILDER IS TO PROVIDE AN UNOBSTRUCTED PASSAGEWAY TO A/C UNIT WHERE DIMENSIONS ARE LARGE ENOUGH TO ALLOW REMOVAL OF UNIT. THE PASSAGEWAY SHALL HAVE A CONTINUOUS SOLID FLOORING NOT LESS THAN 24" WIDE & A LEVEL SERVICE SPACE NO LESS THAN 30" x 30" IN FRONT OF THE UNIT. - THE UNIT IS TO BE LOCATED WITHIN 6" MAX. OF ACCESS DOOR. - A DEVICE IS INSTALLED TO ALERT THE OWNER OR SHUT THE UNIT DOWN WHEN THE CONDENSATION DRAIN IS NOT WORKING PROPERLY. - A NOTICE IS POSTED ON THE ELECTRIC SERVICE PANEL INDICATING TO THE HOMEOWNER THAT THE AIR HANDLER IS LOCATED IN THE ATTIC.

REVISIONS	
05/01/2006	

SOFTPLAN
ARCHITECTURAL DESIGN SOFTWARE



WINDLOAD ENGINEER: Mark Disosway
P.E. No. 53815, P.O. Box 868, Lake City, FL 32056, 386-754-5419

DIMENSIONS: Shaded dimensions supersede scaled dimensions. Refer all questions to Mark Disosway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS: Mark Disosway, P.E. hereby expressly reserves its common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disosway.

CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with section F501.2.1, Florida Building Code Residential 2004, to the best of my knowledge.

LIMITATION: This design is valid for one building, at specified location.

MARK DISOSWAY
P.E. 53815

Mark Disosway
SEAL

LYN & LYNNETTE
BURKS

ADDRESS:
Blue Bird Landing S/D
Columbia County Florida

Mark Disosway P.E.
P.O. Box 868
Lake City, Florida 32056
Phone: (386) 754 - 5419
Fax: (386) 269 - 4871

PRINTED DATE:
May 05, 2006

DRAWN BY: Ben Sparks
STRUCTURAL BY: Ben Sparks

FINALS DATE:
05 / May / 06

JOB NUMBER:
602175

DRAWING NUMBER

A-2
OF 6 SHEETS


AREA SUMMARY

LIVING AREA	2975	S . F .
LOFT AREA	306	S . F .
STORAGE AREA	366	S . F .
PORCH AREA	638	S . F .
TOTAL AREA	4285	S . F .

FLOOR PLAN

SCALE: 1/4" = 1'-0"

ALL CEILINGS TO BE 10' UNLESS NOTED OTHERWISE





TYPICAL DESIGN WALL SECTION NON - STRUCTURAL DATA

SCALE: 1" = 1'-0"

REVISIONS	
05/01/2006	

SOFTPLAN
ARCHITECTURAL DESIGN SOFTWARE



ELECTRICAL PLAN NOTES

- E -1 WIRE ALL APPLIANCES, HVAC UNITS AND OTHER EQUIPMENT PER MANUF. SPECIFICATIONS.
- E -2 CONSULT THE OWNER FOR THE NUMBER OF SEPERATE TELEPHONE LINES TO BE INSTALLED.
- E -3 ALL INSTALLATIONS SHALL BE PER NATL. ELECTRIC CODE.
- E -4 ALL SMOKE DETECTORS SHALL BE 120V W BATTERY BACKUP OF THE PHOTOELECTRIC TYPE, AND SHALL BE INTERLOCKED TOGETHER. INSTALL INSIDE AND NEAR ALL BEDROOMS.
- E -5 TELEPHONE, TELEVISION AND OTHER LOW VOLTAGE DEVICES OR OUTLETS SHALL BE AS PER THE OWNER'S DIRECTIONS, & IN ACCORDANCE W/ APPLICABLE SECTIONS OF NEC-LATEST EDITION.
- E -6 ELECTRICAL CONTR. SHALL BE RESPONSIBLE FOR THE DESIGN & SIZING OF ELECTRICAL SERVICE AND CIRCUITS.
- E -7 ENTRY OF SERVICE (UNDERGROUND OR OVERHEAD) TO BE DETERMINED BY POWER COMPANY.
- E -8 ALL BEDROOM RECEPTACLES SHALL BE AFCI (ARC FAULT CIRCUIT INTERRUPT)
- E -9 ALL OUTLETS TO BE LOCATED ABOVE BASE FLOOD ELEVATION
- E -10 A SERVICE DISCONNECT WITH OVER CURRENT PROTECTION SHALL BE INSTALLED OUTSIDE OF THE BUILDING, ON THE LOAD SIDE OF THE METER. AT THE PLACE ELECTRIC CONDUCTORS ENTER THE BUILDING. SERVICE ENTRANCE CONDUCTORS MAY NOT BE LOCATED INSIDE OF THE OF THE BUILDING WITHOUT SPECIAL APPROVAL OF THE BUILDING OFFICIAL.

ELECTRICAL LEGEND	
	CEILING FAN (PRE-WIRE FOR LIGHT KIT)
	DOUBLE SECURITY LIGHT
	2X4 FLUORESCENT LIGHT FIXTURE
	RECESSED CAN LIGHT
	BATH EXHAUST FAN WITH LIGHT
	BATH EXHAUST FAN
	LIGHT FIXTURE
	DUPLEX OUTLET
	220v OUTLET
	GFI DUPLEX OUTLET
	SMOKE DETECTOR
	WALL SWITCH
	3 WAY WALL SWITCH
	4 WAY WALL SWITCH
	WATER PROOF GFI OUTLET
	PHONE JACK
	TELEVISION JACK
	GARAGE DOOR OPENER
	WALL HEATER

WINDLOAD ENGINEER: Mark Disoway,
P.E. No. 53915, P.O. Box 868, Lake City, FL
32056, 386-754-5419

DIMENSIONS:
Stated dimensions supercede scaled dimensions. Refer all questions to Mark Disoway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:
Mark Disoway, P.E. hereby expressly reserves its common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disoway.

CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with section R301.2.1, Florida building code residential 2004, to the best of my knowledge.

LIMITATION: This design is valid for one building, at specified location.

MARK DISOWAY
P.E. 53915

Mark Disoway
05/01/06
SEAL

LYN & LYNNETTE
BURKS

ADDRESS:
Blue Bird Landing S/D
Columbia County Florida

Mark Disoway P.E.
P.O. Box 868
Lake City, Florida 32056
Phone: (386) 754 - 5419
Fax: (386) 269 - 4871

PRINTED DATE:
May 05, 2006

DRAWN BY: Ben Sparks STRUCTURAL BY: Ben Sparks


FINALS DATE:
05 / May / 06

JOB NUMBER:
602175

DRAWING NUMBER


A-3

OF 6 SHEETS




REVISIONS	
05/01/2006	


SOFTPLAN
ARCHITECTURAL DESIGN SOFTWARE




F2 S-2 INTERIOR BEARING FOOTING
SCALE: 1/2" = 1'-0"




F12 S-2 ALT. STEM WALL PORCH FOOTING
SCALE: 1/2" = 1'-0"




F5 S-2 PORCH FOOTING
SCALE: 1/2" = 1'-0"



F6 S-2 TYPICAL NON - BEARING STEP FOOTING
SCALE: 1/2" = 1'-0"



F9 S-2 STEM WALL FOOTING
SCALE: 1/2" = 1'-0"



FOUNDATION PLAN
SCALE: 1/4" = 1'-0"
DIMENSIONS ON STRUCTURAL SHEETS
ARE NOT EXACT. REFER TO ARCHITECTURAL
FLOOR PLAN FOR ACTUAL DIMENSIONS

TALL STEM WALL TABLE

The table assumes 60 ksi reinforcing bars with 6" hook in the footing and bent 24" into the reinforced slab at the top. The vertical steel is to be placed toward the tension side of the CMU wall (away from the soil pressure, within 2" of the exterior side of the wall). If the wall is over 8' high, add Durowall ladder reinforcement at 16"OC vertically or a horizontal bond beam with 1#5 continuous at mid height. For higher parts of the wall 12" CMU may be used with reinforcement as shown in the table below.

STEMWALL HEIGHT (FEET)	UNBALANCED BACKFILL HEIGHT	VERTICAL REINFORCEMENT FOR 8" CMU STEMWALL (INCHES O.C.)			VERTICAL REINFORCEMENT FOR 12" CMU STEMWALL (INCHES O.C.)		
		#5	#7	#8	#5	#7	#8
3.3	3.0	96	96	96	96	96	96
4.0	3.7	96	96	96	96	96	96
4.7	4.3	88	96	96	96	96	96
5.3	5.0	56	96	96	96	96	96
6.0	5.7	40	80	96	80	96	96
6.7	6.3	32	56	80	56	96	96
7.3	7.0	24	40	56	40	80	96
8.0	7.7	16	32	48	32	64	80
8.7	8.3	8	24	32	24	48	64
9.3	9.0	8	16	24	16	40	48

WINDLOAD ENGINEER: Mark Disoway, P.E. No.53915, POB 868, Lake City, FL 32056, 386-754-5419

DIMENSIONS:
Stated dimensions supersede scaled dimensions. Refer all questions to Mark Disoway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS:
Mark Disoway, P.E. hereby expressly reserves its common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disoway.

CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with section F301.2.1, Florida building code residential 2004, to the best of my knowledge.

LIMITATION: This design is valid for one building, at specified location.

MARK DISOWAY
P.E. 53915

Mark Disoway
05/04/06
SEAL

**LYN & LYNNETTE
BURKS**

ADDRESS:
Blue Bird Landing S/D
Columbia County Florida

Mark Disoway P.E.
P.O. Box 868
Lake City, Florida 32056
Phone: (386) 754 - 5419
Fax: (386) 269 - 4871


PRINTED DATE:
May 05, 2006
DRAWN BY: Ben Sparks
STRUCTURAL BY: Ben Sparks

FINALS DATE:
05 / May / 06


JOB NUMBER:
602175

DRAWING NUMBER
S-2
OF 6 SHEETS

REVISIONS	
05/01/2006	



BONUS ROOM / GABLE END BRACING
SCALE: 1/2"=1'-0"



THREADED ROD LEGEND

- INDICATES LOCATION OF:
1ST FLOOR 1/2" A307 ALL THREADED ROD
- INDICATES LOCATION OF:
2ND FLOOR 1/2" A307 ALL THREADED ROD

HEADER LEGEND

- HEADER/BEAM CALL-OUT (U.N.O.)
- NUMBER OF KING STUDS (FULL LENGTH)
- NUMBER OF JACK STUDS (UNDER HEADER)
- SPAN OF HEADER
- SIZE OF HEADER MATERIAL
- NUMBER OF PLIES IN HEADER

STRUCTURAL PLAN NOTES

- SN-1 ALL LOAD BEARING FRAME WALL & PORCH HEADERS SHALL BE A MINIMUM OF (2) 2X12 SYP#2 (U.N.O.)
- SN-2 ALL LOAD BEARING FRAME WALL HEADERS SHALL HAVE (1) JACK STUD & (1) KING STUD EACH SIDE (U.N.O.)
- SN-3 DIMENSIONS ON STRUCTURAL SHEETS ARE NOT EXACT. REFER TO ARCHITECTURAL FLOOR PLAN FOR ACTUAL DIMENSIONS
- SN-4 PERMANENT TRUSS BRACING IS TO BE INSTALLED AT LOCATIONS AS SHOWN ON THE SEALED TRUSS DRAWINGS. LATERAL BRACING IS TO BE RESTRAINED PER BCSI-03, BCSI-B1, BCSI-B2, & BCSI-B3. BCSI-B1, BCSI-B2, & BCSI-B3 ARE FURNISHED BY THE TRUSS SUPPLIER, WITH THE SEALED TRUSS PACKAGE

WALL LEGEND

SWS = 1.0'	1ST FLOOR EXTERIOR WALL
SWS = 0.0'	2ND FLOOR EXTERIOR
IBW	1ST FLOOR INTERIOR BEARING WALLS SEE DETAILS ON SHEET S-1
IBW	2ND FLOOR INTERIOR BEARING WALLS SEE DETAILS ON SHEET S-1

ALL CEILINGS TO BE 10' UNLESS NOTED OTHERWISE

STRUCTURAL PLAN
SCALE: 1/4" = 1'-0"

TOTAL SHEAR WALL SEGMENTS
SWS = 0.0' INDICATES SHEAR WALL SEGMENTS

	REQUIRED	ACTUAL
TRANSVERSE	33.0'	84.0'
LONGITUDINAL	30.0'	83.0'

WINDLOAD ENGINEER: Mark Disoway, P.E. No. 53815, FOS 868, Lake City, FL 32056, 386-754-5419

DIMENSIONS: Stated dimensions supercede scaled dimensions. Refer all questions to Mark Disoway, P.E. for resolution. Do not proceed without clarification.

COPYRIGHTS AND PROPERTY RIGHTS: Mark Disoway, P.E. hereby expressly reserves its common law copyrights and property right in these instruments of service. This document is not to be reproduced, altered or copied in any form or manner without first the express written permission and consent of Mark Disoway.

CERTIFICATION: I hereby certify that I have examined this plan, and that the applicable portions of the plan, relating to wind engineering comply with section R301.2.1, Florida building code residential 2004, to the best of my knowledge.

LIMITATION: This design is valid for one building, at specified location.

MARK DISOWAY
P.E. 53815

LYN & LYNNETTE BURKS

ADDRESS:
Blue Bird Landing S/D
Columbia County Florida

Mark Disoway P.E.
P.O. Box 868
Lake City, Florida 32056
Phone: (386) 754 - 5419
Fax: (386) 269 - 4871

PRINTED DATE:
May 05, 2006

DRAWN BY: Ben Sparks STRUCTURAL BY: Ben Sparks


FINALS DATE:
05 / May / 06

JOB NUMBER:
602175

DRAWING NUMBER
S-3
OF 6 SHEETS

CONNECTIONS, WALL, & HEADER DESIGN IS BASED ON REACTIONS & UPLIFTS FROM TRUSS ENGINEERING FURNISHED BY BUILDER. BUILDERS FIRSTSOURCE CO. (JOB #L159830)

A BOUNDARY SURVEY IN:
SECTION 31, TOWNSHIP 7 SOUTH, RANGE 17 EAST,
COLUMBIA COUNTY, FLORIDA.



NOTE: ALL PROPERTY CORNERS LOCATED ARE IDENTIFIED AS L.E. BRITT, P.L.S. 1079.

CURVE TABLE

NO.	RADIUS	DELTA	ARC	TANGENT	CHORD	CHORD BEARING
1	105.00'	42°33'27"	77.99'	40.69'	76.21'	S.23°02'04"E
2	135.00'	19°24'42"	45.74'	23.09'	45.52'	S.12°11'06"E
3	25.00'	108°01'19"	47.13'	34.42'	40.46'	N.32°44'13"E

SYMBOL LEGEND

4"x4" CONCRETE MONUMENT FOUND	4"x4" CONCRETE MONUMENT SET
IRON PIPE FOUND	IRON PIN AND CAP SET
POWDER POLE	WATER METER
CENTERLINE	WELL
SATELLITE DISH	TELEPHONE BOX
ELECTRIC LINES	WIRE FENCE
CHAIN LINK FENCE	WOODEN FENCE

SCALE: 1" = 100'

DESCRIPTION: PARCEL 17
A PART OF THE W 1/2 OF SECTION 31, TOWNSHIP 7 SOUTH, RANGE 17 EAST, BEING MORE PARTICULARLY DESCRIBED AS FOLLOWS: COMMENCE AT THE NW CORNER OF SAID SECTION 31, AND RUN THENCE S.01°41'00"E, ALONG THE WEST LINE OF SAID SECTION 31, A DISTANCE OF 1884.99 FEET, THENCE N.88°18'50"E, A DISTANCE OF 814.42 FEET TO THE POINT OF BEGINNING, THENCE N.01°45'20"W, A DISTANCE OF 359.61 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE LEFT, HAVING A RADIUS OF 105.00 FEET, A CENTRAL ANGLE OF 42°33'27", A TANGENT LENGTH OF 40.69 FEET, A CHORD BEARING OF N.23°02'04"E, AND A CHORD LENGTH OF 76.21 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC LENGTH OF 77.99 FEET TO THE POINT OF TANGENCY OF SAID CURVE, THENCE N.44°18'47"W, A DISTANCE OF 46.97 FEET, THENCE N.86°39'38"E, A DISTANCE OF 616.14 FEET, THENCE S.02°07'36"E, A DISTANCE OF 775.52 FEET, THENCE S.86°23'44"W, A DISTANCE OF 561.79 FEET, THENCE N.01°45'20"W, A DISTANCE OF 311.37 FEET TO THE POINT OF BEGINNING, PARCEL CONTAINS 10.02 ACRES, MORE OR LESS.

DESCRIPTION: EASEMENT
AN EASEMENT FOR INGRESS AND EGRESS, BEING 60 FEET IN WIDTH AND LYING 30 FEET TO THE LEFT AND 30 FEET TO THE RIGHT, AS MEASURED PERPENDICULAR TO THE FOLLOWING DESCRIBED CENTERLINE, COMMENCE AT THE NE CORNER OF THE NW 1/4 OF SECTION 31, TOWNSHIP 7 SOUTH, RANGE 17 EAST, COLUMBIA COUNTY, FLORIDA, AND RUN THENCE S.87°14'55"W, ALONG THE NORTH LINE OF SAID SECTION 31, A DISTANCE OF 757.64 FEET TO A POINT ON THE SOUTHERLY RIGHT-OF-WAY LINE OF A COUNTY MAINTAINED GRADE ROAD, SAID POINT BEING THE POINT OF BEGINNING, THENCE S.01°47'48"E, A DISTANCE OF 114.27 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE LEFT HAVING A RADIUS OF 2300.00 FEET, A CENTRAL ANGLE OF 55°09'08", A TANGENT LENGTH OF 120.18 FEET, A CHORD BEARING OF S.29°22'22"E, AND A CHORD LENGTH OF 212.95 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 281.39 FEET TO A POINT OF REVERSE CURVE OF A CURVE TO THE RIGHT, HAVING A RADIUS OF 1700.00 FEET, A CENTRAL ANGLE OF 72°58'42", A TANGENT LENGTH OF 125.74 FEET, A CHORD BEARING OF S.20°27'35"E, AND A CHORD LENGTH OF 208.19 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 216.53 FEET, THENCE S.16°01'48"W, A DISTANCE OF 288.20 FEET TO A POINT HEREINAFTER REFERRED TO AS POINT "A", SAID POINT ALSO BEING THE POINT OF CURVATURE OF A CURVE TO THE LEFT, HAVING A RADIUS OF 3000.00 FEET, A CENTRAL ANGLE OF 16°57'20", A TANGENT LENGTH OF 44.72 FEET, A CHORD BEARING OF S.07°33'38"W, AND A CHORD LENGTH OF 88.46 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 88.78 FEET, THENCE S.00°55'34"E, A DISTANCE OF 223.29 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE LEFT HAVING A RADIUS OF 2700.00 FEET, A CENTRAL ANGLE OF 09°39'10", A TANGENT LENGTH OF 26.40 FEET, A CHORD BEARING OF S.05°40'09"E, AND A CHORD LENGTH OF 44.63 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 44.70 FEET, THENCE S.10°24'44"E, A DISTANCE OF 143.54 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE RIGHT, HAVING A RADIUS OF 3300.00 FEET, A CENTRAL ANGLE OF 15°15'21", A TANGENT LENGTH OF 44.19 FEET, A CHORD BEARING OF S.02°47'03"E, AND A CHORD LENGTH OF 87.61 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 87.87 FEET, THENCE S.04°50'27"W, A DISTANCE OF 125.00 FEET TO A POINT HEREINAFTER REFERRED TO AS POINT "B", THENCE CONTINUE S.04°50'37"W, A DISTANCE OF 58.27 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE LEFT, HAVING A RADIUS OF 8000 FEET, A CENTRAL ANGLE OF 25°22'17", A TANGENT LENGTH OF 160.14 FEET, A CHORD BEARING OF S.07°30'29"E, AND A CHORD LENGTH OF 351.4 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 354.49 FEET, THENCE S.02°31'41"E, A DISTANCE OF 284.45 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE RIGHT, HAVING A RADIUS OF 3000.00 FEET, A CENTRAL ANGLE OF 19°54'39", A TANGENT LENGTH OF 52.66 FEET, A CHORD BEARING OF S.10°34'21"E, AND A CHORD LENGTH OF 103.73 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 104.25 FEET, THENCE S.00°37'02"E, A DISTANCE OF 176.66 FEET TO A POINT TO A POINT HEREINAFTER REFERRED TO AS POINT "C", THENCE CONTINUE S.00°37'02"E, A DISTANCE OF 266.23 FEET TO THE POINT OF CURVATURE OF A CURVE, HAVING A RADIUS OF 15000 FEET, A CENTRAL ANGLE OF 47°59'58", A TANGENT LENGTH OF 125.62 FEET, A CHORD BEARING OF S.47°21'56"W, A DISTANCE OF 70.00 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE LEFT, HAVING A RADIUS OF 15000 FEET, A CENTRAL ANGLE OF 59°35'13", A TANGENT LENGTH OF 94.15 FEET, A CHORD BEARING OF S.18°04'19"W, AND A CHORD LENGTH OF 146.78 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 153.39 FEET, THENCE S.11°15'17"E, A DISTANCE OF 203.89 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE RIGHT, HAVING A RADIUS OF 15000 FEET, A CENTRAL ANGLE OF 43°09'40", A TANGENT LENGTH OF 59.33 FEET, A CHORD BEARING OF S.12°12'33"W, AND A CHORD LENGTH OF 110.34 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 113.00 FEET, THENCE S.31°56'25"W, A DISTANCE OF 185.61 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE LEFT, HAVING A RADIUS OF 3300.00 FEET, A CENTRAL ANGLE OF 12°59'20", A TANGENT LENGTH OF 37.37 FEET, A CHORD BEARING OF S.25°26'43"W, AND A CHORD LENGTH OF 74.65 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 74.81 FEET TO A POINT HEREINAFTER REFERRED TO AS POINT "D", SAID POINT BEING A POINT OF TERMINATION OF SAID CENTERLINE, THENCE BEGIN AT THE AFOREMENTIONED POINT "A", AND RUN THENCE N.81°32'45"E, A DISTANCE OF 701.09 FEET, THENCE N.87°14'29"E, A DISTANCE OF 627.20 FEET TO THE RADIUS POINT OF A 50 FOOT CUL-DE-SAC, SAID POINT BEING A POINT OF TERMINATION OF SAID CENTERLINE, THENCE BEGIN AT A AFOREMENTIONED POINT "B", AND RUN THENCE S.84°04'22"W, A DISTANCE OF 140.14 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE RIGHT, HAVING A RADIUS OF 3000.00 FEET, A CENTRAL ANGLE OF 29°28'54", A TANGENT LENGTH OF 78.93 FEET, A CHORD BEARING OF N.81°11'11"W, AND A CHORD LENGTH OF 152.67 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 154.37 FEET, THENCE N.66°26'45"W, A DISTANCE OF 156.72 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE LEFT, HAVING A RADIUS OF 3300.00 FEET, A CENTRAL ANGLE OF 16°57'20", A TANGENT LENGTH OF 44.72 FEET, A CHORD BEARING OF N.79°53'33"W, AND A CHORD LENGTH OF 153.48 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 154.90 FEET, THENCE S.86°39'38"W, A DISTANCE OF 616.14 FEET TO A POINT HEREINAFTER REFERRED TO AS POINT "C", THENCE N.44°18'47"W, A DISTANCE OF 17.12 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE RIGHT, HAVING A RADIUS OF 2000.00 FEET, A CENTRAL ANGLE OF 42°00'37", A TANGENT LENGTH OF 78.03 FEET, A CHORD BEARING OF N.28°59'59"W, AND A CHORD LENGTH OF 145.39 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 148.80 FEET, THENCE N.01°41'10"W, A DISTANCE OF 565.91 FEET TO THE RADIUS POINT OF A 50 FOOT CUL-DE-SAC, SAID POINT BEING A POINT OF TERMINATION OF SAID CENTERLINE, THENCE RETURNING TO THE AFOREMENTIONED POINT "C", AND RUN THENCE S.44°18'47"W, A DISTANCE OF 46.97 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE RIGHT, HAVING A RADIUS OF 1050.00 FEET, A CENTRAL ANGLE OF 42°33'27", A TANGENT LENGTH OF 40.69 FEET, A CHORD BEARING OF S.23°02'04"E, AND A CHORD LENGTH OF 76.21 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 77.99 FEET, THENCE S.01°45'20"E, A DISTANCE OF 1970.74 FEET TO THE RADIUS POINT OF A 50 FOOT CUL-DE-SAC, SAID POINT BEING A POINT OF TERMINATION OF SAID CENTERLINE, THENCE BEGIN AT THE AFOREMENTIONED POINT "C", AND RUN THENCE N.85°13'54"E, A DISTANCE OF 93.53 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE LEFT, HAVING A RADIUS OF 3000.00 FEET, A CENTRAL ANGLE OF 19°54'39", A TANGENT LENGTH OF 52.66 FEET, A CHORD BEARING OF N.78°11'07"E, AND A CHORD LENGTH OF 72.39 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC LENGTH OF 72.57 FEET, THENCE N.71°28'21"E, A DISTANCE OF 354.70 FEET, THENCE N.77°56'34"E, 62.17 FEET, THENCE S.66°25'47"E, A DISTANCE OF 207.86 FEET, THENCE S.89°03'47"E, 142.06 FEET, THENCE N.87°13'37"E, A DISTANCE OF 301.36 FEET TO THE RADIUS POINT OF A 50 FOOT CUL-DE-SAC, SAID POINT BEING A POINT OF TERMINATION OF SAID CENTERLINE, THENCE BEGIN AT THE AFOREMENTIONED POINT "D", AND RUN THENCE N.71°02'57"W, A DISTANCE OF 6.24 FEET, THENCE S.19°16'58"W, A DISTANCE OF 21.70 FEET, THENCE S.78°18'51"E, A DISTANCE OF 780.47 FEET TO THE POINT OF CURVATURE OF A CURVE TO THE LEFT, HAVING A RADIUS OF 3000.00 FEET, A CENTRAL ANGLE OF 20°12'26", A TANGENT LENGTH OF 30.82 FEET, A CHORD BEARING OF S.88°32'34"E, AND A CHORD LENGTH OF 177.59 FEET, THENCE ALONG THE ARC OF SAID CURVE, AN ARC DISTANCE OF 178.52 FEET, THENCE N.87°13'43"E, A DISTANCE OF 541.88 FEET TO THE RADIUS POINT OF A 50 FOOT CUL-DE-SAC, HEREINAFTER KNOWN AS POINT "F", THENCE CONTINUING FROM POINT "F", FOLLOWING THE LOT LINE BETWEEN LOTS 36 AND 41, S.01°26'00"W, A DISTANCE OF 537.38 FEET TO POINT "G", RUN THENCE S.13°29'22"W, A DISTANCE OF 679.83 FEET TO A RADIUS POINT OF A 5000 FOOT CUL-DE-SAC AND THE POINT OF TERMINATION OF SAID EASEMENT, ALSO AN EASEMENT 40.00 FEET IN WIDTH LYING TO THE RIGHT OF THE FOLLOWING DESCRIBED LINE, COMMENCE AT THE ABOVE MENTIONED POINT "G", AND RUN N.01°36'50"E, A DISTANCE OF 230.00 FEET FOR A POINT OF BEGINNING, THENCE RUN S.82°05'06"E, A DISTANCE OF 641.91 FEET, THENCE N.85°57'47"E, 105.01 FEET TO THE NORTHWEST CORNER OF THE SE 1/4 OF THE SE 1/4 OF SAID SECTION 31, THENCE CONTINUE N.85°57'47"E, A DISTANCE OF 141.00 FEET, THENCE CONTINUE N.85°57'47"E, A DISTANCE OF 459.82 FEET TO THE TERMINATION OF SAID EASEMENT.

SURVEYOR'S NOTES:

- BOUNDARY BASED ON MONUMENTATION FOUND IN ACCORDANCE WITH THE RETRACEMENT OF A PREVIOUS SURVEY BY THIS OFFICE.
- BEARINGS ARE BASED ON SAID PREVIOUS SURVEY BY THIS OFFICE.
- THIS PARCEL IS IN ZONE "X" AND IS DETERMINED TO BE OUTSIDE THE 300 YEAR FLOOD PLAIN AS PER FLOOD RATE MAP, DATED 5 JANUARY, 1980 COMMUNITY PANEL NUMBER 120070 0270 B, HOWEVER, THE FLOOD INSURANCE RATE MAPS ARE SUBJECT TO CHANGE.
- THE IMPROVEMENTS, IF ANY, INDICATED ON THIS SURVEY DRAWING ARE AS LOCATED ON DATE OF FIELD SURVEY AS SHOWN HEREDIN.
- IF THEY EXIST, NO UNDERGROUND ENCROACHMENTS AND/OR UTILITIES WERE LOCATED FOR THIS SURVEY EXCEPT AS SHOWN HEREDIN.
- THIS SURVEY WAS COMPLETED WITHOUT THE BENEFIT OF A TITLE COMMITMENT OR A TITLE POLICY.

BRITT SURVEYING

CERTIFIED TO:

LYNETTE BURKS & LYN BURKS

FIELD BOOK: 285 PAGE(S): 65

JOB NUMBER: L-17219

SHEET
1 of 1

I HEREBY CERTIFY THAT THIS SURVEY WAS MADE UNDER MY RESPONSIBLE CHARGE AND MEETS THE MINIMUM TECHNICAL STANDARDS AS SET FORTH BY THE FLORIDA BOARD OF PROFESSIONAL SURVEYORS AND MAPPERS IN CHAPTER 6007-6, FLORIDA ADMINISTRATIVE CODE, PURSUANT TO SECTION 472.027, FLORIDA STATUTES.


DATE OF SURVEY: 03/20/06
DATE OF CERTIFICATION: 04/07/06
FIELD SURVEY DATE: 03/20/06
DATE OF CERTIFICATION: 04/07/06

NOTE: UNLESS IT BEARS THE SIGNATURE AND THE ORIGINAL RAISED SEAL OF A FLORIDA LICENSED SURVEYOR AND MAPPER, THIS DRAWING, SKETCH, PLAN OR MAP IS FOR INFORMATIONAL PURPOSES ONLY AND IS NOT VALID.




LAND SURVEYORS AND MAPPERS
830 WEST DUVAL STREET
LAKE CITY, FLORIDA 32055
TELEPHONE: (386) 752-7163 FAX: (386) 752-5573


Copyright © 1999 HEDJ Engineering, Inc. THESE PLANS AND DESIGNS ARE THE PROPERTY OF HEDJ ENGINEERING, INC. AND MAY NOT BE REPRODUCED OR OTHERWISE USED WITHOUT THE EXPRESS WRITTEN PERMISSION OF HEDJ ENGINEERING, INC. THIS DOCUMENT IS PROTECTED BY SECTION 100 OF THE UNITED STATES PATENT AND TRADEMARK ACT. ANY UNAUTHORIZED REPRODUCTION OR USE OF THIS DOCUMENT IS PROHIBITED WITHOUT WRITTEN CONSENT OF HEDJ ENGINEERING.




LANDING DETAIL R
NTS (SEE NOTE 16)




LANDING STIFFENER S
NTS




LANDING RAIL T
NTS




TYPICAL WOOD RAIL SECTION U
NTS




DETAIL V
NTS




STARTING POST
NTS




90 DEG LANDING PLAN L
1" = 1'-0"




60 DEG LANDING PLAN F
1" = 1'-0"




TYPICAL RAILING M
1" = 1'-0"




SPINDLE N
1/2" = 1"




DETAIL P
1/2" = 1"




SECTION H
NTS




SECTION J
1-1/2" = 1'-0"




SECTION K
NTS
COLUMN BASE




TYPICAL ELEVATION A
1/2" = 1'-0"




FAN GRATE TREAD B
1-1/2" = 1'-0"



TYPICAL COLLAR C
NTS



SECTION E
NTS
COLUMN BASE



STAIR NOTES

1. LANDING IS REVERSIBLE. 60 OR 90 DEGREE EDGE OF LANDING MAY BE USED FOR TOP STP.
2. 8.9" MINIMUM RISER HEIGHT REQUIRED FOR HEADROOM BELOW SQUARE LANDING.
3. IF DOORWAY OCCURS AT LANDING, A LARGER LANDING MAY BE REQUIRED. SEE NOTE 16 & DETAIL R.

TREAD, COLUMN & FOOTING SCHEDULE									
INTERMEDIATE 3/4", 16 GA PICKETS	STAIR DIAMETER "D"	TREAD "R"	COLUMN "C"	PIPE DIA & TYPE	MAX LOAD KIPS	CONC PAD "W"	SOIL BEARING VALUE 1000 PSF 1500 PSF	SLEEVE X 6" LONG	
3 @ 3.26"	5'-0"	2'-6"	14'-3/4"	3" STD	2.70	3'-1/2"	20"	16"	3 1/2" STD
3 @ 4.25"	6'-0"	3'-0"	17'-3/4"	3" STD	3.27	3'-1/2"	22"	17"	3 1/2" STD
3 @ 4.64"	6'-0"	3'-0"	17'-3/4"	3" EXT STRONG	3.99	3'-1/2"	24"	18"	3 1/2" STD
3 @ 4.04"	6'-0"	3'-0"	19'-3/8"	4" STD	4.56	3'-1/2"	26"	19"	4" STD
3 @ 4.34"	7'-0"	3'-6"	21'-3/8"	4" EXT STRONG	5.23	3'-1/2"	28"	21"	4" STD

GENERAL NOTES

1. CONTRACTOR SHALL VERIFY ALL CONDITIONS AND DIMENSIONS AT THE JOB SITE.
2. SOIL BEARING MAXIMUM - 1500 LBS PER SQ FT (ASSUMED).
3. SOIL BEARING MINIMUM - 1000 LBS PER SQ FT (ASSUMED).
4. CONCRETE FOR NEW FOOTINGS SHALL BE STANDARD MIX, 2500 PSI @ 28 DAYS.
5. STRUCTURAL STEEL PLATES & BARS SHALL BE ASTM A-36 (OR HIGHER) YIELD STRENGTH.
6. PIPE COLUMNS & SLEEVES SHALL BE ASTM A-53 GRADE B.
7. STEEL TUBES SHALL BE ASTM A500-GRADE C (Fy = 50 KSI).
8. BOLTS: ASTM A-307, RED HEAD (RR #2748), SET SCREWS: ASTM F912.
9. RAIL: ALUMINUM ALLOY 3003-H14 - 0.125" THICK X 1-1/2" O.D. TUBE.
10. WELDING SHALL BE PER U.B.C. USING SHIELDED METAL ARC PROCESS W/ E70XX.
11. ELECTRODES IN AN APPROVED FABRICATOR'S SHOP.
12. ALL FABRICATION SHALL BE DONE IN THE SHOP OF A LICENSED FABRICATOR OF THE STATE OF FLORIDA.
13. STAIRWAYS SHALL CONFORM TO THE 1991 EDITION OF THE U.B.C., SECTION 3306 & THE STANDARD BUILDING CODE, LATEST EDITION, & SOUTHERN FLORIDA B.C. AND LATEST 1007.8.2.3.
14. SPIRAL STAIRWAYS MAY BE INSTALLED ONLY IN 1 & 2 FAMILY DWELLINGS AND IN PRIVATE STAIRWAYS WITHIN INDIVIDUAL UNITS. SUCH STAIRWAYS MAY BE USED FOR REQUIRED EXITS WHEN THE AREA SERVED IS LIMITED TO 400 SQ. FT. (NOTE THAT A PRIVATE STAIRWAY IS A STAIRWAY THAT SERVES A SINGLE TENANT. A SINGLE TENANT MAY BE ONE OR MORE OCCUPANTS.)
15. SPIRAL STAIRWAYS MAY ALSO BE INSTALLED IN ANY OCCUPANCY WHERE THEY ARE USED ONLY TO ATTEND EQUIPMENT & NEED NOT HAVE HANDRAILS OR GUARDRAILS. FOR THE APPROVED OCCUPANCIES, HANDRAIL EXTENSIONS ARE NOT REQUIRED.
16. PROVIDE MINIMUM 30" WALKING AREA FROM OUTER EDGE OF SUPPORT COLUMN TO INNER EDGE OF HANDRAIL. 1/2" MINIMUM RUN AT A POINT 12" FROM WHERE THE TREAD IS NARROWEST MINIMUM 6'-6" HEADROOM, & RISE NOT TO EXCEED 9 1/2".
17. THE TOP OF GUARDRAILS SHALL BE 36" - 42" IN HEIGHT. OPEN GUARDRAILS SHALL HAVE INTERMEDIATE RAILS OR AN ORNAMENTAL PATTERN SUCH THAT A 4" SPHERE CANNOT PASS THROUGH.
18. HANDRAILS SHALL BE CONTINUOUS THE FULL LENGTH OF THE STAIRS. FOR PRIVATE STAIRWAYS, HANDRAILS ARE NOT REQUIRED TO EXTEND 12" BEYOND THE TOP OR BOTTOM RISER PER U.B.C. SECTIONS 3306(I) & 3301.
19. LANDINGS & LANDINGS AT DOORS SHALL COMPLY WITH U.B.C. SECTIONS 3306(G) & 3304(J). STAIRS SERVING AN UNOCCUPIED ROOF OR STAIRS USED ONLY TO ATTEND EQUIPMENT ARE EXEMPT FROM THESE PROVISIONS.
20. REDUCED PLANS OR POOR QUALITY PRINTS (100 DARK OR TOO LIGHT) WILL NOT BE ACCEPTABLE FOR OBTAINING A BUILDING PERMIT.

HEDJ Engineering Inc.

HOME OFFICE
1487 Second Street, Suite 208
Orlando, FL 32806
(407) 925-5948

BRANCH OFFICES
ORLANDO
VERO BEACH

2.21.03 HRW
2.21.03 HRW

2.21.03 HRW
2.21.03 HRW

1
00-30

1
00-30