## Envelope Leakage Test Report (Blower Door Test) Residential Prescriptive, Performance or ERI Method Compliance 2020 Florida Building Code, Energy Conservation, 7th Edition

Jurisdiction: Columbia	Permit #:	43364	
Job Information Avata			
Builder: Bryan Zecher Community: We	sterwoods *	Lot:	NA- 17
Address: 137 SW Phlox Glen			
City: lake City State	: FL	Zip: 32	2024
Air Leakage Test Results Passing results must meet either the Performance, Prescriptive, or ERI Method			
PRESCRIPTIVE METHOD-The building or dwelling unit shall be tested and verified as having an air leakage rate of not exceeding 7 air changes per hour at a pressure of 0.2 inch w.g. (50 Pascals) in Climate Zones 1 and 2.  PERFORMANCE or ERI METHOD-The building or dwelling unit shall be tested and verified as having an air leakage rate of not exceeding the selected ACH(50) value, as shown on Form R405-2020 (Performance) or R406-2020 (ERI), section labeled as infiltration, sub-section ACH50.  ACH(50) specified on Form R405-2020-Energy Calc (Performance) or R406-2020 (ERI):			
ACH(50) specified on Form R403-2020-Energy Can  The specified on Form R403-2020-Energy Can  The specified of Form R403-2020-Energy Can  The specified of Form R403-2020-Energy Can  The specified of Form R403-2020-Energy Can  ACH(50)  The specified of Form R403-Energy Can  ACH(50)  The	_	Method for calculated Retrieved from Code software	ting building volume:
R402.4.1.2 Testing. Testing shall be conducted in accordance with ANSI/RESNET/ICC 380 and reported at a pressure of 0.2 inch w.g. (50 Pascals). Testing shall be conducted by either individuals as defined in Section 553.993(5) or (7), Florida Statues.or individuals licensed as set forth in Section 489.105(3)(f), (g), or (i) or an approved third party. A written report of the results of the test shall be signed by the party conducting the test and provided to the code official. Testing shall be performed at any time after creation of all penetrations of the building thermal envelope.  During testing:  1. Exterior windows and doors, fireplace and stove doors shall be closed, but not sealed, beyond the intended weatherstripping or other infiltration control measures.  2. Dampers including exhaust, intake, makeup air, back draft and flue dampers shall be closed, but not sealed beyond intended infiltration control measures.  3. Interior doors, if installed at the time of the test, shall be open.  4. Exterior doors for continuous ventilation systems and heat recovery ventilators shall be closed and sealed.  5. Heating and cooling systems, if installed at the time of the test, shall be fully open.			
Testing Company			
Company Name: TC Testing Service LLC I hereby verify that the above Air Leakage results are in accordant Energy Conservation requirements according to the compliance in Signature of Tester:  Printed Name of Tester: Tanya C. Sikes  License/Certification #: 5059953	ce with the 2020 7 nethod selected at	of Test: 8-1	uilding Code