

#51889

2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27

#51889





Prime

Prime

#51889

La resistencia al desliz puede variar de acuerdo a las condiciones de la superficie, tipo de calzado y condiciones de la temperatura.

Slip resistance may vary with surface conditions, weather, footwear and temperature.

Generon Peak Roofing & Siding, Inc.
800-561-9121
www.generonpeak.com

generonpeak.com



Slip resistance may vary with surface conditions, weather, footwear and roof pitch.
La resistencia al desliz puede variar de acuerdo a las condiciones de la superficie, tipo de calzado o clima y la pendiente del techo.
Le degré de résistance au glissement peut varier dépendant de la température, chaussures utilisées et le toit pente.

MEETS / SATISFAIT / ASTM D4836 TYPE IV, ASTM D6837
CALIFORNIA FIRE PASS / CALIFORNIA FIRE PASS
FORMA FIRE PASS APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

24 321C

MEETS / SATISFAIT / ASTM D4836 TYPE IV, ASTM D6837
CALIFORNIA FIRE PASS / CALIFORNIA FIRE PASS
FORMA FIRE PASS APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

MEETS / SATISFAIT / ASTM D4836 TYPE IV, ASTM D6837
CALIFORNIA FIRE PASS / CALIFORNIA FIRE PASS
FORMA FIRE PASS APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

MEETS / SATISFAIT / ASTM D4836 TYPE IV, ASTM D6837
CALIFORNIA FIRE PASS / CALIFORNIA FIRE PASS
FORMA FIRE PASS APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

MEETS / SATISFAIT / ASTM D4836 TYPE IV, ASTM D6837
CALIFORNIA FIRE PASS / CALIFORNIA FIRE PASS
FORMA FIRE PASS APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727




MEETS / SATISFAIT / ASTM D4836 TYPE IV, ASTM D6837
CALIFORNIA FIRE PASS / CALIFORNIA FIRE PASS
FORMA FIRE PASS APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

MEETS / SATISFAIT / ASTM D4836 TYPE IV, ASTM D6837
CALIFORNIA FIRE PASS / CALIFORNIA FIRE PASS
FORMA FIRE PASS APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

MEETS / SATISFAIT / ASTM D4836 TYPE IV, ASTM D6837
CALIFORNIA FIRE PASS / CALIFORNIA FIRE PASS
FORMA FIRE PASS APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

MEETS / SATISFAIT / ASTM D4836 TYPE IV, ASTM D6837
CALIFORNIA FIRE PASS / CALIFORNIA FIRE PASS
FORMA FIRE PASS APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

Slip resistance may vary with surface conditions, weather, footwear and roof pitch.
La resistencia al desliz puede variar de acuerdo a las condiciones de la superficie, tipo de calzado o clima y la pendiente del techo.
Le degré de résistance au glissement peut varier dépendant de la température, chaussures utilisées et le toit pente.





100%
OZON

Rhino

100%
OZON

Rhino

100%
OZON

eavetoppeak.com/RhinoRoof | 800-567-9727

eavetoppeak.com/RhinoRoof | 800-567-9727

eavetoppeak.com/RhinoRoof | 800-567-9727

eavetoppeak.com/RhinoRoof | 800-567-9727

eavetoppeak.com/RhinoRoof | 800-567-9727

eavetoppeak.com/RhinoRoof | 800-567-9727


eavetoppeak

4002616 25102223 627 L

4002616 25102223 627 L

MEETS / SATISFAIT : ASTM D226 TYPE IV, ASTM D4859 TYPE IV, ASTM D5257
CAN/CSA A122.3 & A220.1
FLORIDA PRODUCT APPROVAL

MEETS / SATISFAIT : ASTM D226 TYPE IV, ASTM D4859 TYPE IV, ASTM D5257
CAN/CSA A122.3 & A220.1
FLORIDA PRODUCT APPROVAL



La resistencia al desliz puede variar de acuerdo a las condiciones de la superficie, tipo de calzado o clima y la pendiente del techo
Le degré de résistance au glissement peut varier dépendant de la température, chaussures utiliser et le toit pente



Slip resistance may vary with surface conditions, weather, footwear and roof pitch
La resistencia al desliz puede variar de acuerdo a las condiciones de la superficie, tipo de calzado o clima y la pendiente del techo
Le degré de résistance au glissement peut varier dépendant de la température, chaussures utiliser et le toit pente

eavetoppeak



Slip resistance may vary with surface conditions, weather, footwear and roof pitch
La resistencia al desliz puede variar de acuerdo a las condiciones de la superficie, tipo de calzado o clima y la pendiente del techo
Le degré de résistance au glissement peut varier dépendant de la température, chaussures utiliser et le toit pente

MADE IN CANADA
APPROVED

MEETS / SATISFAIT : ASTM D226 TYPE IV, ASTM D4859 TYPE IV, ASTM D5257
CAN/CSA A122.3 & A220.1
FLORIDA PRODUCT APPROVAL