Manufacturer Address
HOMES OF MERIT, INC.
P.O. BOX 2097
LAKE CITY FL 32056

Plant Number 3

Date of Manufacture	HUD Label No.(s)
9/28/00	FLA 697157-B, FLA 697158-A

Manufacturer's Serial Number and Model Unit Designation
FLRML3P1580-23962AB

Owner/Lessee: [illegible] CARTER
[illegible] WHITE STRIPE AVENUE
CLEARWATER FL 33519

This manufactured home is designed to comply with the federal manufactured home construction and safety standards in force at time of manufacture.
(For additional information, consult owner's manual.)

The factory installed equipment includes:

Equipment	Manufacturer	Model Designation
For heating		
For air cooling		
For cooking	GE	JBP78WBWW
Refrigerator	GE	TFX20JRBWW
Water Heater	STATE	SCV402RMSE
Washer		
Clothes Dryer		
Dishwasher	GE	GSD3230PWW
Garbage Disposal		
Fire Alarm	SMOKE DETECTOR FIREX	H
	MICROWAVE GE	JVM1640WB
	WATER FILTER GE	GNUT05B

HOME CONSTRUCTED FOR ☐ Zone I ☒ Zone II ☐ Zone III

This home has not been designed for the higher wind pressure and uplifting forces required for manufactured homes and should not be located within 1500' of the coastline in Wind Zones II and III, unless the home's anchoring and foundation system has been designed for the increased requirements specified in Appendix D of 24 CFR 3280.306(c)(1)(ii).

This home has ___ has not ___ been equipped with shade shutters or other protective coverings for windows and exterior door openings. For homes designed to be located in Wind Zones II and III, which have not been provided with shutters or equivalent covering devices, it is strongly recommended that the home be made ready to be equipped with these devices in accordance with the method recommended in manufacturers owners instructions.

BASIC WIND ZONE MAP

DESIGN ROOF LOAD ZONE MAP

North 40 PSF South 30 PSF
Middle 30 PSF Other ___ PSF

COMFORT HEATING

This manufactured home has been thermally insulated to conform with the requirements of the federal manufactured home construction and safety standards for all locations within U/O value zone I (See map at bottom)

Heating equipment manufacturer and model (See list at left).
The above heating equipment has the capacity to maintain an average 70° F temperature in this home at outdoor temperatures of ___ °F.
To maximize furnace operating economy, and to conserve energy, it is recommended that this home be installed where the outdoor winter design temperature (97 1/2%) is not higher than ___ degrees Fahrenheit.
The above information has been calculated assuming a maximum wind velocity of 15 mph at standard atmospheric pressure.

COMFORT COOLING

☐ Air conditioner provided at factory (Alternate I)

Air conditioner manufacturer and model (see list at left).
Certified capacity ___ B.T.U./hour in accordance with the appropriate air conditioning and refrigeration institute standards.
The nominal air conditioning system provided in this home has been sized assuming an orientation of the front (hitch end) of the home facing ___. On the basis the system is designed to maintain an indoor temperature of 75° F when outdoor temperatures are ___ °F dry bulb and ___ °F wet bulb.

The temperature to which this home can be cooled will change depending upon the amount of exposure of the windows of this home to the sun's radiant heat. Therefore, the home's heat gains will vary dependent upon its orientation to the sun and any permanent shading provided. Information concerning the calculation of cooling loads at various locations, window exposures and shadings are provided in Chapter 22 of the 1989 edition of the ASHRAE Handbook of Fundamentals.

Information necessary to calculate cooling loads at various locations and orientations is provided in the special comfort cooling information provided with this home.

☒ Air conditioner not provided at factory (Alternate II)
The air distribution system of this home is suitable for the installation of central air conditioning.

The supply air distribution system installed in this home is sized for a manufactured home central air conditioning system of up to 39570 B.T.U./hr. rated capacity which are certified in accordance with the appropriate air conditioning and refrigeration institute standards, when the air circulation of such air conditioners are rated at 0.3 inch water column static pressure or greater for the cooling air delivered to the manufactured home supply or duct system.
Information necessary to calculate cooling loads at various locations and orientations is provided in the special comfort cooling information provided with the manufactured home.

☐ Air conditioning not recommended (Alternate III)
The air distribution system of this home has not been designed in anticipation of the use with a central air conditioning system.

To determine the required capacity of equipment to cool a home efficiently and economically, a cooling load (heat gain) calculation is required. The cooling load is dependent on the orientation, location and the exposure of the home. Central air conditioners operate most efficiently and provide the greatest comfort when their capacity closely approximates the calculated cooling load. Each home's air conditioner should be sized in accordance with Chapter 22 of the American Society of Heating, Refrigerating and Air Conditioning Engineers (ASHRAE) Handbook of Fundamentals 1989 edition, once the location and orientation are known.

INFORMATION PROVIDED BY THE MANUFACTURER NECESSARY TO CALCULATE SENSIBLE HEAT GAIN

Walls (without windows) (Btu/hr/ft.)	.085
Ceilings and roofs of light color	.076
Ceilings and roofs of dark color	
Floors	.034
Air ducts in floor	.238
Air ducts in ceiling	.23
Air ducts installed outside the home	

The following are the duct areas in this home:

Air ducts in floor	___ sq. ft.
Air ducts in ceiling	469 sq. ft.
Air ducts outside the home	30 sq. ft.

U/O VALUE ZONE MAP

FO-M 00rev-O-Ad, Inc. Rev. 11/94

HOME CONSTRUCTION INFORMATION
NEEDED FOR SETUP 2-29-02

Homes of Merit

FLOOR SYSTEM CONSTRUCTION	2x6 ☒		2x8 ☐	
MAXIMUM OVERHANG	2"☐	6"☒	12"☐	
FLOOR WIDTH	138"☐	140"☐	160"☐	184"☒