





ELK

ROOFING PRODUCTS SPECIFICATIONS – TUSCALOOSA, AL



**PRESTIQUE®
HIGH DEFINITION®**



RAISED PROFILE®

Prestique Plus *High Definition* and Prestique Gallery Collection™

Product size _____ 13 1/4" x 39 1/2"
Exposure _____ 5 1/2"
Pieces/Bundle _____ 16
Bundles/Square _____ 4/98.5 sq.ft.
Squares/Pallet _____ 11

50-year limited warranty period:
5-7**years non-prorated coverage for
shingles and application labor with
prorated coverage for remainder of
limited warranty period, plus an
option for transferability*. 5-year
limited wind warranty*. Wind
Coverage: standard 80 mph, extended
110 mph***

Raised Profile

Product size _____ 13 1/4" x 38 1/2"
Exposure _____ 5 1/2"
Pieces/Bundle _____ 22
Bundles/Square _____ 3/100 sq.ft.
Squares/Pallet _____ 16

30-year limited warranty period:
5-7**years non-prorated coverage for
shingles and application labor with
prorated coverage for remainder of
limited warranty period, plus an
option for transferability*. 5-year
limited wind warranty*. Wind
Coverage: standard 70 mph.

Prestique I *High Definition*

Product size _____ 13 1/4" x 39 1/2"
Exposure _____ 5 1/2"
Pieces/Bundle _____ 16
Bundles/Square _____ 4/98.5 sq.ft.
Squares/Pallet _____ 14

40-year limited warranty period:
5-7**years non-prorated coverage for
shingles and application labor with
prorated coverage for remainder of
limited warranty period, plus an
option for transferability*. 5-year
limited wind warranty*. Wind
Coverage: standard 80 mph, extended
90 mph***

HIP AND RIDGE SHINGLES

Seal-A-Ridge® w/FLX™

Size: 12" x 12"
Exposure: 6 1/2"
Pieces/Bundle: 45
Coverage: 4 Bundles =
100 linear feet

Vented RidgeCrest™ w/FLX™

Size: 13" x 13 1/4"
Exposure: 9 1/4"
Pieces/Box: 26
Coverage: 5 boxes =
100 linear feet

Prestique *High Definition*

Product size _____ 13 1/4" x 38 1/2"
Exposure _____ 5 1/2"
Pieces/Bundle _____ 22
Bundles/Square _____ 3/100 sq.ft.
Squares/Pallet _____ 16

30-year limited warranty period:
5-7**years non-prorated coverage for
shingles and application labor with
prorated coverage for remainder of
limited warranty period, plus an
option for transferability*. 5-year
limited wind warranty*. Wind
Coverage: standard 80 mph.

Elk Starter Strip

52 Bundles/Pallet
18 Pallets/Truck
936 Bundles/Truck
19 Pieces/Bundle
1 Bundle = 120.33 linear feet

Available Colors (Check Availability): Antique Slate, Weatheredwood, Shakeswood, Sablewood, Hickory, Barkwood, Forest Green, Wedgewood, Birchwood, Sandalwood.
Gallery Collection: Balsam Forest™, Weathered Sage™, Sienna Sunset™.

All Prestique, Raised Profile and Seal-A-Ridge, and Prestique Starter Strip roofing products contain sealant which activates with the sun's heat, bonding shingles into a wind and weather resistant cover that resists blow-offs and leaks.

Check for availability with built-in StainGuard™ treatment to inhibit the discoloration of roofing granules caused by the growth of certain types of algae.

All Prestique and Raised Profile shingles meet UL Wind Resistant (UL 997) and Class "A" Fire Ratings (UL 790);
and ASTM Specifications D 3018, Type-I; D 3161, Type-I; E 108 and the requirements of ASTM D 3462.

All Prestique and Raised Profile shingles have approval from the Florida Building Code Commission, Metro-Dade County, ICBO, and Texas Department of Insurance

*See actual limited warranty for conditions and limitations.

** Effective January 1, 2004, the seven year non-prorated Umbrella Coverage Period applies only when a full Elk Roof System is installed with the original installation of the Elk shingles, all in accordance with Elk's application instructions for such products. A full Elk roof system includes Elk Hip and Ridge shingles on all hips and ridges, Elk Starter Strip along all rake and eave edges, an Elk ventilation system, and Elk All-Climate Self-Adhering Underlayment in all valleys. Additionally, Elk All-Climate Self-Adhering Underlayment is required along the rake and eave edges of the roof in and north of the states of VA, KY, MO, KS, CO, UT, NV, & OR

***For a limited Wind Warranty up to 110 mph for Prestique Gallery Collection, Prestique Plus, or 90 mph for Prestique I or Grandé, at least six (6) properly placed NAILS and Elk Starter Strip shingles are required. See application instructions printed on the shingle wrapper for additional requirements.

SPECIFICATIONS

SCOPE: Work includes furnishing all labor, materials and equipment necessary to complete installation of (name) shingles specified herein. Color shall be (name of color). Hip and ridge type to be Elk Seal-A-Ridge with formula FLX.

All exposed metal surfaces (flashing, vents, etc.) to be painted with matching Elk roof accessory paint.

PREPARATION OF ROOF DECK: Roof deck to be dry, well-seasoned 1" x 6" (25.4mm x 152.4mm) boards; exterior-grade plywood (exposure 1 rated sheathing) at least 3/8" (9.525mm) thick conforming to the specifications of the American Plywood Association; 7/16" (11.074mm) oriented strandboard; or chipboard. Most fire retardant plywood decks are NOT approved substrates for Elk shingles. Consult Elk Field Service for application specifications over other decks and other slopes.

Materials: Underlayment for standard roof slopes, 4" per foot (101.6/304.8mm) or greater: apply non-perforated No. 15 or 30 asphalt-saturated felt underlayment. For Low slopes (4" per foot (101.6/304.8mm) to a minimum of 2" per foot (50.8/304.8mm)), use two plies of underlayment overlapped a minimum of 19". Fasteners shall be of sufficient length and holding power for securing material as required by the application instructions printed on shingle wrapper.

For areas where algae is a problem, shingles shall be (name) with StainGuard treatment, as manufactured by the Elk Tuscaloosa plant. Hip and ridge type to be Seal-A-Ridge with formula FLX with StainGuard treatment.

Complete application instructions are published by Elk and printed on the back of every shingle bundle. All warranties are contingent upon the correct installation as shown on the instructions. These instructions are the minimum required to meet Elk application requirements. In some areas, building codes may require additional application techniques or methods beyond our instructions. In these cases, the local code must be followed. Under no circumstances will Elk accept application requirements less than those contained in its application instructions.

For specifications in CSI format, call 800.354.SPEC (7732) or e-mail specinfo@elkcorp.com.

SOUTHEAST &
ATLANTIC OFFICE:

CORPORATE HEADQUARTERS:
800.354.7732

PLANT LOCATION:
800.945.5545

ELK